



aerospace  
climate control  
electromechanical  
filtration  
fluid & gas handling  
hydraulics  
pneumatics  
process control  
sealing & shielding



# CAT 4660

Parflex® Thermoplastic & Fluoropolymer Products  
Hose, Tubing, Fittings & Accessories, Jan. 2012



ENGINEERING YOUR SUCCESS.

Extra care is taken in the preparation of this literature but Parker is not responsible for any inadvertent typographical errors or omissions. Information subject to change without notice. The information in this catalog is only accurate as of the date of publication. For a more current information base, please consult the Parflex® Division web site at [www.parker.com/pfd](http://www.parker.com/pfd).



FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

### **Offer of Sale**

The items described in this document are hereby offered for sale by Parker Hannifin Corporation, its subsidiaries or its authorized distributors. This offer and its acceptance are governed by the provisions stated in the "Offer of Sale".



# Welcome to The Parflex® Division



## Our Charter

To be the global leader in engineered polymer-based products while providing system solutions for the conveyance and control of fluids.

As part of the Parker Fluid Connectors Group, the Parflex® Division is responsible for the design and manufacture of hoses and tubing to handle extreme applications. Products include thermoplastic and fluoropolymer hose and tubing, hose bundles, harnesses and accessories.

The Parflex® Division includes the Ravenna division headquarters in Ohio, and manufacturing facilities in:

- Manistowoc, WI
- Fort Worth, TX
- Randleman, NC
- Monterrey, Mexico



*For detailed ordering information, please consult price list or contact Parflex® Division.*


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

# Table of Contents

<b>A Hose - Thermoplastic A-1 : A-64</b>		<b>Hose - Fluoropolymer A-65 : A-85</b>	
Parflex Thermoplastic _____	A-4 : A-64	Parflex PTFE _____	A-65 : A-74
		PAGE PTFE _____	A-75 : A-85
<b>B Tubing - Thermoplastic B-1 : B-41</b>		<b>Tubing - Fluoropolymer B-42 : B-85</b>	
Polyethylene _____	B-8 : B-15	PTFE _____	B-50 : B-69
Nylon _____	B-16 : B-25	FEP _____	B-70 : B-77
Polypropylene _____	B-26 : B-33	PFA _____	B-78 : B-81
Polyurethane _____	B-34 : B-38	PVDF _____	B-82 : B-85
Clear Vinyl _____	B-39 : B-41		
<b>C Coiled Air Hose &amp; Fittings C-1 : C-21</b>			
Fast-Stor® Air Hose _____	C-8 : C-9	NoMar™ Fast-Stor® Fittings _____	C-18 : C-19
Fast-Stor® Fittings _____	C-10 : C-13	Ultra-Lite Superbraided _____	C-20 : C-21
NoMar™ Fast-Stor® Assemblies _____	C-14 : C-17		
<b>D Transportation (Fleet) D-1 : D-15</b>			
Air Brake Tubing _____	D-4 : D-5	Slider Coil™ _____	D-11 : D-11
Diesel Fuel Tubing (PTFE-FL) _____	D-6 : D-6	Fifth Wheel Slider Coil _____	D-12 : D-12
Diesel Fuel Tubing (HTFL High Temperature) _____	D-7 : D-7	Custom Harnesses, Bundles & Tubing _____	D-13 : D-13
BRAKCOIL® _____	D-8 : D-8	SCR Hose _____	D-14 : D-15
Duo-Coil® _____	D-9 : D-9		
<b>E Fittings E-1 : E-105</b>			
Hose Fittings _____	E-1 : E105		
<b>F Tooling F-1 : F-26</b>			
Crimpers _____	F-6 : F-13	Sewer Hose Swagers & Accessories _____	F-17 : F-17
Pumps _____	F-14 : F-15	Hose Accessories _____	F-18 : F-26
Conversion Kits _____	F-16 : F-16		
<b>G General Technical G-1 : G-66</b>			
Hose Selection, Installation & Mtn. _____	G-3 : G-9	Die Selection & Crimping Chart _____	G-41 : G-41
Hose Assembly & Crimping _____	G-10 : G-29	Technical Data _____	G-42 : G-58
Die Selection & Crimping Chart _____	G-30 : G-40		
Safety Guide _____	G-60		
Offer of Sale _____	G-65		
Part Number Index _____	i		
Keyword Index _____	v		

# Partner with Parflex®

**We customize our extreme hose and tubing solutions every day to meet your needs.**



**Parker Parflex offers an extensive selection of high-quality thermoplastic and fluoropolymer hose and tubing, fittings and accessory solutions.**

**We specialize in designing products to meet specific needs for increased profitability and efficiency. We customize our products every day to meet your needs.**

## The Parflex® Advantage

One stop shopping for high value conveyance solutions.

Thermoplastic and Fluoropolymer Hose, Tubing, Fittings and Accessories for extreme applications.

### Hose

When compared to wire reinforced rubber hose or even metal tubing, thermoplastic hose offers a significant added value. Thermoplastic provides extreme chemical compatibility, noise-level reduction and ultraviolet and corrosion resistance, while fiber reinforcement retains flexibility — even at low temperatures. In addition, Parflex has long-length capabilities resulting in less scrap being generated during assembly...fewer connections, results in fewer potential leak points.

For fluoropolymer hose, Parflex has expanded its PTFE Hose line to include the PAGE product line, manufactured in Fort Worth, TX. PAGE products are comprised of fluoropolymer hoses with specialty braid and construction options. These hoses are designed to handle high temperatures in chemical and corrosive environments for the pharmaceutical and food and beverage markets. Specialty products like PAGE-flex SBF™ (a hose with 1/2 the minimum bend radius of a conventional smooth bore hose) and EPDM rubber covered hoses are now available. We also design a full range of Parflex and PAGE hose fittings.

And that's just the beginning...


### Tubing


Parflex has also expanded the tubing line to include PTFE, FEP, PFA and PVDF tubing. All are available in a smoothbore design and others are available in beading, heat shrinkable tubing and convoluted tubing. This tubing operates in high temperatures (up to 500°F/260°C) and in cryogenic applications with temperatures as low as -100°F/-75°C. Extrusions are resistant to UV radiation and moisture and offer the lowest coefficient of friction of any material available.

Additionally, ALL Parflex tubing products are made from resins and colors that are certified to be free of mercury, heavy metals and other materials that are restricted in accordance with the RoHS directive.

### Unique Preforming Capabilities

Parflex preforming combines the precision of steel tubing with the flexibility of a hose. Preformed products profile complex shapes and long lengths, offering a working





rigidity that ensures that the hose stays true to your lines and a superior flexibility to allow for unparalleled alignment compensation.

The Parflex Polyurethane Air Hose (Ultra-Lite Superbraided) weighs 29% less than equivalent thermoplastic products and 63% less than equivalent rubber air hoses.

In addition to installation ease, Parker preformed products increase productivity thanks to dramatic reductions in weight, leak paths and the number of components. They also are highly cost effective for the manufacturer. With excellent shape retention, Parker products can be easily coiled and packed in standard boxes, saving on shipping costs and inventory space.

### Extremely Lightweight

Compared to rubber equivalents, Parflex products are lighter in weight due to their fiber reinforcements. In fact, a Parflex hose can weigh more than 70% less than a comparable rubber hose assembly. As a result of this greater strength-to-weight ratio, thermoplastics are easier to work with. Operator handling becomes less fatiguing and it is quicker and easier to route hoses onto equipment.

### Thermoplastic vs. Rubber Hose Weight\*

Size	Typical 100R7 Hose (Thermoplastic)	Typical 100R1 Hose (Rubber)
-4	0.052	0.170
-6	0.096	0.250
-8	0.148	0.300
-12	0.188	0.460
-16	0.269	0.660

\*Weight: pounds/foot

### Economical Small Bore

Prior to thermoplastics, system designers had to use hoses that were oversized for certain applications. More economical, small-bore rubber hose was simply not available in sizes smaller than 1/4" for applications with flows less than 3 gallons per minute. The use of oversized hoses resulted in substantial waste in systems; costing more, reducing response times and increasing installation times.

### Thermoplastic vs. Rubber Hose O.D.\*

Size	Typical 100R7 Hose (Thermoplastic)	Typical 100R1 Hose (Rubber)
-4	0.47	0.53
-6	0.63	0.69
-8	0.81	0.81
-12	1.08	1.09
-16	1.32	1.41

\*Outside Diameter: inches

Today, system designers have a wealth of options to the 1/4" rubber hose. In fact, thermoplastic hose manufacturers have established full lines of hose for every application. With sizes that include 1/4", 3/16", 1/8", and 3/32", Parflex compact designs allow tighter bend radius characteristics, work well in smaller enveloped areas and give excellent fluid compatibility and higher abrasion resistance.

For detailed ordering information, please consult price list or contact Parflex® Division.



### Superior Abrasion and Fatigue Resistant

Thermoplastic products are known for having superior abrasion resistance over their rubber equivalents. Providing significantly longer wear, they offer as much as 100 to 30,000 times the abrasion resistance. Fiber braided thermoplastic hose also maintains better fatigue resistance than a wire-reinforced hose.

Parflex offers a choice of wire or fiber braid reinforced hose products. All hoses are specially designed to withstand abrasion and the abuse of constant flexing, assuring a longer service life without breaking or weakening. This makes them ideal for over-the-sheave applications and boom trucks, as well as an excellent option for abrasive environments like construction, forestry, mining and refuse.

### Bonded Hose

Bonded assemblies help prevent hose-to-hose abrasion at high stress levels. By bonding 2 to 10 varying-sized hoses (maximum 10" O.D.) together, bonded assemblies keep hoses from rubbing

against each other or tangling. They are particularly beneficial for long runs, such as cable tracks. Parflex hose bonding keeps hoses straight for easier and more stable routing while improving quality by maintaining continuous hoses from end to end.

### Convenient Harness and Bundle Integration

Similar to bonding, Parflex harnesses and bundles ensure quick assembly, eliminate waste and improve throughput. Custom engineered to meet the exact requirements of each manufacturer, Parflex harnesses reduce labor by supplying a pre-designed bundle of tubes to fit a customer's specific application. With all the connections secured together, the preformed harness decreases overall installation time, waste and human error, while improving part consistency for a neater and cleaner design. Companies can then re-allocate excess resources to bottleneck areas – increasing their overall throughput.






### Cleanliness and Safety

Parflex products are designed with safety and cleanliness in mind. The erosion resistant core maintains long-term system cleanliness with mandrel free construction to ensure zero lubricant contamination. And with fiber reinforced Parflex thermoplastic hose, there's little to no contamination due to cutting because they do not require a hose saw.

While cleanliness is inherent in thermoplastic core tubes, some Parflex hoses also maintain non-conductivity, keeping the operator safe from electric shock. Most hoses feature a UV and ozone resistant jacket, which resists cracking and UV damage, thus extending the service life of the hose.

Parflex has developed specific products that focus on safety. The new, 944B/955B high pressure PTFE hoses handle pressures up to 5,500 psi and are available with fire sleeves to facilitate safer operator handling.

*For detailed ordering information, please consult price list or contact Parflex® Division.*



### **Environmental Concerns**

In addition to being innovative and safe, Parflex is committed to being environmentally conscious as a company and global manufacturer and continues to develop environmental solutions for emerging markets such as compressed natural gas (CNG), oil and gas and wind power.

Within the CNG market, Parflex has designed a special CNG hose and bonded assemblies for use with CNG dispensers, transfer applications and transportation refill trailers. New fluoropolymer hoses have also been designed to target the oil and gas market. Finally, Parflex engineers have assembled comprehensive hydraulic and lubrication systems for the wind power sector. These systems include preformed, twinline, HLB lubrication hoses and hose bundles.

Existing markets will continue to change and new markets will emerge. And as they do, Parflex Engineers will be there to help you develop solutions for the new challenges and obstacles that arise. Parflex offers complete engineering support, including custom design solutions, on-site prototyping, pre-production fit-up and print creation.

### **Environmental Sustainability**

Parflex is committed to managing our business, products and manufacturing activities in an environmentally conscious and sustainable method.

Parflex manufacturing locations are either ISO 14001 certified or ISO 14001 ready. The ISO 14001 Environmental Management System (EMS), developed by the International Standards Organization (ISO), provides a framework for companies to minimize the environmental impact of their operations, ensure compliance with applicable laws and regulations and to ensure continual improvement.

Utilizing the ISO 14001 system, Parflex has made significant progress towards reducing its carbon foot print through; reduced energy consumption, increased recycling activities and the reduction of raw material consumption through innovative product design, material selection and manufacturing technologies.

Parflex ensures consistent quality and faster implementation  
– all to save you time and money.



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



## Thermoplastic Hose Construction

### 1. Core

Contains Media

Materials: Nylon, Polyethylene, Polyurethane, Co-Polyester

### 2. Reinforcement

Provides Resistance to Internal Pressure


Materials: Fiber (Nylon, Polyester, Aramid), Steel, Stainless Steel

### 3. Jacket


Protects Reinforcement

Advantages: Aesthetics, Color and Marking

Materials: Polyurethane, Nylon, Synthetic Rubber, Co-Polyester, Polyurethane, Proprietary Blend (PFX)



## Fluoropolymer Hose Construction



### 1. Core

Contains Media

Materials: PTFE Smoothbore or Convoluted, PFA

### 2. Reinforcement

Provides Resistance to Internal Pressure

Materials: Steel, Stainless Steel, Polypropylene, Nomex®, Proprietary Composite

### 3. Jacket or Protective Sleeve

Protects Reinforcement

Materials: Silicone, Polyolefin, EPDM Rubber

Nomex® is a registered trademark of Dupont.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)





# How to Use This Catalog

## Table of Contents

For quick, easy listing of topics covered by section, reference the Table of Contents on pg. 1.

## Information by Part Number

See the Part Number Index in Section G pgs. i : iv.

## Information by Type of Part

Reference the Table of Contents on pg. 1, or check the Section Table of Contents/Visual Index found on the first page of each section in the catalog.

## Information by Fitting End Configuration














See Standard Fitting Configurations by Connection and End Code in Section E, pg. 4. This list identifies the cataloged fittings by a description of the end configuration and the fitting end code.


## The Parker Part Numbering System

The part numbering system for hose, fittings and tubing is explained on pgs. 12 & 13. Specific nomenclature sheets are located in the Hose Section on pgs. A-18 : A-21. In the Tubing Section, part number information is included on each product page.

## International Symbols

An explanation of the symbols and their meaning used in the product tables can be found below.

Symbol	Meaning	Symbol	Meaning
#	Part Number		Minimum Burst Pressure
	Hose Inner Diameter (I.D.)		Weight
	Hose Outer Diameter (O.D.)		Vacuum Rating
	Working Pressure		Thread Size
	Minimum Bend Radius		Hex Size
	Crimp Die		Diameter
	Crimp Fitting		Field Attachable Fitting



## Icon Identification Key



Transportation



Mobile  
Hydraulics



Industrial  
Pneumatic



Industrial  
Hydraulics



Fluid  
Handling



Life  
Science



Food &  
Beverage

*For detailed ordering information, please consult price list or contact Parflex® Division.*

**Parker Hannifin Corporation** | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)




# Selecting the Right Hose

## Choosing Your Hose

**Before selecting** hoses from Catalog 4660, it will be easier if you familiarize yourself with the basics of thermoplastic and fluoropolymer hoses. If you review the symbols on pg. 8 and the "How to Build A Hose Assembly" on pages 12 & 13 you will have a foundation for selecting your hose. Also, the Parflex Hose Selections Charts (located in Section A) will help pinpoint the hose you require. It will help you identify individual hoses by:

- Brief general description
- Specific size with corresponding working pressure
- Industry specification (ie. SAE)
- Core tube material
- Reinforcement/type of construction
- Cover material
- Specific page number where further detailed product information can be found

For fittings, refer to the visual indexes in Section E.




## General Construction

Construction standards may vary between specific thermoplastic hoses.

Parflex bonds hose layers to provide maximum kink resistance and flexibility through a wide range of applications. Specific braid materials, wire reinforcements, spiral reinforcements and distinguishing features are clearly called out with each hose product. Perforated and non-perforated hoses are available based on application.

WITH NOTED EXCEPTIONS, Parflex hoses are engineered and manufactured to a 4:1 burst pressure to working pressure ratio that follows SAE design standards. Never operate a hose beyond its published working pressure. [Working Pressure x 4 = Minimum Burst]





## "STAMPED"

### Size

The appropriate inside and outside diameters and length of the hose should be determined

### Temperature

The ambient and/or maximum temperature of the material being conveyed

### Application

External conditions including abrasion, climate, heat, flexing, crushing, kinking, and degrees of bending

### Media

The composition of the substance being conveyed and chemical compatibility with the hose inner core and, if applicable, the outer jacket

### Pressure

The maximum pressure of the system, including pressure spikes

### Ends

The appropriate end connection and attachment method for the application

### Delivery

Testing, quality, packaging, and delivery requirements

*For detailed ordering information, please consult price list or contact Parflex® Division.*



# Hose, Fittings & Tubing Part Numbers

To make ordering of Parflex products easier, a part number description section has been added for hose, tubing and fitting products. For additional nomenclature information, refer to the following pages:

- Hose - Section A .....pgs. A-1 : A-86
- Tubing - Section B .....See specific product page
- Fittings - Section E .....pgs. E-1 : E-108

## Hose Part Numbers

Parflex has expanded the Hose section to include the PAGE Fluoropolymer product line. The PAGE product line is comprised of fluoropolymer hoses with specialty braid and construction options.

<p><b>Thermoplastic &amp; Fluoropolymer</b></p> <p><b>Example: 520N – 8</b></p> <p><b>520N</b> – 8 – <b>Hose type</b> (General Hydraulic Hose)                  520N – <b>8</b> – <b>Hose inside diameter</b> dash size (1/2")</p>	<p><b>Parflex PAGE Fluoropolymer</b></p> <p><b>Example: 16-SCW</b></p> <p><b>16-SCW</b> – <b>Hose inside diameter</b> dash size (1")                  16-<b>SCW</b> – <b>Hose type</b> (Seamless Convuluted with Stainless Steel Braid)</p>
--	---

## Hose Assembly Part Numbers

**Example: F540N0639080808C-30"**

This assembly example reflects a 1/2" I.D., 540N hose with a female JIC 37° swivel straight fitting on the first end and a female JIC 37° - swivel - 90° elbow fitting on the other. The fittings are stainless steel and crimped (permanently attached) onto the hose. The overall length is 30".



<p><b>1. Prefix</b></p> <p>F540N0639080808C-30"</p> <p>F = Crimp                  R = Field Attachable                  A = 54 Series Factory</p>	<p><b>3. Fitting 1<sup>st</sup> End</b></p> <p>F540N0639080808C-30"</p> <p>SAE 1/2" female JIC 37° swivel straight fitting</p>	<p><b>5. Size 1<sup>st</sup> End</b></p> <p>F540N0639080808C-30"</p> <p>1/2"</p>	<p><b>7. Hose End Dash Size</b></p> <p>F540N0639080808C-30"</p> <p>1/2"</p>
<p><b>2. Hose type</b></p> <p>F540N0639080808C-30"</p> <p>General Hydraulic Hose</p>	<p><b>4. Fitting 2<sup>nd</sup> End</b></p> <p>F540N0639080808C-30"</p> <p>SAE 1/2" 90° female JIC 37° swivel elbow fitting</p>	<p><b>6. Size 2<sup>nd</sup> End</b></p> <p>F540N0639080808C-30"</p> <p>1/2"</p>	<p><b>8. Fitting Material</b></p> <p>F540N0639080808C-30"</p> <p>- Blank = Steel (unless noted)                  - C = Stainless                  - B = Brass</p>
<p><b>9. Length</b></p> <p>F540N0639080808C-30"</p> <p>30" overall length</p>			

**A complete nomenclature guide for Parflex PAGE hoses is located in Section A on pg. A-21.**



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## Hose Fittings Part Numbers

Parflex has expanded the Fitting Section to include several new series of part numbers. New series include CY Series, SF Series, 54 Series Rapid Assembly and PAGE fittings, designed to use with traditional PAGE hoses. PAGE fittings are not designed for use on the Parflex fluoropolymer hoses 919, 929, 939, 943B, 944B, 950B or 955B hoses.

### Example: 10355-8-6

This example describes a permanent crimp 1/2" Male JIC 37° Rigid hose end with a 3/8" hose end. This fitting is constructed of steel since the designated material is blank.

10355-8-6 – **Fitting Type** (1 = Permanent/Crimp)

10355-8-6 – **End Configuration Code**  
(Male JIC 37° Rigid)

10355-8-6 – **Fitting Series** (Series 55)

10355-8-6 – **End Size** (1/2")

10355-8-6 – **Hose Size** (3/8")

### Fitting Material

- Blank = Steel (unless otherwise noted)
- B = All Brass
- C = Stainless Steel
- S = All Carbon Steel – Used only with PTFE Fittings

## Tubing Part Numbers

Parflex has expanded the Tubing Section to include the TexLoc Fluoropolymer product line. In addition to smooth bore tubing, TexLoc products include beading, convoluted tubing and heat shrinkable tubing. This tubing is supplied in natural and colors are available upon request. For a detailed fluoropolymer nomenclature guide, review Section B, pgs. B-46 : B-47.

### Thermoplastic

Example: U-21-BLU-0250

U-21-BLU-0250 – **Polyurethane**

U-21-BLU-0250 – **Tube O.D.**

in sixteenths of an inch (1/8")

U-21-BLU-0250 – **Tube I.D.**

in sixteenths of an inch (1/16")

U-21-BLU-0250 – **Color** (Blue)

U-21-BLU-0250 – **Package quantity** (250')

#### Available colors

- |                  |                              |
|------------------|------------------------------|
| ● BLK = Black    | ● ORG = Orange               |
| ● BLU = Blue     | ● RED = Red                  |
| ● GRY = Gray     | ● YEL = Yellow               |
| ● GRN = Green    | (colors may vary by product) |
| ● None = Natural |                              |

### Fluoropolymer

Example: 101-0250062-NT-0100

101-0250062-NT-0100 – **PTFE**

101-0250062-NT-0100 – **Tube O.D.**

inch displayed in decimals (1/4")

101-0250062-NT-0100 – **Wall Thickness**

inch displayed in decimals (.062")

101-0250062-NT-0100 – **Color** (Natural)

101-0250062-NT-0100 – **Bulk Tubing**

101-0250062-NT-0100 – **Package quantity** (100')

#### Available colors

- |               |              |
|---------------|--------------|
| ● N = Natural | ● 5 = Green  |
| ● 0 = Black   | ● 3 = Orange |
| ● 6 = Blue    | ● 2 = Red    |
| ● 1 = Brown   | ● 4 = Yellow |
| ● 8 = Gray    | ● 9 = White  |

For detailed ordering information, please consult price list or contact Parflex® Division.

# Why Use Thermoplastic Tubing?



## Benefits of Thermoplastic Tubing Materials and Applications\*

Nylon	Strength Chemical Compatibility	Instrumentation Food & Beverage
Polyethylene	Food/Water Contact Cost	Potable Water Chemical Transfer
Polyurethane	Flexibility	Pneumatics
Polypropylene	Food Contact Chemical Transfer Chlorinated Water	Robotics Machine Tools Lubrication
Vinyl	Cost Flexibility Food Contact Clarity	Pest Control Lines Semiconductor Marine Applications Weld Spatter/Spark Environments

\*Certain materials perform better in particular applications. Contact Customer Service for details.

# Why Use Fluoropolymer Tubing?



## Benefits of Fluoropolymer Tubing Materials and Applications\*

All	Self extinguishing Nonwetting FDA & USP Class VI compliant	Pharmaceutical Solar Panels
PTFE	Operates up to 500°F Lowest coefficient of friction	Pulp & Paper Food Processing
FEP	Operates up to 400°F Long, continuous lengths	Environmental Sampling Chemical Delivery
PFA	Operates up to 500°F Long, continuous lengths High purity resins available	Chromatography Paint Equipment Instrumentation
PVDF	Operates up to 265°F Food Contact Chemical Transfer Chlorinated Water	Heat Exchanger Ink Rollers Medical Devices

\*Certain materials perform better in particular applications. Contact Customer Service for details.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Mobile Hydraulics



Parflex Mobile Hydraulic products meet the needs of four primary market segments: aerial lift, agriculture, construction and material handling. Why are Parflex products so popular? Namely, cleanliness, high-impulse hybrid hoses, low volumetric expansion, lightweight and long-length manufacturing, as well as, ease of service and preformed capabilities.

Within the aerial lift market, Parflex products range from the eXtreme™ Duty hose to twin and multi-bonded hoses to preformed products and crimping. For the agriculture market,

Parflex products are used for oil return lines on tractors, polyethylene transfer tubes for sprayer application and grease lines on harvesters. In the construction market, Parflex products help save you money by replacing single-line rubber hoses with non-abrasive, lighter weight bonded thermoplastics on equipment. Finally, in material handling, Parflex products answer over-the-sheave and cold/refrigerated challenges.

## Applications

- General Hydraulics
  - Off-Road Construction
  - Earth Moving Equipment
  - Lift Trucks
  - Material Handling
  - Construction Equipment
  - Refuse Haulers
  - Agricultural Equipment
- Lubrication lines
- Over-the-sheave applications
- Power steering
- Compressor discharge
- General hydraulics
- Hydraulic & pneumatic systems
- Commercial refrigeration
- Cold storage
- Testing labs
- Material handling
- Conveyor equipment
- Mower attachments
- Implement hydraulic power
- Diagnostics/Gaging
- PTO's
- Aerial Lift Hydraulic Tools
- Pilot Control Lines
- Turbo Drain Lines







## Markets

- Material Handling Equipment
- Marine
- Agricultural Equipment
- Utility Equipment
- Sewer Cleaning Equipment
- Aerial Lift
- Construction Equipment
- Rough Terrain Equipment
- Refuse Haulers
- Mining



*For detailed ordering information, please consult price list or contact Parflex® Division.*

# Fluid Handling



Parflex Fluid Handling products are categorized by their thermoplastic and fluoropolymer (PTFE) makeup. Thermoplastic products service lubrication, carpet (power) cleaning, sewer cleaning, breathing air, media transfer, and refrigeration markets while Fluoropolymer (PTFE) products meet a wide array of needs as a result of PTFE's unique material benefits.

Fluoropolymer (PTFE) products – which include smooth bore & convoluted hose, as well as steel, stainless steel, and brass fittings – service automotive, oil & gas, power generation, packaging/chemical transfer, and pulp & paper markets and applications. All of these markets and applications greatly benefit from PTFE's chemical resistance, extreme temperature range, low friction, non-stick and flexibility. They also take advantage of PTFE's

unlimited shelf life, high purity and natural FDA-compliant and black static dissipative core tube.

The Parflex PAGE fluoropolymer hose line extends the PTFE hose selection even further with convoluted hose assemblies, PTFE encapsulated fittings and PTFE flare-thru fittings for the pharmaceutical and food and beverage market.

## Applications

- Car care
- Semi-conductor (Pure air or gas transfer)
- Pharmaceutical dispensing
- Lubrication systems
  - Forklift
  - Machine tool
  - Heavy equipment
- Breathing air systems
- Chemical dispensing
- Sewer cleaning
- Alternative Fuels
- Potable water delivery
- Carpet (Power) cleaning
- Coolant lines
- Agricultural spraying
- Oil & Gas transfer (Petrochemical)
- Food and Beverage
- Chemical and Gas Transfer





## Markets

- Industrial Equipment
- Utilities (CNG)
- Semiconductor
- Chemical
- Commercial Refrigeration
- Water Treatment
- Power Cleaning
- Power Generation
- Car Care
- Pharmaceutical
- Bio-Pharmaceutical
- Pulp & Paper
- Oil & Gas



*For detailed ordering information, please consult price list or contact Parflex® Division.*



# Industrial Pneumatics



Parflex Industrial Pneumatics provide high-quality air tool, robotic and coiled thermoplastic solutions. A diverse product line includes lightweight, non-marring, flexible hose and thermoplastic or fluoropolymer tubing.

Ideal for construction, carpentry, automotive and aerospace industries, Parflex air hose assemblies are a smart investment over rubber counterparts. Parflex hoses are lighter weight, feature a no-mar, easy-clean outer cover and can be coiled or uncoiled down to -40°F without memory effect. All of which helps to improve worker safety, reduce property damage, lessen equipment repair/replacement, and, most importantly, increase productivity.

Parflex additionally offers products specifically designed for robotic applications, such as low-pressure 83FR hose and HUFR tubing. Tubing and hose bundling products for general robotics reduce installation time and promote longer life. For coiled thermoplastic solutions, look no further than Parflex tough, abrasion and kink-resistant coiled hoses.

The Parflex coiled selection includes Fast-Stor® coils and Ultra-Lite Superbraid, designed for markets like transportation, manufacturing and robotics.



## Applications

- Air tools
- Robotic welding
- End-of-arm tooling
- Metal working
- Automotive maintenance
- General robotics

## Markets

- Robotics
- Packaging Machinery
- Machine Tool
- Construction
- Automotive Maintenance
- Medical Equipment
- Laboratory Equipment
- Furniture Manufacturing
- Aerospace



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)





# Industrial Hydraulics



Parflex Industrial Hydraulics develops thermoplastic hose and fitting products – from fiber, wire and Aramid fiber reinforced products to steel, stainless steel, and brass fittings to equipment & accessories – for today's fastest growing markets.

Parflex provides the power generation market with hose, tubing and bundles for turbine control valves, fuel systems and steam monitoring and thermoplastic hose and bonded hose assemblies for car & truck wash applications. In addition, Parflex manufactures hose reels for service

garages, auto and truck dealers, construction service shops and farm equipment service centers.

Parflex also provides hydraulic product equipment, such as MiniKrimp™ machines, to rental yards and forklift service companies. Ideal for field repairs, the lightweight, economical MiniKrimp™ hand pump and air/hydraulic models can crimp a majority of Parker thermoplastic, rubber, hybrid and PTFE hoses up to 3/4" I.D.

## Applications

- Injection molding
- Patient handling
- Car care
- Lubrication systems
- Molding and transfer lines for plastics
- Hydraulic or vacuum connections
- General hydraulic lines
- Metal cutting
- Metal forming
- Vertical machining centers
- Hand brakes
- Press brakes
- Bending machines
- Automotive maintenance
- Rescue tools



## Markets

- Machine Tools
- Hydraulic Tools
- Power Generation
- Mining Equipment
- Patient Handling
- Car Care
- Automotive
- Rescue Tools
- Lubrication Systems
- Recreational Vehicles



*For detailed ordering information, please consult price list or contact Parflex® Division.*



# Transportation



Parflex Transportation products have been specifically designed to meet the needs of trucks, specialty trucks (such as military, fire and terminal), buses and RVs, engines, and trailers.

An extensive line of transportation products includes a selection of air brake tubing for standard distribution and large OEMs, air brake harnesses, coils, fuel tubing and 100% pressure-tested fleet tubing for use with diesel fuel.

Steering lines on transit buses run from the back engine all the way to the front steering gear, which can require up to 40 feet of stainless steel tubing. Parflex offers a more manageable solution:

the eXtreme™ Duty Hose. Parflex also supplies products for turbo supply/drain and other coolant lines, from smooth bore to convoluted, lightweight lubricant systems, and flexible metal hose.

Parflex metal hose assemblies are built, tested, cleaned and packaged to suit customer requirements. With zero permeation, excellent chemical resistance and a full vacuum rating, Parflex metal hose handles temperatures that simply aren't compatible with rubber or other thermoplastics!

## Applications

- Fuel lines
- Power steering
- Coiled air brake
- Exhaust and AC lines
- Lubrication systems
- Mini hydraulics
- Compressor discharge
- Fast response
- Compressed natural gas
- Fuel transfer





## Markets

- Class 8 Heavy Truck
- Standard Box Truck
- Diesel Truck
- Bus
- Refrigeration Truck
- Refuse Truck
- Fire Truck
- Trailers
- Street Sweepers
- Military Vehicles
- RV's



*For detailed ordering information, please consult price list or contact Parflex® Division.*





Parflex has extended the selection of medical tubing capabilities through the TexMed® side of the TexLoc® business unit in Fort Worth, TX. TexMed specializes in the extrusion of precision tolerances for custom tubing and custom profiles of TexFluor® PTFE, ePTFE, FEP, PFA, and ETFE. Coupled with the traditional line of thermoplastic tubing in Vinyl, Polypropylene and Nylon Pure Air tubing, Parflex has a tube for almost every medical application.

With an emphasis on partnering, Parflex Engineers work closely with our customer's engineers to create tubing products with increased performance. The newest development is a medical grade FEP Heat Shrink for catheter forming. Unlike typical FEP heat shrink, which often wrinkles, twist or grows up to 20% in length when shrinking, the new heat shrink has a uniform recovery and a maximum constrained elongation up to + 5%. And with a faster recovery time, medical grade FEP Heat Shrink is very responsive in reflow applications for catheter manufacturing.

Parker/TexMed Advantages include:

- Application and Material Engineering Support
- Precision tolerance tubing
- Ability to handle low volume start up projects
- Class 10,000 clean room
- Complete traceability on each lot of product
- Wide range of US Class VI compliant materials

In the value added service department, specialty operations such as laser marking, tube cutting, scoring, slitting, marking, flanging, flaring, tipping and other services are available.



## Applications

- Catheter construction
- Sheathing
- Forming devices
- Introducers
- Dental equipment
- Endoscopic instruments
- Tracheotomy tubes
- Blood analyzer
- Lab instruments
- General robotics
- Air and gas transport
- Packaging





## Markets

- Medical Device
- Medical Equipment
- Dental



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)





# Food & Beverage



Parflex Hose and Tubing for the Food and Beverage market is comprised of FDA compliant thermoplastic tubing and fluoropolymer hose and tubing. Tubing is available in Polyethylene, Polypropylene, Vinyl and Fluoropolymers, consisting of PTFE, FEP, PFA & PVDF.

Parflex PAGE high temperature food processing hoses are available in several types and sizes. All of these hoses offer a seamless tube that resists the collection of bacteria, preserve taste and are very easy to clean. For added strength and durability, each hose has an added reinforcement that withstands internal pressures, a helical wire for full vacuum capabilities, and a high-grade weather and abrasion resistant cover for longevity.

All of the Parflex PAGE Food Transfer Hoses are compliant with FDA, 3A and USDA product standards. Additional compliance for specialty hoses includes PMPO (Grade A Pasteurized Milk Ordinance) and CFIA (Canadian Food Inspection Agency).

One of the more unique hoses, PAGE-flex® SBF™, offers a superior bend radius (1/2 the bend radius of conventional fluoropolymer braided hoses) coupled with superior kink and vacuum resistance. The newest hoses, 944B and 955B can handle pressures up to 5,500 psi.

## Applications


- Transport of edible oils, syrup, milk and other food products
- Dispensing equipment
- Tank transfer of raw products
- In-plant transfer for processing





## Markets

- Food
- Beverage



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)







# Hose

Thermoplastic

Fluoropolymer





# Table of Contents

## Introduction

Visual Index .....	A-4 : A-6
Understanding Parflex Hose .....	A-7
How to Read the Hose Section.....	A-8
Thermoplastic Hose Selection - Construction/Specifications, PSI.....	A-10
Thermoplastic Hose Selection - Construction/Specifications, MPa .....	A-14
Fluoropolymer Hose Selection - Construction/Specifications, PSI.....	A-12
Fluoropolymer Hose Selection - Construction/Specifications, MPa.....	A-16
Nomenclature - Parflex Thermoplastic Hose Assembly.....	A-18
Nomenclature - Parflex PTFE Hose Assembly.....	A-19
Nomenclature - PAGE Industrial S30 & S40 Hose Assembly.....	A-20
Nomenclature - “True-Bore” & Convoluted Hose Assembly.....	A-21

## Parflex Thermoplastic Hose

510A Refrigerant .....	A-34
510C General Hydraulic .....	A-35
518C General Hydraulic .....	A-36
515H Compact .....	A-37
520N General Hydraulic .....	A-38
526BA Breathing Air Refill, 6000 psi .....	A-39
527BA Breathing Air Refill, 7000 psi .....	A-40
528N General Hydraulic, Non-Conductive.....	A-38
53DM DuraMax™ Low Temperature.....	A-41
538DM DuraMax™ Low Temperature, Non-Conductive .....	A-41
540N General Hydraulic .....	A-42
540P Specialty Water .....	A-43
55LT Low Temperature .....	A-44
560 General Hydraulic.....	A-30
563 General Hydraulic.....	A-31
56DH Diagnostic .....	A-45
568DH Diagnostic, Non-Conductive .....	A-45
573X Fast Response, 3000 psi.....	A-46
575X Fast Response, 5000 psi.....	A-47
580N/H580N High Pressure .....	A-48
588N High Pressure, Non-Conductive.....	A-48
590 General Hydraulic.....	A-32
593 General Hydraulic.....	A-33
83FR General Purpose .....	A-49
1035A Power Cleaning.....	A-50
1035HT Power Cleaning, Non-Conductive .....	A-51
B9 General Purpose, Transfer Hose.....	A-52
CNG Compressed Natural Gas .....	A-53
D6 Constant Pressure, 3000 psi.....	A-22
Duraflex 528N/548N.....	A-64



**Parflex Thermoplastic Hose (cont.)**

H6 Constant Pressure, 3000 psi .....	A-23
HFS Firescreen® .....	A-24
HFS2 Firescreen II® .....	A-25
HJK Highjack® Jackline .....	A-29
HLB Lubrication Line.....	A-54
HTB Eliminator®, Compact .....	A-28
M8 High Pressure, Hydraulic.....	A-27
MSH Marine Steering .....	A-55
MSXL Marine Steering .....	A-56
PTH Marine Power Tilt.....	A-57
R6 Constant Pressure, Hydraulic Abrasion King® .....	A-26
S4 Predator® Water Jetting, 4000 psi.....	A-58
S5 Predator® Water Jetting, 4000 psi.....	A-59
S6 Predator® Water Jetting, 2500 psi .....	A-60
S9 Predator® Water Jetting, 3000 psi.....	A-61
SLH Sewer Leader .....	A-62
XDH eXtreme™ Duty .....	A-63

**Parflex Fluoropolymer Hose**

919/919B PTFE Hose, Natural & Static Dissipative Core Tube .....	A-65
919J PTFE Hose, Silicone Jacket .....	A-66
919U PTFE Hose, High Abrasion Resistance .....	A-67
929/929B Heavy Wall PTFE Hose, Natural & Static Dissipative Core Tube .....	A-68
929BJ PTFE Hose, Static Dissipative Core Tube, Silicone Jacket.....	A-69
939/939B Convoluted PTFE Hose, Natural & Static Dissipative Core Tube .....	A-70
943B High Pressure PTFE Hose, Static Dissipative Core Tube, 3000 psi.....	A-71
944B High Pressure PTFE Hose, Static Dissipative Core Tube, up to 4500 psi .....	A-72
950B High Pressure PTFE Hose, Static Dissipative Core Tube, 4000 psi.....	A-73
955B High Pressure PTFE Hose, Static Dissipative Core Tube, 5500 psi.....	A-74

**PAGE Fluoropolymer Hose**

S30/S30B PTFE Hose, Nominal I.D., Natural & Static Dissipative Core Tube.....	A-75
S40/S40B Heavy Wall PTFE Hose, Nominal I.D., Natural & Static Dissipative Core Tube .....	A-76
STW/STB PTFE Hose, "True-Bore", Natural & Static Dissipative Core Tube .....	A-77
SBFW/SBFB PTFE Hose, PAGE-flex® SBF, Natural & Static Dissipative Core Tube.....	A-78
SCW/SCB Convoluted PTFE Hose, SS Braid, Natural & Static Dissipative Core Tube .....	A-79
PCW/PCB Convoluted PTFE Hose, PP Braid, Natural & Static Dissipative Core Tube .....	A-80
SCWW/SCBV Heavy Wall Convoluted PTFE Hose, SS Braid, Natural & Static Dissipative Core Tube .....	A-81
PCWW/PCBV Heavy Wall Convoluted PTFE Hose, PP Braid, Natural & Static Dissipative Core Tube .....	A-82
SCWW-FS/SCBV-FS Flare-Seal® PTFE Hose, SS Braid, Natural & Static Dissipative Core Tube .....	A-83
PCWW-FS/PCBV-FS Flare-Seal® PTFE Hose, PP Braid, Natural & Static Dissipative Core Tube.....	A-84
RCTW/RCTB EPDM Rubber Covered Hose, Natural & Static Dissipative Core Tube .....	A-85

For detailed ordering information, please consult price list or contact Parflex® Division.

# Parflex Hose Visual Index

<b>Parflex Thermoplastic</b>		<b>510A</b> Refrigerant	<b>510C</b> General Hydraulic	<b>518C</b> Non-Conductive Hydraulic
		 A-34	 A-35	 A-36
<b>515H</b> Compact/Lightweight	<b>520N</b> General Hydraulic	<b>528N</b> Non-Conductive Hydraulic	<b>526BA</b> Breathing Air Refill 6000 PSI	
 A-37	 A-38	 A-38	 A-39	
<b>527BA</b> Breathing Air Refill 7000 PSI	<b>53DM</b> DuraMax™ Low Temperature 3000 PSI	<b>538DM</b> DuraMax™ Low Temperature, Non-Conductive 3000 PSI	<b>540N</b> General Hydraulic	
 A-40	 A-41	 A-41	 A-42	
<b>540P</b> Specialty Water	<b>55LT</b> Low Temperature	<b>560</b> General Hydraulic	<b>563</b> General Hydraulic	
 A-43	 A-44	 A-30	 A-31	
<b>56DH</b> Diagnostic Hose	<b>568DH</b> Non-Conductive Diagnostic Hose	<b>573X</b> Fast Response 3000 PSI	<b>575X</b> Fast Response 5000 PSI	
 A-45	 A-45	 A-46	 A-47	
<b>580N H580N</b> High Pressure	<b>588N</b> Non-Conductive High Pressure	<b>590</b> General Hydraulic Hose	<b>593</b> General Hydraulic Hose	
 A-48	 A-48	 A-32	 A-33	
<b>83FR</b> General Purpose	<b>1035A</b> Power Cleaning	<b>1035HT</b> High Temperature Power Cleaning	<b>B9</b> General Purpose	
 A-49	 A-50	 A-51	 A-52	
<b>CNG</b> Compressed Natural Gas	<b>D6</b> Constant Pressure 3000 PSI	<b>Duraflex</b> 528N & 548N	<b>H6</b> Constant Pressure Hydraulic	
 A-53	 A-22 <b>HYBRID</b>	 A-64	 A-23	
<b>HFS</b> Firescreen®	<b>HFS2</b> Firescreen II®	<b>HJK</b> Highjack® Jackline	<b>HLB</b> Lubrication Line	
 A-24 <b>HYBRID</b>	 A-25 <b>HYBRID</b>	 A-29 <b>HYBRID</b>	 A-54	



For detailed ordering information, please consult price list or contact Parflex® Division.



# Parflex Hose Visual Index (cont.)

<b>Parflex Thermoplastic (cont.)</b>		<b>HTB</b> Eliminator® Compact  A-28 <b>HYBRID</b>	<b>M8</b> High Pressure Hydraulic  A-27 <b>HYBRID</b>	<b>MSH</b> Marine Steering  A-55
		<b>MSXL</b> Marine Steering  A-56	<b>PTH</b> Marine Power Tilt  A-57	<b>R6</b> Constant Pressure Hydraulic  A-26
<b>S5</b> Predator® Water Jetting 4000 PSI  A-59	<b>S6</b> Predator® Water Jetting 2500 PSI  A-60	<b>S9</b> Predator® Water Jetting 3000 PSI  A-61	<b>SLH</b> Predator® Sewer Leader  A-62	
<b>XDH</b> eXtreme™ Duty Hose  A-63				

<b>Parflex PTFE</b>		<b>919</b> PTFE Hose  A-65	<b>919B</b> PTFE Hose with Static-Dissipative Tube  A-65	<b>919J</b> Silicone Jacketed PTFE Hose  A-66
		<b>919U</b> High Abrasion Resistance PTFE Hose  A-67	<b>929</b> Heavy Wall PTFE Hose  A-68	<b>929B</b> Heavy Wall PTFE Hose with Static-Dissipative Tube  A-68
<b>939</b> Convoluted PTFE Hose  A-70	<b>939B</b> Convoluted PTFE Hose with Static-Dissipative Tube  A-70	<b>943B</b> High Pressure PTFE Hose with Static-Dissipative Tube  A-71	<b>944B</b> High Pressure PTFE Hose with Static-Dissipative Tube  A-72	
<b>950B</b> High Pressure PTFE Hose with Static-Dissipative Tube  A-73	<b>955B</b> High Pressure PTFE Hose with Static-Dissipative Tube  A-74			

For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# Parflex Hose Visual Index (cont.)

<b>PAGE Product Line</b> <b>PTFE &amp; Specialty</b> Nominal I.D. "True Bore" I.D.	<b>S30</b> Industrial .030 wall with SS Braid  A-75	<b>S30B</b> Conductive Industrial .030 wall with SS Braid  A-75	<b>S40</b> Heavy Wall .040 with SS Braid  A-76
	<b>S40B</b> Conductive Heavy Wall .040 with SS Braid  A-76	<b>STW</b> "True-Bore" with SS Braid  A-77	<b>STB</b> Conductive "True-Bore" with SS Braid  A-77
<b>SBFB</b> Conductive PAGE-flex® SBF  A-78	<b>SCW</b> Convuluted with SS Braid  A-79	<b>SCB</b> Conductive Convuluted with SS Braid  A-79	<b>PCW</b> Convuluted with PP Braid  A-80
<b>PCB</b> Conductive Convuluted with PP Braid  A-80	<b>SCWV</b> Heavy Wall Convuluted with SS Braid  A-81	<b>SCBV</b> Conductive Heavy Wall Convuluted with SS Braid  A-81	<b>PCWV</b> Heavy Wall Convuluted with PP Braid  A-82
<b>PCBV</b> Conductive Heavy Wall Convuluted PP Braid  A-82	<b>SCWV-FS</b> Flare-Seal® with SS Braid  A-83	<b>SCBV-FS</b> Conductive Flare-Seal® with SS Braid  A-83	<b>PCWV-FS</b> Flare-Seal® with PP Braid  A-84
<b>PCBV-FS</b> Conductive Flare-Seal® with PP Braid  A-84	<b>RCTW</b> EPDM Rubber Covered Natural  A-85	<b>RCTB</b> EPDM Rubber Covered Conductive  A-85	

# Understanding Parflex Hoses

Parflex hoses are designed to handle extremes. They are used in some of the harshest applications around, such as over-the-sheave or aerial lift because they are specifically designed to handle extreme abrasion, temperatures, flexing, impulse and other factors that cause many hoses to fail.

## Hydraulic & Pneumatic Hose Selection

Parflex offers several lines of hydraulic and pneumatic hoses; General Hydraulic, Specialty and Hybrid hoses. Specialty hoses were designed to solve specific application problems. Hybrid Hoses belong specifically to Parflex, with no exact competitor equivalents. These hoses were developed to cross typical SAE boundaries and meet specific challenges our customers were bringing to us.

The visual index and hose pages indicate which hoses are Hybrid designs.

Review the STAMPED guide (Size, Temperature, Media, Application, Pressure, End Configuration, and Delivery Preferences) on page 11 to help narrow your search for the desired product.

## Fluoropolymer Selection

Parflex offers two lines of Fluoropolymer Hoses; the traditional Parflex PTFE hoses, many that meet 100R14 standards, and the PAGE hose line, comprised of specialty braid and construction options.

Hoses in PAGE product line are manufactured with materials that are compliant to the following standards:

- FDA 21 CFR 177.1550 and 177.2600
- USP XXII Class
- Pharmacopoeia 3.1.9
- ISO 10093, Sections 5, 6 10, and 11
- USDA Standards
- 3A Standards

The visual index and hose pages indicate which hoses are from the PAGE product line.

## Hose Assemblies

To determine hose part numbers for assemblies use the following nomenclature pages:

- Parflex Thermoplastic Hose Assembly Nomenclature pg. A-18
- Parflex PTFE Hose Assembly Nomenclature pg. A-19
- PAGE Product Line - Industrial S30 & S40 Hose Assembly Nomenclature pg. A-20
- PAGE Product Line - "True-Bore" & Convuluted Hose Assembly Nomenclature pg. A-21

*For detailed ordering information, please consult price list or contact Parflex® Division.*



# How to Read the Hose Section

Parker Parflex offers an extensive selection of thermoplastic, hybrid and PTFE hose products, covering the full range of industrial fluid transfer applications. Parflex hose products have been tested and approved to meet and exceed global standards. Hoses range in size from 1/16" to 4" I.D. and are compatible with permanent crimp and field attachable fittings.

## D6 – Hybrid Hose

Base part number, product description



### Features

Product features and benefits

### Certifications

Product certifications

## Applications/Markets

Product applications for all pertinent markets



Transportation



Mobile Hydraulics



Industrial Pneumatic



Industrial Hydraulics



Fluid Handling



Life Science



Food & Beverage

# How to Read the Hose Section

1 Part Number	2 Nominal I.D.		3 Maximum O.D.		4 Maximum Working Pressure		5 Minimum Bend Radius		6 Weight		7 Permanent Fitting Series
#											
	inch	mm	inch	mm	psi/73°F	bar/23°C	inch	mm	lbs./ft.	kg./mtr.	
D604	1/4	6	.51	13	3,000	20.7	2.00	51	.12	.18	43/HY

Base part number example.

**NOTE:** The primary dimensions are in black. The metric/inch equivalents appear in blue.

## 1 Part Number

Hose Series Part Number - When two part numbers are listed, the second number is the static-dissipative or non-conductive design.

## 2 Inside Diameter

A critical value along with pressure when calculating fluid flow rate and pressure drop.

## 3 Outside Diameter

A critical measurement when considering hose fittings and applications where envelope size is limited.

## 4 Working Pressure

Working pressure rating must meet or exceed the maximum operating pressure of the system including pressure spikes.

## 5 Minimum Bend Radius

Minimum radius that the hose can be bent. Exceeding the bend radius can cause kinking, inner tube washout, or excessive stress on reinforcement resulting in shortened service life.

## 6 Weight

Provided where weight is a critical parameter in the design of the system.

## 7 Approved Fitting

Permanent or field attachable fitting series approved for selected hose. Products with no fitting selection are only available in factory built assemblies.

# Thermoplastic Hose Selection PSI

Reinforcement Type		PSI Thermoplastic Hose Working Pressures												
		3/32	1/8	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2	
Dash Size		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	
Hose	Description	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	
Wire	D6 Hybrid - Constant Pressure Hydraulic				3000		3000	3000	3000	3000	3000			
	H6 Constrant Pressure Hydraulic				3000	3000	3000	3000	3000	3000				
	R6 Constrant Pressure Hydraulic				3000		3000	3000	3000	3000	3000			
	HFS Hybrid - General Hydraulic				3000	3000	2500	2500		1500	1250			
	HFS2 Hybrid - General Hydraulic				5000		4000	3500	2750	2250	2000			
	M8 Hybrid - High Pressure Hydraulic						4000	4000	4000					
	HTB Hybrid - Compact High Pressure Hydraulic				7000		5500	5000	4000	4000	3500			
	HJK Hybrid - Jackline				10000									
	560 General Hydraulic			3500	3250	3000	2750	2500	2000	1750				
	563 Constant Pressure Hydraulic				3000		3000	3000						
	590 General Hydraulic			5000	5000		4000	3500	3000	2500	2000			
	593 General Hydraulic									3000	3250			
	XDH Formed Hose				5000		4000	4000						
	Fiber	510A Industrial Refrigerant		2500	3000	2750	2500	2250	2000		1250	1000		
		510C General Hydraulic		2500	3250	3000	2500	2250	2250	1500	1250	1000		
518C Non-conductive Hydraulic			2500	3250	3000	2500	2250	2250	1500	1250	1000			
515H Compact/Lightweight Hydraulic				2175	2000	1750	1500	1500						
520N / 528N General Hydraulic / Non-conductive Hydraulic				5000	5000	4500	4000	3500						
526BA Breathing Air Refill				6000	6000		6000							
527BA Breathing Air Refill				7000	7000									
53DM / 538DM Low Temperature Hydraulic				3000	3000	3000	3000	3000	3000	3000				
540N General Hydraulic			3000	3000	2750	2500	2250	2000		1250				
540P Specialty Water					2750		2250	2000		1250				
55LT Low Temperature Hydraulic			3000	3250	3000	2500	2250	2000		1250				
56DH / 568DH Diagnostic		6000	6000											
573X Fast Response Hydraulic				3000								3000		
575X Fast Response Hydraulic				5000	5000		5000	5000		5000	5000			
580N / 588N General Hydraulic / Non-conductive Hydraulic					5000		4000	3500	2750	2250	2000			
H580N General Hydraulic											3000			
1035A Power Cleaning					1500	1200								
1035HT Power Cleaning				2000	1750	1500								
83FR General Purpose Air/Water					300		300	300		300				
B9 General Purpose Air/Water				250	250	250	250	250	250					
5CNG Compressed Natural Gas			5000	5000		5000	5000		5000	5000				
HLB Lubrication		3000	3000											
MSH Marine Steering					1000	1000								
MSXL Marine Steering					1500									
PTH Power Tilt				3000										
S4 Sewer Cleaning - Lateral Cleaning							4000	4000						
S5 Sewer Cleaning - Lateral Cleaning							4000							
S6 Sewer Cleaning									2500	2500	2500	2500		
S9 Sewer Cleaning									3000	3000				
SLH Sewer Cleaning Leader Hose							4000	4000	3000	3000				
Duraflex - 548N Aerial Lift - Hydraulic Tool							2250							
Duraflex - 528N Aerial Lift - Hydraulic Tool							4000							



For detailed ordering information, please consult price list or contact Parflex® Division.



# Construction/Specifications

## PSI Thermoplastic Construction and Specifications

Core Tube	Reinforcement Material	Cover Material	SAE Specification	Additional Specifications	Page #	Description		Reinforcement Type
							Hose	
P	Wire	R	100R17	MSHA IC-40/32	A-22	Hybrid - Constant Pressure Hydraulic	D6	Wire
P	Wire	P	100R17		A-23	Constrant Pressure Hydraulic	H6	
P	Wire	F	100R17		A-26	Constrant Pressure Hydraulic	R6	
P	Wire	R	100R1 / J1942	MSHA IC-40/32	A-24	Hybrid - General Hydraulic	HFS	
P	Wire	R	100R2 / 100R16 / J1942	MSHA IC-40/32	A-25	Hybrid - General Hydraulic	HFS2	
P	Wire	R	100R12	MSHA IC-40/32	A-27	Hybrid - High Pressure Hydraulic	M8	
P	Wire	R	J1942	MSHA IC-40/32	A-28	Hybrid - Compact High Pressure Hydraulic	HTB	
P	Wire	R	-	IJ-100	A-29	Hybrid - Jackline	HJK	
P	Wire	U	100R1	MSHA IC-40/32 / DNV	A-30	General Hydraulic	560	
P	Wire	U	100R17	MSHA IC-40/32	A-31	Constant Pressure Hydraulic	563	
P	Wire	U	100R2 / 100R16	DNV	A-32	General Hydraulic	590	
P / N	Wire	U	100R2	MSHA IC-40/32 / DNV	A-33	General Hydraulic	593	
PFX	Wire	PFX	100R2 / 100R16 / 100R17/100R19		A-63	Formed Hose	XDH	
PFX	Fiber	U	100R7	MSHA IC-40/32*	A-34	Industrial Refrigerant	510A	
P	Fiber	PFX	100R7	MSHA IC-40/32*	A-35	General Hydraulic	510C	
P	Fiber	PFX	100R7	DNV	A-36	Non-conductive Hydraulic	518C	
P	Fiber	U	-	MSHA IC-40/32	A-37	Compact/Lightweight Hydraulic	515H	
N	Fiber	U	100R8	MSHA IC-40/32 / DNV*	A-38	General Hydraulic / Non-conductive Hydraulic	520N / 528N	
N	Fiber	U	-	CGA / NFPA 1901	A-39	Breathing Air Refill	526BA	
N	Fiber	U	-	CGA / NFPA 1901	A-40	Breathing Air Refill	527BA	
P	Fiber	P	100R18		A-41	Low Temperature Hydraulic	53DM / 538DM	
N	Fiber	U	100R7	MSHA IC-40/32 / DNV	A-42	General Hydraulic	540N	
PE	Fiber	U	100R7	FDA / NSF 51	A-43	Specialty Water	540P	
P	Fiber	P	100R7		A-44	Low Temperature Hydraulic	55LT	
N	Fiber	U	-	MSHA IC-40/32*	A-45	Diagnostic	56DH / 568DH	
N	Fiber	U	-	MSHA IC-40/32 / DNV*	A-46	Fast Response Hydraulic	573X	
N	Fiber	U	-	MSHA IC-40/32 / DNV	A-47	Fast Response Hydraulic	575X	
N	Fiber	U	100R8	MSHA IC-40/32 / DNV*	A-48	General Hydraulic / Non-conductive Hydraulic	580N / 588N	
N	Fiber	U	100R8	DNV	A-48	General Hydraulic	H580N	
PFX	Fiber	U	-		A-50	Power Cleaning	1035A	
N	Fiber	U	-		A-51	Power Cleaning	1035HT	
U	Fiber	U	-	DNV	A-49	General Purpose Air/Water	83FR	
U	Fiber	U	-		A-52	General Purpose Air/Water	B9	
N	Fiber	U	-	ANSI IAS NGV4.2-CSA 12.52 / ECE R110*	A-53	Compressed Natural Gas	CNG	
P	Fiber	U	-	MSHA IC-40/32	A-54	Lubrication	HLB	
N	Fiber	U	-		A-55	Marine Steering	MSH	
N	Fiber	U	-		A-56	Marine Steering	MSXL	
N	Fiber / SS Wire	U	-		A-57	Power Tilt	PTH	
P	Fiber	U	-	Wastec WRP05-1996	A-58	Sewer Cleaning - Lateral Cleaning	S4	
P	Fiber	U	-	Wastec WRP05-1996	A-59	Sewer Cleaning - Lateral Cleaning	S5	
P	Fiber	U	-	Wastec WRP05-1996	A-60	Sewer Cleaning	S6	
P	Fiber	U	-	Wastec WRP05-1996	A-61	Sewer Cleaning	S9	
P	Wire	R	-		A-62	Sewer Cleaning Leader Hose	SLH	
N	Fiber	U	100R7		A-64	Aerial Lift - Hydraulic Tool	Duraflex - 548N	
N	Fiber	U	100R8		A-64	Aerial Lift - Hydraulic Tool	Duraflex - 528N	

\*View Government & Agency Specifications for exceptions, pg. G-59

### Legend

N – Nylon  
NP – Neoprene  
P – Copolyester  
PE – Polyethylene  
PFX – Proprietary Mat'l  
S – Silicone  
R – Rubber  
U – Urethane  
F – Fiber

For detailed ordering information, please consult price list or contact Parflex® Division.



# Fluoropolymer Hose Selection PSI

Reinforcement Type		PSI Fluoropolymer Hose Working Pressures															
		Fractional Size	Nominal Sizes														
			1/8	3/16	1/4	5/16	13/32	1/2	5/8	7/8	1-1/8	1/8	1/4	3/8	1/2	5/8	
				15/64			7/16			29/32							
Dash Size		-3	-4	-5	-6	-8	-10	-12	-16	-20	-3	-4	-6	-8	-10		
		PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI	PSI		
Wire	919	PTFE Hose	3000	3000	3000	2500	2000	1500	1200	1000	625						
	919B	PTFE Hose with static-dissipative core		3000	3000	2500	2000										
	919J	Silicone Jacketed PTFE Hose		3000	3000	2500	2000	1500	1200								
	919U	High Abrasion Resistance PTFE Hose		3000		2500	2000		1200	1000							
	929	Heavy Wall PTFE Hose		3000		2500	2000										
	929B	Heavy Wall PTFE Hose with static-dissipative core		3000		2500	2000		1200	1250							
	929BJ	Silicone Jacketed PTFE Hose with static-dissipative core		3000		2500	2000		1200	1250							
	939	Convoluted PTFE Hose												1500	1350	1000	
	939B	Convoluted PTFE Hose with static-dissipative core												1500	1350	1000	
	943B	High Pressure PTFE Hose with static-dissipative core				3000	3000	3000	3000	3000							
	944B	High Pressure PTFE Hose with static-dissipative core		4500		4500	4500	4500	4500	4000							
	950B	High Pressure PTFE Hose with static-dissipative core		4000		4000	4000	4000	4000	4000							
	955B	High Pressure PTFE Hose with static-dissipative core		5500		5500	5500	5500	5500	5500							
	S30	PAGE Ind. PTFE Hose	3000	3000	3000	2500	2000	1750	1500	1000							
	S30B	PAGE Ind. PTFE Hose with static-dissipative core	3000	3000	3000	2500	2000	1750	1500	1000							
S40	PAGE Ind. Heavy Wall PTFE Hose	3000	3000	3000	2500	2000	1750	1500	1000								
S40B	PAGE Ind. Heavy Wall PTFE Hose with static-dissipative core	3000	3000	3000	2500	2000	1750	1500	1000								
STW Z-STW*	PAGE Heavy Wall PTFE Hose *Double Braid										3000	3000	2000	1750			
STB Z-STB*	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid										3000	3000	2000	1750			
SCW	PAGE Convoluted PTFE Hose											1500	1500	1500			
SCB	PAGE Convoluted PTFE Hose with static-dissipative core											1500	1500	1500			
SCWW	PAGE Heavy Wall Convoluted PTFE Hose													1500			
SCBV	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core													1500			
SCWW-FS	PAGE Flare-Seal® PTFE Hose													500			
SCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core													500			
Fiber	PCW	PAGE Convoluted PTFE Hose, PP Braid										350	350	300			
	PCB	PAGE Convoluted PTFE Hose with static-dissipative core, PP Braid										350	350	300			
	PCWW	PAGE Heavy Wall Convoluted PTFE Hose, PP Braid												300			
	PCBV	PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core, PP Braid												300			
	PCWW-FS	PAGE Flare-Seal® PTFE Hose, PP Braid												300			
	PCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid												300			
Other	RCTW	PAGE Rubber Covered EPDM												500			
	RCTB	PAGE Rubber Covered EPDM with static-dissipative core												500			
	SBFW	PAGE Page-Flex® SBF												300	300		
	SBFB	PAGE Page-Flex® SBF with static-dissipative core												300	300		

\*Z indicates double braid.

**Legend**

PTFE – Polytetrafluoroethylene

PTFE-S – Polytetrafluoroethylene, Static Dissipative

FEP – Fluorinated Ethylene Propylene

PFA – Perfluoroalkoxy



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

# Construction/Specifications

PSI Fluoropolymer Construction and Specifications														Reinforcement Type	
3/4	1	1 1/4	1 1/2	2	2-1/2	3	4					Fractional Size			
-12 PSI	-16 PSI	-20 PSI	-24 PSI	-32 PSI	-40 PSI	-48 PSI	-64 PSI	Core Tube	Reinforcement Material	Cover Material	Page #	Dash Size			
								PTFE	SS Wire	—	A-65	PTFE Hose		919	
								PTFE-S	SS Wire	—	A-65	PTFE Hose with static-dissipative core		919B	
								PTFE	SS Wire	S	A-66	Silicone Jacketed PTFE Hose		919J	
								PTFE	SS Wire	U	A-67	High Abrasion Resistance PTFE Hose		919U	
								PTFE	SS Wire	—	A-68	Heavy Wall PTFE Hose		929	
								PTFE-S	SS Wire	—	A-68	Heavy Wall PTFE Hose with static-dissipative core		929B	
								PTFE-S	SS Wire	S	A-69	Silicone Jacketed PTFE Hose with static-dissipative core		929BJ	
	1100	1000	1000	750	250			PTFE	SS Wire	—	A-70	Convuluted PTFE Hose		939	
	1100	1000	1000	1000	1000			PTFE-S	SS Wire	—	A-70	Convuluted PTFE Hose with static-dissipative core		939B	
								PTFE-S	SS Wire	—	A-71	High Pressure PTFE Hose with static-dissipative core		943B	
								PTFE-S	SS Wire	—	A-72	High Pressure PTFE Hose with static-dissipative core		944B	
								PTFE-S	SS Wire	—	A-73	High Pressure PTFE Hose with static-dissipative core		950B	
								PTFE-S	SS Wire	—	A-74	High Pressure PTFE Hose with static-dissipative core		955B	
								PTFE	SS Wire	—	A-75	PAGE Ind. PTFE Hose		S30	
								PTFE-S	SS Wire	—	A-75	PAGE Ind. PTFE Hose with static-dissipative core		S30B	
								PTFE	SS Wire	—	A-76	PAGE Ind. Heavy Wall PTFE Hose		S40	
								PTFE-S	SS Wire	—	A-76	PAGE Ind. Heavy Wall PTFE Hose with static-dissipative core		S40B	
	1000	1000 1200*	1000*	900*				PTFE	SS Wire	—	A-77	PAGE Heavy Wall PTFE Hose *Double Braid		STW Z-STW*	
	1000	1000 1200*	1000*	900*				PTFE-S	SS Wire	—	A-77	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid		STB Z-STB*	
	1200	1000	750	650	450			PTFE	SS Wire	—	A-79	PAGE Convuluted PTFE Hose		SCW	
	1200	1000	750	650	450			PTFE-S	SS Wire	—	A-79	PAGE Convuluted PTFE Hose with static-dissipative core		SCB	
	1200	1000	750	650	450	200	175	150	PTFE	SS Wire	—	A-81	PAGE Heavy Wall Convuluted PTFE Hose		SCWV
	1200	1000	750	650	450	200	175	150	PTFE-S	SS Wire	—	A-81	PAGE Heavy Wall Convuluted PTFE Hose with static-dissipative core		SCBV
	425	350	325	300	250	200	175	150	PTFE	SS Wire	—	A-83	PAGE Flare-Seal® PTFE Hose		SCWV-FS
	425	350	325	300	250	200	175	150	PTFE-S	SS Wire	—	A-83	PAGE Flare-Seal® PTFE Hose with static-dissipative core		SCBV-FS
	250	250	200	200	200	200	200	200	PTFE	PP	—	A-80	PAGE Convuluted PTFE Hose, PP Braid		PCW
	250	250	200	200	200	200	200	200	PTFE-S	PP	—	A-80	PAGE Convuluted PTFE Hose with static-dissipative core, PP Braid		PCB
	250	250	200	200	200	150	125	100	PTFE	PP	—	A-82	PAGE Heavy Wall Convuluted PTFE Hose, PP Braid		PCWV
	250	250	200	200	200	150	125	100	PTFE-S	PP	—	A-82	PAGE Heavy Wall Convuluted PTFE Hose with static-dissipative core, PP Braid		PCBV
	250	250	200	200	200	150	125	100	PTFE	PP	—	A-84	PAGE Flare-Seal® PTFE Hose, PP Braid		PCWV-FS
	250	250	200	200	200	150	125	100	PTFE-S	PP	—	A-84	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid		PCBV-FS
	500	450	375	375	300	200	200	150	FEP	Double Wire Helix	EPDM	A-85	PAGE Rubber Covered EPDM		RCTW
	500	450	375	375	300	200	200	150	PFA-S	Double Wire Helix	EPDM	A-85	PAGE Rubber Covered EPDM with static-dissipative core		RCTB
	250	250		200					PFA	Bonded Wire-Silicone-Fiber	—	A-78	PAGE Page-Flex® SBF		SBFW
	250	250		200					PFA-S	Bonded Wire-Silicone-Fiber	—	A-78	PAGE Page-Flex® SBF with static-dissipative core		SBFB

PFA-S – Perfluoroalkoxy, Static Dissipative  
PP – Polypropylene

S – Silicone  
U – Polyurethane

For detailed ordering information, please consult price list or contact Parflex® Division.





# Thermoplastic Hose Selection MPa

Reinforcement Type	MPa Thermoplastic Hose Working Pressures													
	Dash Size		3/32	1/8	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2
	Hose	Description	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa
Wire	D6	Hybrid - Constant Pressure Hydraulic				20.7		20.7	20.7	20.7	20.7	20.7		
	H6	Constrant Pressure Hydraulic				20.7	20.7	20.7	20.7	20.7	20.7			
	R6	Constrant Pressure Hydraulic				20.7		20.7	20.7	20.7	20.7	20.7		
	HFS	Hybrid - General Hydraulic				20.7	20.7	17.2	17.2		10.3	8.6		
	HFS2	Hybrid - General Hydraulic				34.5		27.6	24.1	19.0	15.5	13.8		
	M8	Hybrid - High Pressure Hydraulic						27.6	27.6	27.6				
	HTB	Hybrid - Compact High Pressure Hydraulic				48.3		37.9	34.5	27.6	27.6	24.1		
	HJK	Hybrid - Jackline				68.9								
	560	General Hydraulic			24.1	22.4	20.7	19.0	17.2	13.8	12.1			
	563	Constant Pressure Hydraulic				20.7		20.7	20.7					
	590	General Hydraulic			34.5	34.5		27.6	24.1	20.7	17.2	13.8		
	593	General Hydraulic								20.7	22.4			
	XDH	Formed Hose				34.5		27.6	27.6					
Fiber	510A	Industrial Refrigerant		17.2	20.7	19.0	17.2	15.5	13.8		8.6	6.9		
	510C	General Hydraulic		17.2	22.4	20.7	17.2	15.5	15.5	10.3	8.6	6.9		
	518C	Non-conductive Hydraulic		17.2	22.4	20.7	17.2	15.5	15.5	10.3	8.6	6.9		
	515H	Compact/Lightweight Hydraulic			15.0	13.8	12.1	10.3	10.3					
	520N / 528N	General Hydraulic / Non-conductive Hydraulic			34.5	34.5	31.0	27.6	24.1					
	526BA	Breathing Air Refill			41.4	41.4		41.4						
	527BA	Breathing Air Refill			48.3	48.3								
	53DM / 538DM	Low Temperature Hydraulic			20.7	20.7	20.7	20.7	20.7	20.7	20.7			
	540N	General Hydraulic		20.7	20.7	19.0	17.2	15.5	13.8		8.6			
	540P	Specialty Water				19.0		15.5	13.8		8.6			
	55LT	Low Temperature Hydraulic		20.7	22.4	20.7	17.2	15.5	13.8		8.6			
	56DH / 568DH	Diagnostic	41.4	41.4										
	573X	Fast Response Hydraulic			20.7							20.7		
	575X	Fast Response Hydraulic			34.5	34.5		34.5	34.5		34.5	34.5		
	580N / 588N	General Hydraulic / Non-conductive Hydraulic				34.5		27.6	24.1	19.0	15.5	13.8		
	H580N	General Hydraulic										20.7		
	1035A	Power Cleaning				10.3	8.3							
	1035HT	Power Cleaning			13.8	12.1	10.3							
	83FR	General Purpose Air/Water				2.1		2.1	2.1		2.1			
	B9	General Purpose Air/Water			1.7	1.7	1.7	1.7	1.7	1.7				
	5CNG	Compressed Natural Gas			34.5	34.5		34.5	34.5		34.5	34.5		
	HLB	Lubrication		20.7	20.7									
	MSH	Marine Steering					6.9	6.9						
	MSXL	Marine Steering					10.3							
	PTH	Power Tilt				20.7								
	S4	Sewer Cleaning - Lateral Cleaning							27.6	27.6				
S5	Sewer Cleaning - Lateral Cleaning							27.6						
S6	Sewer Cleaning									17.2	17.2	17.2	17.2	
S9	Sewer Cleaning									20.7	20.7			
SLH	Sewer Cleaning Leader Hose							27.6	27.6	20.7	20.7			
Duraflex - 548N	Aerial Lift - Hydraulic Tool						15.5							
Duraflex - 528N	Aerial Lift - Hydraulic Tool						27.6							



For detailed ordering information, please consult price list or contact Parflex® Division.

# Construction/Specifications

## MPa Thermoplastic Construction and Specifications

Core Tube	Reinforcement Material	Cover Material	SAE Specification	Additional Specifications	Page #	Description		Reinforcement Type
						Description	Hose	
P	Wire	R	100R17	MSHA IC-40/32	A-22	Hybrid - Constant Pressure Hydraulic	D6	Wire
P	Wire	P	100R17		A-23	Constrant Pressure Hydraulic	H6	
P	Wire	F	100R17		A-26	Constrant Pressure Hydraulic	R6	
P	Wire	R	100R1 / J1942	MSHA IC-40/32	A-24	Hybrid - General Hydraulic	HFS	Wire
P	Wire	R	100R2 / 100R16 / J1942	MSHA IC-40/32	A-25	Hybrid - General Hydraulic	HFS2	
P	Wire	R	100R12	MSHA IC-40/32	A-27	Hybrid - High Pressure Hydraulic	M8	
P	Wire	R	J1942	MSHA IC-40/32	A-28	Hybrid - Compact High Pressure Hydraulic	HTB	
P	Wire	R	-	IJ-100	A-29	Hybrid - Jackline	HJK	
P	Wire	U	100R1	MSHA IC-40/32 / DNV	A-30	General Hydraulic	560	
P	Wire	U	100R17	MSHA IC-40/32	A-31	Constant Pressure Hydraulic	563	
P	Wire	U	100R2 / 100R16	DNV	A-32	General Hydraulic	590	
P / N	Wire	U	100R2	MSHA IC-40/32 / DNV	A-33	General Hydraulic	593	
PFX	Wire	PFX	100R2 / 100R16 / 100R17/100R19		A-63	Formed Hose	XDH	
PFX	Fiber	U	100R7	MSHA IC-40/32*	A-34	Industrial Refrigerant	510A	Fiber
P	Fiber	PFX	100R7	MSHA IC-40/32*	A-35	General Hydraulic	510C	
P	Fiber	PFX	100R7	DNV	A-36	Non-conductive Hydraulic	518C	
P	Fiber	U	-	MSHA IC-40/32	A-37	Compact/Lightweight Hydraulic	515H	
N	Fiber	U	100R8	MSHA IC-40/32 / DNV*	A-38	General Hydraulic / Non-conductive Hydraulic"	520N / 528N	
N	Fiber	U	-	CGA / NFPA 1901	A-39	Breathing Air Refill	526BA	
N	Fiber	U	-	CGA / NFPA 1901	A-40	Breathing Air Refill	527BA	
P	Fiber	P	100R18		A-41	Low Temperature Hydraulic	53DM / 538DM	
N	Fiber	U	100R7	MSHA IC-40/32 / DNV	A-42	General Hydraulic	540N	
PE	Fiber	U	100R7	FDA / NSF 51	A-43	Specialty Water	540P	
P	Fiber	P	100R7		A-44	Low Temperature Hydraulic	55LT	
N	Fiber	U	-	MSHA IC-40/32*	A-45	Diagnostic	56DH / 568DH	
N	Fiber	U	-	MSHA IC-40/32 / DNV*	A-46	Fast Response Hydraulic	573X	
N	Fiber	U	-	MSHA IC-40/32 / DNV	A-47	Fast Response Hydraulic	575X	
N	Fiber	U	100R8	MSHA IC-40/32 / DNV*	A-48	General Hydraulic / Non-conductive Hydraulic	580N / 588N	
N	Fiber	U	100R8	DNV	A-48	General Hydraulic	H580N	
PFX	Fiber	U	-		A-50	Power Cleaning	1035A	
N	Fiber	U	-		A-51	Power Cleaning	1035HT	
U	Fiber	U	-	DNV	A-49	General Purpose Air/Water	83FR	
U	Fiber	U	-		A-52	General Purpose Air/Water	B9	
N	Fiber	U	-	ANSI IAS NGV4.2-CSA 12.52 / ECE R110*	A-53	Compressed Natural Gas	CNG	
P	Fiber	U	-	MSHA IC-40/32	A-54	Lubrication	HLB	
N	Fiber	U	-		A-55	Marine Steering	MSH	
N	Fiber	U	-		A-56	Marine Steering	MSXL	
N	Fiber / SS Wire	U	-		A-57	Power Tilt	PTH	
P	Fiber	U	-	Wastec WRP05-1996	A-58	Sewer Cleaning - Lateral Cleaning	S4	
P	Fiber	U	-	Wastec WRP05-1996	A-59	Sewer Cleaning - Lateral Cleaning	S5	
P	Fiber	U	-	Wastec WRP05-1996	A-60	Sewer Cleaning	S6	
P	Fiber	U	-	Wastec WRP05-1996	A-61	Sewer Cleaning	S9	
P	Wire	R	-		A-62	Sewer Cleaning Leader Hose	SLH	
N	Fiber	U	100R7		A-64	Aerial Lift - Hydraulic Tool	Duraflex - 548N	
N	Fiber	U	100R8		A-64	Aerial Lift - Hydraulic Tool	Duraflex - 528N	

\*View Government & Agency Specifications for exceptions, pg. G-59

### Legend

N – Nylon  
NP – Neoprene  
P – Copolyester  
PE – Polyethylene  
PFX – Proprietary Mat'l  
S – Silicone  
R – Rubber  
U – Urethane  
F – Fiber

For detailed ordering information, please consult price list or contact Parflex® Division.



# Fluoropolymer Hose Selection MPa

Reinforcement Type		MPa Fluoropolymer Hose Working Pressures															
		Fractional Size	Nominal Sizes														
			1/8	3/16	1/4	5/16	13/32	1/2	5/8	7/8	1-1/8	1/8	1/4	3/8	1/2	5/8	
			15/64	7/16	29/32	-3	-4	-5	-6	-8	-10	-12.1	-16	-20	-3	-4	-6
Dash Size		MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa	MPa
Wire	919	PTFE Hose	20.7	20.7	20.7	17.2	13.8	10.3	8.3	6.9	4.3						
	919B	PTFE Hose with static-dissipative core	20.7	20.7	17.2	13.8											
	919J	Silicone Jacketed PTFE Hose	20.7	20.7	17.2	13.8	10.3	8.3									
	919U	High Abrasion Resistance PTFE Hose	20.7		17.2	13.8		8.3	6.9								
	929	Heavy Wall PTFE Hose	20.7		17.2	13.8											
	929B	Heavy Wall PTFE Hose with static-dissipative core	20.7		17.2	13.8		8.3	9								
	929BJ	Silicone Jacketed PTFE Hose with static-dissipative core	20.7		17.2	13.8		8.3	9								
	939	Convuluted PTFE Hose												10.3	9.3	6.9	
	939B	Convuluted PTFE Hose with static-dissipative core												10.3	9.3	6.9	
	943B	High Pressure PTFE Hose with static-dissipative core				20.7	20.7	20.7	20.7	20.7							
944B	High Pressure PTFE Hose with static-dissipative core		31.0		31.0	31.0	31.0	31.0	27.5								
950B	High Pressure PTFE Hose with static-dissipative core		27.5		27.5	27.5	27.5	27.5	27.5								
955B	High Pressure PTFE Hose with static-dissipative core		37.9		37.9	37.9	37.9	37.9	37.9								
S30	PAGE Ind. PTFE Hose	20.7	20.7	20.7	17.2	13.8	12.1	10.3	6.9								
S30B	PAGE Ind. PTFE Hose with static-dissipative core	20.7	20.7	20.7	17.2	13.8	12.1	10.3	6.9								
S40	PAGE Ind. Heavy Wall PTFE Hose	20.7	20.7	20.7	17.2	13.8	12.1	10.3	6.9								
S40B	PAGE Ind. Heavy Wall PTFE Hose with static-dissipative core	20.7	20.7	20.7	17.2	13.8	12.1	10.3	6.9								
STW Z-STW*	PAGE Heavy Wall PTFE Hose *Double Braid												20.7	20.7	13.8	12.1	
STB Z-STB*	PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid												20.7	20.7	13.8	12.1	
SCW	PAGE Convuluted PTFE Hose												10.3	10.3	10.3		
SCB	PAGE Convuluted PTFE Hose with static-dissipative core												10.3	10.3	10.3		
SCWV	PAGE Heavy Wall Convuluted PTFE Hose														10.3		
SCBV	PAGE Heavy Wall Convuluted PTFE Hose with static-dissipative core														10.3		
SCWV-FS	PAGE Flare-Seal® PTFE Hose														3.5		
SCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core														3.5		
Fiber	PCW	PAGE Convuluted PTFE Hose, PP Braid												2.4	2.4	2.1	
	PCB	PAGE Convuluted PTFE Hose with static-dissipative core, PP Braid												2.4	2.4	2.1	
	PCWV	PAGE Heavy Wall Convuluted PTFE Hose, PP Braid														2.1	
	PCBV	PAGE Heavy Wall Convuluted PTFE Hose with static-dissipative core, PP Braid														2.1	
	PCWV-FS	PAGE Flare-Seal® PTFE Hose, PP Braid														2.1	
	PCBV-FS	PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid														2.1	
Other	RCTW	PAGE Rubber Covered EPDM														3.5	
	RCTB	PAGE Rubber Covered EPDM with static-dissipative core														3.5	
	SBFW	PAGE Page-Flex® SBF														2.1	2.1
	SBFB	PAGE Page-Flex® SBF with static-dissipative core														2.1	2.1

\*Z indicates double braid.

**Legend**

PTFE – Polytetrafluoroethylene

PTFE-S – Polytetrafluoroethylene, Static Dissipative

FEP – Fluorinated Ethylene Propylene

PFA – Perfluoroalkoxy



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Construction/Specifications

PSI Fluoropolymer Construction and Specifications														Reinforcement Type
3/4	1	1 1/4	1 1/2	2	2-1/2	3	4						Fractional Size	
-12. PSI	-16 PSI	-20 PSI	-24 PSI	-32 PSI	-40 PSI	-48 PSI	-64 PSI	Core Tube	Reinforcement Material	Cover Material	Page #		Dash Size	
								PTFE	SS Wire	—	A-65		PTFE Hose	919
								PTFE-S	SS Wire	—	A-65		PTFE Hose with static-dissipative core	919B
								PTFE	SS Wire	S	A-66		Silicone Jacketed PTFE Hose	919J
								PTFE	SS Wire	U	A-67		High Abrasion Resistance PTFE Hose	919U
								PTFE	SS Wire	—	A-68		Heavy Wall PTFE Hose	929
								PTFE-S	SS Wire	—	A-68		Heavy Wall PTFE Hose with static-dissipative core	929B
								PTFE-S	SS Wire	S	A-69		Silicone Jacketed PTFE Hose with static-dissipative core	929BJ
7.6	6.9	6.9	5.2	1.7				PTFE	SS Wire	—	A-70		Convoluted PTFE Hose	939
7.6	6.9	6.9	5.2	1.7				PTFE-S	SS Wire	—	A-70		Convoluted PTFE Hose with static-dissipative core	939B
								PTFE-S	SS Wire	—	A-71		High Pressure PTFE Hose with static-dissipative core	943B
								PTFE-S	SS Wire	—	A-72		High Pressure PTFE Hose with static-dissipative core	944B
								PTFE-S	SS Wire	—	A-73		High Pressure PTFE Hose with static-dissipative core	950B
								PTFE-S	SS Wire	—	A-74		High Pressure PTFE Hose with static-dissipative core	955B
								PTFE	SS Wire	—	A-75		PAGE Ind. PTFE Hose	S30
								PTFE-S	SS Wire	—	A-75		PAGE Ind. PTFE Hose with static-dissipative core	S30B
								PTFE	SS Wire	—	A-76		PAGE Ind. Heavy Wall PTFE Hose	S40
								PTFE-S	SS Wire	—	A-76		PAGE Ind. Heavy Wall PTFE Hose with static-dissipative core	S40B
6.9	6.9 8.3*	6.9*	6.2*					PTFE	SS Wire	—	A-77		PAGE Heavy Wall PTFE Hose *Double Braid	STW Z-STW*
6.9	6.9 8.3*	6.9*	6.2*					PTFE-S	SS Wire	—	A-77		PAGE Heavy Wall PTFE Hose with static-dissipative core *Double Braid	STB Z-STB*
8.3	6.9	5.2	4.5	3.1				PTFE	SS Wire	—	A-79		PAGE Convoluted PTFE Hose	SCW
8.3	6.9	5.2	4.5	3.1				PTFE-S	SS Wire	—	A-79		PAGE Convoluted PTFE Hose with static-dissipative core	SCB
8.3	6.9	5.2	4.5	3.1	1.4	1.2	1.0	PTFE	SS Wire	—	A-81		PAGE Heavy Wall Convoluted PTFE Hose	SCWV
8.3	6.9	5.2	4.5	3.1	1.4	1.2	1.0	PTFE-S	SS Wire	—	A-81		PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core	SCBV
2.9	2.4	2.2	2.1	1.7	1.4	1.2	1.0	PTFE	SS Wire	—	A-83		PAGE Flare-Seal® PTFE Hose	SCWV-FS
2.9	2.4	2.2	2.1	1.7	1.4	1.2	1.0	PTFE-S	SS Wire	—	A-83		PAGE Flare-Seal® PTFE Hose with static-dissipative core	SCBV-FS
1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4	PTFE	PP	—	A-80		PAGE Convoluted PTFE Hose, PP Braid	PCW
1.7	1.7	1.4	1.4	1.4	1.4	1.4	1.4	PTFE-S	PP	—	A-80		PAGE Convoluted PTFE Hose with static-dissipative core, PP Braid	PCB
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE	PP	—	A-82		PAGE Heavy Wall Convoluted PTFE Hose, PP Braid	PCWV
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE-S	PP	—	A-82		PAGE Heavy Wall Convoluted PTFE Hose with static-dissipative core, PP Braid	PCBV
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE	PP	—	A-84		PAGE Flare-Seal® PTFE Hose, PP Braid	PCWV-FS
1.7	1.7	1.4	1.4	1.4	1.0	.86	.69	PTFE-S	PP	—	A-84		PAGE Flare-Seal® PTFE Hose with static-dissipative core, PP Braid	PCBV-FS
3.5	3.1	2.6	2.6	2.1	1.4	1.4	1.0	FEP	Double Wire Helix	EPDM	A-85		PAGE Rubber Covered EPDM	RCTW
3.5	3.1	2.6	2.6	2.1	1.4	1.4	1.0	PFA-S	Double Wire Helix	EPDM	A-85		PAGE Rubber Covered EPDM with static-dissipative core	RCTB
1.7	1.7		1.4					PFA	Bonded Wire-Silicone-Fiber	—	A-78		PAGE Page-Flex® SBF	SBFW
1.7	1.7		1.4					PFA-S	Bonded Wire-Silicone-Fiber	—	A-78		PAGE Page-Flex® SBF with static-dissipative core	SBFB

PFA-S – Perfluoroalkoxy, Static Dissipative  
PP - Polypropylene


S – Silicone  
U – Polyurethane

For detailed ordering information, please consult price list or contact Parflex® Division.



# Parflex Thermoplastic Hoses

## Parflex Thermoplastic Hose Assembly Nomenclature




F	Prefix	540N	Hose	06-39	Fitting Configuration*																																									
F	<p>F – Parkrimp (i.e. 55 series)</p> <p>A – Factory Crimp (i.e. 54 series)</p> <p>R – Field Attachable (i.e. 51 series)</p>		<table border="1"> <tr><td>D6</td><td>53DM</td></tr> <tr><td>H6</td><td>540N</td></tr> <tr><td>R6</td><td>540P</td></tr> <tr><td>HFS</td><td>55LT</td></tr> <tr><td>HFS2</td><td>56DH</td></tr> <tr><td>M8</td><td>575X</td></tr> <tr><td>HTB</td><td>580N</td></tr> <tr><td>HJK</td><td>H580N</td></tr> <tr><td>560</td><td>588N</td></tr> <tr><td>563</td><td>1035A</td></tr> <tr><td>590</td><td>1035HT</td></tr> <tr><td>593</td><td>83FR</td></tr> <tr><td>510A</td><td>B9</td></tr> <tr><td>510C</td><td>5CNG</td></tr> <tr><td>518C</td><td>HLB</td></tr> <tr><td>515H</td><td>MSH</td></tr> <tr><td>520N</td><td>MSXL</td></tr> <tr><td>528N</td><td>PTH</td></tr> <tr><td>526BA</td><td>SLH</td></tr> <tr><td>527BA</td><td></td></tr> </table>	D6	53DM	H6	540N	R6	540P	HFS	55LT	HFS2	56DH	M8	575X	HTB	580N	HJK	H580N	560	588N	563	1035A	590	1035HT	593	83FR	510A	B9	510C	5CNG	518C	HLB	515H	MSH	520N	MSXL	528N	PTH	526BA	SLH	527BA				<p>01 – Male Pipe Thread (with hex) - NPTF</p> <p>02 – Female Pipe Thread - NPT</p> <p>03 – Male SAE (JIC) 37° Flare</p> <p>05 – Male Straight Thread w/ O-Ring</p> <p>06 – Female SAE (JIC) 37° Swivel</p> <p>07 – Female Pipe Swivel</p> <p>13 – Male Pipe Swivel - NPTF</p> <p>37 – Female SAE (JIC) 37° Swivel - 45° Elbow</p> <p>39 – Female SAE (JIC) 37° Swivel - 90° Elbow</p> <p>41 – Female SAE (JIC) 37° Swivel - 90° Long Elbow</p> <p>JC – Female Seal-Lok™ (ORFS) Swivel Short</p> <p>FU – Female JIC/BSP 30° Flare Swivel</p> <p>MU – Metric Female JIC/BSP 30° Flare Swivel</p> <p>J0 – Male Seal-Lok™ (ORFS) Rigid Straight w/O-Ring</p> <p>GU – Female JIC/BSP Parallel Pipe Swive (60° Cone)</p> <p>JS – Female Seal-Lok™ (ORFS) Swivel</p> <p>J7 – Female Seal-Lok™ (ORFS) Swivel - 45° Elbow</p> <p>J9 – Female Seal-Lok™ (ORFS) Swivel - 90° Elbow</p> <p>TU – Universal Tube Stub</p> <p>AL – A-Lok® Compression</p>
D6	53DM																																													
H6	540N																																													
R6	540P																																													
HFS	55LT																																													
HFS2	56DH																																													
M8	575X																																													
HTB	580N																																													
HJK	H580N																																													
560	588N																																													
563	1035A																																													
590	1035HT																																													
593	83FR																																													
510A	B9																																													
510C	5CNG																																													
518C	HLB																																													
515H	MSH																																													
520N	MSXL																																													
528N	PTH																																													
526BA	SLH																																													
527BA																																														

\* See pg. E-4 for detailed list of available fitting configurations.

12	Connection Size 1	12	Connection Size 2	12	Hose Size	C	Fitting Material
-2	1 1/8	-2	2 1/8	-2	= 1/8	<p>** No Material Designation, Steel</p> <p>C = Stainless Steel</p> <p>B = Brass</p>	
-3	1 3/16	-3	2 3/16	-3	= 3/16		
-4	1 1/4	-4	2 1/4	-4	= 1/4		
-5	1 5/16	-5	2 5/16	-5	= 5/16		
-6	1 3/8	-6	2 3/8	-6	= 3/8		
-8	1 1/2	-8	2 1/2	-8	= 1/2		
-10	1 5/8	-10	2 5/8	-10	= 5/8		
-12	1 3/4	-12	2 3/4	-12	= 3/4		
-16	1 1	-16	2 1	-16	= 1		
-20	1 1-1/4	-20	2 1-1/4	-16	= 1		

52	Overall Length	##	Displacement Angle
	Expressed in inches		Specified only if two elbow fittings are used to construct hose assembly.



# Parflex PTFE Hoses

## Parflex PTFE Hose Assembly Nomenclature



**P** **919** **06** **39** **06** **06** **06** **C** - **30**

<b>P</b> Prefix	<b>919</b> Hose	<b>06-39</b> Fitting Configuration*																				
P – Permanent Crimp (i.e. 91N series) R – Field Attachable (i.e. 90 series) Factory Crimp (i.e. 94 series)	<table border="1"> <thead> <tr> <th>Natural</th> <th>Static Dissipative</th> </tr> </thead> <tbody> <tr><td>919</td><td>919B</td></tr> <tr><td>919J</td><td>929BJ</td></tr> <tr><td>919U</td><td>–</td></tr> <tr><td>929</td><td>929B</td></tr> <tr><td>939</td><td>939B</td></tr> <tr><td>–</td><td>943B</td></tr> <tr><td>–</td><td>944B</td></tr> <tr><td>–</td><td>950B</td></tr> <tr><td>–</td><td>944B</td></tr> </tbody> </table>	Natural	Static Dissipative	919	919B	919J	929BJ	919U	–	929	929B	939	939B	–	943B	–	944B	–	950B	–	944B	01 – Male Pipe Thread (with hex) - NPTF 02 – Female Pipe Thread - NPT 03 – Male SAE (JIC) 37° Flare 05 – Male Straight Thread w/ O-Ring 07 – Female Pipe Swivel 13 – Male Pipe Swivel - NPTF 37 – Female SAE (JIC) 37° Swivel - 45° Elbow 39 – Female SAE (JIC) 37° Swivel - 90° Elbow 41 – Female SAE (JIC) 37° Swivel - 90° Long Elbow JC – Female Seal-Lok™ (ORFS) Swivel Short FU – Female JIC/BSP 30° Flare Swivel MU – Metric Female JIC/BSP 30° Flare Swivel JO – Male Seal-Lok™ (ORFS) Rigid Straight w/O-Ring GU – Female JIC/BSP Parallel Pipe Swive (60° Cone) JS – Female Seal-Lok™ (ORFS) Swivel J7 – Female Seal-Lok™ (ORFS) Swivel - 45° Elbow J9 – Female Seal-Lok™ (ORFS) Swivel - 90° Elbow TU – Universal Tube Stub AL – A-Lok® Compression
	Natural	Static Dissipative																				
919	919B																					
919J	929BJ																					
919U	–																					
929	929B																					
939	939B																					
–	943B																					
–	944B																					
–	950B																					
–	944B																					

\* See pg. E-4 for detailed list of available fitting configurations.

<b>06</b> Connection Size 1	<b>06</b> Connection Size 2	<b>06</b> Hose Size	<b>C</b> Fitting Material	<b>30</b> Overall Length																																																																																																												
<table border="1"> <tr><td>-2</td><td>1</td><td>1/8</td></tr> <tr><td>-3</td><td>1</td><td>3/16</td></tr> <tr><td>-4</td><td>1</td><td>1/4</td></tr> <tr><td>-5</td><td>1</td><td>5/16</td></tr> <tr><td>-6</td><td>1</td><td>3/8</td></tr> <tr><td>-8</td><td>1</td><td>1/2</td></tr> <tr><td>-10</td><td>1</td><td>5/8</td></tr> <tr><td>-12</td><td>1</td><td>3/4</td></tr> <tr><td>-16</td><td>1</td><td>1</td></tr> <tr><td>-20</td><td>1</td><td>1-1/4</td></tr> <tr><td>-24</td><td>1</td><td>1-1/2</td></tr> <tr><td>-32</td><td>1</td><td>2</td></tr> </table>	-2	1	1/8	-3	1	3/16	-4	1	1/4	-5	1	5/16	-6	1	3/8	-8	1	1/2	-10	1	5/8	-12	1	3/4	-16	1	1	-20	1	1-1/4	-24	1	1-1/2	-32	1	2	<table border="1"> <tr><td>-2</td><td>2</td><td>1/8</td></tr> <tr><td>-3</td><td>2</td><td>3/16</td></tr> <tr><td>-4</td><td>2</td><td>1/4</td></tr> <tr><td>-5</td><td>2</td><td>5/16</td></tr> <tr><td>-6</td><td>2</td><td>3/8</td></tr> <tr><td>-8</td><td>2</td><td>1/2</td></tr> <tr><td>-10</td><td>2</td><td>5/8</td></tr> <tr><td>-12</td><td>2</td><td>3/4</td></tr> <tr><td>-16</td><td>2</td><td>1</td></tr> <tr><td>-20</td><td>2</td><td>1-1/4</td></tr> <tr><td>-24</td><td>2</td><td>1-1/2</td></tr> <tr><td>-32</td><td>2</td><td>2</td></tr> </table>	-2	2	1/8	-3	2	3/16	-4	2	1/4	-5	2	5/16	-6	2	3/8	-8	2	1/2	-10	2	5/8	-12	2	3/4	-16	2	1	-20	2	1-1/4	-24	2	1-1/2	-32	2	2	<table border="1"> <tr><td>-2</td><td>=</td><td>1/8</td></tr> <tr><td>-3</td><td>=</td><td>3/16</td></tr> <tr><td>-4</td><td>=</td><td>1/4</td></tr> <tr><td>-5</td><td>=</td><td>5/16</td></tr> <tr><td>-6</td><td>=</td><td>3/8</td></tr> <tr><td>-8</td><td>=</td><td>1/2</td></tr> <tr><td>-10</td><td>=</td><td>5/8</td></tr> <tr><td>-12</td><td>=</td><td>3/4</td></tr> <tr><td>-16</td><td>=</td><td>1</td></tr> <tr><td>-20</td><td>=</td><td>1-1/4</td></tr> <tr><td>-24</td><td>=</td><td>1-1/2</td></tr> <tr><td>-32</td><td>=</td><td>2</td></tr> </table>	-2	=	1/8	-3	=	3/16	-4	=	1/4	-5	=	5/16	-6	=	3/8	-8	=	1/2	-10	=	5/8	-12	=	3/4	-16	=	1	-20	=	1-1/4	-24	=	1-1/2	-32	=	2	** No Material Designation C = Stainless Steel B = Brass (91N) S = All Steel (91N)	Expressed in Inches OAL measured from centerline of fitting seat if elbow fittings are used.
-2	1	1/8																																																																																																														
-3	1	3/16																																																																																																														
-4	1	1/4																																																																																																														
-5	1	5/16																																																																																																														
-6	1	3/8																																																																																																														
-8	1	1/2																																																																																																														
-10	1	5/8																																																																																																														
-12	1	3/4																																																																																																														
-16	1	1																																																																																																														
-20	1	1-1/4																																																																																																														
-24	1	1-1/2																																																																																																														
-32	1	2																																																																																																														
-2	2	1/8																																																																																																														
-3	2	3/16																																																																																																														
-4	2	1/4																																																																																																														
-5	2	5/16																																																																																																														
-6	2	3/8																																																																																																														
-8	2	1/2																																																																																																														
-10	2	5/8																																																																																																														
-12	2	3/4																																																																																																														
-16	2	1																																																																																																														
-20	2	1-1/4																																																																																																														
-24	2	1-1/2																																																																																																														
-32	2	2																																																																																																														
-2	=	1/8																																																																																																														
-3	=	3/16																																																																																																														
-4	=	1/4																																																																																																														
-5	=	5/16																																																																																																														
-6	=	3/8																																																																																																														
-8	=	1/2																																																																																																														
-10	=	5/8																																																																																																														
-12	=	3/4																																																																																																														
-16	=	1																																																																																																														
-20	=	1-1/4																																																																																																														
-24	=	1-1/2																																																																																																														
-32	=	2																																																																																																														

<b>##</b> Displacement Angle
Specified only if two elbow fittings are used to construct hose assembly.


For detailed ordering information, please consult price list or contact Parflex® Division.





# Parflex PAGE Product Line

## PAGE Industrial S30 & S40 Hose Assembly Nomenclature



Assembly Code	
Permanently Attached	X
Field Attachable	FA

Size Code	
1/8"	03
3/16"	04
1/4"	05
5/16"	06
13/32"	08
1/2"	10
5/8"	12
7/8"	16
1-1/8"	20

Hose Code	
S30	S
S30B	SB
S40	H
S40B	HB
ZS40	R
ZS40B	RB
944B	944B
955B	955B

Fitting Code	
<b>Pipe Thread Fittings</b>	
Male Pipe NPT Hex	10
Male Pipe NPT Step Up	15
Male Pipe NPT Step Down	20
Male Union	11
Male Union 45°	14
Male Union 90°	19
Male Union Step Up	16
Male Union Step Down	21
Female Pipe NPT Hex	55
Female Pipe Step Up	58
Female Pipe Step Down	59
Female Union	80
Female Union Step Up	84
Female Union Step Down	88
<b>JIC Fittings</b>	
JIC Female Swivel	68
JIC Female 45° Elbow	66
JIC Female 90° Elbow	67
SAE Female Swivel	69
SAE Female 45° Elbow	70
SAE Female 90° Elbow	71
JIC Female Step Up	64
JIC Female Step Down	65
<b>Tube Stub Fittings</b>	
Tube Stub	91
Tube Stub Step Up	93
Tube Stub Step Down	95
SAE Male Compression	96
<b>Inverted Flare &amp; Power Trim Fittings</b>	
Male Straight	76

Fitting Material	
Stainless (SS)	S
Brass	B
Carbon Steel	C

Accessory Code	
None	
Spring Guard	S
Armour Guard	A
End Bend Restrictors	E
Fire Sleeve	F
Rubber Sleeve	H
FEP Heat Shrink	T
Polyolefin Heat Shrink	P
Silicone Sleeve	M
Internal Spring	I
Vacuum Spring Wire	W
Specials	X

**Example:** X08H10S68S0-0300  
**Size:** 08 (13/32 I.D.)      **Style:** S40  
**Braid:** SS Single Braid  
**Core:** Heavy Wall Smoothbore Convuluted PTFE  
**End 1:** 1/2" 316 SS Male NPT  
**End 2:** 1/2" 316 SS Female 37° Seat JIC Swivel



**Length:** 300" from end of Male Pipe to seat of Female JIC

**NOTE:** Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.



# Parflex PAGE Product Line

## “True-Bore” & Convoluted Hose Assembly Nomenclature



Size Code	
3/16"	03
1/4"	04
5/16"	05
3/8"	06
1/2"	08
5/8"	10
3/4"	12
7/8"	14
1"	16
1-1/4"	20
1-1/2"	24
2"	32
2-1/2"	40
3"	48
4"	64

Hose Code	
ACW	A
CBV	BV
CWV	V
KCB	RB
KCW	R
NCB	MB
NCW	M
PCB	NB
PCBV	PB
PCW	N
PCWV	P
RCTB	GB
RCTW	G
SBFV	SBF
SCB	TB
SCBV	JB
SCW	T
SCWV	J
STB	SB
STW	S

Fitting Code	
<b>Industrial Thread</b>	
Male Pipe NPT Hex	03
Female Pipe NPT Hex	06
Male Pipe NPT Step Down	13
Male Pipe NPT Step Up	23
Male Union Step Up	34
Male Union Step Down	35
JIC Female Swivel	30
Male JIC 37°	31
JIC Female Step Up	32
Male Union	33
Female Union	36
Female NPSH	27
Female ORFS Swivel	80
Male ORFS	81
Male O-Ring Boss	86
<b>Flanges</b>	
Flange Retainer	05
Flare-Seal® Flange Retainer	29
<b>Cam Lock</b>	
Female Cam Lock	07
With Locking Handles	17
Male Cam Lock	08
<b>Sanitary</b>	
Sanitary Tri Clamp	40
Sanitary Tri Clamp 45°	4K
Sanitary Tri Clamp 90°	4L
Sanitary 1-Step Up	4A
Sanitary 2-Step Up	4B
Sanitary 3-Step Up	4C
Sanitary Flare Seal™	4F
Sanitary Mini	42
Sanitary Mini Step Up	43
I-Line Male	48
I-Line Female	49
Bevel Seat Female	45
Bevel Seat Male	46
<b>Tube and Vacuum</b>	
PAGElok™ Tube Adapter	38
PAGElok™ Tube Compression Fitting	39
<b>Special Ends</b>	
Standard Cuffed Ends	90
Non Standard Fitting	99

Fitting Material	
304 Stainless (SS 304)	4
316 Stainless (SS 316)	6
316 Stainless (SS 15Ra) Electropolished to 15Ra	E
Carbon Steel	C
PFA Encapsulated	T
Hastelloy	H
Monel	M

Flange Material	
None	0
Carbon Steel Epoxy Coated	D
304SS	4
316SS	6
Kynar	K
Polypropylene	P
Non Standard	X

Accessory Code	
None	
Spring Guard	S
Armour Guard	A
End Bend Restrictors	E
Fire Sleeve	F
Rubber Sleeve	H
FEP Heat Shrink	T
Polyolefin Heat Shrink	P
Silicone Sleeve	M
Vacuum Spring Wire	W
Specials	X

**Example:** 32J03C13C0-0120-A  
**Size:** 2"    **Style:** SCWV  
**Braid:** 316 SS Single Braid  
**Core:** Heavy Wall Open Pitch Convoluted PTFE  
**End 1:** 2" Male Pipe NPT Hex  
**End 2:** 2" Male Pipe NPT Step Down

**Length:** 120" from end of Male NPT to end of Male Step Down

**NOTE:** Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

The part numbering system shows the entire product line offered by the Parker PAGE International business unit. This catalog section only displays a few common hoses. To order items not listed in this catalog, please contact Parker PAGE Customer Service direct at (800) 847-7280 or email [page@parker.com](mailto:page@parker.com).

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# D6 – Hybrid Hose



## Features

- Ideally suited for inventory consolidations to cover all SAE 100R1 pressure and many SAE 100R2 pressure requirements.

## Certifications

- Exceeds SAE 100R17
- MSHA Accepted

## Applications/Markets



- Medium pressure hydraulic applications
- Agricultural equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.	
#												
D604	1/4	6	.51	13	3,000	20.7	2.00	51	28	.12	.18	43**HY***
D606	3/8	10	.67	17	3,000	20.7	2.50	64	28	.19	.28	58/43**/HY***
D608	1/2	13	.82	21	3,000	20.7	3.50	89	28	.29	.43	58/43**/HY***
D610*	5/8	16	1.02	26	3,000	20.7	4.00	102	28	.47	.70	58/HY***
D612*	3/4	19	1.20	30	3,000	20.7	4.80	122	28	.73	1.09	43**/HY***
D616*	1	25	1.50	38	3,000	20.7	6.00	152	28	1.01	1.50	43**/HY***

## Construction

Tube: Copolyester

Reinforcement: One or two braids of high tensile steel wire

Cover: Smooth synthetic rubber

## Operating Parameters

Temperature Range:

-40°F to +250°F (-40°C to +121°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in length at working pressure is +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12

43 Series – (\*\*43 Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

\*Two wire braid



# H6 – High Performance Hydraulic Hose



## Features

- Largest temperature range in a medium pressure hydraulic hose
- Low length change capability under pressure
- Ideally suited for inventory consolidations to cover all SAE 100R1 pressure and many SAE 100R2 pressure and abrasion requirements

## Certifications

- Exceeds SAE 100R17 Requirements

## Applications/Markets



- Medium pressure hydraulic applications
- Over the sheave and boom hose applications

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
H604	1/4	6	.49	12	3,000	20.7	2.00	51	28	.12	.18	HY***
H605	5/16	8	.56	14	3,000	20.7	2.25	57	28	.14	.21	HY***
H606	3/8	10	.65	17	3,000	20.7	2.50	64	28	.19	.28	58/43**
H608	1/2	13	.78	20	3,000	20.7	3.50	89	28	.29	.43	58/HY***
H610*	5/8	16	1.00	25	3,000	20.7	4.00	102	28	.47	.70	HY***
H612*	3/4	19	1.17	30	3,000	20.7	4.75	121	28	.69	1.03	HY***

## Construction

Tube: Copolyester

Reinforcement: One or two braids of high tensile steel wire

Cover: Copolyester

## Operating Parameters

Temperature Range:

(H604 thru H608) -70°F to +250°F (-57°C to +121°C)

(H610 thru H612) -50°F to +250°F (-45°C to +121°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in length at working pressure is +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12

43 Series – (\*\*43 Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

\*Two wire braid

Twin line hose available

Preformed assemblies

For detailed ordering information, please consult price list or contact Parflex® Division.



# HFS – Firescreen® Hybrid Hose



## Features

- Excellent flexibility
- Consistent long-lengths
- Lightweight
- Compact design

## Certifications

- Exceeds SAE 100R1
- Marine Applications (SAE J1942 listed)
- MSHA Accepted

## Applications/Markets



- Used in high temperature (to +250° F), medium pressure hydraulic applications
- Mobile equipment
- Machine tools
- Agricultural equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.		
#													
HFS04	1/4	6	.51	13	3,000	20.7	2.00	51	28	.12	.18	43*/HY**	BA
HFS05	5/16	8	.59	15	3,000	20.7	2.25	57	28	.17	.25	HY**	–
HFS06	3/8	10	.67	17	2,500	17.2	2.50	64	28	.19	.28	58/43*/HY**	BA
HFS08	1/2	13	.79	20	2,500	17.2	3.50	89	28	.25	.37	58/43*/HY**	BA
HFS12	3/4	19	1.07	27	1,500	10.3	5.00	127	28	.37	.55	43*/HY**	–
HFS16	1	25	1.37	35	1,250	8.6	10.00	254	28	.53	.79	HY**	–

## Construction

Tube: Copolyester  
 Reinforcement: One braid of high tensile steel wire  
 Cover: Smooth synthetic rubber

## Operating Parameters

Temperature Range:  
 -40°F to +250°F (-40°C to +121°C)  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
 Change in working length @ Rated WPSI: +2%/-4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12  
 BA Series – pg. E-79  
 43 Series – (\*43 Series Fittings available from Parker Hose Products Division)  
 HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

# HFS2 – Firescreen II® Hybrid Hose



## Features

- Excellent flexibility
- Consistent long-lengths
- Lightweight
- Compact design

## Certifications

- Meets or Exceeds SAE 100R2 & 100R16
- Marine Applications (SAE J1942 listed)
- MSHA Accepted

## Applications/Markets



- Medium pressure hydraulic applications
- Mobile equipment
- Machine tools
- Agricultural equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
	#	inch	mm	inch	mm	psi	MPa	inch		mm	lbs./ft.		
HFS204*	1/4	6	.57	14	5,000	34.5	2.00	51	28	.21	.31	43**/HY***	BA
HFS206	3/8	10	.68	17	4,000	27.6	2.50	64	28	.23	.34	58/43**/HY***	BA
HFS208	1/2	13	.82	21	3,500	24.1	3.50	89	28	.29	.43	58/43**/HY***	BA
HFS210	5/8	16	.97	25	2,750	19.0	4.00	102	28	.38	.57	43**/HY***	–
HFS212	3/4	19	1.10	28	2,250	15.5	4.75	121	28	.45	.67	43**/HY***	BA
HFS216*	1	25	1.45	37	2,000	13.8	6.00	152	28	.80	1.19	43**/HY***	BA

## Construction

Tube: Copolyester

Reinforcement: One or two braids of high tensile steel wire

Cover: Smooth synthetic rubber

## Operating Parameters

Temperature Range:

-40°F to +212°F (-40°C to +100°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: +2%/-4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12

BA Series – pg. E-79

43 Series – (\*\*43 Series Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

\*Two wire braid

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)





# R6 – Abrasion King® Hose



## Features

- Excellent abrasion resistance
- Blue plait provides hose identification

## Certifications

- Exceeds SAE 100R17 Requirements

## Applications/Markets



- Medium pressure hydraulic applications
- Agricultural equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
R604	1/4	6	.53	13	3000	20.7	2.00	51	28	.11	.16	HY***
R606	3/8	10	.69	18	3000	20.7	2.50	64	28	.20	.30	58/HY***
R608	1/2	13	.84	21	3000	20.7	3.50	89	28	.27	.40	58/HY***
R610*	5/8	16	1.09	28	3000	20.7	4.00	102	28	.51	.76	HY***
R612*	3/4	19	1.24	31	3000	20.7	4.75	121	28	.71	1.06	HY***
R616*	1	25	1.55	39	3000	20.7	6.00	152	28	1.00	1.49	43**

## Construction

Tube: Copolyester

Reinforcement: One or two braids of high tensile steel wire

Cover: Abrasion-resistant Nylon Fabric

## Operating Parameters

Temperature Range:

(R604 thru R610) -50°F to +250°F (-46°C to +121°C)

(R612 thru R616) -50°F to +212°F (-45°C to +100°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: +2%/-4%

Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12

43 Series – (\*\*43 Series Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

\*Two wire braid



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

# M8 – E-Z FLEX™ Hybrid Hose



## Features

- Four-spiral wire hose performance in a high tensile two-wire braid construction
- Excellent flexibility
- Consistent long-lengths

## Certifications

- Meets or Exceeds SAE 100R12
- MSHA Accepted

## Applications/Markets



- High-pressure hydraulic applications typically reserved for spiral wire reinforced hoses

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
M806	3/8	10	.76	19	4,000	27.6	2.50	64	28	.37	.55	43*
M808	1/2	13	.90	23	4,000	27.6	3.50	89	28	.46	.68	43*
M810	5/8	16	1.07	27	4,000	27.6	4.00	102	28	.63	.94	43*

## Construction

Tube: Copolyester  
 Reinforcement: Two braids of high tensile steel wire  
 Cover: Smooth synthetic rubber

## Operating Parameters

Temperature Range:  
 -40°F to +250°F (-40°C to +121°C)  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
 Change in working length @ Rated WPSI: +2%/-4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

43 Series – (\*43 Series Fittings available from Parker Hose Products Division)

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

For detailed ordering information, please consult price list or contact Parflex® Division.



# HTB – Eliminator® Hybrid Hose



## Features

- Four-spiral wire hose performance in a high tensile two-wire braid construction
- Excellent flexibility
- Consistent long-lengths

## Certifications

- Marine Applications (SAE J1942 listed)
- MSHA Accepted

## Applications/Markets



- High-pressure hydraulic applications typically reserved for spiral wire reinforced hoses

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
HTB04	1/4	6	.62	16	7,000	48.3	4.00	102	28	.27	.40	HY**
HTB06	3/8	10	.76	19	5,500	37.9	6.00	152	28	.37	.55	43***
HTB08	1/2	13	.90	23	5,000	34.5	7.00	178	28	.46	.68	43***
HTB10	5/8	16	1.03	26	4,000	27.6	8.00	203	28	.52	.77	43***
HTB12	3/4	20	1.20	30	4,000	27.6	9.50	241	28	.73	1.09	43***
HTB16	1	25	1.50	38	3,500	24.1	12.00	305	28	1.01	1.50	43***

## Construction

Tube: Copolyester

Reinforcement: Two braids of high tensile steel wire

Cover: Smooth synthetic rubber

## Operating Parameters

Temperature Range:

-40°F to +212°F (-40°C to +100°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: +2%/-4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

43 Series – (\*\*43 Series Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

HTB04 cover must be skived prior to fitting attachment



# HJK – Highjack® Jackline Hybrid Hose



## Features

- 10,000 PSI Jack Hose

## Certifications

- MSHA Accepted
- Meets IJ-100 Requirements

## Applications/Markets



- Used for high pressure jackline applications
- Not for high impulse applications

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.
HJK04	1/4	6	.62	16	10,000	69	4.0	102	28	.27	.40

## Construction

Tube: Copolyester

Reinforcement: Two braids of High Tensile Wire

Cover: Smooth synthetic rubber

## Operating Parameters

Temperature Range:

-40°F to +150°F (-40°C to +65°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 3x Max. Working Pressure at 73°F (23°C)

## Fittings

HY Series – pg. E-87 (HY Fittings available from Parker Hose Products Division)

Connection configurations limited to:  
-Male Pipe (01)

## Colors

- Black

## Notes

Factory-made assemblies only

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# 560 – General Hydraulic Hose



## Features

- Twin or multi-line available. Lighter and smaller than 100R1 with longer lengths
- Fast response hose
- Polyurethane cover for best abrasion resistance

## Certifications

- Meets or Exceeds SAE 100R1
- MSHA Accepted

## Applications/Markets



- Hydraulic circuits and systems wherever 100R1 hose is specified
- Most synthetic hydraulic fluids, water and wide range of chemicals, industrial equipment, machine tools

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
560-3	3/16	5	.44	11	3,500	24.1	0.75	19	28	.07	.11	55
560-4	1/4	6	.51	13	3,250	22.4	1.75	44	28	.10	.15	55
560-5	5/16	8	.58	15	3,000	20.7	2.00	51	28	.12	.19	55
560-6	3/8	10	.65	17	2,750	19.0	2.25	57	28	.15	.22	55
560-8	1/2	13	.81	21	2,500	17.2	3.25	83	28	.20	.30	55
560-10	5/8	16	.94	24	2,000	13.8	6.00	152	28	.30	.44	55
560-12	3/4	19	1.13	29	1,750	12.1	7.00	178	28	.41	.61	58

## Construction

Tube: Copolyester

Reinforcement: High tensile steel wire braid

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +250°F (-40°C to +121°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

58 Series – pg. E-12

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover

# 563 – General Hydraulic Hose



## Features

- Polyurethane cover for best abrasion resistance

## Certifications

- Meets or Exceeds SAE 100R17
- MSHA Accepted

## Applications/Markets



- Industrial medium pressure hydraulic hose for use with petroleum, water base and synthetic hydraulic fluids, gases and some solvents and chemical solutions

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
563-4	1/4	6	.49	12	3,000	20.7	2.00	51	28	.12	.18	55/HY*
563-6	3/8	10	.65	17	3,000	20.7	2.50	64	28	.19	.28	55/HY*
563-8	1/2	13	.78	20	3,000	20.7	3.50	89	28	.29	.42	55/HY*

## Construction

Tube: Copolyester

Reinforcement: High tensile steel wire braid

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +250°F [212°F for size -8]

(-40°C to +121°C) [100°C for size -8]

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# 590 – General Hydraulic Hose



## Features

- Two wire strength, one wire construction, improved bend radius results
- Twin and multi-line available
- Polyurethane cover for best abrasion resistance

## Certifications

- Meets or Exceeds SAE 100R2 / 100R16
- MSHA Accepted

## Applications/Markets



- Construction equipment, machine tools, hydrostatic transmission, refuse vehicles and agriculture equipment

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F / 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
590-3	3/16	5	.44	11	5,000	34.5	1.50	38	28	.10	.15	55
590-4	1/4	6	.53	13	5,000	34.5	1.75	44	28	.14	.21	55
590-6	3/8	10	.65	17	4,000	27.6	2.25	57	28	.20	.30	55
590-8	1/2	13	.78	20	3,500	24.1	3.25	82	28	.26	.38	55
590-10	5/8	16	.98	25	3,000	20.7	6.00	152	28	.39	.57	58
590-12	3/4	19	1.11	28	2,500	17.2	7.00	178	28	.45	.67	58
590-16	1	25	1.43	36	2,000	13.8	8.00	203	28	.59	.88	58

## Construction

Tube: Copolyester

Reinforcement: Aramid fiber, high tensile wire braid

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +250°F (-40°C to +121°C)

(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

58 Series – pg. E-12

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover



# 593 – General Hydraulic Hose



## Features

- Works with synthetic hydraulic fluids, water and a range of chemicals
- Two wire strength with one braid flexibility
- Polyurethane cover for best abrasion resistance

## Certifications

- Meets or Exceeds SAE 100R2 Pressure Requirements
- MSHA Accepted

## Applications/Markets



- General hydraulic service

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Vac. Rating Hg./73°F	Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.		
#												
593-12	3/4	20	1.10	28	3000	20.7	7.00	178	.47	.70	28	LV
593-16	1	25	1.45	37	3250	22.4	8.00	203	.69	1.02	28	LV

## Construction

Tube: 12 – Copolyester ,16 – Nylon  
 Reinforcement: High tensile steel wire braid  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +250°F (-40°C to +121°C)  
 (Size -12 only limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
 Change in working length @ Rated WPSI: ±2%  
 Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

LV Series – pg. E-104  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.



# 510A – Refrigerant Hose



## Features

- Excellent impulse life
- Compatible with most common hydraulic and refrigeration fluids

## Certifications

- Meets or Exceeds SAE 100R7 except -2
- MSHA Accepted except -4, -5, -6

## Applications/Markets



- Medium pressure service for both field attachable and permanent fittings
- Used with most common refrigerants

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Vac. Rating Hg./73°F	Permanent Fitting Series	Field Attachable Series
	#	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.			
510A-2	1/8	3	.34	9	2,500	17.2	0.50	13	.03	.05	28	57	–
510A-3	3/16	5	.43	11	3,000	20.7	2.00	51	.05	.07	28	55	51
510A-4	1/4	6	.47	12	2,750	19.0	2.50	64	.05	.08	28	55	51
510A-5	5/16	8	.57	14	2,500	17.2	3.00	76	.08	.12	28	55	51
510A-6	3/8	10	.64	16	2,250	15.5	4.00	102	.08	.13	28	55	51
510A-8	1/2	13	.81	21	2,000	13.8	5.50	140	.13	.20	28	55	51
510A-12	3/4	19	1.10	28	1,250	8.6	7.50	191	.19	.29	28	–	51
510A-16	1	25	1.40	36	1,000	6.9	10.00	254	.28	.41	28	–	51

## Construction

Tube: Proprietary nylon blend

Reinforcement: Fiber

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +212°F (-40°C to +100°C)

Change in working length @ Rated WPSI: ±3%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

51 Series – pg. E-5

55 Series – pg. E-12

57 Series – pg. E-37

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Perforated cover

51 Series field attachable couplings are not intended for use on hose that has previously been in service

# 510C – General Hydraulic Hose



## Features

- Superior abrasion resistance
- Extreme flexibility
- Medium pressure service for permanent and field attachable fittings

## Certifications

- Meets or Exceeds SAE 100R7 except -2
- MSHA Accepted except -4

## Applications/Markets



- Medium pressure service for both field attachable and permanent fittings

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Vac. Rating Hg./73°F	Permanent Fitting Series	Field Attachable Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.			
#													
510C-2	1/8	3	.34	9	2,500	17.2	0.50	13	.03	.05	28	57	–
510C-3*	3/16	5	.43	11	3,250	22.4	0.75	19	.05	.07	28	55	51
510C-4*	1/4	6	.47	12	3,000	20.7	1.50	38	.05	.08	28	55	51
510C-5	5/16	8	.57	14	2,500	17.2	1.75	44	.08	.11	28	55	51
510C-6	3/8	10	.64	16	2,250	15.5	2.00	51	.10	.14	28	55	51
510C-8	1/2	13	.81	21	2,250	15.5	3.00	76	.15	.22	28	55	51
510C-10	5/8	16	.97	25	1,500	10.3	4.00	102	.20	.29	28	58	–
510C-12	3/4	19	1.09	28	1,250	8.6	5.00	127	.21	.31	28	55	51
510C-16	1	25	1.32	34	1,000	6.9	8.00	203	.27	.40	28	55	51

## Construction

Tube: Copolyester  
 Reinforcement: Fiber  
 Cover: Proprietary Blend (PFX)

## Operating Parameters

Temperature Range:  
 -40°F to +212°F (-40°C to +100°C)  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

51 Series – pg. E-5                      55 Series – pg. E-12  
 57 Series – pg. E-37                    58 Series – pg. E-12  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Perforated cover  
 \*3/16" and 1/4" working pressure reduced to 3,000 and 2,750 PSI respectively when using field attachable couplings  
 51 Series field attachable couplings are not intended for use on hose that has previously been in service

For detailed ordering information, please consult price list or contact Parflex® Division.



# 518C – Non-Conductive Hose



## Features

- Twin or multi-line constructions available
- High density braid for maximum impulse life without loss of flexibility

## Certifications

- Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per ft.
- Meets or exceeds SAE 100R7 specifications and Electrical Standards except 518C-2 with respect to Maximum working pressure
- ANSI A92.2

## Applications/Markets



- Medium pressure hydraulic service where both field attachable and permanent hydraulic circuit exposure and contact with high voltage may be encountered

Part Number	Nominal I.D.		Maximum O.D.		ANSI A92.2 Max. Working Pressure 73°F/ 23°C		SAE 100R7 Max. Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
	inch	mm	inch	mm	psi	MPa	psi	MPa	inch	mm		lbs./ft.	kg./mtr.		
#															
518C-2	1/8	3	.34	9	3,150	21.7	2,500	17.2	0.50	13	28	.03	.05	57	–
518C-3*	3/16	5	.43	11	3,250	22.4	3,250	20.7	0.75	19	28	.05	.07	55	51
518C-4*	1/4	6	.47	12	3,150	21.7	3,000	19.0	1.50	38	28	.05	.08	55	51
518C-5	5/16	8	.57	14	3,150	21.7	2,500	17.2	1.75	44	28	.08	.11	55	51
518C-6	3/8	10	.64	16	3,000	20.7	2,250	15.5	2.00	51	28	.10	.14	55	51
518C-8	1/2	13	.81	21	3,000	20.7	2,250	15.5	3.00	76	28	.15	.22	55	51
518C-10	5/8	16	.97	25	2,000	13.8	1,500	10.3	4.00	102	28	.20	.29	58	–
518C-12	3/4	19	1.09	28	1,660	11.5	1,250	8.6	5.00	127	28	.21	.31	55	51
518C-16	1	25	1.32	34	1,330	9.2	1,000	6.9	8.00	203	28	.27	.40	55	51

## Construction

Tube: Copolyester  
 Reinforcement: Fiber  
 Cover: Proprietary Blend (PFX)

## Operating Parameters

Temperature Range:  
 -40°F to +212°F (-40°C to +100°C)  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
 Change in working length @ Rated WPSI: ±2%

### Min. Burst Pressure:

4:1 Design Factor is required if hose failure will result in movement of aerial device  
 3:1 Design Factor is acceptable if hose failure will not result in movement of aerial device

## Operating Parameters (cont.)

SAE requires 4:1 Design Factor

## Colors

- Orange

## Fittings

51 Series – pg. E-5 55 Series – pg. E-12  
 57 Series – pg. E-37 58 Series – pg. E-12  
 For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Non-perforated cover  
 Lay lines on this hose will have both ANSI and SAE maximum working pressure listed. ANSI A92.2-1990 “Vehicle Mounted Elevating and Rotating Aerial Devices”

\*3/16” and 1/4” working pressure reduced to 3,000 and 2,750 PSI respectively when using field attachable couplings

51 Series field attachable couplings are not intended for use on hose that has previously been in service



For detailed ordering information, please consult price list or contact Parflex® Division.



# 515H – Compact/Light Weight Hose



## Features

- Twin or multi-line available
- Compact OD, lightweight, flexible
- Special order colors for system color coding

## Certifications

- MSHA Accepted

## Applications/Markets



- Hydraulic and pneumatic systems where a small O.D. hose is necessary
- Pilot lines
- Joystick controls

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
515H-3*	3/16	5	.34	9	2,175	15.0	0.75	19	28	.03	.04	54
515H-4	1/4	6	.41	10	2,000	13.8	1.50	38	28	.04	.05	54
515H-5*	5/16	8	.49	12	1,750	12.0	1.75	44	28	.05	.07	54
515H-6	3/8	10	.56	14	1,500	10.3	2.00	51	28	.05	.08	54
515H-8*	1/2	13	.71	18	1,500	10.3	3.00	76	28	.11	.16	54

## Construction

Tube: Copolyester  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +212°F (-40°C to +100°C)  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

54 Series – pg. E-8  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

\*Factory-made assemblies only -3, -5 and -8  
 Approved with rapid assembly fitting system

For detailed ordering information, please consult price list or contact Parflex® Division.



# 520N/528N – General Hydraulic Hose



## Features

- Twin and multi-line available
- Fast response, lighter and smaller O.D. than 100R2 hose

## Certifications

- Meets or Exceeds SAE 100R8
- 520N MSHA Accepted
- 528N Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

## Applications/Markets



- Hydraulic and pneumatic circuits and systems
- Ideal in hot water applications
- Not suggested for use in over-the-sheave (pulley system) applications

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
520N-3	528N-3	3/16	5	.43	11	5,000	34.5	1.50	38	28	.05	.07	55
520N-4	528N-4	1/4	6	.51	13	5,000	34.5	2.00	51	28	.07	.10	55
520N-5	528N-5	5/16	8	.57	14	4,500	31.0	2.50	64	28	.08	.12	55
520N-6	528N-6	3/8	10	.65	17	4,000	27.6	2.50	64	28	.08	.13	55
520N-8	528N-8	1/2	13	.81	21	3,500	24.1	4.00	102	28	.14	.20	55
520N-10	528N-10	5/8	16	.92	23	2,750	19.0	6.00	152	28	.17	.25	55

## Construction

Tube: Nylon

Reinforcement: Aramid fiber

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +212°F (-40°C to +100°C)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

● Black

● Orange (Non-Conductive)

## Notes

Perforated cover - 520N

Non-Perforated cover - 528N

# 526BA – Breathing Air Refill Hose



## Features

- 6000 PSI Constant Pressure

## Certifications (Complies with:)

- CGA G7.1-1997 Grade E Breathing Air Standards
- NFPA 1901

## Applications/Markets



- Integrated containment fill stations
- Mobile and stationary systems with or without cascade controls
- Mobile trailer/truck systems
- Portable SCBA fill

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
526BA-3	3/16	5	.42	11	6,000	41.4	1.50	38	28	.05	.07	55
526BA-4	1/4	6	.50	13	6,000	41.4	2.00	51	28	.07	.10	55
526BA-6	3/8	10	.64	16	6,000	41.4	3.00	76	28	.09	.13	55

## Construction

Tube: Nylon

Reinforcement: Aramid fiber

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +180°F (-40°C to +82°C)

Change in working length @ Rated WPSI: ±2% Max.

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Gray

## Notes

Perforated cover

Not for use as part of a SCBA systems

This hose is not for use between a pressure reducing regulator and breathing mask

For fitting attachment lubricate only with water or non-toxic lubricant. Do not assemble with petroleum or hydrocarbon based lubricants. Do not flush with solvents of any kind

This hose does not contain a conductive element; therefore, it should not be used with explosive gases such as pure oxygen and hydrogen

Hose is compliant with CGA Grade E Breathing Air Standards, however air quality is dependent upon all system components

# 527BA – Breathing Air Refill Hose



## Features

- 7000 PSI constant pressure

## Certifications (Complies with:)

- CGA G7.1-1997 Grade E Breathing Air Standards
- NFPA 1901

## Applications/Markets



- Integrated containment fill stations
- Mobile and stationary systems with or without cascade controls
- Mobile trailer/truck systems
- Portable SCBA fill

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
527BA-3	3/16	5	.43	11	7,000	48.3	1.50	38	28	.05	.07	55
527BA-4	1/4	6	.52	13	7,000	48.3	2.00	51	28	.07	.11	55

## Construction

Tube: Nylon  
Reinforcement: Aramid fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:  
-40°F to +180°F (-40°C to +82°C)  
Change in working length @ Rated WPSI: ±2% Max.  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
Connection configurations limited to:  
-Male Pipe (01)  
-Female Pipe (02)  
-Male JIC (03, 3E)  
-Female JIC Swivel (06, 37, 39, 41, L9)

For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Blue

## Notes

Perforated cover  
Not for use as part of a SCBA systems  
This hose is not for use between a pressure reducing regulator and breathing mask  
For fitting attachment lubricate only with water or non-toxic lubricant. Do not assemble with petroleum or hydrocarbon based lubricants. Do not flush with solvents of any kind  
This hose does not contain a conductive element; therefore, it should not be used with explosive gases such as pure oxygen and hydrogen  
Hose is compliant with CGA Grade E Breathing Air Standards, however air quality is dependent upon all system components



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# 53DM/538DM – DuraMax™ Low Temperature



## Features

- Matte jacket for low coefficient of friction
- Superior flexibility in cold temperature applications
- Better bend radius than SAE J517 and 100R7
- Smaller O.D.s than 100R7 and 100R18
- 3000 PSI constant pressure

## Certifications

- Meets or Exceeds SAE 100R18
- 538DM Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

## Applications/Markets



- Excellent over-the-sheave in lift truck applications
- Cold storage or refrigerated areas
- Construction and agriculture equipment in cold climate
- 53DM-12 Not suggested for use in over-the-sheave (pulley system) applications

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#	⊙		⊙		⌚		↷		U	lbs	kg	⊗
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
53DM-3	538DM-3	3/16	5	.43	11	3,000	20.7	1.00	25	28	.06	.08	55
53DM-4	538DM-4	1/4	6	.49	12	3,000	20.7	1.25	32	28	.07	.10	55/HY*
53DM-5	538DM-5	5/16	8	.60	15	3,000	20.7	2.00	51	28	.10	.15	58/HY*
53DM-6	538DM-6	3/8	10	.66	17	3,000	20.7	2.00	51	28	.11	.16	55/58/HY*
53DM-8	538DM-8	1/2	13	.84	21	3,000	20.7	3.50	89	28	.17	.26	55/58/HY*
53DM-10	538DM-10	5/8	16	1.03	26	3,000	20.7	4.00	102	28	.22	.33	58
53DM-12	-	3/4	19	1.13	29	3,000	20.7	6.50	165	28	.26	.39	58H

## Construction

Tube: Copolyester  
Reinforcement: Fiber  
Cover: Copolyester

## Operating Parameters

Temperature Range:  
-70°F to +212°F (-57°C to +100°C)  
For use with water and water-based hydraulic fluids to +135°F (+57°C)  
Change in working length @ Rated WPSI: ±2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12    58 Series – pg. E-12  
58H Series – pg. E-41  
HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black
- Orange (Non-Conductive)

## Notes

Perforated cover - 53DM  
Non-perforated cover - 538DM

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# 540N – General Hydraulic Hose



## Features

- Matte jacket for low coefficient of friction
- Special order colors
- Twin or multi-line available
- Excellent chemical compatibility
- Greater range of fluid compatibility than SAE 100R1 hose

## Certifications

- Meets or Exceeds SAE 100R7
- MSHA Accepted

## Applications/Markets



- Hydraulic and pneumatic systems, agricultural spraying, polyurethane foam mixers, robotics, fire-resistant fluid and hot water

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
540N-2	1/8	3	.34	9	3,000	20.7	0.50	13	28	.03	.05	57
540N-3	3/16	5	.44	11	3,000	20.7	0.75	19	28	.04	.06	55
540N-4	1/4	6	.50	13	2,750	19.0	1.50	38	28	.07	.10	55
540N-5	5/16	8	.58	15	2,500	17.2	1.75	44	28	.07	.10	55
540N-6	3/8	10	.65	17	2,250	15.5	2.00	51	28	.09	.13	55
540N-8	1/2	13	.81	21	2,000	13.8	3.00	76	28	.13	.19	55
540N-12	3/4	19	1.05	27	1,250	8.6	6.00	152	28	.17	.25	55

## Construction

Tube: Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:  
-40°F to +212°F (-40°C to +100°C)  
Change in working length @ Rated WPSI: ±2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
57 Series – pg. E-37  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Perforated cover

# 540P – Specialty Water Hose



## Features

- Plasticizer free non-leaching core tube
- Low-moisture permeability

## Certifications

- Meets or Exceeds SAE 100R7
- Core tube compliant with FDA Title 21 & NSF 51

## Applications/Markets



- Potable water delivery to remote sites
- Distilled and de-ionized water

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
540P-4	1/4	6	.50	13	2,750	19.0	1.25	32	28	.05	.08	55
540P-6	3/8	10	.65	17	2,250	15.5	2.00	51	28	.09	.13	55
540P-8	1/2	13	.81	21	2,000	13.8	3.00	76	28	.13	.19	55
540P-12	3/4	19	1.05	27	1,250	8.6	5.00	127	28	.19	.28	55

## Construction

Tube: Polyethylene  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +150°F (-40°C to +66°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Aqua

## Notes

Perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# 55LT – Low Temperature Hose



## Features

- Twin and multi-line available
- Superior flexibility in cold temperature applications

## Certifications

- Meets or Exceeds SAE 100R7

## Applications/Markets



- Hydraulic systems exposed to very low temperatures
- Excellent over-the-sheave in lift truck applications
- Cold storage or refrigerated areas
- Construction and agriculture equipment in cold climates

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
55LT-2	1/8	3	.34	9	3,000	20.7	0.50	13	28	.03	.05	57
55LT-3	3/16	5	.43	11	3,250	22.4	0.75	19	28	.05	.08	55
55LT-4	1/4	6	.51	13	3,000	20.7	1.25	32	28	.07	.10	55
55LT-5	5/16	8	.57	14	2,500	17.2	1.75	44	28	.09	.13	55
55LT-6	3/8	10	.66	17	2,250	15.5	2.00	51	28	.10	.14	55
55LT-8	1/2	13	.81	21	2,000	13.8	3.00	76	28	.14	.21	55
55LT-12	3/4	19	1.09	28	1,250	8.6	5.00	127	28	.21	.31	55

## Construction

Tube: Copolyester  
Reinforcement: Fiber  
Cover: Copolyester

## Operating Parameters

Temperature Range:

-70°F to +212°F (-57°C to +100°C)

For use with water and water-based hydraulic fluids  
to +135°F (+57°C)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

57 Series – pg. E-37

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Perforated cover



# 56DH/568DH – Diagnostic Hose



## Features

- Twin or multi-line available
- Compact OD, lightweight, flexible

## Certifications

- MSHA Accepted for -2 only

## Applications/Markets



- Hydraulic and pneumatic systems where a small O.D. hose is necessary
- Diagnostic equipment

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Permanent Fitting Series
#	#											
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
56DH-1.5	568DH-1.5	.09	2	.20	5	6,000	41.4	0.25	6	.02	.01	SF
56DH-2	568DH-2	.14	4	.32	8	6,000	41.4	0.50	13	.03	.05	CY

## Construction

Tube: Nylon  
 Reinforcement: Aramid fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +200°F (-40°C to +93°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

CY Series – pg. E-81  
 SF Series – pg. E-85  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black
- Orange (Non-Conductive)

## Notes

Perforated cover - 56DH  
 Non-Perforated cover - 568DH

For detailed ordering information, please consult price list or contact Parflex® Division.



Hose  
 A  
 Tubing  
 B  
 Coiled Air Hose & Fittings  
 C  
 Transportation  
 D  
 Fittings  
 E  
 Tooling, Equipment & Accessories  
 F  
 General Technical  
 G

# 573X – Fast Response Hose



## Features

- Fast response even over longer lengths
- 3000 PSI constant pressure

## Certifications

- MSHA Accepted -3 only

## Applications/Markets



- Marine, offshore drilling
- Applications requiring fast and accurate response time

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.	
#												
573X-3	3/16	5	.34	9	3,000	20.7	2.00	51	28	.03	.04	LV
573X-16	1	25	1.46	37	3,000	20.7	10.00	254	28	.41	.60	LV

## Construction

Tube: Nylon  
 Reinforcement: Aramid fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +200°F (-40°C to +93°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

LV Series – pg. E-104

## Colors

- Black

## Notes

Non-perforated cover  
 Factory-made assemblies only

# 575X – Fast Response Hose



## Features

- Fast response even over longer lengths
- 5000 PSI constant pressure

## Certifications

- MSHA Accepted

## Applications/Markets



- Marine, offshore drilling
- Applications requiring fast and accurate response time

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
575X-3	3/16	5	.43	11	5,000	34.5	1.50	38	28	.05	.07	55
575X-4	1/4	6	.51	13	5,000	34.5	2.00	51	28	.07	.10	55
575X-6	3/8	10	.64	16	5,000	34.5	3.00	76	28	.09	.13	55
575X-8	1/2	13	.81	21	5,000	34.5	4.00	102	28	.14	.21	55
575X-12	3/4	19	1.15	29	5,000	34.5	8.00	203	28	.24	.36	58H
575X-16	1	25	1.59	40	5,000	34.5	10.00	254	28	.36	.54	58H

## Construction

Tube: Nylon  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +212°F (-40°C to +100°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
 58H Series – pg. E-41  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.



# 580N/H580N/588N – High Pressure Hose



## Features

- Twin and multi-line available
- Lighter weight and smaller O.D. than 100R2



## Certifications

- Meets or Exceeds SAE 100R8 specifications
- 580N MSHA Approved
- 588N Meets SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

## Applications/Markets



- Hydraulic and pneumatic circuits and systems
- Replaces 100R2 rubber hose wherever greater flexibility, fluid compatibility, and cover durability are required

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Non-Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
580N-4	588N-4	1/4	6	.62	16	5,000	34.5	2.00	51	28	.11	.16	58
580N-6	588N-6	3/8	10	.77	20	4,000	27.6	2.50	64	28	.15	.22	58
580N-8	588N-8	1/2	13	.89	23	3,500	24.1	4.00	102	28	.21	.31	58
580N-10	588N-10	5/8	16	.98	25	2,750	19.0	6.00	152	28	.21	.31	58
580N-12	588N-12	3/4	19	1.15	29	2,250	15.5	8.00	203	28	.23	.35	58
580N-16	588N-16	1	25	1.47	37	2,000	13.8	10.00	254	28	.38	.56	58
H580N-16*	-	1	25	1.58	40	3,000	20.7	10.00	254	28	.53	.79	58H

## Construction

Tube: Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:  
-40°F to +212°F (-40°C to +100°C)  
Change in working length @ Rated WPSI: ±2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12  
58H Series – pg. E-41  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black
- Orange (Non-Conductive)

## Notes

Perforated cover - 580N  
\*Non-Perforated cover -588N, H580N-16



# 83FR – DuraGard™ General Purpose Polyurethane



## Features

- Weld spatter resistant
- Excellent abrasion resistance
- Extreme flexibility
- Compact bend radius
- Specially formulated polyurethane tube
- Twin-line or multi-line constructions available

## Certifications

- MSHA Accepted
- Non-conductive per SAEJ343 test procedures for thermoplastic hose
- UL94HB compliant

## Applications/Markets



- General purpose air and water hose often used in robotic welding applications

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	PushLok Fitting*
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.		
#													
83FR-4	1/4	6	.48	12	300	2.1	1.00	25	28	.05	.07	55/HV**	82*
83FR-6	3/8	10	.60	15	300	2.1	2.00	51	28	.08	.11	55/HV**	82*
83FR-8	1/2	13	.76	19	300	2.1	2.50	64	28	.12	.17	55/HV**	82*
83FR-12	3/4	19	1.04	26	300	2.1	3.50	89	28	.19	.28	55/HV**	82*

## Construction

Tube: Specially formulated polyurethane  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -20°F to +200°F (-29°C to +93°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
 82 Series – (\*82 Series Fittings available from Parker Hose Products Division)  
 HY Series – pg. E-87 (\*\*HY Fittings available from Parker Hose Products Division)  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black (BLK)
- Blue (BLU)
- Brown (BRN)
- Green (GRN)
- Gray (GRA)
- Red (RED)

## Notes

\*Temperature and pressure reduced with 82 series  
 Push-Lok Fitting:  
 -20°F to +145°F (-29°C to +63°C)  
 175 PSI maximum working pressure  
 Non-perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.



# 1035A – Power Cleaning



## Features

- Non-marring
- Extremely flexible

## Applications/Markets



- Pressure washers (low pressure)
- Carpet cleaning

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.	
#												
1035A-4	1/4	6	.51	13	1,500	10.3	.63	16	28	.08	.13	55
1035A-6	3/8	10	.62	16	1,200	8.3	.88	22	28	.10	.15	55

## Construction

Tube: Special PFX compound

Reinforcement: Fiber

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-25°F to +212°F (-32°C to +100°C)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Blue

## Notes

Perforated cover

No chlorinated solvents should be used

HBR (Hose Bend Restrictor) suggested for carpet cleaning applications - See Hose Guard in Tooling Equipment and Accessories Section

# 1035HT – High Temperature Power Cleaning



## Features

- Non-marring
- Broad temperature range

## Applications/Markets



- Pressure washers (low pressure, high temperature)
- Carpet cleaning

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
1035HT-3	3/16	5	.43	11	2,000	13.8	0.75	19	28	.04	.06	55
1035HT-4	1/4	6	.50	13	1,750	12.1	1.50	38	28	.06	.08	55
1035HT-6	3/8	10	.65	17	1,500	10.3	2.00	51	28	.09	.13	55

## Construction

Tube: Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:  
-40°F to +230°F (-40°C to +110°C)  
Change in working length @ Rated WPSI: ±2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Yellow

## Notes

Perforated cover  
No chlorinated solvents should be used  
HBR (Hose Bend Restrictor) suggested for carpet cleaning applications - See Hose Guard in Tooling Equipment and Accessories Section pg. F-21

For detailed ordering information, please consult price list or contact Parflex® Division.

# B9 - General Purpose Transfer Hose



## Features

- Excellent flexibility

## Applications/Markets



- Low pressure transmission of air, oil, water, and coolants

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Vac. Rating Hg./73°F	Permanent Fitting Series	Field Attachable Series
	#	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.			
B903	3/16	5	.39	10	250	1.7	1.00	25	.04	.06	28	55	–
B904	1/4	6	.46	12	250	1.7	1.50	38	.05	.07	28	55/HY*	82*
B905	5/16	8	.55	14	250	1.7	2.00	51	.08	.12	28	55/HY*	–
B906	3/8	10	.64	16	250	1.7	3.00	76	.09	.13	28	55/HY*	82*
B908	1/2	13	.78	20	250	1.7	3.00	76	.13	.19	28	55/HY*	82*
B910	5/8	16	.93	24	250	1.7	4.00	102	.20	.30	28	55/HY*	82*

## Construction

Tube: Specially formulated polyurethane  
 Reinforcement: Fiber  
 Cover: Specially formulated polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +200°F (-40° C to +93° C)  
 (Limited to +130°F (+54°C) for water and water-based fluids)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series - pg. E-12  
 82 Series - (\*82 Series Fittings available from Parker Hose Products Division)

HY Series - pg. E-87 (\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Red
- Black (BK)

## Notes

\*Temperature and pressure reduced with 82 series  
 Push-Lok Fitting:  
 -20°F to +100°F (-29°C to +38°C)  
 100 PSI maximum working pressure  
 Non-perforated cover



# CNG – Electrically Conductive Compressed Natural Gas Hose



## Features

- Twin and multi-line available

## Certifications

- Conforms to:
- NFPA 52
- ANSI/IAS NGV 4.2-1999
- CSA12.52-M99

## Applications/Markets



- CNG Dispenser
- Fleet transit
- CNG Fuel transfer
- Residential CNG refueling

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.
#											
5CNG-3	3/16	5	.43	11	5,000	34.5	1.50	38	28	.05	.07
5CNG-4	1/4	6	.62	16	5,000	34.5	2.00	51	28	.11	.16
5CNG-6	3/8	10	.65	16	5,000	34.5	3.00	76	28	.09	.13
5CNG-8	1/2	13	.90	23	5,000	34.5	4.00	102	28	.21	.31
5CNG-12	3/4	19	1.15	29	5,000	34.5	7.50	191	28	.24	.36
5CNG-16	1	25	1.59	40	5,000	34.5	10.00	254	28	.36	.53

## Construction

Tube: Electrically conductive nylon  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +180°F (-40°C to +82°C)  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

Factory-made assemblies only  
 55 Series – pg. E-12      58 Series – pg. E-12  
 58H Series – pg. E-41  
 For Crimp Die Selection charts see pgs. G-30 : G-41

## Colors

- Red

## Notes

Perforated cover  
 CNG hose must be assembled at the factory or by a Parflex approved facility  
 Wire spring guards must be used on ANSI/CSA design certified CNG dispenser hose assembly sizes -3 through -8: single and multi-line bonded assemblies - pg. F-21

For detailed ordering information, please consult price list or contact Parflex® Division.



# HLB – Lubrication Line Hose



## Features

- HLB remote lubrication system versus 1/4" rubber hoses can save money per line in reduced component and installation labor costs
- Unique GK bulkhead hose fittings with integrated nipple can save money per zerk connection in unnecessary adapter costs
- Compact 1/8" hoses save hundreds of dollars of waste in your operation by eliminating gallons of unnecessary "in-line" grease versus larger bore rubber hoses

## Certifications

- MSHA Accepted

## Applications/Markets



- Grease and lubrication lines
- Agriculture
- Construction
- Industrial
- Material handling
- Mobile equipment
- Transportation

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F / 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
	#	inch	mm	inch	mm	psi	MPa	inch		mm	lbs./ft.		
HLB02*	1/8	3.2	.32	8	3,000	20.7	.50	13	28	.03	.04	CY	BU
HLB03**	3/16	4.8	.41	10	3,000	20.7	.75	19	28	.06	.08	CY	BU

## Construction

Tube: Copolyester  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +212°F (-40°C to +100°C) with CY fittings  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)

BU Series Field Attachable Fitting limited to 120°F  
 Change in working length @ Rated WPSI: ±3%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

BU Series - pg. E-80  
 CY Series - pg. E-81  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Not for use as a whip hose on hand-operated grease guns  
 Bend restrictions are available only for permanent fittings.  
 HBR (Hose Bend Restrictor) available for Marine Steering Hose Assemblies. See Hose Guard in Tooling Equipment and Accessories Section pg. F-21  
 \*HLB-2 - Guard P.N. CY02-652317  
 \*\*HLB-3 - Guard P.N. 3CNG-4



# MSH – Marine Steering Fast Response Hose



## Features

- Fast, accurate response
- Permanent or field attachable
- Salt water, corrosion resistant

## Applications/Markets



- Wide range of marine applications
- Marine hydraulic steering systems

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.		
#													
MSH-5	5/16	8	.48	12	1,000	6.9	2.25	57	28	.05	.07	MS	MS
MSH-6	3/8	10	.59	15	1,000	6.9	3.00	76	28	.07	.11	MS	MS

## Construction

Tube: Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:  
-40°F to +200°F (-40°C to +93°C)  
(Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
Change in working length @ Rated WPSI: ±2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

MS Series – pg. E-105  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover  
Bend restrictions are available only for permanent fittings.  
HBR (Hose Bend Restrictor) available for Marine Steering Hose Assemblies. See Hose Guard in Tooling Equipment and Accessories Section pg. F-21

For detailed ordering information, please consult price list or contact Parflex® Division.



# MSXL – High Pressure Marine Steering Hose



## Features

- Fast, accurate response
- Low volumetric expansion
- Salt water, corrosion resistant

## Applications/Markets



- Wide range of marine applications
- Marine hydraulic steering systems

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.	
MSXL-5	5/16	8	.50	13	1,500	10.3	2.25	57	28	.05	.07	MS

## Construction

Tube: Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:  
-40°F to +185°F (-40°C to +85°C)  
Change in working length @ Rated WPSI: ±2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

MS Series – pg. E-105  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Non-perforated cover


HBR (Hose Bend Restrictor) available for Marine Steering Hose Assemblies. See Hose Guard in Tooling Equipment and Accessories Section pg. F-21



For detailed ordering information, please consult price list or contact Parflex® Division.



# PTH – Marine Power Tilt Hose



## Features

- Compact design
- Abrasion resistant polyurethane jacket
- Excellent flexibility
- Corrosion resistant

## Applications/Markets



- Power tilt mechanisms for outboard and stern drive engines
- Trim Tab assemblies
- Jack plate assemblies

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Vac. Rating Hg./73°F	Minimum Bend Radius			Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa		inch	inch	mm	lbs./ft.	kg./mtr.	
PTH-3	3/16	5	.43	11	3,000	20.7	28	0.75	19	.08	.11	92	

## Construction

Tube: Nylon  
 Reinforcement: Fiber and Stainless Steel braid  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +212°F (-40°C to +100°C)  
 Change in working length @ Rated WPSI: ±2%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

92 Series – pg. E-65  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Clear

## Notes

Non-perforated cover  
 Also available as custom order with black jacket

# S4 – Predator® Hose (Water Jetting/Lateral Cleaning)



## Features

- Easily identified lime green cover signifies 4000 PSI constant pressure
- Slim profile and lightweight provide easy handling and routing

## Certifications

- NSWMA (National Solid Waste Management Association)
- WASTEC (Waste Equipment Technology Association)
- WEMI (Waste Equipment Management Institute)
- Specifications for repair/inspection procedures for high pressure hose used in conjunction with sewer/catch basin cleaning equipment

## Applications/Markets



- High-pressure water equipment for cleaning or debris removal in lateral sewer lines
- Lines provide connection from commercial, industrial or residential structure to the main sewer line located under the streets
- Lateral lines are smaller in diameter than the main lines, and rely more on water pressure than water volume to clear residue and obstructions
- For water/slurry applications, contact Parflex for chemical compatibility/recommendations

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
#											
S408	1/2	13	.89	23	4,000	27.6	4.00	102	.20	.29	58/HY*
S410	5/8	16	1.06	27	4,000	27.6	5.00	127	.32	.48	43**

## Construction

Tube: Gray Copolyester  
Reinforcement: Fiber  
Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +135°F for water (-40°C to +57°C)

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12

43 Series – (\*\*43 Series Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Green

## Notes

Available in bulk hose only

Not for use in hydraulic applications

Perforated cover - S410

Non-perforated cover - S408

# S5 – Predator® Hose (Water Jetting/Lateral Cleaning)



## Features

- Easily identified lime green cover signifies 4000 PSI constant pressure
- Slim profile and lightweight provide easy handling and routing

## Certifications

- NSWMA (National Solid Waste Management Association)
- WASTEC (Waste Equipment Technology Association)
- WEMI (Waste Equipment Management Institute)
- Specifications for repair/inspection procedures for high pressure hose used in conjunction with sewer/catch basin cleaning equipment

## Applications/Markets



- High-pressure water equipment for cleaning or debris removal in lateral sewer lines
- Lines provide connection from commercial, industrial or residential structure to the main sewer line located under the streets
- Lateral lines are smaller in diameter than the main lines, and rely more on water pressure than water volume to clear residue and obstructions
- For water/slurry applications, contact Parflex for chemical compatibility/recommendations

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
S508	1/2	13	.80	20	4000	27.6	4.00	102	.16	.24	HY*/55

## Construction

Tube: Gray Copolyester  
 Reinforcement: Aramid Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +135°F for water (-40°C to +57°C)  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series – pg. E-12  
 HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Green

## Notes

Available in bulk hose only  
 S508 product can be mended with a swaged 1HUHY-8-8;  
 HY end connections must be crimped  
 Not for use in hydraulic applications  
 Perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# S6 – Predator® Hose (Sewer Cleaning)



## Features

- Easily identified orange cover signifies 2500 PSI constant pressure
- Bonded construction provides excellent kink resistance and flexibility

## Certifications

- NSWMA (National Solid Waste Management Association)
- WASTEC (Waste Equipment Technology Association)
- WEMI (Waste Equipment Management Institute)
- Specifications for repair/inspection procedures for high pressure hose used in conjunction with sewer/catch basin cleaning equipment

## Applications/Markets



- High-pressure and high-volume water equipment for cleaning or debris removal in large sewer lines
- For water/slurry applications, contact Parflex for chemical compatibility/recommendations

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
#											
S612	3/4	19	1.14	29	2,500	17.2	4.00	102	.29	.43	58/SQ/HY*
S616	1	25	1.41	36	2,500	17.2	6.00	152	.38	.57	58/SQ/HY*
S620	1-1/4	32	1.78	45	2,500	17.2	12.00	305	.61	.91	SQ
S624	1-1/2	38	2.11	54	2,500	17.2	15.00	381	.83	1.24	71**

## Construction

Tube: Gray Copolyester, S624 – Gray Nylon  
Reinforcement: Fiber  
Cover: Polyurethane

## Colors

- Orange

## Operating Parameters

Temperature Range:

-40°F to +135°F (-40°C to +57°C)

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

## Notes

Available in bulk hose only

Not for use in hydraulic applications

Perforated cover - S612, S616

Non-perforated cover - S620, S624

## Fittings

58 Series – pg. E-12

SQ Series (Swage Only)– pg. E-107

71 Series – (\*\*71 Series Fittings available from Parker Hose Products Division)

HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)



# S9 – Predator® Hose (Sewer Cleaning)



## Features

- Easily identified blue cover signifies 3000 PSI constant pressure
- Bonded construction provides excellent kink resistance and flexibility

## Certifications

- NSWMA (National Solid Waste Management Association)
- WASTEC (Waste Equipment Technology Association)
- WEMI (Waste Equipment Management Institute)
- Specifications for repair/inspection procedures for high pressure hose used in conjunction with sewer/catch basin cleaning equipment

## Applications/Markets



- High-pressure and high-volume water equipment for cleaning or debris removal in large sewer lines
- For water/slurry applications, contact Parflex for chemical compatibility/recommendations

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm	lbs./ft.	kg./mtr.	
#											
S912	3/4	19	1.15	29	3,000	20.7	4.00	102	.30	.45	58/SQ/HY*
S916	1	25	1.47	37	3,000	20.7	8.00	203	.46	.68	58/SQ/HY*

## Construction

Tube: Gray Copolyester  
 Reinforcement: Fiber  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +135°F for water (-40°C to +57°C)  
 Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12  
 SQ Series (Swage Only)– pg. E-107  
 HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Blue

## Notes

Available in bulk hose only  
 Not for use in hydraulic applications  
 Perforated cover

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# SLH – Sewer Leader Hose



## Features

- Easily identified black cover indicates termination of hose

## Certifications

- NSWMA (National Solid Waste Management Association)
- WASTEC (Waste Equipment Technology Association)
- WEMI (Waste Equipment Management Institute)

## Applications/Markets



- Leader hose for S4/S5/S6/S9 high-pressure sewer cleaning hose

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
SLH-8	1/2	13	0.77	20	4,000	27.6	3.50	89	28	.25	.37	58/HY*
SLH-10	5/8	16	0.95	24	4,000	27.6	4.00	102	28	.38	.57	HY*
SLH-12	3/4	19	1.08	27	3,000	20.7	4.80	122	28	.45	.67	HY*
SLH-16	1	25	1.43	36	3,000	20.7	6.00	152	28	.80	1.19	HY*

## Construction

Tube: Gray Copolyester  
Reinforcement: Wire  
Cover: Neoprene

## Operating Parameters

Temperature Range:

-40°F to +150°F (-40°C to +66°C)

Min. Burst Pressure is 2.5x Max. Working Pressure at 73°F (23°C)

## Fittings

58 Series – pg. E-12

HY Series – pg. E-87 (\*HY Fittings available from Parker Hose Products Division)

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Not for use in hydraulic applications

# XDH eXtreme™ Duty Hose



## Features

- Designed for high volume, repeatable applications in extreme environmental conditions such as high temperatures, complicated routings, and high abrasion areas
- All hoses heat formed into customized routings
- Can be easily routed throughout extreme environments, eliminating the need for metal tubing/hose combinations and multiple connecting points

## Certifications

- Meets or Exceeds performance criteria of:
  - SAE J517 100R16
  - SAE J517 100R2
  - SAE J517 100R17
  - SAE J517 100R19

## Applications/Markets



- Ideally suited for extreme environmental conditions such as high temperatures, complicated routings, high abrasion and aggressive fluids.

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.
#	⊙		⊙		⌚		↷		U	lbs	kg
XDH-4	1/4	6	.43	11	5,000	35	2.0	50	28	.10	.14
XDH-6	3/8	10	.62	16	4,000	28	2.5	64	28	.19	.28
XDH-8	1/2	13	.75	19	4,000	28	3.5	89	28	.25	.37

## Construction

Tube: Engineered Thermoplastic  
 Reinforcement: Braided Steel wire  
 Cover: Engineered Thermoplastic

## Operating Parameters

Temperature Range:  
 -65°F to +300°F (-54°C to +150°C)  
 (Limited to +135°F (+57°C) for synthetic hydraulic fluids and water-based fluids)  
 Min. Burst Pressure is 4x Max Working Pressure at 73°F (23°C)  
 Change in working length @ Rated WPSI: +1%/-2%

## Fittings


55 Series - pg. E-12

## Colors

- Black

## Notes

Factory-made assemblies only



For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# Duraflex™ Hydraulic Hose Coil



## Features

- Bonded twin-line construction
- Self retracting coil design

## Certifications

- 528N - Meets or Exceeds SAE 100R8
- 548N - Meets or Exceeds SAE 100R7
- Meet SAE J517 for less than 50 micro-amps leakage under 75,000 volts per foot

## Applications/Markets



- Hydraulic tool hose for aerial lift applications
- General hydraulics

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.	
#												
548N-6	3/8	10	.65	17	2,250	15.5	2.00	51	28	.09	.13	55
528N-6	3/8	10	.65	17	4,000	27.6	2.50	64	28	.08	.13	55

### Nomenclature

HC-548N-06MP-06MP-10

#### Configuration

HC twin-line hose coil  
(blank) twin-line straight hose

#### Hose Type (see specifications below)

548N Med Pressure - straight or coiled  
528N High Pressure - straight or coiled

#### End Connectors

06MP 3/8" Rigid Male Pipe  
06FJ 3/8" Female JIC Swivel

#### Effective Working Length

6 6 foot length  
8 8 foot length  
10 10 foot length  
12 12 foot length

#### Notes

- 1) Part Number example shown is a stocked item.
- 2) Other combinations from this chart are readily available.
- 3) For options not shown, please consult Parflex Division.

## Construction

Tube: Nylon

Reinforcement: 528N-Aramid fiber/548N-Fiber

Cover: Polyurethane

## Operating Parameters

Temperature Range:

-40°F to +212°F (-40°C to +100°C)

Change in working length @ Rated WPSI: ±2%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

55 Series - pg. E-12

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Orange (Non-Conductive)

## Notes

Non-Perforated cover



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# 919/919B – PTFE Hose



## Features

- Excellent chemical compatibility
- Handles extreme temperatures to +450°F
- Environmentally safe
- Resists moisture
- Low friction minimizes pressure drops and deposits

## Certifications

- Meets or Exceeds SAE 100R14A - 919
- Meets or Exceeds SAE 100R14B - 919B
- FDA CFR 177.1550 (Natural tube)

## Applications/Markets



- Chemical transfer lines
- General hydraulics
- Compressed air/gases
- Adhesive dispensing
- Coolant Lines
- Medical Gases

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
#	#													
Natural	Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.		
919-3	-	1/8	3	.25	6	3,000	20.7	1.50	38	28	.04	.06	91	-
919-4	919B-4	3/16	5	.32	8	3,000	20.7	2.00	51	28	.06	.09	91N	90
919-5	919B-5	1/4	6	.38	10	3,000	20.7	3.00	76	28	.09	.13	91N	90
919-6	919B-6	5/16	8	.44	11	2,500	17.2	4.00	102	28	.10	.15	91N	90
919-8	919B-8	13/32	10	.53	13	2,000	13.8	5.00	127	28	.13	.19	91N	90
919-10	-	1/2	13	.63	16	1,500	10.3	6.50	165	28	.15	.22	91N	90
919-12	-	5/8	16	.75	19	1,200	8.3	7.50	191	12	.19	.28	91N	90
919-16	-	7/8	22	1.03	26	1,000	6.9	9.00	229	14	.27	.40	91N	90
919-20	-	1-1/8	29	1.28	33	625	4.3	16.00	406	10	.39	.58	91	90

## Construction

Tube: 919 - Natural FDA Compliant PTFE  
 919B - Black Static-Dissipative PTFE  
 Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:  
 -100°F to +450°F (-73°C to +232°C)  
 Change in length at working pressure is +2% to -4%  
 Min. Burst Pressure is 4x Max. Working Pressure  
 at 73°F (23°C)

## Fittings

90 Series – pg. E-45  
 91 Series – pg. E-52  
 91N Series – pg. E-52  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Use hose type 919B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# 919J – Silicone Jacketed PTFE Hose



## Features

- Silicone jacket provides a clean, smooth cover to protect the stainless steel wire reinforcement against wear, fraying and contaminants
- Steam cleanable

## Certifications

- Meets or Exceeds SAE 100R14A
- FDA CFR 177.1550

## Applications/Markets



- Chemical transfer lines
- General hydraulics
- Compressed air/gases
- Adhesive dispensing
- Coolant Lines
- Medical Gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.	
#												
919J-4-RED	3/16	5	.45	11	3,000	20.7	2.00	51	28	.12	.18	91N
919J-5-RED	1/4	6	.52	13	3,000	20.7	3.00	76	28	.14	.21	91N
919J-6-RED	5/16	8	.58	15	2,500	17.2	4.00	102	28	.17	.25	91N
919J-8-RED	13/32	10	.68	17	2,000	13.8	5.00	127	28	.20	.30	91N
919J-10-RED	1/2	13	.78	20	1,500	10.3	6.50	165	28	.24	.35	91N
919J-12-RED	5/8	16	.91	23	1,200	8.3	7.50	191	12	.29	.43	91N

## Construction

Tube: Natural FDA compliant PTFE  
 Reinforcement: 304 Stainless Steel braid  
 Cover: Extruded silicone

## Operating Parameters

Temperature Range:  
 -40°F to +450°F (-40°C to +232°C)  
 Change in length at working pressure is +2% to -4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

91N Series – pg. E-52  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Red

## Notes

Cover must be skived prior to fitting attachment

# 919U – High Abrasion Resistance PTFE Hose



## Features

- Non-Marring, abrasion resistant polyurethane jacket protects the stainless steel wire reinforcement against wear, fraying and contaminants

## Certifications

- Meets or Exceeds SAE 100R14A but operates at a temperature range of -40°F to +275°F
- FDA CFR 177.1550

## Applications/Markets



- Chemical transfer lines
- General hydraulics
- Compressed air/gases
- Adhesive dispensing
- Coolant Lines
- Medical Gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#												
919U-4	3/16	5	.37	9	3,000	20.7	2.00	51	28	.08	.13	91N
919U-6	5/16	8	.51	13	2,500	17.2	4.00	102	28	.13	.20	91N
919U-8	13/32	10	.61	15	2,000	13.8	5.00	127	28	.15	.22	91N
919U-12	5/8	16	.84	21	1,200	8.3	7.50	191	12	.22	.33	91N
919U-16	7/8	22	1.12	28	1,000	6.9	9.00	229	14	.31	.47	91N

## Construction

Tube: Natural FDA compliant PTFE  
 Reinforcement: 304 Stainless Steel braid  
 Cover: Polyurethane

## Operating Parameters

Temperature Range:  
 -40°F to +275°F (-40°C to +135°C)  
 Change in length at working pressure is +2% to -4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

91N Series – pg. E-52  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Black

## Notes

Cover must be skived prior to fitting attachment  
 Other colors available upon request

For detailed ordering information, please consult price list or contact Parflex® Division.



# 929/929B – Heavy Wall PTFE Hose



## Features

- Tight bend radius
- Excellent kink resistance
- Enhanced resistance to gas permeation due to increased PTFE wall thickness (.040")

## Certifications

- Meets or Exceeds SAE 100R14A - 929
- Meets or Exceeds SAE 100R14B - 929B
- FDA CFR 177.1550 (Natural tube)

## Applications/Markets



- Chemical transfer lines
- General hydraulics
- Compressed air/gases
- Adhesive dispensing
- Coolant Lines
- Medical Gases
- 919 (100R14) hose applications requiring tight routings

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
929-4	929B-4	3/16	5	.34	9	3,000	20.7	2.00	51	28	.08	.12	91N
929-6	929B-6	5/16	8	.47	12	2,500	17.2	4.00	102	28	.12	.18	91N
929-8	929B-8	13/32	10	.59	15	2,000	13.8	4.60	117	28	.16	.23	91N
-	929B-12	5/8	16	.81	21	1,200	8.3	6.50	165	12	.19	.28	91N
-	929B-16	7/8	22	1.14	29	1,250	8.6	7.40	188	12	.49	.73	91N

## Construction

Tube: 929 - Natural FDA Compliant PTFE  
 929B - Black Static-Dissipative PTFE  
 Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:  
 -100°F to +450°F (-73°C to +232°C)  
 Change in length at working pressure is +2% to -4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

91N Series – pg. E-52  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Use hose type 929B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.



# 929BJ – Silicone Jacketed PTFE Hose (with Static-Dissipative Tube)



## Features

- Silicone jacket protects SS wire reinforcement against wear and fraying, up to 450°F
- Silicone jacket provides clean, smooth cover and prevents contaminants from accumulating in braid
- Tight bend radius
- Excellent kink resistance
- Enhanced resistance to gas permeation due to increased PTFE wall thickness
- Steam cleanable

## Applications/Markets



- Vacuum lines for high temperature autoclaves (may require internal spring guard)
- General hydraulics
- Compressed air/gases

Part Number	Nominal I.D.		Maximum O.D.		Tube Wall		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
	inch	mm	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.	
#	⊙		⊙				↻		↻		U	lbs	kg	⊗
929BJ-4	3/16	5	.58	15	.040	1.02	3,000	20.7	2.00	51	28	.17	.25	91N
929BJ-6	5/16	8	.70	18	.040	1.02	2,500	17.2	4.00	102	28	.23	.34	91N
929BJ-8	13/32	10	.81	20	.044	1.12	2,000	13.8	4.60	117	28	.29	.43	91N
929BJ-12	5/8	16	1.04	26	.048	1.22	1,200	8.3	6.50	165	12	.40	.60	91N
929BJ-16	7/8	22	1.36	35	.048	1.22	1,250	8.6	7.40	188	14	.78	1.16	91N

## Construction

Tube: Black static-dissipative PTFE  
 Reinforcement: 304 Stainless Steel braid  
 Cover: Silicone jacket

## Operating Parameters

Temperature Range:  
 -65°F to +450°F (-54°C to +232°C)  
 Change in length at working pressure is +2% to -4%  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

91N Series – pg. E-52  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Colors

- Brown

## Notes

Cover must be skived prior to fitting attachment

For detailed ordering information, please consult price list or contact Parflex® Division.



# 939/939B – Convoluted PTFE Hose



## Features

- Excellent flexibility
- Exceptional kink resistance

## Certifications

- FDA CFR 177.1550 (Natural tube)

## Applications/Markets



- Chemical transfer
- General hydraulics
- Hose applications requiring tight routings

Part Number		Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#	⊘		⊘		⌚		↷		U	lbs	kg	⊗
Natural	Conductive	inch	mm	inch	mm	psi	MPa	inch	mm	inch	lbs./ft.	kg./mtr.	
939-6	939B-6	3/8	10	.59	15	1,500	10.3	2.25	57	28	.12	.18	93N
939-8	939B-8	1/2	13	.79	20	1,350	9.3	2.88	73	28	.21	.31	93N
939-10	939B-10	5/8	16	.88	22	1,000	6.9	3.00	76	28	.24	.36	93N
939-12	939B-12	3/4	19	1.09	28	1,100	7.6	3.75	95	28	.32	.47	93N
939-16	939B-16	1	25	1.33	34	1,000	6.9	5.00	127	28	.45	.67	93N
939-20	939B-20	1-1/4	32	1.75	44	1,000	6.9	6.25	159	20*	.70	1.04	93N
939-24	939B-24	1-1/2	38	2.05	52	750	5.2	7.50	191	12*	.80	1.18	93N
939-32	939B-32	2	51	2.56	65	250	1.7	10.00	254	5*	1.01	1.50	93N

## Construction

Tube: 939 - Natural FDA Compliant PTFE

939B - Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:

-100°F to +450°F (-73°C to +232°C)

Change in length at working pressure is +2% to -4%

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

93N Series - pg. E-67

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Use hose type 939B with static-dissipative core tube when conveying non-conducting fluids such as oils, paints, fuels, steam, etc.

Not suggested for steam-cold water cycling applications  
\* 28 in/Hg can be obtained by using 2799 internal spring guard. See pg. F-23

# 943B – 3,000 PSI W.P. High Temp Hose



## Features

- High temperature hydraulic hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

## Certifications

- Meets or Exceeds SAE 100R7 and SAE 100R17

## Applications/Markets



- High temp hydraulic applications
- Chemical transfer
- Compressed air/gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F / 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.
#											
943B-6	5/16	8	.49	12	3,000	20.7	2.50	64	28	.18	.26
943B-8	13/32	10	.62	16	3,000	20.7	2.88	73	28	.24	.35
943B-10	1/2	13	.73	19	3,000	20.7	3.25	83	28	.32	.46
943B-12	5/8	16	.99	25	3,000	20.7	4.00	102	28	.70	1.01
943B-16	29/32	23	1.25	32	3,000	20.7	5.00	127	28	1.02	1.53

## Construction

Tube: Black static-dissipative PTFE  
Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:  
-65°F to +400°F (-54°C to +204°C)  
Change in length at working pressure is +2% to -2%  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

## Fittings

94 Series – pg. E-70

## Notes

Factory-made assemblies only  
Not suggested for steam-cold water cycling applications

For detailed ordering information, please consult price list or contact Parflex® Division.

# 944B – 4,000-4,500 PSI W.P. High Temp Hose



## Features

- High temperature hydraulic hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

## Applications/Markets



- General hydraulics
- Chemical transfer
- Compressed air/gases
- Paint stripping

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F / 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		inch	lbs./ft.
#											
944B-4	15/64	6	.39	10	4,500	31.0	1.50	38	28	.11	.16
944B-6	5/16	8	.49	12	4,500	31.0	2.50	64	28	.17	.24
944B-8	7/16	11	.62	16	4,500	31.0	2.88	73	28	.25	.35
944B-10	1/2	13	.73	19	4,000	27.6	3.25	83	28	.31	.45
944B-12	5/8	16	.99	25	4,000	27.6	4.00	102	28	.74	1.05
944B-16	29/32	23	1.25	32	4,000	27.6	5.00	127	28	1.09	1.55

## Construction

Tube: Black static-dissipative PTFE

Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:

-65°F to +400°F (-54°C to +204°C)

Change in length at working pressure is +2% to -2%

Min. Burst Pressure is 3x Max. Working Pressure at 73°F (23°C)

## Fittings

94 Series - pg. E-70

## Notes

Factory-made assemblies only

Not suggested for steam-cold water cycling applications

Reduce pressure to 3,000 psi (20.7MPa) for pressure impulse applications



# 950B – 4,000 PSI W.P. High Temp Hose



## Features

- High temperature hydraulic hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

## Applications/Markets



- High temp hydraulic applications
- Chemical transfer
- Compressed air/gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.
#											
950B-4	15/64	6	.50	13	4,000	27.6	3.00	76	28	.20	.27
950B-6	5/16	8	.62	16	4,000	27.6	5.00	127	28	.24	.36
950B-8	7/16	11	.75	19	4,000	27.6	5.75	146	28	.45	.68
950B-12	5/8	16	1.08	27	4,000	27.6	7.75	197	28	.96	1.43
950B-16	29/32	23	1.36	34	4,000	27.6	9.63	245	28	1.30	1.93

## Construction

Tube: Black static-dissipative PTFE

Reinforcement: Multiple high density braids of 304 Stainless Steel

## Fittings

95 Series – pg. E-70

## Notes

Factory-made assemblies only

## Operating Parameters

Temperature Range:

-65°F to +400°F (-54°C to +204°C)

Change in length at working pressure is +2% to -2%

Min. Burst Pressure is 3x Max. Working Pressure at 73°F (23°C)

# 955B – 5,500 PSI W.P. High Temp Hose



## Features

- High temperature hydraulic hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

## Applications/Markets



- General hydraulics
- Chemical transfer
- Compressed air/gases

Part Number	Nominal I.D.		Maximum O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
	inch	mm	inch	mm	psi	MPa	inch	mm		lbs./ft.	kg./mtr.
#											
955B-4	15/64	6	.50	13	5,500	37.9	3.00	76	28	.23	.34
955B-6	5/16	8	.62	16	5,500	37.9	5.00	127	28	.24	.35
955B-8	7/16	11	.75	19	5,500	37.9	5.75	146	28	.46	.68
955B-10	1/2	13	.91	23	5,500	37.9	6.50	165	28	.91	1.34
955B-12	5/8	16	1.08	27	5,500	37.9	7.75	197	28	.92	1.36
955B-16	29/32	23	1.36	34	5,500	37.9	9.63	245	28	1.20	1.77

## Construction

Tube: Black static-dissipative PTFE

Reinforcement: Multiple high density braids of 304 Stainless Steel

## Fittings

95 Series – pg. E-70

## Notes

Factory-made assemblies only

Not suggested for steam-cold water cycling applications

Reduce operating pressure to 4000 PSI (27.6 MPa) for impulse service applications

## Operating Parameters

Temperature Range:

-65°F to +400°F (-54°C to +204°C)

Change in length at working pressure is +2% to -2%

Min. Burst Pressure is 16,000 psi at 73°F (23°C)

# S30/S30B - Industrial .030" wall PTFE Hose, Stainless Steel Braid



## Features

- High temperature hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

## Compliances

- FDA 21 CFR 177.1550, 177.2600 (Natural tube)

## Applications/Markets



- Food & Beverage
- Pharmaceutical
- Fluid handling
- Chemical transfer
- Cosmetics
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
#	#													
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.		
03-S30	03-S30B	1/8	3	.250	6	3,000	207	1-1/2	38	28	.05	.08	91	NA
04-S30	04-S30B	3/16	5	.305	8	3,000	207	2	51	28	.06	.09	91N	90
05-S30	05-S30B	1/4	6	.375	10	3,000	207	3	76	28	.11	.16	91N	90
06-S30	06-S30B	5/16	8	.430	11	2,500	172	4	102	28	.13	.20	91N	90
08-S30	08-S30B	13/32	10	.535	14	2,000	138	5	127	28	.15	.22	91N	90
10-S30	10-S30B	1/2	13	.636	16	1,750	121	6-1/2	165	28	.19	.28	91N	90
12-S30	12-S30B	5/8	16	.765	19	1,500	103	7-1/2	191	12	.24	.36	91N	90
16-S30	16-S30B	7/8	22	1.030	26	1,000	69	9	229	14	.31	.47	91N	90

## Construction

Tube: S30 - Natural FDA Compliant PTFE  
S30B - Black Static-Dissipative PTFE  
Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:  
-100°F to +450°F (-73°C to +232°C)  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)  
All ratings based on 72°F/23°C  
Change in length at working pressure is +2% to -4%

## Fittings

90 Series - pg. E-45  
91 Series - pg. E-52  
91N Series - pg. E-52  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Available from PAGE Business Unit, Ft. Worth, Texas  
(817) 624-1329 or email [page@parker.com](mailto:page@parker.com)  
See pg. A-20 for part numbering system

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



A-75

# S40/S40B - Industrial .040 wall Heavy Wall PTFE Hose, Stainless Steel Braid



## Features

- 33% more PTFE
- High temperature hose
- Excellent chemical compatibility
- Improved bend radius
- Decreased gas permeation
- Low friction minimizes pressure drops and deposits

## Compliances

- FDA 21 CFR 177.1550, 177.2600

## Applications/Markets



- Food & Beverage
- Pharmaceutical
- Fluid handling
- Chemical transfer
- Cosmetics
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series	Field Attachable Series
#	#													
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.		
03-S40	03-S40B	1/8	3	.250	6	3,000	207	1-1/2	38	28	.05	.08	91	NA
04-S40	04-S40B	3/16	5	.320	8	3,000	207	2	51	28	.08	.13	91N	90
05-S40	05-S40B	1/4	6	.375	10	3,000	207	3	76	28	.11	.16	91N	90
06-S40	06-S40B	5/16	8	.435	11	2,500	172	4	102	28	.12	.18	91N	90
08-S40	08-S40B	13/32	10	.565	14	2,000	138	5	127	28	.16	.23	91N	90
10-S40	10-S40B	1/2	13	.656	17	1,750	121	6-1/2	165	28	.17	.25	91N	90
12-S40	12-S40B	5/8	16	.780	20	1,500	103	7-1/2	191	12	.19	.28	91N	90
16-S40	16-S40B	7/8	22	1.05	27	1,000	69	9	229	14	.49	.73	91N	90

## Construction

Tube: S40 - Natural FDA Compliant PTFE  
S40B - Black Static-Dissipative PTFE  
Reinforcement: 304 Stainless Steel braid

## Operating Parameters

Temperature Range:  
-100°F to +450°F (-73°C to +232°C)  
Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)  
All ratings based on 72°F/23°C  
Change in length at working pressure is +2% to -4%

## Fittings

90 Series - pg. E-45  
91 Series - pg. E-52  
91N Series - pg. E-52  
For Crimp Die Selection charts see pgs. G-30 : G-41  
Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Available from PAGE Business Unit, Ft. Worth, Texas  
(817) 624-1329 or email [page@parker.com](mailto:page@parker.com)  
See pg. A-20 for part numbering system



# STW/STB - "TRUE BORE"

## Smoothbore PTFE Hose, Stainless Steel Braid



### Features

- High temperature hose
- Excellent chemical compatibility
- Resists moisture
- Low friction minimizes pressure drops and deposits

### Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

### Applications/Markets



- Food & Beverage
- Pharmaceutical
- Fluid handling
- Chemical transfer
- Cosmetics
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
03-STW	03-STB	1/8	3	.25	6	3,000	207	1-1/2	38	28	.05	.08	NA
04-STW	04-STB	1/4	6	.37	9	3,000	207	3	76	28	.08	.13	PAGE
06-STW	06-STB	3/8	10	.51	13	2,000	138	5	127	28	.11	.16	PAGE
08-STW	08-STB	1/2	13	.63	16	1,750	121	6-1/2	165	28	.16	.24	PAGE
12-STW	12-STB	3/4	19	.88	22	1,000	69	8.5	216	28	.20	.30	PAGE
16-STW	16-STB	1	25	1.13	29	1,000	69	12	305	20	.33	.49	PAGE
16Z-STW	16Z-STB	1	25	1.22	31	1,000	69	12	305	20	.56	.83	PAGE
20Z-STW	20Z-STB	1-1/4	32	1.52	38	1,000	69	14	356	18	.68	1.02	PAGE
24Z-STW	24Z-STB	1-1/2	38	1.73	44	900	62	15	381	15	.79	1.18	PAGE

### Construction

Tube: STW - Natural FDA Compliant PTFE

STB - Black Static-Dissipative PTFE

Reinforcement: 304 Stainless Steel braid

### Operating Parameters

Temperature Range:

-100°F to +450°F (-73°C to +232°C)

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

All ratings based on 72°F/23°C

Change in length at working pressure is +2% to -4%

### Fittings

PAGE Fittings – pg. E-71

Uses crimp collar ST300, see pg. E-72

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

### Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

"Z" indicates double braid

See pg. A-21 for part numbering system

Cannot be used with 90 or 91N series fittings

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



A-77

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# SBFW/SBFB - PAGE-flex™ SBF

## Extra Flexible Fluoropolymer Hose



### Features

- Half the minimum bend radius of conventional smoothbore products
- Kink and vacuum resistant
- Easily cleaned
- PPIH full line of optional reinforcement types
- Cooler outside temperatures reduces operator burns
- Reduces environment temperatures in confined areas
- Available with white Silicone jacket

### Compliances

- FDA 21 CFR 177.1550, 177.2600
- **USP Class VI Certified**
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

### Applications/Markets



- Food & Beverage
- Pharmaceutical
- Fluid handling
- Chemical transfer
- Cosmetics
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#											
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
06-SBFW	06-SBFB	3/8	10	.63	16	300	21	2	51	28	.16	.24
08-SBFW	08-SBFB	1/2	13	.76	19	300	21	2-1/2	64	28	.23	.34
12-SBFW	12-SBFB	3/4	19	1.04	26	250	17	3	76	28	.37	.55
16-SBFW	16-SBFB	1	25	1.29	33	250	17	4	102	28	.54	.80
24-SBFW	24-SBFB	1-1/2	38	1.85	47	200	14	7	178	28	.83	1.23

### Construction

Tube: SBFW - Natural PFA tube

SBFB - Black Static-dissipative PFA tube

Reinforcement: bonded wire braid - silicone - textile braided composite with 316 Stainless Steel braid

### Operating Parameters

Temperature Range:

-65°F to +325°F (-54°C to +163°C)

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

All ratings based on 72°F/23°C

### Fittings

PAGE Fittings – pg. E-71

Complete line of standard PPIH crimp fittings

### Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

Factory-made assemblies only

SBFB - Special order only

Available with white silicone jacket

See pg. A-21 for part numbering system

# SCW/SCB - Convoluted PTFE Hose 316 Stainless Steel Braid



## Features

- High temperature hose
- Excellent corrosion resistance
- Seamless
- Open pitch
- Self draining
- Withstands extreme flexing
- Environmentally safe; low effusion
- Long life expectancy

## Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

## Applications/Markets



- Fluid handling
- Chemical transfer
- Semiconductor
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#	⊘		⊘		↻		↻		U	lbs	kg	⊘
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
04-SCW	04-SCB	1/4	6	.46	12	1,500	104	3/4	19	28	.08	.11	PAGE
06-SCW	06-SCB	3/8	10	.54	14	1,500	104	1	25	28	.14	.21	PAGE
08-SCW	08-SCB	1/2	13	.72	18	1,500	104	1-1/2	38	28	.16	.23	PAGE
12-SCW	12-SCB	3/4	19	1.02	26	1,200	83	2	51	28	.27	.40	PAGE
16-SCW	16-SCB	1	25	1.31	33	1,000	69	2-1/2	64	28	.37	.55	PAGE
20-SCW	20-SCB	1-1/4	32	1.73	44	750	52	3	76	28	.46	.68	PAGE
24-SCW	24-SCB	1-1/2	38	1.93	49	650	45	3-3/4	95	28	.55	.81	PAGE
32-SCW	32-SCB	2	51	2.42	62	450	31	4-3/4	121	28	.90	1.4	PAGE

## Construction

Tube: SCW - Natural FDA Compliant PTFE

SCB - Black Static-Dissipative PTFE

Reinforcement: 316 Stainless Steel braid

## Operating Parameters

Temperature Range:

-100°F to +500°F (-73°C to +260°C)

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

All ratings based on 72°F/23°C

## Fittings

PAGE Fittings - pg. E-71

Uses crimp collar SC300, see pg. E-72

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

Not suggested for steam-cold water cycling applications

See pg. A-21 for part numbering system

Cannot be used with 90 or 91N series fittings

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



A-79

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# PCW/PCB - Convoluted PTFE Hose

## Polypropylene Braid



### Features

- Personal handling safety
- Excellent corrosion resistance
- Seamless
- Open pitch
- Self draining
- Withstands extreme flexing
- Environmentally safe; low effusion
- Long life expectancy

### Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

### Applications/Markets



- Fluid handling
- Chemical transfer
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#	⊘		⊘		↻		↻		U	lbs	kg	⊘
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
04-PCW	04-PCB	1/4	6	.55	14	350	59	3/4	19	28	.03	.05	PAGE
06-PCW	06-PCB	3/8	10	.64	16	350	59	1	25	28	.06	.09	PAGE
08-PCW	08-PCB	1/2	13	.84	21	300	21	1-1/2	38	28	.15	.22	PAGE
12-PCW	12-PCB	3/4	19	1.15	29	250	17	2	51	28	.18	.27	PAGE
16-PCW	16-PCB	1	25	1.50	38	250	17	2-1/2	64	28	.26	.39	PAGE
20-PCW	20-PCB	1-1/4	32	1.92	49	200	14	3	76	28	.37	.55	PAGE
24-PCW	24-PCB	1-1/2	38	2.12	54	200	14	3-3/4	95	28	.42	.63	PAGE
32-PCW	32-PCB	2	51	2.65	67	200	14	4-3/4	121	28	.56	.83	PAGE

### Construction

Tube: PCW - Natural FDA Compliant PTFE

PCB - Black Static-Dissipative PTFE

Reinforcement: Polypropylene

### Operating Parameters

Temperature Range:

0°F to +212°F (-18°C to +100°C)

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

All ratings based on 72°F/23°C

### Fittings

PAGE Fittings - pg. E-71

Uses crimp collar PC300, see pg. E-72

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

### Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

Not suggested for steam-cold water cycling applications

See pg. A-21 for part numbering system

Cannot be used with 90 or 91N series fittings



# SCWV/SCBV

## Stainless Steel Braid, Heavy Wall Convoluted PTFE Hose



### Features

- High temperature hose
- Open pitch
- Thicker wall
- Handles vacuum applications at elevated temperatures
- Excellent chemical compatibility
- Easy Cleaning
- Non Adhesive

### Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

### Applications/Markets



- Fluid handling
- Chemical transfer
- Semiconductor
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
08-SCWV	08-SCBV	1/2	13	.75	19	1,500	104	2	51	28	.17	.26	PAGE
12-SCWV	12-SCBV	3/4	19	1.04	26	1,200	83	2-3/4	70	28	.33	.49	PAGE
16-SCWV	16-SCBV	1	25	1.25	32	1,000	69	4	102	28	.37	.55	PAGE
20-SCWV	20-SCBV	1-1/4	32	1.66	42	750	52	5-1/2	140	28	.56	.83	PAGE
24-SCWV	24-SCBV	1-1/2	38	1.92	49	650	45	7	178	28	.64	.95	PAGE
32-SCWV	32-SCBV	2	51	2.49	63	450	31	8-1/2	216	28	.84	1.24	PAGE
40-SCWV	40-SCBV	2-1/2	64	3.25	83	200	14	12	305	28	1.52	2.26	PAGE
48-SCWV	48-SCBV	3	76	3.80	97	175	12	14	356	28	1.82	2.71	PAGE
64-SCWV	64-SCBV	4	102	4.76	121	150	10	16	406	28	2.10	3.13	PAGE

### Construction

Tube: SCWV - Heavy Wall Natural FDA Compliant PTFE  
 SCBV - Heavy Wall Black Static-dissipative PTFE  
 Reinforcement: 316 Stainless Steel braid

### Operating Parameters

Temperature Range:  
 -100°F to +500°F (-73°C to +260°C)  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F(23°C)  
 All ratings based on 72°F/23°C

### Fittings

PAGE Fittings - pg. E-71  
 Uses crimp collar SC300, see pg. E-72  
 For Crimp Die Selection charts see pgs. G-30 : G-41  
 Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

### Notes

Available from PAGE Business Unit, Ft. Worth, Texas  
 (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)  
 Not suggested for steam-cold water cycling applications  
 See pg. A-21 for part numbering system  
 Cannot be used with 90 or 91N series fittings  
 Vacuum wire recommended for 2-1/2, 3 and 4 inch

For detailed ordering information, please consult price list or contact Parflex® Division.



# PCWV/PCBV

## Polypropylene Braid, Heavy Wall Convoluted PTFE Hose



### Features

- Personal handling safety
- Open pitch
- Thicker wall
- Handles vacuum applications at elevated temperatures
- Excellent chemical compatibility
- Easy Cleaning
- Non Adhesive

### Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

### Applications/Markets



- Fluid handling
- Chemical transfer
- Paint

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#												
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
08-PCWV	08-PCBV	1/2	13	.81	21	300	21	3	76	28	.14	.20	PAGE
12-PCWV	12-PCBV	3/4	19	1.30	33	250	17	3-1/2	89	28	.22	.32	PAGE
16-PCWV	16-PCBV	1	25	1.44	36	250	17	4-1/2	114	28	.32	.47	PAGE
20-PCWV	20-PCBV	1-1/4	32	1.86	47	200	14	5	127	28	.40	.59	PAGE
24-PCWV	24-PCBV	1-1/2	38	2.10	53	200	14	6	152	28	.49	.73	PAGE
32-PCWV	32-PCBV	2	51	2.66	68	200	14	8-1/2	216	28	.66	.99	PAGE
40-PCWV	40-PCBV	2-1/2	64	3.57	91	150	10	12	305	28	1.21	1.80	PAGE
48-PCWV	48-PCBV	3	76	3.92	100	125	9	14	356	28	1.45	2.16	PAGE
64-PCWV	64-PCBV	4	102	4.92	125	100	7	16	406	28	1.68	2.50	PAGE

### Construction

Tube: PCWV - Heavy Wall Natural FDA Compliant PTFE

PCBV - Heavy Wall Black Static-dissipative PTFE

Reinforcement: Polypropylene

### Operating Parameters

Temperature Range:

0°F to +212°F (-18°C to +100°C)

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

All ratings based on 72°F/23°C

PAGE Fittings - pg. E-71

Uses crimp collar PC300, see pg. E-72

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

### Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

Not suggested for steam-cold water cycling applications

See pg. A-21 for part numbering system

Cannot be used with 90 or 91N series fittings

Vacuum wire recommended for 2-1/2, 3 and 4 inch

### Fittings



For detailed ordering information, please consult price list or contact Parflex® Division.

# SCWV-FS/SCBV-FS - Flare-Seal® Stainless Steel Braid



## Features

- Flare Seal fitting - Continuous PTFE through fitting; no area for bacterial entrapment
- Increased flow
- Thicker wall
- Excellent chemical compatibility
- Easy Cleaning
- Non Adhesive

## Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

## Applications/Markets



- Fluid handling
- Chemical transfer
- Paint
- Pharmaceutical
- Food & Beverage

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#											
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
08-SCWV-FS	08-SCBV-FS	1/2	13	.75	19	500	35	2	51	28	.17	.26
12-SCWV-FS	12-SCBV-FS	3/4	19	1.04	26	425	29	2-3/4	70	28	.33	.49
16-SCWV-FS	16-SCBV-FS	1	25	1.25	32	350	24	4	102	28	.37	.55
20-SCWV-FS	20-SCBV-FS	1-1/4	32	1.66	42	325	22	5-1/2	140	28	.56	.83
24-SCWV-FS	24-SCBV-FS	1-1/2	38	1.92	49	300	21	7	178	28	.64	.95
32-SCWV-FS	32-SCBV-FS	2	51	2.49	63	250	17	8-1/2	216	28	.84	1.24
40-SCWV-FS	40-SCBV-FS	2-1/2	64	3.25	83	200	14	12	305	28	1.52	2.26
48-SCWV-FS	48-SCBV-FS	3	76	3.80	97	175	12	14	356	28	1.82	2.71
64-SCWV-FS	64-SCBV-FS	4	102	4.76	121	150	10	16	406	28	2.10	3.13

## Construction

Tube: SCWV -FS- Heavy Wall Natural FDA Compliant PTFE  
 SCBV-FS - Heavy Wall Black Static-dissipative PTFE  
 Reinforcement: 316 Stainless Steel braid

## Operating Parameters

Temperature Range:  
 -100°F to +500°F (-73°C to +260°C)  
 Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)  
 All ratings based on 73°F/23°C

## Fittings

PAGE Fittings - pg. E-71

## Notes

Available from PAGE Business Unit, Ft. Worth, Texas  
 (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)  
 Factory-made assemblies only  
 Not suggested for steam-cold water cycling applications  
 All dimensions nominal  
 See pg. A-21 for part numbering system  
 Cannot be used with 90 or 91N series fittings

For detailed ordering information, please consult price list or contact Parflex® Division.



# PCWV-FS/PCBV-FS - Flare-Seal®

## Polypropylene Braid



### Features

- Flare Seal fitting - Continuous PTFE through fitting; no area for bacterial entrapment
- Increased flow
- Personal handling safety
- Good chemical compatibility
- Easy Cleaning
- Non Adhesive

### Compliances

- FDA 21 CFR 177.1550, 177.2600
- USP Class VI
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

### Applications/Markets



- Fluid handling
- Chemical transfer
- Paint
- Pharmaceutical
- Food & Beverage

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight	
#	#											
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.
08-PCWV-FS	08-PCBV-FS	1/2	13	.810	21	300	21	3	76	28	.14	.20
12-PCWV-FS	12-PCBV-FS	3/4	19	1.10	28	250	17	3-1/2	89	28	.22	.32
16-PCWV-FS	16-PCBV-FS	1	25	1.44	36	250	17	4-1/2	114	28	.31	.47
20-PCWV-FS	20-PCBV-FS	1-1/4	32	1.86	47	200	14	5	127	28	.40	.59
24-PCWV-FS	24-PCBV-FS	1-1/2	38	2.10	53	200	14	6	152	28	.49	.73
32-PCWV-FS	32-PCBV-FS	2	51	2.66	68	200	14	8-1/2	216	28	.66	.99
40-PCWV-FS	40-PCBV-FS	2-1/2	64	3.42	87	150	10	12	305	28	1.21	1.80
48-PCWV-FS	48-PCBV-FS	3	76	3.92	100	125	9	14	356	28	1.45	2.16
64-PCWV-FS	64-PCBV-FS	4	102	4.92	125	100	7	16	406	28	1.68	2.50

### Construction

Tube: PCWV-FS - Heavy Wall Natural FDA Compliant PTFE

PCBV-FS- Heavy Wall Black Static-dissipative PTFE

Reinforcement: Polypropylene

### Operating Parameters

Temperature Range:

0°F to +212°F (-18°C to +100°C)

Min. Burst Pressure is 4x Max. Working Pressure at 73°F (23°C)

All ratings based on 73°F/23°C

### Fittings

PAGE Fittings - pg. E-71

### Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

Factory-made assemblies only

Not suggested for steam-cold water cycling applications

See pg. A-21 for part numbering system

Cannot be used with 90 or 91N series fittings



# RCTW/RCTB EPDM Rubber Covered Fluoropolymer Hose



## Features

- Personal handling safety
- Handles full vacuum
- Good chemical compatibility
- Easy Cleaning
- Non Adhesive

## Compliances

- FDA 21 CFR 177.1550, 177.2600
- **USP Class VI Certified**
- European Pharmacopoeia 3.1.9
- ISO 10993 Sections 5, 6, 10, 11

## Applications/Markets



- Food & Beverage
- Pharmaceutical
- Fluid handling
- Chemical
- Industrial
- Paint
- Semiconductor

Part Number		Nominal I.D.		Nominal O.D.		Maximum Working Pressure 73°F/ 23°C		Minimum Bend Radius		Vac. Rating Hg./73°F	Weight		Permanent Fitting Series
#	#	⊘		⊘		↗		↘		U	lbs	kg	⊗
Natural	Conductive	inch	mm	inch	mm	psi	bar	inch	mm	inch	lbs./ft.	kg./mtr.	
08-RCTW	08-RCTB	1/2	13	.95	24	500	35	2-1/2	64	30	.33	.49	PAGE
12-RCTW	12-RCTB	3/4	19	1.25	32	500	35	3	76	30	.51	.76	PAGE
16-RCTW	16-RCTB	1	25	1.53	39	450	31	4	102	30	.67	1.00	PAGE
20-RCTW	20-RCTB	1-1/4	32	1.74	44	375	26	7	178	30	.72	1.07	PAGE
24-RCTW	24-RCTB	1-1/2	38	2.13	54	375	26	9	229	30	1.10	1.51	PAGE
32-RCTW	32-RCTB	2	51	2.68	68	300	21	10-1/2	267	30	1.54	2.30	PAGE
40-RCTW	40-RCTB	2-1/2	64	3.30	84	200	14	15	381	30	2.07	3.09	PAGE
48-RCTW	48-RCTB	3	76	3.88	99	200	14	18	457	30	2.99	4.46	PAGE
64-RCTWV	64-RCTB	4	102	4.98	127	150	10	22-1/2	572	30	4.33	6.46	PAGE

## Construction

Tube: RCTW - Natural FEP tube

RCTB - Static-dissipative PFA tube

Reinforcement: Double wire helix - multi layered rubber

Cover: Textile reinforced EPDM

## Operating Parameters

Temperature Range:

-40°F to +300°F (-40°C to +149°C) Decrease working pressure one percent for every 2°F above 212°F.

Operating pressures shown are for non-impulse service

All ratings based on 73°F/23°C

## Fittings

PAGE Fittings - pg. E-71

Uses crimp collar RC300, see pg. E-72

For Crimp Die Selection charts see pgs. G-30 : G-41

Crimp information can be found online, for most Parker products, at [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

## Notes

Available from PAGE Business Unit, Ft. Worth, Texas (817) 624-1329 or email [page@parker.com](mailto:page@parker.com)

RCTB - Special order only

See pg. A-21 for part numbering system

Cannot be used with 90 or 91N series fittings

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



A-85

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical



# Tubing



## Thermoplastic

Polyethylene

Nylon

Polypropylene

Polyurethane

Clear Vinyl


## Fluoropolymer

PTFE

FEP

PFA

PVDF



# Table of Contents

## Introduction

Intro .....	B-4 : B-5
Tubing Compatibility Chart Material Overview .....	B-5

## Polyethylene Tubing

Fractional – Series E.....	B-8
Metric – Series E .....	B-10
Flame Resistant – Series PEFR.....	B-12
High Density – Series HDPE.....	B-14

## Nylon Tubing

Fractional – Series N .....	B-16
Metric – Series N .....	B-18
Pure Air Tubing – Series PAT .....	B-20
Semi-rigid Tubing – Series NR .....	B-22
Series NTNA.....	B-24

## Polypropylene Tubing

Laboratory Grade – Series PP.....	B-26
Ultraviolet Light Resistant – Series PPB .....	B-26

## Polyurethane Tubing

Fractional Polyether Base – Series U .....	B-28
Metric Polyether Base – Series UM.....	B-30
HUFR MicroWeld™ – Series HUFR.....	B-32
Fractional – Series HU.....	B-34
Metric Series HUM .....	B-36

## Clear Vinyl Tubing

Clear Vinyl Tubing – Series PV .....	B-39
--------------------------------------	------





# Fluoropolymer Tubing

## Introduction

Intro .....	B-42 : B47
Material Overview.....	B-44
Fluoropolymer Nomenclature.....	B-46

## PTFE Tubing

AWG – Series TFH, TFS, TFT, TFL .....	B-50
Fractional – Series TFS, TFT, TFL.....	B-48
Fractional – Series 101 .....	B-56
Metric – Series 201.....	B-58
Beading - Series TFB .....	B-60
PTFE Fractional Heat Shrink - Series HS2TFS, HS2TFT, HS2TFL, HS2TFI .....	B-62
PTFE AWG 2:1 Heat Shrink - Series HS2TFS, HS2TFT, HS2TFL .....	B-64
PTFE AWG 4:1 Heat Shrink - Series HS4TFI .....	B-68

## FEP Tubing

Fractional – Series 103.....	B-70
Metric – Series 203.....	B-72
FEP 1.3:1 Heat Shrink - Series HS1.3FEP .....	B-74
FEP 1.67:1 Heat Shrink - Series HS1.67FEP .....	B-76

## PFA Tubing

Fractional – Series 104.....	B-78
Metric – Series 204.....	B-80

## PVDF Tubing

Flex™– Series 110.....	B-82
Super-Flex® – Series 111 .....	B-84

For detailed ordering information, please consult price list or contact Parflex® Division.



# Parflex Tubing Introduction

## Parflex Tubing Tutorial

- Review the general attributes of Parflex thermoplastic and fluoropolymer tubing – this provides an excellent overview for the tubing product line.
- Review the symbols pages - this will help you clear up any questions you may have on the product tables within the section. The market/applications table identifies and provides a “good fit” summary.
- Review the pressure bar graph - provides relative pressure ratings for the entire line of thermoplastic tubing. For fluoropolymer tubing, please contact your Customer Service Representative.
- Review the STAMPED guide (Size, Temperature, Media, Application, Pressure, End Configuration, and Delivery Preferences) on page 11 to help narrow your search for the desired product.
- Specific nomenclature, features, advantages and benefits can be found at the beginning page of each product line.
- Text appears in 2 colors. The primary dimensions are in black. As courtesy, the metric/inch equivalent has been added and appears in blue.

## Tube Line Fabrication Guide for Leak Free Systems

Every hydraulic, pneumatic and lubrication system requires some form of tube line fabrication and fitting installation for completion. Proper fabrication and installation are essential for the overall efficiency, leak free performance and general appearance of any system.

Start by planning ahead. After sizing the tube lines and selecting the appropriate style of fitting, consider the following in the design of your system:

- Accessibility of joints
- Proper routing of lines
- Adequate tube line supports
- Available fabricating tools

### Routing of Lines

Routing of lines is probably the most difficult, yet most significant, of these system design considerations. Proper routing involves getting a connecting line from one point to another through the most logical path.

Always try to leave fitting joints as accessible as possible. Hard to reach joints are hard to assemble and tighten properly. Inaccessible joints are also more difficult and time consuming to service.

## Applications/Markets

Product applications for all pertinent markets



Transportation



Mobile Hydraulics



Industrial Pneumatic



Industrial Hydraulics



Fluid Handling




Life Science



Food & Beverage

# Parflex Tubing Introduction

## Tubing Compatibility Chart Parker Tubing / Hose Capability with Parker FSC Fittings

 <b>Parker Tubing Compatibility with Parker FSC Fittings</b>		Thermoplastic Tubing														Fluoropolymer Tubing						
		Industrial Tubing Series (Outside Diameter Shown)														Transportation Tubing						
		Polyethylene E & EB Inch (4.5,6,8,10) Metric (6,8,10,12)	Polyethylene PEFR Inch (2.5,4,6,8)	Polyethylene HDPE Inch (4,6)	Nylon N Inch (2,2.5,3,4,5,6,8) Metric (4mm - 20mm)	Nylon PAT Inch (2,4,6,8,10,12)	Nylon NR Inch (2,2.4,5,6,8)	Nylon NT Inch (2,2.5,3,4,5,6,8)	Polypropylene PP & PPB Inch (2,2.5,3,4,5,6,8)	Polyurethane U & UM (90 - 95 Shore A) Inch (2,3,4,6,8,9,12) Metric (4,6,8,10,12)	Polyurethane HU & HUM (95 Shore A) Inch (2,2.5,4,6,8,12) Metric (4,6,8,10,12)	Polyurethane HUFER (MicroWeld Tubing) Inch (4,6,8)	Clear Vinyl Inch (1/8" - 2 1/2")	1120/1220 Air Brake (SAE J844) Inch (2,2.5,3,4,5,6,8,10,12)	Air Brake DIN 74324 (Nylon 12) Metric (4,6,8,10,12,15,16,18)	PPT Diesel Fuel Sizes 4,6,8,10,12	HTFL Diesel Fuel Sizes 4,6,8,10,12	PPA Fluoropolymer Inch (3/32" - 1") Metric (4mm - 12mm)	FEP Fluoropolymer Inch (1/8" - 1") Metric (3mm - 12mm)	PTFE Fluoropolymer Inch (3/32" - 1 1/4") Metric (3mm - 16mm)	PVDF Fluoropolymer Inch (2,3,4,5,6,8,10,12,16)	
<b>Compression &amp; Flare</b> <b>Compression</b> Inch (2,3,4,5,6,7,8,10,12,14) <b>Compress-Align®</b> Inch (2,3,4,5,6,8,10,12,14,16) <b>Metru-Lok™</b> Metric (4,6,8,10,12,14,16,18,22) <b>Poly-Tite</b> Inch (2,3,4,5,6,8) <b>Hi-Duty</b> Inch (2,3,4,5,6,8,10) <b>45 degree flare</b> Inch (2,3,4,5,6,8,10,12,14) <b>Inverted Flare</b> Inch (2,3,4,5,6,8,10,12,14) <b>Fast &amp; Tite</b> Inch (4,5,6,8,10)	PS	PS	PS	PS	PS	PS	PS	PS														
	TS	TS	TS	TS	TS	TS	TS	TS														
	BS																					
	CL																					
	-																					
	<b>Push-to-Connect</b> <b>Flow Controls</b> Inch (2,2.5,4,5,6,8) Metric (4,6,8,10,12) <b>Prestolok Brass</b> Inch (2,2.5,3,4,5,6,8) Metric (4,5,6,8,10,12,14) <b>Prestolok Composite</b> Inch (2,2.5,3,4,5,6,8) Metric (4,5,6,8,10,12,14) <b>Prestoweld</b> Inch (4,5,6,8) <b>Global Connect</b> Inch (2,2.5,3,4,5,6,8) Metric (4,6,8,10,12) <b>Liquifit</b> Inch (4,6,8) <b>TrueSeal™</b> Inch (4,5,6,8)	PS	PS	PS	PS	PS	PS	PS	PS													
		TS	TS	TS	TS	TS	TS	TS	TS													
		BS																				
		CL																				
		-																				
<b>Barb</b> <b>Par-Barb®</b> Inch (2,3,4,5,6,8,10,12) <b>Dubi-Barb®</b> Inch (2,5,4,6,8) <b>Hose Barb</b> Inch (2,3,4,5,6,8,10,12,16) Inside Diameter <b>Garden Hose</b>																						
		PS	PS	PS	PS	PS	PS	PS	PS													
		TS	TS	TS	TS	TS	TS	TS	TS													
		BS																				
		CL																				
<b>DOT Transportation</b> <b>NTA®</b> Inch (3,4,6,8,10,12) <b>Transmission Fittings</b> Inch (2,2.5) <b>Air Brake</b> Inch (4,6,8,10,12,16) <b>Air Brake Hose</b> Inch (6,8) <b>Vibra-Lok</b> Inch (2,3,4,5,6,8,10,12) <b>Prestomatic</b> Inch (2,2.5,3,4,6,8,10,12) Metric (6,8,10,12,16) <b>PTC</b> Inch (4,6,8,10,12) <b>SAE Cartridges</b> Inch (2,5,4,6,8,10,12) <b>Manifolds</b> Inch (4,6,8)																						
	PS	PS	PS	PS	PS	PS	PS	PS														
	TS	TS	TS	TS	TS	TS	TS	TS														
	BS																					
	CL																					
	-																					

For detailed ordering information, please consult price list or contact Parflex® Division.



Tubing  
Thermoplastic

Coiled Air Hose  
& Fittings

Transportation

Fittings

Tooling, Equipment  
& Accessories

General Technical

# Thermoplastic Tubing

Tubing  
Thermoplastic  
B

## Polyethylene

- Parflex polyethylene tubing meets FDA, NSF Standard 51 for all food contact applications and NSF-61 for potable water applications.
- E-Series tubing is made of 100% virgin resin material.
- Polyethylene tubing meets ASTM D-1693 (10% IGEPAL) for stress crack resistance.
- Parflex also offers special PE tubing: PEFR (flame retardant) and HDPE (high density).

## Nylon

- Flexible nylon tubing is constructed of high-grade resins for strength and flexibility for routing in tight spaces.
- Semi-rigid high strength nylon is constructed of high-grade resins without the addition of plasticizers for higher pressure tubing applications.
- Pure Air Tubing (PAT) is the tubing choice for pure air systems (semiconductor) due to its cleanliness; in addition, it offers excellent chemical and UV light resistance.
- NTNA Tubing meets NSF Standard 51 for all food contact applications and may be used for instrumentation lines, lubrication and process piping systems and oil and refrigerant lines.

Coiled Air Hose  
& Fittings  
C

## Polypropylene

- Polypropylene tubing meets FDA, NSF Standard 51 for all food contact applications.
- Polypropylene tubing exhibits excellent chemical resistance to chlorinated water applications.
- Black Polypropylene tubing is commonly used in outdoor applications where UV light stabilization is required.

Transportation  
D

## Polyurethane

- Polyurethane tubing is a flexible, kink-resistant and abrasion-resistant material commonly used in pneumatic applications.
- Polyurethane is available in multiple transparent and opaque colors for system color coding.
- Polyurethane is available in the following durometers (measurement of material hardness):
  - Medium durometer: (90 – 95)
  - High durometer: (>95) for higher pressures

Fittings  
E

## Polyvinyl Chloride (PVC)

- PVC tubing is made from 100% virgin resin material and meets all FDA specifications for materials in contact with food and drugs.
- PVC tubing is a very flexible, 70 durometer tubing. It is crystal-clear and ideal for situations where visible fluid flow is necessary (i.e. sight gauges for tank identification).

Tooling, Equipment  
& Accessories  
F

**All plastic tubing dimensions are laser monitored to ensure overall quality product.  
Most tubing sizes are packaged in convenient 100-ft., 250-ft., 500-ft. and 1,000-ft. lengths.**


General Technical  
G



# Thermoplastic Tubing

Product Family	Series	Suggested Markets and Applications
Polyethylene	E and EB	Potable water, chemical transfer, and low-cost, low-pressure pneumatics, NSF-51 & NSF- 61
	PEFR	Pneumatic controls in HVAC
High Density Polyethylene	HDPE	Chemical transfer and low-cost pneumatics
Nylon	N	Pneumatic and petroleum-based chemical transfer
	PAT	Pure air and gas distribution systems, semiconductor
	NR	High pressure pneumatic, low pressure lubrication and hydraulic, marine control systems
	NTNA	Instrumentation lines, lubrication and process piping systems, oil and refrigerant lines, NSF-51
Polypropylene	PP and PPB	Food contact and chemical transfer applications, chlorinated water, NSF-51
Urethane	U and UM	Pneumatic controls requiring high flexibility, kink resistance and movement
	HU and HUM	High-pressure pneumatics requiring flexibility and kink resistance, robotics
Vinyl	PV	Low-pressure chemical and medical applications requiring high clarity and flexibility, FDA

## Tubing Pressure Ranges



Working pressures are at 73°F (23°C). Pressure ratings are also effected by diameter of tubing and wall thickness. Actual performance may vary with different media and working conditions. Use this information for comparison only.

For detailed ordering information, please consult price list or contact Parflex® Division.





# Polyethylene Tubing

Series E: Instrument Grade – FDA, NSF Listed  
Series EB: Ultraviolet Light Resistant



## Features

- Made from 100% virgin resin material
- Chemically resistant and flexible
- High molecular weight resin provides increased dimensional stability, uniformity and long-term strength
- Economical system solution

## Certifications

- FDA compliant for food contact
- ASTM D-1693 (10% IGEPAL) for stress crack resistance
- NSF - 51
- NSF - 61

## Applications/Markets



- Potable water
- Chemical transfer
- Low-pressure pneumatics

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Minimum Burst at 73°F / 23°C		Package Quantity	Minimum Bend Radius		Weight	
		#	#	inch	mm	inch	mm	inch	mm	psi	bar		psi	bar	feet	inch
E-43-XXXX	EB-43-XXXX	1/4	6.4	.170	4.3	.040	1.0	120	8.3	480	33.1	0100, 0500, 1000	1.00	25.4	.011	.016
E-53-XXXX	EB-53-XXXX	5/16	7.9	.187	4.8	.062	1.6	145	10.0	580	40.0	0100, 0500	1.13	28.7	.020	.030
E-64-XXXX	EB-64-XXXX	3/8	9.5	.250	6.4	.062	1.6	125	8.6	500	34.5	0100, 0500	1.25	31.8	.025	.037
E-86-XXXX	EB-86-XXXX	1/2	12.7	.375	9.5	.062	1.6	90	6.2	360	24.8	0100, 0500	2.50	63.5	.034	.051
E-108-XXXX	EB-108-XXXX	5/8	15.9	.500	12.7	.062	1.6	70	4.8	280	19.3	0100	4.00	101.6	.044	.065

Standard black is not NSF approved.



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## Order Information

### Example: E-64-Y-0500

**E-64-Y-0500 – Polyethylene**

E-64-Y-0500 – **Tube O.D.** in sixteenths of an inch (**3/8"**)

E-64-Y-0500 – **Tube I.D.** in sixteenths of an inch (**.250"**)






E-64-Y-0500 – **Color**, i.e. **Yellow** (Omit for Natural and Black)

**E-64-0500** – Natural Polyethylene

**EB-64-0500** – Black Polyethylene


E-64-Y-0500 – **Package Quantity** in feet (**500'**)

Available in black as well as nine other colors, as recommended by the Instrument Society of America

Color Code		
	-	Natural
	-	Black
	B	Blue
	G	Green
	O	Orange
	P	Purple
	R	Red
	GRA	Gray
	Y	Yellow
	WHT	White

## Polyethylene Tubing (Series E)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- Liquifit
- TrueSeal™
- Dubl-Barb®
- Prestomatic
- SAE Cartridge

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- FDA, NSF-51 and NSF-61 compliant black polyethylene tubing is also available. Add -NSF suffix to the EB part number (ie. EB-64-0500-NSF)
- E series natural and colored tubing meet FDA, NSF-51 requirements for food contact applications and NSF-61 for potable water
- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (10% IGEPAL)
- Black (EB) tubing contains an ultraviolet inhibitor which is recommended for use in sunlit areas and in close proximity to high ultraviolet light sources
- All tubing conforms to ASTM D-1248, Type I, Class A, Category 4, Grade E5
- The recommended operating temperature range for service at rated pressures with compatible fluids is -80°F (-62°C) to +150°F (+66°C)

## Colors

- See Color Code Table

For detailed ordering information, please consult price list or contact Parflex® Division.



# Metric Polyethylene Tubing

Series E: Instrument Grade – FDA, NSF Listed  
Series EB: Ultraviolet Light Resistant



## Features

- Made from 100% virgin resin material
- Chemically resistant and flexible
- High molecular weight resin provides increased dimensional stability, uniformity and long-term strength
- Economical system solution

## Certifications

- FDA compliant for food contact
- ASTM D-1693 (10% IGEPAL) for stress crack resistance
- NSF - 51
- NSF - 61

## Applications/Markets



- Potable water
- Chemical transfer
- Low-pressure pneumatics

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
		mm	inch	mm	inch	mm	inch	bar	psi	bar	psi		feet	mm	inch	kg./mtr.
#	#															
Natural	Black															
E-6X1-0100	EB-6X1-0100	6	.236	4	.157	1.00	.039	8.6	125	34.5	500	0100	25	1.00	.019	.013
E-8X1-0100	EB-8X1-0100	8	.315	6	.236	1.00	.039	6.9	100	27.6	400	0100	38	1.50	.021	.014
E-10X1.5-0100	EB-10X1.5-0100	10	.393	7	.276	1.50	.059	8.6	125	34.5	500	0100	38	1.50	.039	.026
E-12X1.5-0100	EB-12X1.5-0100	12	.472	9	.354	1.50	.059	6.2	100	24.8	400	0100	63	2.50	.048	.032

Standard black is not NSF approved.



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## Order Information

### Example: E-8x1-0100

**E-8x1-0100 – Metric Polyethylene (Natural)**

**EB-8x1-0100 – Metric Polyethylene (Black)**


**E-8x1-0100 – Tube O.D. in millimeters (8 mm)**

**E-8x1-0100 – Tube Wall Thickness in millimeters (1 mm)**

**E-8x1-0100 – Package Quantity in feet (100')**

## Metric Polyethylene Tubing (Series E)

### Maximum Working Pressure (bar)



## Fitting Recommendations

Parker Fittings available from:  
 Fluid System Connectors Division  
 Otsego, MI  
 (269) 692-6555  
 (269) 694-4614 FAX

### FSC Product Families:

- Metru-Lok™
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- Prestomatic

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- E series natural and colored tubing listed below meet FDA, NSF-51 requirements for food contact applications and NSF-61 for potable water
- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (10% IGEPAL)
- Black (EB) tubing contains an ultraviolet inhibitor which is recommended for use in sunlit areas and in close proximity to high ultraviolet light sources
- All tubing conforms to ASTM D-1248, Type I, Class A, Category 4, Grade E5
- The recommended operating temperature range for service at rated pressures with compatible fluids is -62°C (-80°F) to +66°C (+150°F)

## Colors

- Natural
- Black

For detailed ordering information, please consult price list or contact Parflex® Division.



# Polyethylene Tubing

## Series PEFR: Flame Resistant



### Features

- Excellent stress crack resistance

### Certifications

- UL 94 V-2
- ASTM D-1693 (10% IGEPAL) for stress crack resistance

### Applications/Markets



- Pneumatic controls in HVAC applications
- Weld spatter/spark environments

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.
#															
Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
PEFR-2.5-XXXX	5/32	4.0	.096	2.4	.030	0.76	185	12.8	740	51.0	0500	.50	12.7	.006	.009
PEFR-4-XXXX	1/4	6.4	.170	4.3	.040	1.0	140	9.7	560	38.6	0500, 1000	.75	17.4	.012	.018
PEFR-6-XXXX	3/8	9.5	.250	6.4	.062	1.6	155	10.7	620	42.8	0500	1.50	36.1	.029	.043
PEFR-8-XXXX	1/2	12.7	.375	9.5	.062	1.6	100	6.9	400	27.6	0250	1.75	39.1	.041	.061



For detailed ordering information, please consult price list or contact Parflex® Division.



## Order Information


### Example: PEFR-4-0500

**PEFR-4-0500** – Flame Resistant Polyethylene

PEFR-**4**-0500 – **Tube O.D.** in sixteenths of an inch (**1/4"**)

PEFR-4-**0500** – **Package Quantity** in feet (**500'**)

## Flame Resistant Polyethylene Tubing (Series PEFR) Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

- FSC Product Families:
- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- Dubl-Barb®

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

Using the same base linear low-density polyethylene (LLDPE) as the E-Series tubing, Parker Hannifin, Parflex Division's PEFR tubing has the following advantages:

- Resistant to environmental stress cracking exceeding that of ordinary polyethylene tubing as measured by ASTM D-1693 (10% IGEPAL)
- The recommended operating temperature range for service at rated pressures with compatible fluids is -85°F (-65°C) to +150°F (+66°C).

## Colors

- Black

For detailed ordering information, please consult price list or contact Parflex® Division.

# Polyethylene Tubing

## Series HDPE: High Density



### Features

- Manufactured from high strength, high density polyethylene
- Semi-rigid tubing that is inherently resistant to most chemicals, less easily cut or damaged and has a higher burst pressure rating than Series E tubing
- Economical system solution

### Applications/Markets



- Chemical transfer
- Low-pressure pneumatics

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Package Quantity	Minimum Bend Radius		Weight	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.
<b>#</b>															
<b>Black</b>															
HDPE-43-XXXX	1/4	6.4	.170	4.3	.040	1.0	300	20.7	1200	82.7	0250, 0500	1.50	38.1	.011	.016
HDPE-64-XXXX	3/8	8.5	.250	6.4	.062	1.6	300	20.7	1200	82.7	0250, 0500	2.50	63.5	.025	.037

Only available in black.

## Order Information

### Example: HDPE-43-0500

**HDPE-43-0500** – High Density Polyethylene


HDPE-**43**-0500 – **Tube O.D.** in sixteenths of an inch (**1/4"**)

HDPE-**43**-0500 – **Tube I.D.** in sixteenths of an inch (**.170"**)

HDPE-43-**0500** – **Package Quantity** in feet (**500'**)

## High Density Polyethylene Tubing (Series HDPE)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

- FSC Product Families:
- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Recommended operating temperature range for service at rated pressures with compatible fluids is -80°F (-62°C) to +175°F (+80°C).


## Colors

- Black

For detailed ordering information, please consult price list or contact Parflex® Division.

# Nylon Tubing

## Series N: Flexible



### Features

- Flexible nylon tubing uses high-grade resins for strength and flexibility for routing in tight spaces
- Made from abrasion-resistant, heat and light-stabilized nylon
- Exhibits low-level water absorption
- Chemically resistant

### Certifications

- UL94HB  
(Natural only in wall thickness greater than .033")

### Applications/Markets



- Robotics
- Machine tool
- General pneumatics
- Lubrication
- Petroleum-based chemical transfer
- Pest control lines

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
		inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.
#	#															
Natural	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
NN-2-016	NB-2-016	1/8	3.2	.093	2.4	.016	0.41	250	17.2	1000	69.0	0100, 0250	.25	4.6	.003	.005
NN-2-031	NB-2-031	1/8	3.2	.064	1.6	.031	0.79	500	34.5	2000	137.9	0100, 0250	.25	4.6	.004	.006
NN-2.5-025	NB-2.5-025	5/32	4.0	.106	2.7	.025	0.64	300	20.7	1200	82.7	0100, 0250	.50	12.7	.005	.007
NN-3-025	NB-3-025	3/16	4.8	.138	3.5	.025	0.64	250	17.2	1000	69.0	0100, 0250	.63	16.0	.006	.009
NN-3-046	NB-3-046	3/16	4.8	.096	2.4	.046	1.2	500	34.5	2000	137.9	0100, 0250	.44	11.2	.009	.013
NN-4-035	NB-4-035	1/4	6.4	.180	4.6	.035	0.89	250	17.2	1000	69.0	0100, 0250	.88	22.4	.011	.016
NN-4-040	NB-4-040	1/4	6.4	.170	4.3	.040	1.0	310	21.4	1250	86.2	0100, 0250	.88	22.4	.012	.018
NN-4-062	NB-4-062	1/4	6.4	.127	3.2	.062	1.6	500	34.5	2000	137.9	0100, 0250	.50	12.7	.017	.025
NN-5-040	NB-5-040	5/16	7.9	.233	5.9	.040	1.0	250	17.2	1000	69.0	0100, 0250	1.13	28.7	.016	.024
NN-6-050	NB-6-050	3/8	9.5	.275	7.0	.050	1.3	250	17.2	1000	69.0	0100, 0250	1.13	28.7	.023	.034
NN-6-093	NB-6-093	3/8	9.5	.190	4.8	.093	2.4	500	34.5	2000	137.9	0100, 0250	.75	19.0	.038	.056
NN-8-062	NB-8-062	1/2	12.7	.375	9.5	.062	1.6	250	17.2	1000	69.0	0100, 0250	1.25	31.8	.039	.058
NN-8-124	NB-8-124	1/2	12.7	.253	6.4	.124	3.2	500	34.5	2000	137.9	0100, 0250	1.00	25.4	.067	.099



For detailed ordering information, please consult price list or contact Parflex® Division.


## Order Information

### Example: N-2-016-RED-0100

- N-2-016-RED-0100** – Nylon
- N-2-016-RED-0100 – **Tube O.D.** in sixteenths of an inch (**1/8"**)
- N-2-**016**-RED-0100 – **Wall Thickness** in inches (**.016"**)
- N-2-016-**RED**-0100 – **Colors** (Omit for Natural and Black)
  - NN**-2-016-0100 - Natural Nylon
  - NB**-2-016-0100 - Black Nylon
- N-2-016-RED-**0100** – **Package Quantity** in feet (**100'**)  
(Omit quantity number after color for 250' reel length)

Color Code		
○	NN	Natural
●	NB	Black
●	BLU	Blue
●	GRN	Green
●	RED	Red
●	YEL	Yellow

## Nylon Tubing (Series N) Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

### FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- TrueSeal™
- NTA®
- Transmission
- Prestomatic
- SAE Cartridge

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- The recommended operating temperature range for service at rated pressures with compatible fluids, depending upon conditions, is -65°F (-54°C) to +200°F (+93°C)
- Black tubing suggested for use in sunlit areas and in close proximity to high ultraviolet light sources

## Colors

- See Color Code Table

For detailed ordering information, please consult price list or contact Parflex® Division.





# Metric Nylon Tubing

## Series N: Flexible



### Features

- Flexible nylon tubing uses high-grade resins for strength and flexibility for routing in tight spaces
- Made from abrasion-resistant, heat and light-stabilized nylon
- Exhibits low-level water absorption
- Chemically resistant

### Certifications

- UL94HB  
(Natural only in wall thickness of 1mm and greater)

### Applications/Markets



- Robotics
- Machine tool
- General pneumatics
- Lubrication
- Petroleum-based chemical transfer
- Pest control lines

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Minimum Burst at 73°F / 23°C		Reel Length	Weight	
		mm	inch	mm	inch	mm	inch	bar	psi	bar	psi		kg./mtr.	lbs./ft.
#	#													
Natural	Black													
NN4X.65	NB4X.65	4	.157	2.7	.107	0.65	.026	26.0	377	68	986	100	.007	.005
NN6X1	NB6X1	6	.236	4.0	.157	1.00	.039	23.5	341	94	1363	100	.016	.011
NN8X1	NB8X1	8	.315	6.0	.236	1.00	.039	17.0	247	68	986	100	.024	.016
NN10X1	NB10X1	10	.393	8.0	.315	1.00	.039	12.5	181	50	725	100	.030	.020
NN12X1	NB12X1	12	.472	10.0	.393	1.00	.039	11.0	160	44	638	100	.036	.024
NN14X1.5	NB14X1.5	14	.551	11.0	.433	1.50	.059	15.0	218	60	870	100	.063	.042
NN16X1.5	NB16X1.5	16	.630	13.0	.512	1.50	.059	12.5	181	50	725	100	.073	.049
NN18X1.5	NB18X1.5	18	.709	15.0	.591	1.50	.059	10.5	152	42	609	100	.082	.055
NN20X1.5	NB20X1.5	20	.787	17.0	.669	1.50	.059	9.5	138	38	551	100	.092	.062

## Order Information

### Example: NN4x.65


NN4x.65 – Natural Nylon

NN4x.65 – Tube O.D. in millimeters (4mm)

NN4x.65 – Wall Thickness in millimeters (0.65mm)

## Metric Nylon Tubing (Series N)

### Maximum Working Pressure (bar)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Metru-Lok™
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- Prestomatic

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- The recommended operating temperature range for service at rated pressures with compatible fluids, depending upon conditions, is -54°C (-65°F) to +93°C (+200°F)
- Black tubing suggested for use in sunlit areas and in close proximity to high ultraviolet light sources


## Colors

- Natural
- Black

For detailed ordering information, please consult price list or contact Parflex® Division.

# Nylon Pure Air Tubing

## Series PAT: Ultra Pure, UV Resistant



### Features

- The tubing choice for pure air systems (semiconductor) due to its cleanliness and excellent chemical and UV light resistance
- Maintains good resistance to high ambient temperatures with low moisture absorption
- Manufactured from a specially formulated nylon for use in pure air and gas distribution systems
- Provides high tensile strength with excellent coupling retention in high pressure, temperature and vibration environments
- Sizes -2 and -4 are single wall tubing construction
- Sizes -6 through -12 are reinforced tubing construction

### Applications/Markets



- Pure air and gas distribution systems
- Semi-conductor

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight		
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.	kg./mtr.
<b>#</b>																
PAT2	1/8	3.2	.079	2.0	.023	0.58	250	17.2	1000	69.0	1000	.37	9.4	.035	.052	
PAT4	1/4	6.4	.170	4.3	.040	1.0	300	20.7	1200	82.7	1000	1.00	25.4	.124	.185	
PAT6	3/8	9.5	.251	6.4	.062	1.6	350	24.1	1400	96.4	500	1.50	38.1	.282	.420	
PAT8	1/2	12.7	.376	9.6	.062	1.6	235	16.2	950	65.5	500	2.00	50.8	.395	.588	
PAT10	5/8	15.9	.441	11.2	.092	2.3	225	15.5	900	62.1	250	2.50	63.5	.702	1.04	
PAT12	3/4	19.1	.566	14.4	.092	2.3	200	13.8	800	55.2	250	3.00	76.2	.872	1.30	



For detailed ordering information, please consult price list or contact Parflex® Division.

## Order Information

### Example: PAT4-BLK-0250

**PAT4**-BLK-0250 – Pure Air Tubing

PAT**4**-BLK-0250 – Tube O.D. in sixteenths of an inch (**1/4"**)


PAT4-**BLK**-0250 – Color (**Black**)

PAT4-BLK-**0250** – Package Quantity in feet (**250'**)

Color Code		
●	BLK	Black
●	BRN	Brown
●	SIL	Silver

## Pure Air Nylon Tubing (Series PAT)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align\*
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- NTA\*

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Packaged on corrugated plastic reel with ends capped and shipped in a plastic-lined container
- The suggested operating temperature range for service at rated pressures with compatible fluids is -70°F (-57°C) to +200°F (+93°C)
- PAT tubing is rated for full vacuum service at 28 inch Hg

## Colors

- See Color Code Table

# Nylon Tubing

## Series NR: Semi-rigid High Strength



### Features

- High grade nylon resins without the addition of plasticizers for higher pressure tubing applications
- Better chemical resistance than Series N, good resistance to high ambient temperature and low moisture absorption
- High tensile strength and excellent coupling retention in high pressure, temperature and vibration environments

### Certifications

- UL94HB  
(Natural and Black only in wall thickness greater than .033")

### Applications/Markets



- High-pressure pneumatics
- Lubrication systems
- Marine control systems
- Process lines for chemicals and oils

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
		inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.
#	#															
Natural	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
NNR-2-017	NBR-2-017	1/8	3.2	.091	2.3	.017	0.43	425	29.3	1700	117.2	0100, 0500	.50	12.7	.003	.005
NNR-2-026	NBR-2-026	1/8	3.2	.073	1.9	.026	0.66	625	43.1	2500	172.4	0100, 0500	.38	9.7	.004	.006
NNR-3-024	NBR-3-024	3/16	4.8	.140	3.6	.024	0.61	425	29.3	1700	117.2	0100, 0500	.75	19.0	.006	.009
NNR-3-039	NBR-3-039	3/16	4.8	.110	2.8	.039	0.99	625	43.1	2500	172.4	0100, 0500	.63	16.0	.008	.012
NNR-4-035	NBR-4-035	1/4	6.4	.180	4.6	.035	0.89	425	29.3	1700	117.2	0100, 0250	1.00	25.4	.011	.016
NNR-4-050	NBR-4-050	1/4	6.4	.150	3.9	.050	1.3	625	43.1	2500	172.4	0100, 0250	.88	22.3	.014	.021
NNR-5-040	NBR-5-040	5/16	7.9	.233	5.9	.040	1.0	425	29.3	1700	117.2	0100, 0250	1.50	38.1	.015	.022
NNR-6-048	NBR-6-048	3/8	9.5	.279	7.1	.048	1.2	425	29.3	1700	117.2	0100, 0250	1.75	44.5	.022	.033
NNR-6-075	NBR-6-075	3/8	9.5	.225	5.7	.075	1.9	625	43.1	2500	172.4	0100, 0250	1.50	38.1	.032	.048
NNR-8-062	NBR-8-062	1/2	12.7	.375	9.5	.062	1.6	350	29.3	1400	117.2	0100, 0250	2.38	60.5	.038	.057
NNR-8-075	NBR-8-075	1/2	12.7	.350	8.9	.075	1.9	625	43.1	2500	172.4	0100, 0250	2.50	63.5	.045	.067



For detailed ordering information, please consult price list or contact Parflex® Division.



## Order Information

### Example: NBR-2-017-0100

**NBR-2-017-0100** – Nylon

**NBR-2-017-0100** – Color (Black)

**NBR-2-017-0100** – Rigid

**NBR-2-017-0100** – Tube O.D. in sixteenths of an inch (**1/8"**)


**NBR-2-017-0100** – Wall Thickness in inches (**.017"**)

**NBR-2-017-0100** – Package Quantity in feet (**100'**)

(Omit for other package quantities)

## Semi-rigid Nylon Tubing (Series NR)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

### FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- TrueSeal™
- NTA®
- Transmission
- Prestomatic
- SAE Cartridge

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Suggested operating temperature range for service at rated pressures with compatible fluids is -60°F (-51°C) to +200°F (+93°C)

## Colors

- Natural
- Black

For detailed ordering information, please consult price list or contact Parflex® Division.

# Nylon Tubing

## Series NTNA: Semi-rigid Nylon Tubing



### Features

- High grade nylon resins without the addition of plasticizers
- High tensile strength and excellent coupling retention in high pressure, temperature and vibration environments
- Excellent chemical resistance
- Rugged construction resists vermin attack

### Certifications

- NSF-51

### Applications/Markets



- Instrumentation lines
- Lubrication systems
- Process piping systems
- Refrigerant lines

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Minimum Burst at 73°F / 23°C		Reel Length	Minimum Bend Radius		Weight	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		inch	mm	lbs./ft.	kg./mtr.
#															
22NTNA	1/8	3.2	.091	2.3	.017	0.4	375	25.9	1,500	103.4	500	0.50	12.7	.003	.005
532NTNA	5/32	4.0	.113	2.9	.022	0.6	375	25.9	1,500	103.4	500	0.63	16.0	.004	.006
33NTNA	3/16	4.8	.139	3.5	.024	0.6	375	25.9	1,500	103.4	350	0.75	19.0	.006	.009
44NTNA	1/4	6.4	.184	4.7	.033	0.8	375	25.9	1,500	103.4	200	1.00	25.4	.010	.015
55NTNA	5/16	7.9	.232	5.8	.040	1.0	375	25.9	1,500	103.4	150	1.50	38.1	.015	.022
66NTNA	3/8	9.5	.282	7.1	.048	1.2	375	25.9	1,500	103.4	100	1.75	44.4	.022	.033
88NTNA	1/2	12.7	.375	9.5	.062	1.6	375	25.9	1,500	103.4	100	2.38	60.5	.032	.048



For detailed ordering information, please consult price list or contact Parflex® Division.

## Order Information

### Example: 44NTNA


44NTNA – Tube O.D. in sixteenths of an inch (1/4")

44NTNA – Nylon Tubing

44NTNA – Color (Natural)

## Semi-rigid Nylon Tubing (Series NTNA)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- TrueSeal™

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Suggested operating temperature range from -60°F to +212°F (-51°C to +100°C)

## Colors

- Natural

For detailed ordering information, please consult price list or contact Parflex® Division.

# Polypropylene Tubing

Series PP: Laboratory Grade – FDA, NSF Listed  
Series PPB: Ultraviolet Light Resistant



## Features

- Acid and chemically resistant
- May be used in higher temperatures and working pressures than polyethylene tubing
- Excellent compatibility with high temperature water
- Low water absorption (less than .01%)
- Good compatibility with vegetable oils
- Excellent resistance to environmental stress cracking

## Certifications

- FDA Both in white; NSF also in special black part numbers
- NSF-51

## Applications/Markets



- Food contact - White only
- Chemical transfer
- Chlorinated water

Part Number	Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
		inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.
#	#															
White	Black	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	feet	inch	mm	lbs./ft.	kg./mtr.
PP-21-1000	PPB-21-1000	1/8	3.2	.079	2.0	.023	0.58	350	24.1	1400	96.4	1000	.50	12.7	.003	.005
PP-32-0500	PPB-32-0500	3/16	4.8	.120	3.1	.034	0.86	350	24.1	1400	96.4	0500	.75	14.4	.006	.009
PP-43-0500	PPB-43-0500	1/4	6.4	.170	4.3	.040	1.0	300	20.7	1200	82.7	0500	1.00	25.4	.010	.019
PP-53-0500	PPB-53-0500	5/16	7.9	.188	4.8	.062	1.6	350	24.1	1400	96.4	0500	1.25	31.8	.019	.028
PP-64-0500	PPB-64-0500	3/8	9.5	.250	6.4	.062	1.6	300	20.7	1200	82.7	0500	1.25	31.8	.024	.036
PP-86-0250	PPB-86-0250	1/2	12.7	.375	9.5	.062	1.6	225	15.5	900	62.1	0250	2.50	63.5	.033	.049
PP-108-0100	PPB-108-0100	5/8	15.9	.500	12.7	.062	1.6	175	12.1	700	48.3	0100	4.00	101.6	.042	.062



For detailed ordering information, please consult price list or contact Parflex® Division.

## Order Information

### Example: PP-86-0250

**PP-86-0250 – Polypropylene**


PP-86-0250 – **Tube O.D.** in sixteenths of an inch (**1/2"**)

PP-86-0250 – **Tube I.D.** in sixteenths of an inch (**.375"**)

PP-86-0250 – **Package Quantity** in feet (**250'**)

## Polypropylene Tubing (Series PP & PPB)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
 Fluid System Connectors Division  
 Otsego, MI  
 (269) 692-6555  
 (269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Poly-Tite
- Hi-Duty
- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- Global Connect
- Liquifit
- TrueSeal™

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- NSF black polypropylene tubing is available upon special request. Add -FDA suffix to PPB part number
- Suggested operating temperature range for service at rated pressures with compatible fluids is 0°F (-18°C) to +200°F (+93°C)

## Colors

- White
- Black

For detailed ordering information, please consult price list or contact Parflex® Division.



# Polyurethane Tubing

## Series U: Polyether Base



### Features

- 90 to 95 Shore A durometer
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

### Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General industrial pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

### Also available in coils

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Minimum Burst at 73°F / 23°C		Reel Length	Weight	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	lbs./ft.
#													
Natural													
U-21-XXXX	1/8	3.2	.063	1.6	.031	0.79	125	8.6	375	25.9	0050, 0250, 0500, 1000	.005	.007
U-32-XXXX	3/16	4.8	.125	3.2	.031	0.79	125	8.6	375	25.9	0050, 0250, 0500	.008	.012
U-42-XXXX	1/4	6.4	.125	3.2	.063	1.6	125	8.6	375	25.9	0050, 0250, 0500, 1000	.018	.027
U-64-XXXX	3/8	9.5	.250	6.4	.063	1.6	125	8.6	375	25.9	0050, 0250, 0500, 1000	.030	.045
U-85-XXXX	1/2	12.7	.328	8.3	.086	2.2	125	8.6	375	25.9	0050, 0250, 0500	.044	.065
U-86-XXXX	1/2	12.7	.375	9.5	.063	1.6	85	5.9	255	17.6	0050, 0250, 0500	.042	.062
U-96-XXXX	9/16	14.3	.375	9.5	.094	2.4	125	8.6	375	25.9	0050, 0100	.068	.101
U-128-XXXX	3/4	19.1	.500	12.7	.125	3.2	125	8.6	375	25.9	0050, 0100	.120	.179

## Order Information

### Example: U-21-BLK-0500

U-21-BLK-0500 – Polyurethane

U-21-BLK-0500 – Tube O.D. in sixteenths of an inch (1/8")

U-21-BLK-0500 – Tube I.D. in sixteenths of an inch (.063")

U-21-BLK-0500 – Color (Black) (Omit for Natural)


U-21-BLK-0500 – Package Quantity in feet (500')

Opaque Color Code		
○	-	Natural
●	BLK	Black
●	BLU	Blue
●	GRA	Gray
●	GRN	Green
●	ORG	Orange
●	RED	Red
○	WHT	White
●	YEL	Yellow

Transparent Color Code		
●	TBLU	Transparent Blue
●	TGRN	Transparent Green
●	TORG	Transparent Orange
●	TRED	Transparent Red
●	TYEL	Transparent Yellow

## Polyurethane Tubing (Series U)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- TrueSeal™
- Par-Barb®

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Suggested operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (+82°C)

## Colors

- See Color Code Table

# Metric Polyurethane Tubing

## Series UM: Polyether Base



### Features

- 90 to 95 Shore A durometer
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

### Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General industrial pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi		feet	kg./mtr.
#													
Natural	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi	feet	kg./mtr.	lbs./ft.
UM4x2.5-XXXX	4	.157	2.5	.098	0.75	.030	9.0	131	26.0	377	0100, 0250, 0500	.009	.006
UM6x4-XXXX	6	.236	4.0	.157	1.00	.039	9.0	131	26.0	377	0100, 0250, 0500	.018	.012
UM8x5-XXXX	8	.315	5.0	.196	1.50	.059	9.0	131	26.0	377	0100, 0250, 0500	.036	.024
UM10x6.5-XXXX	10	.393	6.4	.236	1.75	.069	9.0	131	26.0	377	0100, 0250	.053	.036
UM12x8-XXXX	12	.472	8.0	.315	2.00	.079	9.0	131	26.0	377	0100, 0250	.073	.049

## Order Information

### Example: UM6x4-BLK-0100

**UM6X4-BLK-0100 – Polyurethane Metric**

UM**6**X4-BLK-0100 – **Tube O.D.** in millimeters (**6 mm**)

UM**6X4**-BLK-0100 – **Tube I.D.** in millimeters (**4 mm**)

UM6X4-**BLK**-0100 – **Color (Black)** (Omit for Natural)

UM6X4-BLK-**0100** – **Package Quantity** in feet (**100'**)

Opaque Color Code		
○	-	Natural
●	BLK	Black
●	BLU	Blue
●	GRA	Gray
●	GRN	Green
●	ORG	Orange
●	RED	Red
●	YEL	Yellow

Transparent Color Code		
●	TBLU	Transparent Blue
●	TGRN	Transparent Green
●	TORG	Transparent Orange
●	TRED	Transparent Red
●	TYEL	Transparent Yellow

## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Flow Control
- Prestolok Brass
- Prestolok Composite

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes


- The recommended operating temperature range for service at rated pressures with compatible fluids is -40°C (-40°F) to +82°C (+180°F)

## Colors

- See Color Code Table

## Metric Polyurethane Tubing (Series UM)

### Maximum Working Pressure (bar)



For detailed ordering information, please consult price list or contact Parflex® Division.

# HUFR MicroWeld™ Tubing



## Features

- Mono-wall construction eliminates the need for skiving tools or knives, reducing installation time
- Excellent abrasion resistance
- Silicone and halogen free
- Weighs 36% less than equivalent jacketed tubing

## Certifications

- UL 94 V2 compliant

## Applications/Markets



- Robotics
- Welding
- General automation

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Minimum Bend Radius		Weight	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	inch	mm	lbs./ft.
#															
HUFR-4-045-XX-0500	1/4	6.4	.160	4.1	.045	1.1	175	12.1	525	36.2	0500	.50	12.7	.016	.024
HUFR-6-062-XX-0500	3/8	9.5	.251	6.4	.062	1.6	150	10.3	450	31.0	0500	.75	19.1	.033	.049
HUFR-8-090-XX-0250	1/2	12.7	.320	8.1	.090	2.3	160	11.0	475	32.7	0250	1.00	25.4	.063	.094



## Order Information

**Example: HUFR-4-045-BL-0500**

**HUFR-4-045-BL-0500 – MicroWeld™ Polyurethane**

HUFR-4-045-BL-0500 – **Tube O.D.** in sixteenths of an inch (**1/4"**)

HUFR-4-**045**-BL-0500 – **Wall Thickness** in inches (**.045"**)

HUFR-4-045-**BL**-0500 – **Color (Blue)**

HUFR-4-045-BL-**0500** – **Package Quantity** in feet (**500'**)

Color Code		
●	BK	Black
●	BL	Blue
●	GN	Green
●	RD	Red
○	WH	White

## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- PrestoWeld

## Notes


- Suggested operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (+82°C)

## Colors

- See Color Code Table

## MicroWeld™ Tubing (Series HUFR)

### Maximum Working Pressure (psig)



For detailed ordering information, please consult price list or contact Parflex® Division.



# Polyurethane Tubing

## Series HU: High Durometer Polyether Base



### Features

- 95 Shore A durometer or greater
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

### Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General industrial pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Minimum Burst at 73°F / 23°C		Reel Length	Weight	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar		feet	lbs./ft.
#													
HU-2-XXXX	1/8	3.2	.063	1.6	.031	0.79	300	20.7	900	62.1	0100, 0250, 0500	.005	.007
HU-2.5-XXXX	5/32	4.0	.094	2.4	.031	0.79	210	14.5	630	43.4	0100, 0500	.006	.009
HU-4-XXXX	1/4	6.4	.160	4.1	.045	1.1	180	12.4	540	37.2	0100, 0500	.014	.021
HU-6-XXXX	3/8	9.5	.250	6.4	.062	1.6	180	12.4	540	37.2	0100, 0500	.030	.045
HU-8-XXXX	1/2	12.7	.320	8.1	.090	2.3	180	12.4	540	37.2	0100, 0250	.057	.085
HU-12-XXXX	3/4	19.1	.467	11.9	.142	3.6	180	12.4	540	37.2	0100, 0250	.133	.198

## Order Information

**Example: HU-2-BLK-0500**

**HU-2-BLK-0500 – High Durometer Polyurethane**

HU-2-BLK-0500 – **Tube O.D.** in sixteenths of an inch (**1/8"**)


HU-2-**BLK**-0500 – **Color (Black)**

HU-2-BLK-**0500** – **Package Quantity** in feet (**500'**)

Color Code		
●	BLK	Black
●	BLU	Blue
●	DBL	Dark Blue
●	RED	Red
●	YEL	Yellow

## Polyurethane Tubing (Series HU)

### Maximum Working Pressure (psig)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Fast & Tite
- Flow Control
- Prestolok Brass
- Prestolok Composite
- TrueSeal™

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Suggested operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +180°F (+82°C)

## Colors

- See Color Code Table

For detailed ordering information, please consult price list or contact Parflex® Division.

# Metric Polyurethane Tubing

## Series HUM: High Durometer (Metric) Polyether Base



### Features

- 95 Shore A durometer or greater
- Excellent kink and abrasion resistance
- Excellent hydrolytic stability
- Flexible and easy to assemble onto designated fittings
- Polyurethane tubing exhibits the elongation and recovery characteristics of rubber and the chemical resistance associated with plastics

### Applications/Markets



- Pneumatic controls
- Robotics
- Machine tools
- General industrial pneumatics
- Vacuum equipment
- Analytical instrumentation
- Semiconductor equipment
- Medical and laboratory applications

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F /23°C		Minimum Burst at 73°F /23°C		Reel Length	Weight	
	mm	inch	mm	inch	mm	inch	bar	psi	bar	psi		feet	kg./mtr.
#													
HUM-4-XXXX	4	.157	2.4	.094	0.80	.031	12.4	180	37.2	540	0100, 0500	.009	.006
HUM-6-XXXX	6	.236	4.0	.157	1.00	.039	12.4	180	37.2	540	0100, 0500	.018	.012
HUM-8-XXXX	8	.315	5.0	.196	1.50	.059	12.4	180	37.2	540	0100, 0500	.036	.024
HUM-10-XXXX	10	.393	6.4	.236	1.75	.069	12.4	180	37.2	540	0100, 0250	.053	.036
HUM-12-XXXX	12	.472	8.0	.315	2.00	.079	12.4	180	37.2	540	0100, 0250	.073	.049

## Order Information

**Example: HUM-6-BLK-0100**

**HUM-6-BLK-0100 – High Durometer Metric Polyurethane**


HUM-**6**-BLK-0100 – **Tube O.D.** in millimeters (**6mm**)

HUM-6-**BLK**-0100 – **Color (Black)**

HUM-6-BLK-**0100** – **Package Quantity** in feet (**100'**)

## Metric Polyurethane Tubing (Series HUM)

### Maximum Working Pressure (bar)



## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Flow Control
- Prestolok Brass
- Prestolok Composite

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

## Notes

- Suggested operating temperature range for service at rated pressures with compatible fluids is -40°C (-40°F) to +82°C (+180°F)

## Colors

- Natural
- Black

For detailed ordering information, please consult price list or contact Parflex® Division.





# Vinyl Tubing

## Series PV: Clear Vinyl Tubing



### Features

- Made from a virgin clear PVC (polyvinyl chloride) resin; specifically formulated for exceptional purity, clarity and flexibility
- 70 durometer for soft, easy handling and bending without tubing collapse

### Certifications

- FDA compliant

### Applications/Markets



- Low-pressure chemicals
- Pneumatics
- Low-pressure sight flow indicator

### Order Information

#### Example: PV108-1

#### PV108-1 – Poly-Vinyl Tubing

PV108-1 – Tube O.D. in sixteenths of an inch (5/8")

PV108-1 – Tube I.D. in sixteenths of an inch (1/2")

PV108-1 – Formula V-1 FDA Approved Formulation

### Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Poly-Tite
- Fast & Tite
- TrueSeal™
- Par-Barb®
- Hose Barb
- Garden Fitting

A tube support should be used with this tubing for maximum holding power where end loading, vibration or pressure spikes may occur. Reference Tubing/Fitting Compatibility Chart (pg. B-5)

### Notes

- Formula V-1 tubing fully meets all specifications called out by the United States Food and Drug Administration (FDA) for materials in contact with food and drugs for human consumption
- Suggested operating temperature range for service at rated pressures with compatible fluids is -40°F (-40°C) to +150°F (+65°C)

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



B-39

A  
Hose

B  
Tubing  
Thermoplastic

C  
Coiled Air Hose  
& Fittings

D  
Transportation







E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Vinyl Tubing (cont.)

## Series PV: Clear Vinyl Tubing

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Std. Coil	Weight	
	inch	mm	inch	mm	inch	mm	psi	bar		feet	lbs./ft.
#											
PV21-1	1/8	3.2	.063	1.6	.031	.79	35	2.4	100	.005	.007
PV32-1	.170	4.3	.125	3.2	.025	.64	35	2.4	100	.006	.009
PV42-1	1/4	6.4	.125	3.2	.063	1.6	65	4.5	100	.025	.037
PV43-1	1/4	6.4	.170	4.3	.040	1.2	55	3.8	100	.014	.021
PV403-1	1/4	6.4	.188	4.8	.031	.79	22	1.5	100	.011	.016
PV53-1	5/16	7.9	.188	4.8	.063	1.6	55	3.8	100	.025	.037
PV63-1	3/8	9.5	.188	4.8	.094	2.4	65	4.5	100	.043	.064
PV73-1	7/16	11.1	.188	4.8	.125	3.2	75	5.2	100	.063	.094
PV54-1	5/16	7.9	.250	6.4	.031	.79	20	1.4	100	.014	.021
PV64-1	3/8	9.5	.250	6.4	.064	1.6	55	3.8	100	.032	.048
PV74-1	7/16	11.1	.250	6.4	.094	2.4	60	4.1	100	.052	.077
PV84-1	1/2	12.7	.250	6.4	.125	3.2	70	4.8	100	.076	.113
PV75-1	7/16	11.1	.313	7.9	.063	1.6	50	3.4	100	.038	.057
PV85-1	1/2	12.7	.313	7.9	.094	2.4	60	4.1	100	.062	.092
PV95-1	9/16	14.3	.313	7.9	.125	3.2	70	4.8	100	.088	.131
PV86-1	1/2	12.7	.375	9.5	.063	1.6	45	3.1	100	.044	.065
PV96-1	9/16	14.3	.375	9.5	.094	2.4	50	3.4	100	.071	.106
PV106-1	5/8	15.9	.375	9.5	.125	3.2	60	4.1	100	.101	.150
PV97-1	9/16	14.3	.438	11.1	.063	1.6	40	2.8	100	.050	.074
PV107-1	5/8	15.9	.438	11.1	.094	2.4	45	3.1	100	.080	.119
PV117-1	11/16	17.5	.438	11.1	.125	3.2	50	3.4	100	.115	.171
PV108-1	5/8	15.9	.500	12.7	.063	1.6	30	2.1	100	.057	.085
PV118-1	11/16	17.5	.500	12.7	.094	2.4	40	2.8	100	.089	.132
PV128-1	3/4	19.1	.500	12.7	.125	3.2	45	3.1	100	.126	.187
PV138-1	13/16	20.7	.500	12.7	.156	4.0	60	4.1	100	.167	.248
PV129-1	3/4	19.1	.563	14.3	.094	2.4	40	2.8	100	.099	.147
PV139-1	13/16	20.7	.563	14.3	.125	3.2	45	3.1	100	.138	.205

Part Number	Tube O.D.		Tube I.D.		Average Wall Thickness		Working Pressure at 73°F / 23°C		Std. Coil	Weight	
	inch	mm	inch	mm	inch	mm	psi	bar		feet	lbs./ft.
#											
PV1310-1	13/16	26.7	.625	15.9	.094	2.4	35	2.4	100	.108	.161
PV1410-1	7/8	22.2	.625	15.9	.125	3.2	40	2.8	100	.151	.225
PV1510-1	15/16	23.8	.625	15.9	.156	4.0	50	3.5	100	.196	.292
PV1411-1	7/8	22.2	.688	17.5	.094	2.4	30	2.1	100	.118	.176
PV1611-1	1	25.4	.688	17.5	.156	4.0	45	3.1	100	.213	.317
PV1612-1	1	25.4	.750	19.1	.125	3.2	35	2.4	100	.176	.262
PV1712-1	1-1/16	27.0	.750	19.1	.156	4.0	35	2.4	100	.228	.339
PV1812-1	1-1/8	28.6	.750	19.1	.188	4.8	50	3.5	100	.283	.421
PV2012-1	1-1/4	31.8	.750	19.1	.250	6.4	55	3.8	50	.409	.609
PV1814-1	1-1/8	27.0	.875	22.2	.125	3.2	30	2.1	50	.201	.299
PV1914-1	1-3/16	30.2	.875	22.2	.156	4.0	35	2.4	100	.259	.385
PV2014-1	1-1/4	31.8	.875	22.2	.188	4.8	45	3.1	50	.321	.478
PV2016-1	1-1/4	31.8	1.000	25.4	.125	3.2	25	1.7	50	.230	.342
PV2116-1	1-5/16	33.4	1.000	25.4	.156	4.0	30	2.1	50	.291	.433
PV2216-1	1-3/8	34.9	1.000	25.4	.188	4.8	40	2.8	50	.359	.534
PV2416-1	1-1/2	38.1	1.000	25.4	.250	6.4	45	3.1	50	.514	.765
PV2218-1	1-3/8	34.9	1.125	28.6	.125	3.2	25	1.7	50	.252	.375
PV2420-1	1-1/2	38.1	1.250	31.8	.125	3.2	20	1.4	50	.277	.412
PV2620-1	1-5/8	41.3	1.250	31.8	.188	4.8	35	2.4	50	.434	.646
PV2820-1	1-3/4	44.4	1.250	31.8	.250	6.4	45	3.1	50	.604	.899
PV3024-1	1-7/8	47.6	1.500	38.1	.188	4.8	30	2.1	50	.510	.759
PV3224-1	2	50.8	1.500	38.1	.250	6.4	40	2.8	50	.705	1.05
PV3628-1	2-1/4	57.2	1.750	44.4	.250	6.4	30	2.1	50	.806	1.20
PV4032-1	2-1/2	63.5	2.000	50.8	.250	6.4	35	2.4	50	.906	1.35

For detailed ordering information, please consult price list or contact Parflex® Division.



# Fluoropolymer Tubing

## Fluoropolymer Tubing

Parflex Fluoropolymer tubing is available from Parker TexLoc™ in Fort Worth, Texas. Tubing can be ordered directly from TexLoc or through the Parflex Division.

Fluoropolymer tubing features a low coefficient of friction and anti-stick properties, high temperature capabilities and the most corrosion and chemical resistance of all polymers. Within normal use temperatures, fluoropolymers are attacked by so few chemicals that it is easier to describe the exceptions rather than list the chemicals they are compatible with (see Chemical Resistance Summary, pg. B-44). These chemically inert tubes are non-wetting and non-leaching, making them ideal for a wide range of fluid and material handling applications.

Parker TexLoc fluoropolymer tubing is available in PTFE, FEP, PFA and PVDF with some materials operating at temperatures up to 500°F/260°C. Each material has specific dominant characteristics, but all operate in high-temperature, corrosive environments.

- Parflex PTFE, FEP, PFA and PVDF tubing complies with European Standard RoHs and are also FDA compliant to FDA regulation 21 CFR 177.1550, making these products suitable for use in food and beverage applications.
- Parflex PTFE, FEP and PFA are listed VW-1 in the burning test for Underwriters Laboratories and pass the UL-83 vertical flame test. In a flame situation, PTFE, FEP and PFA tubing resist combustion and do not promote flame spread.

**All fluoropolymer tubing dimensions are continuously monitored to ensure an overall quality product. Most tubing sizes are packaged in convenient 25-ft., 50-ft., 100-ft. and 1,000-ft. lengths.**

### PTFE

- PTFE (Polytetrafluorethylene) is offered in beading, smoothbore tubing and heat shrinkable tubing.
- PTFE tubing features unmatched chemical resistance and a non-stick surface that facilitates flow and eliminates media buildup.

### FEP

- FEP (Fluorinated Ethylene Propylene) is available in smoothbore tubing and heat shrinkable tubing.
- FEP tubing offers the highest clarity in the fluoropolymer market and is a close second to PTFE in chemical resistance.
- FEP is available in long, continuous lengths (1,000 feet and longer) whereas the longest lengths for PTFE range from 200 to 1,000 feet depending on size and wall thickness.



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Fluoropolymer Tubing

Product Family	Type	Series		Suggested Applications		Suggested Markets
PTFE	Beading	TFB		Pull Cord O-Ring Seals	Spacers Woven Filter	Chemical High-Temp
	Smoothbore	TFH TFS	TFT TFL	Electrical Insulation Protective Cover	Circuit Board Wire Insulation	Food Instrumentation Laboratory
	Smoothbore	101	201	Electrical Insulation Fluid Transfer	Gas Sampling Laboratory	Gas Sampling Electrical Insulation
	Heat Shrink	HS2T	HS4T	Electrical Insulation Laboratory		Fluid Handling Industrial Equipment
FEP	Smoothbore	103	203	Nitrogen Filling Downhole Pump Ozone Sampling	Hearing Aid Optical Sensors	UV Applications Chemical Instrumentation Laboratory Gas Sampling
	Heat Shrink	HS1.3 HS1.25	HS1.6	Protective Covering UV Light Covering Product Testing	Paper Rollers Ink Rollers	Robotics Fluid Handling Food & Beverage Pharmaceutical
PFA	Smoothbore	104	204	Air Sampling Gas Purge Wetbench Flow Monitoring Steam Plant		Chemical Laboratory Semiconductor Instrumentation Food Environmental Fluid Handling Gas Service Pharmaceutical
PVDF	Smoothbore	110	111	Thermal Cycling Outdoor/Extreme Conditions Water Systems Applications with long cycle life		Chemical Food Gas Environmental

## PFA

- PFA (Perfluoroalkoxy) is available in smoothbore tubing.
- When temperature and clarity are both factors, PFA is the resin of choice because it offers the high-temperature attributes of PTFE, long continuous lengths, and almost as much clarity as FEP.
- High purity resins available.
- Low permeability.

## PVDF

- PVDF (Polyvinylidene Fluoride) is available in flexible and super flexible smoothbore tubing.
- PVDF offers a combination of properties beneficial for use in many critical applications requiring chemical resistance with low permeability.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Fluoropolymer Tubing

Tubing  
Fluoropolymer  
B

## Fluoropolymer - Quick Reference

### PTFE (Polytetrafluoroethylene)

Working Temperature: 500°F (260°C)

Color: Opaque to translucent

- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Excellent flexlife
- Laser markable

Coiled Air Hose  
& Fittings  
C

### PFA (Perfluoroalkoxy)

Working Temperature: 500°F (260°C)

Color: Clear with light blue or tint

- High purity resins available
- Low permeation resins available
- Use when you need the temperature range of PTFE and the clarity of FEP
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Good flexlife

Transportation  
D

### FEP (Fluorinated Ethylene Propylene)

Working Temperature: 400°F (204°C)

Color: Clear

- Excellent chemical resistance
- Nonwetting
- Weldable
- Tubes can be sealed by melting
- Long continuous lengths
- Low refractive index
- Improved clarity over PFA
- Lower cost alternative to PFA

Fittings  
E

### PVDF (Polyvinylidene Fluoride)

Working Temperature: 265°F (130°C)

Color: Varies

- Very good chemical resistance
- Excellent resistance to creep and fatigue
- UV Resistant
- Weldable
- Exceptional corrosion resistance for chlorine, fluorine, or bromine environments

Tooling, Equipment  
& Accessories  
F

General Technical  
G

## Chemical Resistance Summary



Within normal use temperatures, fluoroplastics are attacked by so few chemicals that it is easier to describe the exceptions rather than list the chemicals with which TexFluor™ is compatible.

### DO NOT USE FLUOROPLASTICS WITH THE FOLLOWING:

- Alkali metals such as elemental sodium, potassium, lithium, etc. The alkali metals remove fluorine from the polymer molecule.
- Extremely potent oxidizers, fluorine (F<sub>2</sub>) and related compounds (e.g., chlorine trifluoride, ClF<sub>3</sub>). These can be handled by TexFluor™, but only with great care, as fluorine is absorbed into the resins, and the mixture becomes sensitive to a source of ignition such as impact.
- 80% NaOH (Sodium Hydroxide) or KOH (Potassium Hydroxide), metal hydrides such as Boranes (e.g., B<sub>2</sub>H<sub>6</sub>), Aluminum Chloride, Ammonia (NH<sub>3</sub>), certain Amines (R-NH<sub>2</sub>) and imines (R=NH) and 70% Nitric Acid at temperatures near the suggested service limit.



### WARNING

FAILURE OR IMPROPER SELECTION OR IMPROPER USE OF THE PRODUCTS AND/OR SYSTEMS DESCRIBED HEREIN OR RELATED ITEMS CAN CAUSE DEATH, PERSONAL INJURY AND PROPERTY DAMAGE.

This document and other information from Parker Hannifin Corporation, its subsidiaries and authorized distributors provide product and/or system options for further investigation by users having technical expertise. It is important that you analyze all aspects of your application and review the information concerning the product or system in the current product catalog. Due to the variety of operating conditions and applications for these products or systems, the user, through its own analysis and testing, is solely responsible for making the final selection of the products and systems and assuring that all performance, safety and warning requirements of the application are met.

The products described herein, including without limitation, product features, specifications, designs, availability and pricing, are subject to change by Parker Hannifin Corporation and its subsidiaries at any time without notice.

# Fluoropolymer Tubing

## Property Comparison - Fluoropolymer Resin\*

Properties	ASTM or Unit	PTFE	FEP	PFA	PVDF
<b>MECHANICAL PROPERTIES</b>					
Specific Gravity	D792	2.13-2.20	2.12-2.17	2.12-2.17	1.76-1.78
Elongation %	D638	200-450	250-330	280-400	300-450
Tensile Strength (psi)	D638	2000-7000	2800-5000	4000-4500	4500-6200
Tensile Elastic Modulus (Young's Modulus) (psi)	D638	57,000	50,000	72,500-87,000	160,000
Flexural Modulus	D790(psi) D790 103MPa (103kgf/cm2)	71,000-85,000 0.5-0.6 (5.0-6.0)	78,000-92,000 0.5-0.6 (5.5-6.4)	94,000-99,000 0.6-0.7 (6.6-7.0)	90,000-168,000 na
Flex Life (MIT cycles)	D2176	>1,000,000	5,000-80,000	10,000-500,000	na
Hardness Durometer Shore D	D636	D50-65	D55	D55-60	D75-D85
Coefficient of Friction	(on steel)	0.02	0.05	0.2	0.4
Abrasion Resistance 1000 revs.	Taber	12	14-20	9-17	5-15
Impact Strength IZOD. 73°F/23°C notched ft/lbs/in	D256	3	no break	no break	4
<b>THERMAL PROPERTIES</b>					
Melting Point	°C	327	260	305	171
	°F	621	500	582	340
Upper Service Temperature(20000h)	°C	260	204	260	130
	°F	500	400	500	260
Low Temperature Embrittlement	°C	-268	-268	-268	-62
	°F	-450	-450	-450	-80
<b>ELECTRICAL PROPERTIES</b>					
Dielectric Constant	D150/103Hz	2.1	2.1	2.1	7.72
	D150/106Hz	2.1	2.1	2.1	6.43
Dielectric Strength	D149/125 MIL	500	500	500	na
	D149/10 MIL	≥1400	>1400	≥1400	>1080
<b>GENERAL PROPERTIES</b>					
Chemical/Solvent Resistance	D543	Excellent	Excellent	Excellent	Very Good
Water Absorption 24h,%	D570	<0.01	<0.01	<0.03	<0.04
Refractive Index		1.35	1.338	1.34	1.42

\*General resin properties; Tubing properties may vary.

## Tubing Pressure Ranges

Tubing pressures vary by material, tubing size and wall thickness. Please contact Customer Service for specific pressures.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



B-45

Tubing  
Fluoropolymer  
B

Coiled Air Hose  
& Fittings  
C

Transportation  
D

Fittings  
E


Tooling, Equipment  
& Accessories  
F

General Technical  
G

# Fluoropolymer Tubing

## Fluoropolymer Tubing Nomenclature Smoothbore Fractional and Metric Tubing

# 105-0250062 - N T - 100



PEEK® is a registered trademark of Victrex.




For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

# Fluoropolymer Tubing

## Fluoropolymer Tubing Nomenclature Heat Shrink, Electrical Insulation Tubing and Beading

# HS2\*\* T F T 1/8 - N T\*\*\*



\*When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

\*\*This first configuration is only used for heat shrinkable tubing or spiral wrap. For example, electrical insulation tubing part number would read TFT-1/8-NT.

\*\*\*When changing to cut length, replace the T with C and specify the length in inches. If this part was cut to 4 feet, part number would read TFT-1/8-NC48.000.

\*\*\*\*Sizes for heat shrink designate the size of the heat shrink tube as stated by the applicable specification. The actual O.D. of the tubing does not always match the size. Review actual tables to see the true expanded dimension of the tube.

For detailed ordering information, please consult price list or contact Parflex® Division.





# PTFE Tubing

## Series Fractional: TFL, TFS, TFT



### Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Excellent flexlife
- Laser markable

### Applications/Markets



- Electrical Insulation
- Protective Cover

### Certifications

- Light Wall (TFL) – ASTM D 3295, Class 1, AMS 3654C
- Thin Wall (TFT) – ASTM D 3295, Class 2, AMS 3655B
- Standard Wall (TFS) – ASTM D 3295, Class 3, AMS 3653E
- FDA Compliant
- USP Class VI Compliant

### TFS, TFT & TFL PTFE Fractional Tubing

Size	Nominal I.D.		Standard Wall			Thin Wall			Light Wall			Standard Packaging
			Part Number	Nominal Wall		Part Number	Nominal Wall		Part Number	Nominal Wall		
			#			#			#			
	inch	mm	Natural	inch	mm	Natural	inch	mm	Natural	inch	mm	
1/8	.125	30.2	TFS1/8	.020	0.51	TFT1/8	.015	0.38	TFL1/8	.008	0.20	Random Length Coil
3/16	.188	40.8	TFS3/16	.020	0.51	TFT3/16	.015	0.38	TFL3/16	.010	0.25	Random Length Coil
1/4	.250	60.4	TFS1/4	.020	0.51	TFT1/4	.015	0.38	TFL1/4	.010	0.25	Random Length Coil
5/16	.318	80.1	TFS5/16	.020	0.51	TFT5/16	.015	0.38	TFL5/16	.012	0.30	Random Length Coil
3/8	.381	90.7	TFS3/8	.025	0.64	TFT3/8	.015	0.38	TFL3/8	.015	0.38	Random Length Coil
7/16	.444	110.3	TFS7/16	.025	0.64	TFT7/16	.018	0.46	TFL7/16	.018	0.46	Random Length Coil
1/2	.507	120.9	TFS1/2	.025	0.64	TFT1/2	.018	0.46	TFL1/2	.018	0.46	Random Length Coil
5/8	.632	160.1	TFS5/8	.025	0.64	TFT5/8	.020	0.51	-	-	-	Random Length Coil
3/4	.760	190.7	TFS3/4	.030	0.76	TFT3/4	.025	0.64	-	-	-	Random Length Coil
7/8	.885	220.5	TFS7/8	.035	0.89	-	-	-	-	-	-	Random Length Coil
1	1.010	250.7	TFS10.00	.035	0.89	-	-	-	-	-	-	Random Length Coil

Fractional tubing is supplied in random length coils, with a minimum coil length of 15 feet. Custom packaging, sizes and lengths are quoted upon request.

## Order Information

### Example: TFS1/2-NT

TFS1/2-NT – PTFE

TFS1/2-NT – Standard Wall

TFS1/2-NT – Tube O.D. in inches (1/2")

TFS1/2-NT – Natural

TFS1/2-NT – Bulk Tubing

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

## Fittings

- Fittings available for sizes 3/32" up to 1.1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Package quantities are not continuous

## Colors

- Natural, Opaque to translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC...ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

For detailed ordering information, please consult price list or contact Parflex® Division.

# PTFE Tubing

Series AWG: TFH, TFS, TFT, TFL



## Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Excellent flexlife
- Laser markable

## Applications/Markets



- Electrical Insulation
- Protective Cover
- Circuit Board
- Wire Insulation

## Certifications

- Light Wall (TFL) – ASTM D 3295, Class 1, AMS 3654C
- Thin Wall (TFT) – ASTM D 3295, Class 2, AMS 3655B, UL-224 300V 200°C, CSA 9032-01 300V
- Standard Wall (TFS)– ASTM D 3295, Class 3, AMS 3653E, MIL-I-22129C, UL-224 600V 200°C, CSA 9032-01 600V
- Heavy Wall (TFH) - ASTM D 3295, Class 4
- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

## Order Information

**Example: TFH13-2TC**

TFH13-2TC – PTFE

TFH13-2TC – Heavy Wall

TFH13-2TC – AWG Size

TFS13-2TC – Red

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

## Fittings

- Fittings available for sizes 3/32" up to 1.1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Spaghetti tubing is supplied in random lengths with a minimum length of 25 feet
- Continuous lengths and colors quoted upon request
- AWG spaghetti tubing is also available in FEP and PFA
- Consult factory for pricing and minimum lengths

## Colors

See Color Code Table

- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

For detailed ordering information, please consult price list or contact Parflex® Division.

# PTFE Tubing

## Series AWG: TFH, TFL, TFS, TFT (cont.)

### TFH PTFE AWG Heavy Wall

Part Number	Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
		inch	mm	inch	mm	inch	mm	inch	mm	
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFH24	24	.022	0.56	.020	0.51	.026	0.66	.016 ± .003	0.41 ± 0.08	1,000 ft. Spool
TFH23	23	.026	0.66	.023	0.58	.029	0.74	.016 ± .003	0.41 ± 0.08	1,000 ft. Spool
TFH22	22	.028	0.71	.025	0.64	.032	0.81	.016 ± .003	0.41 ± 0.08	1,000 ft. Spool
TFH21	21	.032	0.81	.029	0.74	.035	0.89	.016 ± .003	0.41 ± 0.08	1,000 ft. Spool
TFH20	20	.034	0.86	.032	0.81	.040	1.02	.018 ± .003	0.46 ± 0.08	1,000 ft. Spool
TFH19	19	.038	0.97	.036	0.91	.044	1.12	.020 ± .004	0.51 ± 0.10	1,000 ft. Spool
TFH18	18	.042	1.07	.040	1.02	.049	1.25	.020 ± .004	0.51 ± 0.10	1,000 ft. Spool
TFH17	17	.048	1.22	.045	1.14	.054	1.37	.020 ± .004	0.51 ± 0.10	1,000 ft. Spool
TFH16	16	.053	1.35	.051	1.30	.061	1.55	.020 ± .004	0.51 ± 0.10	1,000 ft. Spool
TFH15	15	.059	1.50	.057	1.45	.067	1.70	.020 ± .004	0.51 ± 0.10	1,000 ft. Spool
TFH14	14	.066	1.68	.064	1.63	.074	1.88	.020 ± .004	0.51 ± 0.10	500 ft. Spool
TFH13	13	.076	1.93	.072	1.83	.082	2.08	.020 ± .004	0.51 ± 0.10	500 ft. Spool
TFH12	12	.085	2.16	.081	2.06	.091	2.31	.020 ± .004	0.51 ± 0.10	500 ft. Spool
TFH11	11	.095	2.41	.091	2.31	.101	2.57	.020 ± .004	0.51 ± 0.10	500 ft. Spool
TFH10	10	.106	2.69	.102	2.59	.112	2.84	.025 ± .005	0.64 ± 0.13	500 ft. Spool
TFH09	9	.118	3.00	.114	2.90	.124	3.15	.025 ± .005	0.64 ± 0.13	500 ft. Spool
TFH08	8	.133	3.38	.129	3.28	.141	3.58	.030 ± .005	0.76 ± 0.13	Random Length Coil
TFH07	7	.148	3.76	.144	3.66	.158	4.01	.030 ± .005	0.76 ± 0.13	Random Length Coil
TFH06	6	.166	4.22	.162	4.11	.178	4.52	.030 ± .005	0.76 ± 0.13	Random Length Coil
TFH05	5	.185	4.70	.182	4.62	.196	4.98	.032 ± .005	0.81 ± 0.13	Random Length Coil

## Certifications

- Heavy Wall (TFH) - ASTM D 3295, Class 4
- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



## TFS PTFE AWG Standard Wall

Part Number	Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
		inch	mm	inch	mm	inch	mm	inch	mm	
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFS30	30	.012	0.31	.010	0.25	.015	0.38	.009 ± .002	0.23 ± 0.51	1,000 ft. Spool
TFS28	28	.015	0.38	.013	0.33	.018	0.46	.009 ± .002	0.23 ± 0.51	1,000 ft. Spool
TFS26	26	.018	0.46	.016	0.41	.022	0.56	.009 ± .002	0.23 ± 0.51	1,000 ft. Spool
TFS24	24	.022	0.56	.020	0.51	.026	0.66	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS23	23	.026	0.66	.023	0.58	.029	0.74	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS22	22	.028	0.71	.025	0.64	.032	0.81	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS21	21	.032	0.81	.029	0.74	.035	0.89	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFS20	20	.034	0.86	.032	0.81	.040	1.02	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS19	19	.038	0.97	.036	0.91	.044	1.12	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS18	18	.042	1.07	.040	1.02	.049	1.25	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS17	17	.048	1.22	.045	1.14	.054	1.37	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS16	16	.053	1.35	.051	1.30	.061	1.55	.016 ± .003	0.41 ± .0.08	1,000 ft. Spool
TFS15	15	.059	1.50	.057	1.45	.067	1.70	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS14	14	.066	1.68	.064	1.63	.074	1.88	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS13	13	.076	1.93	.072	1.83	.082	2.08	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS12	12	.085	2.16	.081	2.06	.091	2.31	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS11	11	.095	2.41	.091	2.31	.101	2.57	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS10	10	.106	2.69	.102	2.59	.112	2.84	.016 ± .003	0.41 ± .0.08	500 ft. Spool
TFS09	9	.118	3.00	.114	2.90	.124	3.15	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS08	8	.133	3.38	.129	3.28	.141	3.58	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS07	7	.148	3.76	.144	3.66	.158	4.01	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS06	6	.166	4.22	.162	4.11	.178	4.52	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS05	5	.185	4.70	.182	4.62	.196	4.98	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS04	4	.208	5.28	.204	5.18	.224	5.69	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS03	3	.234	5.94	.229	5.82	.249	6.32	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS02	2	.263	6.68	.258	6.55	.278	7.06	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS01	1	.294	7.47	.289	7.34	.311	7.90	.020 ± .004	0.51 ± .0.10	Random Length Coil
TFS00	0	.330	8.38	.325	8.25	.347	8.81	.020 ± .004	0.51 ± .0.10	Random Length Coil

## Certifications

- Standard Wall (TFS)- ASTM D 3295, Class 3, AMS 3653E, MIL-I-22129C, UL-224 600V 200°C, CSA 9032-01 600V
- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)

For detailed ordering information, please consult price list or contact Parflex® Division.

# PTFE Tubing

## Series AWG: TFH, TFL, TFS, TFT (cont.)

### TFT PTFE AWG Thin Wall

Part Number	Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
		inch	mm	inch	mm	inch	mm	inch	mm	
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFT32	32	.010	0.25	.008	0.20	.012	0.31	.007 ± .002	0.18 ± 0.05	1,000 ft. Spool Only
TFT30	30	.012	0.31	.010	0.25	.015	0.38	.009 ± .002	0.23 ± 0.05	1,000 ft. Spool
TFT28	28	.015	0.38	.013	0.33	.018	0.46	.009 ± .002	0.23 ± 0.05	1,000 ft. Spool
TFT26	26	.018	0.46	.016	0.41	.022	0.56	.009 ± .002	0.23 ± 0.05	1,000 ft. Spool
TFT24	24	.022	0.56	.020	0.51	.026	0.66	.010 ± .003	0.25 ± 0.08	1,000 ft. Spool
TFT23	23	.026	0.66	.023	0.58	.029	0.74	.010 ± .003	0.25 ± 0.08	1,000 ft. Spool
TFT22	22	.028	0.71	.025	0.64	.032	0.81	.010 ± .003	0.25 ± 0.08	1,000 ft. Spool
TFT21	21	.032	0.81	.029	0.74	.035	0.89	.010 ± .003	0.25 ± 0.08	1,000 ft. Spool
TFT20	20	.034	0.86	.032	0.81	.040	1.02	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFT19	19	.038	0.97	.036	0.91	.044	1.12	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFT18	18	.042	1.07	.040	1.02	.049	1.25	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFT17	17	.048	1.22	.045	1.14	.054	1.37	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFT16	16	.053	1.35	.051	1.30	.061	1.55	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFT15	15	.059	1.50	.057	1.45	.067	1.70	.012 ± .003	0.31 ± 0.08	1,000 ft. Spool
TFT14	14	.066	1.68	.064	1.63	.074	1.88	.012 ± .003	0.31 ± 0.08	500 ft. Spool
TFT13	13	.076	1.93	.072	1.83	.082	2.08	.012 ± .003	0.31 ± 0.08	500 ft. Spool
TFT12	12	.085	2.16	.081	2.06	.091	2.31	.012 ± .003	0.31 ± 0.08	500 ft. Spool
TFT11	11	.095	2.41	.091	2.31	.101	2.57	.012 ± .003	0.31 ± 0.08	500 ft. Spool
TFT10	10	.106	2.69	.102	2.59	.112	2.84	.012 ± .003	0.31 ± 0.08	500 ft. Spool
TFT09	9	.118	3.00	.114	2.90	.124	3.15	.015 ± .003	0.38 ± 0.08	500 ft. Spool
TFT08	8	.133	3.38	.129	3.28	.141	3.58	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT07	7	.148	3.76	.144	3.66	.158	4.01	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT06	6	.166	4.22	.162	4.11	.178	4.52	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT05	5	.185	4.70	.182	4.62	.196	4.98	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT04	4	.208	5.28	.204	5.18	.224	5.69	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT03	3	.234	5.94	.229	5.82	.249	6.32	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT02	2	.263	6.68	.258	6.55	.278	7.06	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT01	1	.294	7.47	.289	7.34	.311	7.90	.015 ± .003	0.38 ± 0.08	Random Length Coil
TFT00	0	.330	8.38	.325	8.25	.347	8.81	.015 ± .003	0.38 ± 0.08	Random Length Coil

### Certifications

- Thin Wall (TFT) - ASTM D 3295, Class 2, AMS 3655B, UL-224 300V 200°C, CSA 9032-01 300V
- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

### Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

### TFL PTFE AWG Light Wall

Part Number	Size	Nominal I.D.		Minimum I.D.		Maximum I.D.		Nominal Wall		Standard Packaging
		inch	mm	inch	mm	inch	mm	inch	mm	
#										
	AWG	inch	mm	inch	mm	inch	mm	inch	mm	
TFL32	32	.010	0.25	.008	0.20	.012	0.31	.005 ± .002	0.13 ± 0.05	1,000 ft. Spool Only
TFL30	30	.012	0.31	.010	0.25	.015	0.38	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL28	28	.015	0.38	.013	0.33	.018	0.46	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL26	26	.018	0.46	.016	0.41	.022	0.56	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL24	24	.022	0.56	.020	0.51	.026	0.66	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL23	23	.026	0.66	.023	0.58	.029	0.74	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL22	22	.028	0.71	.025	0.64	.032	0.81	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL21	21	.032	0.81	.029	0.74	.035	0.89	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL20	20	.034	0.86	.032	0.81	.040	1.02	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL19	19	.038	0.97	.036	0.91	.044	1.12	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL18	18	.042	1.07	.040	1.02	.049	1.25	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL17	17	.048	1.22	.045	1.14	.054	1.37	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL16	16	.053	1.35	.051	1.30	.061	1.55	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL15	15	.059	1.50	.057	1.45	.067	1.70	.006 ± .002	0.13 ± 0.05	1,000 ft. Spool
TFL14	14	.066	1.68	.064	1.63	.074	1.88	.008 ± .002	0.20 ± 0.05	500 ft. Spool
TFL13	13	.076	1.93	.072	1.83	.082	2.08	.008 ± .002	0.20 ± 0.05	500 ft. Spool
TFL12	12	.085	2.16	.081	2.06	.091	2.31	.008 ± .002	0.20 ± 0.05	500 ft. Spool
TFL11	11	.095	2.41	.091	2.31	.101	2.57	.008 ± .002	0.20 ± 0.05	500 ft. Spool
TFL10	10	.106	2.69	.102	2.59	.112	2.84	.008 ± .002	0.20 ± 0.05	500 ft. Spool
TFL09	9	.118	3.00	.114	2.90	.124	3.15	.008 ± .002	0.20 ± 0.05	500 ft. Spool
TFL08	8	.133	3.38	.129	3.28	.141	3.58	.008 ± .002	0.20 ± 0.05	Random Length Coil
TFL07	7	.148	3.76	.144	3.66	.158	4.01	.008 ± .002	0.20 ± 0.05	Random Length Coil
TFL06	6	.166	4.22	.162	4.11	.178	4.52	.010 ± .003	0.25 ± 0.08	Random Length Coil
TFL05	5	.185	4.70	.182	4.62	.196	4.98	.010 ± .003	0.25 ± 0.08	Random Length Coil
TFL04	4	.208	5.28	.204	5.18	.224	5.69	.010 ± .003	0.25 ± 0.08	Random Length Coil
TFL03	3	.234	5.94	.229	5.82	.249	6.32	.010 ± .003	0.25 ± 0.08	Random Length Coil
TFL02	2	.263	6.68	.258	6.55	.278	7.06	.010 ± .003	0.25 ± 0.08	Random Length Coil
TFL01	1	.294	7.47	.289	7.34	.311	7.90	.012 ± .003	0.31 ± 0.08	Random Length Coil
TFL00	0	.330	8.38	.325	8.25	.347	8.81	.012 ± .003	0.31 ± 0.08	Random Length Coil

### Certifications

- Light Wall (TFL) – ASTM D 3295, Class 1, AMS 3654C
- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

### Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)

For detailed ordering information, please consult price list or contact Parflex® Division.



# PTFE Tubing

## Series Fractional: 101 Industrial & Heavy Wall



### Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Excellent flexlife
- Laser markable

### Applications/Markets



- Electrical Insulation
- Fluid Transfer
- Gas Sampling
- Laboratory

### Certifications

- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

### 101 PTFE Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F /23°C		Burst Pressure at 73°F /23°C		
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi	bar
#																
101-0094031	3/32	.094	± .005	2.40	± 0.13	.031	± .002	0.79	± 0.05	.031	0.79	390	27	1950	134	
101-0125031	1/8	.125	± .005	3.18	± 0.13	.063	± .003	1.57	± 0.05	.031	0.79	290	20	1450	100	
101-0156031	5/32	.156	± .005	3.99	± 0.13	.094	± .004	2.39	± 0.08	.031	0.79	220	15	1100	76	
101-0188031	3/16	.188	± .005	4.78	± 0.13	.125	± .005	3.18	± 0.13	.031	0.79	180	12	900	62	
101-0250031	1/4	.250	± .005	6.35	± 0.13	.190	± .005	4.83	± 0.13	.031	0.79	130	9	650	45	
101-0312031	5/16	.312	± .005	7.92	± 0.13	.250	± .007	6.35	± 0.18	.031	0.79	100	7	500	34	
101-0375031	3/8	.375	± .005	9.52	± 0.13	.312	± .006	7.92	± 0.15	.031	0.79	80	6	400	28	
101-0438031	7/16	.438	± .005	11.13	± 0.13	.375	± .007	9.52	± 0.18	.031	0.79	70	5	350	24	
101-0500031	1/2	.500	± .006	12.70	± 0.15	.438	± .008	11.13	± 0.20	.031	0.79	60	4	300	21	
101-0563031	9/16	.563	± .007	14.30	± 0.18	.500	± .010	12.70	± 0.25	.031	0.79	55	4	275	19	
101-0625031	5/8	.625	± .007	15.88	± 0.18	.563	± .010	14.30	± 0.25	.031	0.79	50	3	250	17	
101-0688031	11/16	.688	± .010	17.48	± 0.25	.625	± .012	15.88	± 0.31	.031	0.79	45	3	225	16	
101-0750032	3/4	.750	± .010	19.05	± 0.25	.688	± .012	17.48	± 0.31	.032	0.81	40	3	200	14	
101-0830040	.830	.830	± .014	21.08	± 0.36	.750	± .014	19.05	± 0.36	.040	1.02	45	3	225	16	
101-0965045	.965	.965	± .016	24.51	± 0.41	.875	± .016	22.22	± 0.41	.045	1.14	45	3	225	16	
101-1100050	1.100	1.100	± .020	27.94	± 0.51	1.000	± .020	25.40	± 0.51	.050	1.27	40	3	200	14	

## Order Information

**Example: 101-0188062-0TC-100**

**101-0188062-0TC-100 – PTFE**

101-**0188**062-0TC-100 – **Tube O.D.** in inches (**3/16"**)

101-0188**062**-0TC-100 – **Tube Wall Thickness** in inches (**.062"**)

101-0188062-**0TC**-100 – **Black**

101-0188062-0TC-**100** – **Package Quantity** in feet (**100'**)

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

## Fittings

- Fittings available for sizes 3/32" up to 1.1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compression-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

## Colors

- Natural, Opaque to translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC...ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

## 101 PTFE Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F /23°C		Burst Pressure at 73°F /23°C		
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi	bar
#																
101-0188062	3/16	.188	± .005	4.78	± 0.13	.063	± .003	1.57	± 0.05	.062	1.57	390	27	1950	134	
101-0250047	1/4	.250	± .005	6.35	± 0.13	.157	± .005	3.99	± 0.13	.047	1.19	210	14	1050	72	
101-0250062	1/4	.250	± .005	6.35	± 0.13	.125	± .005	3.18	± 0.13	.062	1.57	290	20	1450	100	
101-0312062	5/16	.312	± .005	7.92	± 0.13	.188	± .006	4.76	± 0.15	.062	1.57	222	15	1110	77	
101-0375062	3/8	.375	± .005	9.52	± 0.13	.250	± .005	6.35	± 0.13	.062	1.57	180	12	900	62	
101-0438062	7/16	.438	± .005	11.13	± 0.13	.312	± .007	7.92	± 0.18	.062	1.57	150	10	750	52	
101-0500062	1/2	.500	± .005	12.70	± 0.13	.375	± .005	9.52	± 0.13	.062	1.57	130	9	650	45	
101-0563062	9/16	.563	± .007	14.30	± 0.18	.437	± .008	11.13	± 0.20	.062	1.57	110	8	550	38	
101-0625062	5/8	.625	± .007	15.88	± 0.18	.500	± .010	12.70	± 0.25	.062	1.57	100	7	500	34	
101-0688062	11/16	.688	± .010	17.48	± 0.25	.563	± .010	14.30	± 0.25	.062	1.57	90	6	450	31	
101-0750062	3/4	.750	± .010	19.05	± 0.25	.625	± .010	15.88	± 0.25	.062	1.57	80	6	400	28	
101-0875062	7/8	.875	± .014	22.22	± 0.36	.750	± .014	19.05	± 0.36	.062	1.57	70	5	350	24	
101-0100062	1	1.000	± .016	25.40	± 0.25	.875	± .016	22.22	± 0.36	.062	1.57	100	6.9	490	33.8	

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



B-57

A Hose  
 B Tubing, Fluoropolymer  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical



# PTFE Tubing

## Series Metric: 201



### Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Excellent flexlife
- Laser markable

### Applications/Markets



- Electrical Insulation
- Fluid Transfer
- Gas Sampling
- Laboratory

### Certifications

- AMS 3653E
- FDA Compliant
- USP Class VI Compliant

### 201 Metric PTFE Tubing

Part Number	Order Size		Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C		
	mm	mm	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	inch	psi	bar	psi	bar	
#																	
201-0300100	3	3	± 0.11	.118	± .004	1	± 0.11	.039	± .004	1	.039	390	27	1950	134		
201-0400100	4	4	± 0.11	.157	± .004	2	± 0.11	.074	± .004	1	.039	290	20	1450	100		
201-0500100	5	5	± 0.11	.197	± .004	3	± 0.11	.118	± .004	1	.039	220	15	1100	76		
201-0600100	6	6	± 0.13	.236	± .005	4	± 0.13	.157	± .005	1	.039	180	12	900	62		
201-0700100	7	7	± 0.13	.276	± .005	5	± 0.13	.197	± .005	1	.039	150	10	750	52		
201-0800100	8	8	± 0.13	.315	± .005	6	± 0.13	.236	± .005	1	.039	130	9	650	45		
201-0900100	9	9	± 0.13	.354	± .005	7	± 0.13	.276	± .005	1	.039	110	8	550	38		
201-1000100	10	10	± 0.13	.394	± .005	8	± 0.13	.315	± .005	1	.039	100	7	500	34		
201-1200100	12	12	± 0.15	.472	± .006	10	± 0.15	.394	± .006	1	.039	80	6	400	28		
201-1400100	14	14	± 0.15	.551	± .006	12	± 0.15	.472	± .006	1	.039	70	5	350	24		
201-1600100	16	16	± 0.15	.630	± .006	14	± 0.15	.551	± .006	1	.039	60	4	300	21		

## Order Information

**Example: 201-0800100-NT-100**

201-0800100-NT-100 – **Metric PTFE**

201-**0800**100-NT-100 – **Tube O.D.** in millimeters (**8 mm**)

201-0800**100**-NT-100 – **Tube Wall Thickness** in millimeters (**1 mm**)

201-0800100-**NT**-100 – **Natural**

2010800100-NT-**100** – **Package Quantity** in feet (**100'**)

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

## Fittings

- Fittings available for sizes 3mm up to 16mm

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

## Colors

- Natural, Opaque to translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC...ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

*For detailed ordering information, please consult price list or contact Parflex® Division.*

# PTFE Beading

## Series Fractional: TFB



### Features

- Virgin Polytetrafluoroethylene resin
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting
- Excellent flexlife
- Laser markable

### Applications/Markets



- Pull Cord
- O-Ring Seals
- Spacers
- Woven Filter

### Certifications

- ASTM D1710, Type 1, Grade 1, Class B
- FDA Compliant
- USP Class VI Compliant

### Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Package quantities are not continuous

### Colors

- Natural, Opaque to translucent

See Color Code Table

## Order Information

### Example: TFB028-NT

TFB-028-NT – PTFE Beading

TFB-028-NT – Beading O.D. in inches (.028")

TFB-028-NT – Natural

TFB-028-NT – Bulk Tubing

### TFB PTFE Beading

Part Number	Diameter		Tolerance		Standard Packaging
	inch	mm	inch	mm	
#					
TFB015	.015	0.38	± .002	± 0.05	1,000 ft. Spool
TFB020	.020	0.51	± .002	± 0.05	1,000 ft. Spool
TFB025	.025	0.64	± .002	± 0.05	1,000 ft. Spool
TFB028	.028	0.71	± .002	± 0.05	1,000 ft. Spool
TFB031	.031	0.79	± .002	± 0.05	1,000 ft. Spool
TFB035	.035	0.89	± .002	± 0.05	1,000 ft. Spool
TFB039	.039	0.99	± .002	± 0.05	1,000 ft. Spool
TFB043	.043	1.09	± .002	± 0.05	1,000 ft. Spool
TFB047	.047	1.19	± .002	± 0.05	1,000 ft. Spool
TFB050	.050	1.27	± .002	± 0.05	1,000 ft. Spool
TFB055	.055	1.40	± .003	± 0.08	1,000 ft. Spool
TFB060	.060	1.52	± .003	± 0.08	1,000 ft. Spool
TFB062	.062	1.57	± .003	± 0.08	1,000 ft. Spool
TFB070	.070	1.78	± .003	± 0.08	1,000 ft. Spool
TFB072	.072	1.83	± .003	± 0.08	1,000 ft. Spool
TFB078	.078	1.98	± .004	± 0.10	500 ft. Spool
TFB080	.080	2.03	± .004	± 0.10	500 ft. Spool
TFB084	.084	2.13	± .004	± 0.10	500 ft. Spool
TFB090	.090	2.29	± .004	± 0.10	500 ft. Spool
TFB094	.094	2.39	± .004	± 0.10	500 ft. Spool
TFB100	.100	2.54	± .004	± 0.10	500 ft. Spool
TFB109	.109	2.77	± .004	± 0.10	500 ft. Spool
TFB115	.115	2.92	± .004	± 0.10	500 ft. Spool
TFB125	.125	3.18	± .004	± 0.10	Random Length
TFB150	.150	3.81	± .004	± 0.10	Random Length
TFB188	.188	4.78	± .004	± 0.10	Random Length

For detailed ordering information, please consult price list or contact Parflex® Division.

# PTFE Heat Shrinkable Tubing

Series 2:1 Fractional: HS2TFS, HS2TFT, HS2TFL, HS2TFI



## Features

- Virgin Polytetrafluoroethylene resin
- 2:1 Shrink Ratio
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting

## Applications/Markets



- Electrical Insulation
- Protective Cover
- Laboratory

## Certifications

- Light Wall (HS2TFL) - AMS-DTL-23053/12, Class 4
- Thin Wall (HS2TFT) - AMS-DTL-23053/12, Class 3, AMS 3585
- Standard Wall (HS2TFS) - AMS-DTL-23053/12, Class 2, AMS 3586
- Heavy Wall (HS2TFI) - AMS-DTL-23053/12, Class 2
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant

### HS2TFS & HS2TFT PTFE Fractional Heat Shrink Tubing (2:1) SW & TW

Size (Inch)	Minimum Expanded I.D.		Maximum Recovered I.D.		Standard Wall				Thin Wall			
	inch	mm	inch	mm	Mil Spec*	Part Number	Nominal Recovered Wall		Mil Spec*	Part Number	Nominal Recovered Wall	
							inch	mm			inch	mm
1/8	.215	5.5	.130	3.3	23053/12-215	HS2TFS1/8	.020 ± .004	0.51 ± 0.10	23053/12-319	HS2TFT1/8	.015 ± .003	0.38 ± 0.08
1/4	.410	10.4	.260	6.6	23053/12-222	HS2TFS1/4	.020 ± .004	0.51 ± 0.10	23053/12-326	HS2TFT1/4	.015 ± .004	0.38 ± 0.10
5/16	.470	11.9	.329	8.4	23053/12-225	HS2TFS5/16	.020 ± .004	0.51 ± 0.10	23053/12-329	HS2TFT5/16	.015 ± .004	0.38 ± 0.10
3/8	.560	14.2	.399	10.1	23053/12-228	HS2TFS3/8	.025 ± .006	0.64 ± 0.15	-	HS2TF 3/8	.015 ± .004	0.38 ± 0.10
7/16	.655	16.6	.462	11.7	23053/12-229	HS2TFS7/16	.025 ± .006	0.64 ± 0.15	-	HS2TFT7/16	.018 ± .004	0.46 ± 0.10
1/2	.750	19.1	.524	13.3	23053/12-230	HS2TFS1/2	.025 ± .006	0.64 ± 0.15	-	HS2TFT1/2	.018 ± .004	0.46 ± 0.10
5/8	.930	23.6	.655	16.6	23053/12-231	HS2TFS5/8	.030 ± .006	0.76 ± 0.15	-	HS2TF 5/8	.020 ± .004	0.51 ± 0.10
3/4	1.125	28.6	.786	20.0	23053/12-232	HS2TFS3/4	.035 ± .008	0.89 ± 0.20	-	HS2TFT3/4	.025 ± .004	0.64 ± 0.10
7/8	1.130	28.7	.911	23.1	23053/12-233	HS2TFS7/8	.035 ± .008	0.89 ± 0.20	-	HS2TFT7/8	.025 ± .004	0.64 ± 0.10
1	1.500	38.1	1.036	26.3	23053/12-234	HS2TFS1.00	.035 ± .008	0.89 ± 0.20	-	HS2TFT1.00	.025 ± .004	0.64 ± 0.10

### HS2TFL PTFE Fractional Heat Shrink Tubing (2:1) LW

Size (Inch)	Minimum Expanded I.D.		Maximum Recovered I.D.		Light Wall			
	inch	mm	inch	mm	Mil Spec*	Part Number	Nominal Recovered Wall	
							inch	mm
1/8	.215	5.5	.130	3.3	23053/12-415	HS2TFL1/8	.008 ± .002	0.20 ± 0.05
1/4	.410	10.4	.260	6.6	23053/12-422	HS2TFL1/4	.010 ± .003	0.25 ± 0.08
5/16	.470	11.9	.329	8.4	23053/12-425	HS2TFL5/16	.012 ± .003	0.31 ± 0.08



For detailed ordering information, please consult price list or contact Parflex® Division.



## Order Information

### Example: HS2TFI7/8-NT

HS2TFI7/8-NT – Heat Shrink

HS2TFI7/8-NT – Shrink Ratio (2:1)

HS2TFI7/8-NT – PTFE

HS2TFI7/8-NT – Wall Type (Industrial Wall)

HS2TFI7/8-NT – Heat Shrink Size in inches (7/8")

HS2TFI7/8-NT – Natural

HS2TFI7/8-NT – Bulk Tubing

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Shrink Temperature 662°F/350°C for 10 minutes per AMS-DTL-23053/12
- \*Dielectric Strength:  $\geq 1,400$  V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- PTFE Fractional Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

## Colors

- Natural, Opaque to translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC...ie HS2TFT1/8-2TC .. ie HS1.3FEP24-0CC48.000

## HS2TFI PTFE Fractional Heat Shrink Tubing (2:1), Ind. Heavy Wall

Part Number	Size (inch)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
	inch		inch	mm	inch	mm	inch	mm
HS2TFI1/8	1/8	23053/12-101	.166	4.2	.130	3.3	.030 ± .005	0.76 ± 0.13
HS2TFI3/16	3/16	23053/12-102	.250	6.4	.193	4.9	.030 ± .005	0.76 ± 0.13
HS2TFI1/4	1/4	23053/12-103	.333	8.4	.257	6.5	.030 ± .005	0.76 ± 0.13
HS2TFI5/16	5/16	23053/12-104	.415	10.5	.320	8.1	.030 ± .005	0.76 ± 0.13
HS2TFI3/8	3/8	23053/12-105	.498	12.6	.383	9.7	.030 ± .005	0.76 ± 0.13
HS2TFI7/16	7/16	23053/12-106	.580	14.7	.448	11.4	.030 ± .006	0.76 ± 0.15
HS2TFI1/2	1/2	23053/12-107	.666	16.9	.510	13.0	.030 ± .006	0.76 ± 0.15
HS2TFI9/16	9/16	23053/12-108	.748	19.0	.572	14.5	.030 ± .006	0.76 ± 0.15
HS2TFI5/8	5/8	23053/12-109	.830	21.1	.637	16.2	.030 ± .006	0.76 ± 0.15
HS2TFI11/16	11/16	23053/12-110	.915	23.2	.700	17.8	.032 ± .006	0.81 ± 0.15
HS2TFI3/4	3/4	23053/12-111	1.000	25.4	.764	19.4	.040 ± .007	1.02 ± 0.18
HS2TFI7/8	7/8	23053/12-112	1.170	29.7	.891	22.6	.045 ± .007	1.14 ± 0.18
HS2TFI1.00	1	23053/12-113	1.330	33.8	1.020	25.9	.050 ± .008	1.27 ± 0.20

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

For detailed ordering information, please consult price list or contact Parflex® Division.

# PTFE Heat Shrinkable Tubing

## Series 2:1 AWG: HS2TFS, HS2TFT, HS2TFL



### Features

- Virgin Polytetrafluoroethylene resin
- 2:1 Shrink Ratio
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting

### Certifications

- Light Wall – AMS-DTL-23053/12, Class 4
- Thin Wall – AMS-DTL-23053/12, Class 3, AMS 3585
- Standard Wall – AMS-DTL-23053/12, Class 2, AMS 3586
- Heavy Wal – AMS-DTL-23053/12, Class 2
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Electrical Insulation
- Protective Cover
- Wire Insulation

#### HS2TFS Standard Wall (2:1)

Part Number	Size (AWG)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS2TFS24	24	23053/12-201	.050	1.27	.027	0.69	.012 ± .002	0.31 ± 0.05
HS2TFS22	22	23053/12-202	.055	1.40	.032	0.81	.012 ± .002	0.31 ± 0.05
HS2TFS20	20	23053/12-203	.060	1.52	.039	0.99	.016 ± .003	0.41 ± 0.08
HS2TFS19	19	23053/12-204	.065	1.65	.043	1.09	.016 ± .003	0.41 ± 0.08
HS2TFS18	18	23053/12-205	.076	1.93	.049	1.25	.016 ± .003	0.41 ± 0.08
HS2TFS17	17	23053/12-206	.085	2.16	.054	1.37	.016 ± .003	0.41 ± 0.08
HS2TFS16	16	-	.093	2.36	.061	1.55	.016 ± .003	0.41 ± 0.08
HS2TFS15	15	23053/12-207	.110	2.79	.067	1.70	.016 ± .003	0.41 ± 0.08
HS2TFS14	14	23053/12-208	.120	3.05	.072	1.83	.016 ± .003	0.41 ± 0.08
HS2TFS13	13	23053/12-210	.140	3.56	.080	2.03	.016 ± .003	0.41 ± 0.08
HS2TFS12	12	23053/12-211	.150	3.81	.089	2.26	.016 ± .003	0.41 ± 0.08
HS2TFS11	11	23053/12-212	.170	4.32	.101	2.57	.016 ± .003	0.41 ± 0.08
HS2TFS10	10	23053/12-213	.191	4.85	.112	2.84	.016 ± .003	0.41 ± 0.08
HS2TFS09	9	23053/12-214	.205	5.21	.124	3.15	.020 ± .004	0.51 ± 0.10
HS2TFS08	8	23053/12-216	.240	6.10	.141	3.58	.020 ± .004	0.51 ± 0.10
HS2TFS07	7	23053/12-217	.270	6.86	.158	4.01	.020 ± .004	0.51 ± 0.10
HS2TFS06	6	23053/12-218	.302	7.67	.178	4.52	.020 ± .004	0.51 ± 0.10
HS2TFS05	5	23053/12-219	.320	8.13	.198	5.03	.020 ± .004	0.51 ± 0.10
HS2TFS04	4	23053/12-220	.370	9.40	.224	5.69	.020 ± .004	0.51 ± 0.10
HS2TFS03	3	23053/12-221	.390	9.91	.249	6.32	.020 ± .004	0.51 ± 0.10
HS2TFS02	2	23053/12-223	.430	10.9	.278	7.06	.020 ± .004	0.51 ± 0.10
HS2TFS01	1	23053/12-224	.450	11.4	.311	7.90	.020 ± .004	0.51 ± 0.10
HS2TFS00	0	23053/12-226	.470	11.9	.347	8.81	.020 ± .004	0.51 ± 0.10



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## Order Information

### Example: HS2TFS15-4TC-500

HS2TFS15-4TC-500 – Heat Shrink

HS2TFS15-4TC-500 – Shrink Ratio (2:1)

HS2TFS15-4TC-500 – PTFE

HS2TFS15-4TC-500 – Wall Type (Standard Wall)

HS2TFS15-4TC-500 – Heat Shrink Size in AWG (AWG15)

HS2TFS15-4TC-500 – Yellow

HS2TFS15-4TC-500 – Package Quantity in feet (500')

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Shrink Temperature 662°F/350°C for 10 minutes per AMS-DTL-23053/12
- \*Dielectric Strength:  $\geq 1,400$  V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- PTFE AWG Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

## Colors

- Natural, Opaque to translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

For detailed ordering information, please consult price list or contact Parflex® Division.

# PTFE Heat Shrinkable Tubing

## Series 2:1 AWG: HS2TFS, HS2TFT, HS2TFL (cont.)

### HS2TFT Thin Wall (2:1)

Part Number	Size (AWG)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS2TFT30	30	23053/12-301	.034	0.86	.015	0.38	.009 ± .002	0.23 ± 0.05
HS2TFT28	28	23053/12-302	.038	0.97	.018	0.46	.009 ± .002	0.23 ± 0.05
HS2TFT26	26	23053/12-303	.046	1.16	.022	0.56	.010 ± .003	0.25 ± 0.08
HS2TFT24	24	23053/12-304	.050	1.27	.027	0.69	.010 ± .002	0.25 ± 0.08
HS2TFT22	22	23053/12-305	.055	1.40	.032	0.81	.012 ± .003	0.31 ± 0.08
HS2TFT20	20	23053/12-306	.060	1.52	.039	0.99	.012 ± .003	0.31 ± 0.08
HS2TFT19	19	23053/12-307	.065	1.65	.043	1.09	.012 ± .003	0.31 ± 0.08
HS2TFT18	18	23053/12-308	.076	1.93	.049	1.25	.012 ± .003	0.31 ± 0.08
HS2TFT17	17	23053/12-309	.085	2.16	.054	1.37	.012 ± .003	0.31 ± 0.08
HS2TFT16	16	23053/12-310	.093	2.36	.061	1.55	.012 ± .003	0.31 ± 0.08
HS2TFT15	15	23053/12-311	.110	2.79	.067	1.70	.012 ± .003	0.31 ± 0.08
HS2TFT14	14	23053/12-312	.120	3.05	.072	1.83	.012 ± .003	0.31 ± 0.08
HS2TFT13	13	23053/12-313	.140	3.56	.080	2.03	.012 ± .003	0.31 ± 0.08
HS2TFT12	12	23053/12-314	.150	3.81	.089	2.26	.012 ± .003	0.31 ± 0.08
HS2TFT11	11	23053/12-316	.170	4.32	.101	2.57	.012 ± .003	0.31 ± 0.08
HS2TFT10	10	23053/12-317	.191	4.85	.112	2.84	.012 ± .003	0.31 ± 0.08
HS2TFT09	9	23053/12-318	.205	5.21	.124	3.15	.015 ± .004	0.38 ± 0.10
HS2TFT08	8	23053/12-320	.240	6.10	.141	3.58	.015 ± .004	0.38 ± 0.10
HS2TFT07	7	23053/12-321	.270	6.86	.158	4.01	.015 ± .004	0.38 ± 0.10
HS2TFT06	6	23053/12-322	.302	7.67	.178	4.52	.015 ± .004	0.38 ± 0.10
HS2TFT05	5	23053/12-323	.320	8.13	.198	5.03	.015 ± .004	0.38 ± 0.10
HS2TFT04	4	23053/12-324	.370	9.40	.224	5.69	.015 ± .004	0.38 ± 0.10
HS2TFT03	3	23053/12-325	.390	9.91	.249	6.32	.015 ± .004	0.38 ± 0.10
HS2TFT02	2	23053/12-327	.430	10.9	.278	7.06	.015 ± .004	0.38 ± 0.10
HS2TFT01	1	23053/12-328	.450	11.4	.311	7.90	.015 ± .004	0.38 ± 0.10
HS2TFT00	0	23053/12-330	.470	11.9	.347	8.81	.015 ± .004	0.38 ± 0.10

## Certifications

- Thin Wall – AMS-DTL-23053/12, Class 3
- AMS 3585
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

**HS2TFL Light Wall (2:1)**

Part Number	Size (AWG)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS2TFL24	24	23053/12-404	.050	1.27	.025	0.64	.006 ± .002	0.15 ± 0.05
HS2TFL22	22	23053/12-405	.055	1.40	.031	0.79	.006 ± .002	0.15 ± 0.05
HS2TFL20	20	23053/12-406	.060	1.52	.038	0.97	.006 ± .002	0.15 ± 0.05
HS2TFL19	19	23053/12-407	.065	1.65	.043	1.09	.006 ± .002	0.15 ± 0.05
HS2TFL18	18	23053/12-408	.076	1.93	.046	1.17	.006 ± .002	0.15 ± 0.05
HS2TFL17	17	23053/12-409	.085	2.16	.054	1.37	.006 ± .002	0.15 ± 0.05
HS2TFL16	16	23053/12-410	.093	2.36	.057	1.45	.006 ± .002	0.15 ± 0.05
HS2TFL15	15	23053/12-411	.110	2.79	.063	1.60	.006 ± .002	0.15 ± 0.05
HS2TFL14	14	23053/12-412	.120	3.05	.072	1.83	.008 ± .002	0.20 ± 0.05
HS2TFL13	13	23053/12-413	.140	3.56	.080	2.03	.008 ± .002	0.20 ± 0.05
HS2TFL12	12	23053/12-414	.150	3.81	.089	2.26	.008 ± .002	0.20 ± 0.05
HS2TFL11	11	23053/12-416	.170	4.32	.099	2.51	.008 ± .002	0.20 ± 0.05
HS2TFL10	10	23053/12-417	.191	4.85	.110	2.79	.008 ± .002	0.20 ± 0.05
HS2TFL09	9	23053/12-418	.205	5.21	.122	3.10	.008 ± .002	0.20 ± 0.05
HS2TFL08	8	23053/12-420	.240	6.10	.139	3.53	.008 ± .002	0.20 ± 0.05
HS2TFL07	7	23053/12-421	.270	6.86	.154	3.91	.008 ± .002	0.20 ± 0.05
HS2TFL06	6	23053/12-422	.302	7.67	.172	4.37	.010 ± .003	0.25 ± 0.08
HS2TFL05	5	23053/12-423	.320	8.13	.192	4.88	.010 ± .003	0.25 ± 0.08
HS2TFL04	4	23053/12-424	.370	9.40	.214	5.44	.010 ± .003	0.25 ± 0.08
HS2TFL03	3	23053/12-425	.390	9.91	.241	6.12	.010 ± .003	0.25 ± 0.08
HS2TFL02	2	23053/12-427	.430	10.9	.270	6.88	.010 ± .003	0.25 ± 0.08
HS2TFL01	1	23053/12-428	.450	11.4	.301	7.65	.010 ± .003	0.25 ± 0.08
HS2TFL00	0	23053/12-430	.470	11.9	.347	8.81	.012 ± .003	0.31 ± 0.08

**Certifications**

- Light Wall - AMS-DTL-23053/12, Class 4
- ASTM D2902 Type I
- FDA Compliant
- USP Class VI Compliant

**Notes**

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)

For detailed ordering information, please consult price list or contact Parflex® Division.



# PTFE Heat Shrinkable Tubing

## Series 4:1 AWG: HS4TFI



### Features

- Virgin Polytetrafluoroethylene resin
- 4:1 Shrink Ratio
- Chemically inert
- Lowest coefficient of friction
- Superior dielectric strength
- Exceptional heat resistance
- Self extinguishing
- Nonwetting

### Applications/Markets



- Electrical Insulation
- Protective Cover
- Rollers
- Bulb Protection

### Certifications

- AMS-DTL-23053/12, Class 5
- ASTM D2902 Type I
- AMS 3584
- FDA Compliant
- USP Class VI Compliant

### HS4TFI PTFE Industrial Wall Heat Shrink Tubing (4:1)

Part Number	Size (inch)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS4TFI5/64	5/64	23053/12-501	.078	1.98	.025	0.64	.009 ± .002	0.23 ± 0.05
HS4TFI1/8	1/8	23053/12-502	.125	3.18	.037	0.94	.012 ± .002	0.31 ± 0.05
HS4TFI3/16	3/16	23053/12-503	.187	4.75	.050	1.27	.012 ± .002	0.31 ± 0.05
HS4TFI1/4	1/4	23053/12-504	.250	6.35	.063	1.60	.012 ± .002	0.31 ± 0.05
HS4TFI5/16	5/16	23053/12-505	.312	7.92	.078	1.98	.012 ± .002	0.31 ± 0.05
HS4TFI3/8	3/8	23053/12-506	.375	9.52	.096	2.44	.012 ± .002	0.31 ± 0.05
HS4TFI7/16	7/16	23053/12-507	.438	11.1	.112	2.84	.012 ± .002	0.31 ± 0.05
HS4TFI1/2	1/2	23053/12-508	.500	12.7	.144	3.66	.015 ± .004	0.38 ± 0.10
HS4TFI5/8	5/8	23053/12-510	.625	15.9	.178	4.52	.015 ± .004	0.38 ± 0.10
HS4TFI3/4	3/4	23053/12-512	.750	19.1	.224	5.70	.015 ± .004	0.38 ± 0.10
HS4TFI7/8	7/8	23053/12-513	.875	22.2	.244	6.20	.015 ± .004	0.38 ± 0.10
HS4TFI1.00	1	23053/12-514	1.000	25.4	.278	7.06	.015 ± .004	0.38 ± 0.10
HS4TFI1.25	1-1/4	23053/12-515	1.250	31.8	.347	8.81	.015 ± .004	0.38 ± 0.10

## Order Information

### Example: HS4TFI5/8-NT

HS4TFI5/8-NT – Heat Shrink

HS4TFI5/8-NT – Shrink Ratio (4:1)

HS4TFI5/8-NT – PTFE

HS4TFI5/8-NT – Wall Type (Industrial Wall)

HS4TFI5/8-NT – Heat Shrink Size in inches (5/8")

HS4TFI5/8-NT – Natural

HS4TFI5/8-NT – Bulk Tubing

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Shrink Temperature 662°F/350°C for 10 minutes per AMS-DTL-23053/12
- For full recovery, expanded diameter should be 50% larger than the diameter of the object to be recovered over
- \*Dielectric Strength:  $\geq 1,400$  V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- PTFE Fractional Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

## Colors

- Natural, Opaque to translucent

See Color Code Table


- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

For detailed ordering information, please consult price list or contact Parflex® Division.

# FEP Tubing

## Series Fractional: 103 Industrial & Heavy Wall



### Features

- Virgin Fluorinated Ethylene Propylene resin
- Translucent
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Nonwetting
- Weldable

### Certifications

- ASTM D 3296-98
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Nitrogen Filling
- Fluid Transfer
- Gas Sampling
- Laboratory
- Down Hole Pump
- Ozone Sampling
- Life Science

### 103 FEP Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F /23°C		Burst Pressure at 73°F /23°C		
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi	bar
#																
103-0062016	1/16	.062	± .003	1.57	± 0.08	.031	± .003	0.41	± 0.08	.016	0.79	480	33	2400	165	
103-0094031	3/32	.094	± .005	2.40	± 0.13	.031	± .002	0.79	± 0.05	.031	0.79	630	43	3150	217	
103-0125031	1/8	.125	± .003	3.18	± 0.08	.062	± .003	0.79	± 0.08	.031	1.57	470	32	2350	162	
103-0156031	5/32	.157	± .005	3.99	± 0.13	.094	± .005	0.79	± 0.13	.031	2.39	360	25	1800	124	
103-0188031	3/16	.188	± .005	4.78	± 0.13	.125	± .005	0.79	± 0.13	.031	3.18	290	20	1450	100	
103-0250031	1/4	.250	± .005	6.35	± 0.13	.188	± .005	0.79	± 0.13	.031	4.78	210	14	1050	72	
103-0312031	5/16	.312	± .005	7.92	± 0.13	.250	± .005	0.79	± 0.13	.031	6.35	160	11	800	55	
103-0375031	3/8	.375	± .005	9.52	± 0.13	.312	± .005	0.79	± 0.13	.031	7.92	130	9	650	45	
103-0438031	7/16	.438	± .005	11.13	± 0.13	.375	± .005	0.79	± 0.13	.031	9.52	110	8	550	38	
103-0500031	1/2	.500	± .006	12.70	± 0.15	.438	± .006	0.79	± 0.15	.031	11.13	90	6	450	31	
103-0563031	9/16	.563	± .006	14.30	± 0.15	.500	± .006	0.79	± 0.15	.031	12.70	80	6	400	28	

## Order Information

**Example: 103-0250031-NT-100**

103-0250031-NT-100 – **FEP**

103-**0250**031-NT-100 – **Tube O.D.** in inches (**1/4"**)

103-0250**031**-NT-100 – **Tube Wall Thickness** in inches (**.031"**)

103-0250031-**NT**-100 – **Natural**

103-0250031-**NT**-100 – **Bulk Tubing**

103-0250031-NT-**100** – **Package Quantity** in feet (**100'**)

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

### 103 FEP Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C	
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi
#															
103-0188062	3/16	.188	± .005	4.78	± 0.13	.062	± .005	1.63	± 0.13	0.062	1.57	630	43	3150	217
103-0250040	1/4	.250	± .005	6.35	± 0.13	.170	± .005	4.32	± 0.13	0.040	1.02	280	19	1400	97
103-0250047	1/4	.250	± .005	6.35	± 0.13	.156	± .005	3.96	± 0.13	0.047	1.19	340	23	1700	117
103-0250062	1/4	.250	± .005	6.35	± 0.13	.125	± .005	3.18	± 0.13	0.062	1.57	470	32	2350	162
103-0312062	5/16	.312	± .005	7.92	± 0.13	.188	± .005	4.78	± 0.13	0.062	1.57	360	25	1800	124
103-0375062	3/8	.375	± .005	9.52	± 0.13	.250	± .005	6.35	± 0.13	0.062	1.57	290	20	1450	100
103-0438062	7/16	.438	± .005	11.13	± 0.13	.312	± .005	7.92	± 0.13	0.062	1.57	250	17	1250	86
103-0500062	1/2	.500	± .005	12.70	± 0.13	.375	± .005	9.53	± 0.13	0.062	1.57	210	14	1050	72
103-0625062	5/8	.625	± .006	15.88	± 0.15	.500	± .006	12.70	± 0.15	0.062	1.57	160	11	800	55
103-0750062	3/4	.750	± .006	19.05	± 0.15	.625	± .006	15.88	± 0.15	0.062	1.57	130	9	650	45
103-0100062	1	1.000	± .010	25.40	± 0.25	.875	± .010	22.22	± 0.25	0.062	1.57	90	6	450	31

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## Fittings

- Fittings available for sizes 1/8" up to 1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 400°F (204°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

## Colors

- Translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

A  
Hose

B  
Tubing  
Fluoropolymer

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings


F  
Tooling, Equipment  
& Accessories

G  
General Technical



# FEP Tubing

## Series Metric: 203



### Features

- Virgin Fluorinated Ethylene Propylene resin
- Translucent
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Nonwetting
- Weldable

### Certifications

- ASTM D 3296-98
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Nitrogen Filling
- Fluid Transfer
- Gas Sampling
- Laboratory
- Down Hole Pump
- Ozone Sampling
- Life Science

### 203 Metric FEP Tubing

Part Number	Order Size		Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C	
	mm	mm	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	inch	psi	bar	psi	bar
#																
203-0300100	3	3	± 0.11	.118	± .004	1	± 0.11	.039	± .004	1	25.4	27	390	134	1950	
203-0400100	4	4	± 0.11	.157	± .004	2	± 0.11	.078	± .004	1	25.4	20	290	100	1450	
203-0500100	5	5	± 0.11	.197	± .004	3	± 0.11	.118	± .004	1	25.4	15	220	76	1100	
203-0600100	6	6	± 0.13	.236	± .005	4	± 0.13	.157	± .005	1	25.4	12	180	62	900	
203-0700100	7	7	± 0.13	.276	± .005	5	± 0.13	.197	± .005	1	25.4	10	150	52	750	
203-0800100	8	8	± 0.13	.315	± .005	6	± 0.13	.236	± .005	1	25.4	9	130	45	650	
203-0900100	9	9	± 0.13	.354	± .005	7	± 0.13	.276	± .005	1	25.4	8	110	38	550	
203-1000100	10	10	± 0.13	.394	± .005	8	± 0.13	.315	± .005	1	25.4	7	100	34	500	
203-1200100	12	12	± 0.15	.472	± .006	10	± 0.15	.394	± .006	1	25.4	6	80	28	400	



## Order Information

**Example: 203-0600100-NT-50**

203-0600100-NT-50 – **Metric FEP**

203-**0600**100-NT-50 – **Tube O.D.** in millimeters (**6 mm**)

203-0600**100**-NT-50 – **Tube Wall Thickness** in millimeters (**1 mm**)

203-0600100-**NT**-50 – **Natural**

203-0600100-NT-**50** – **Bulk Tubing**

2030600100-NT-**50** – **Package Quantity** in feet (**50'**)

## Fittings

- Fittings available for sizes 3mm up to 12mm

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 400°F (204°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

## Colors

○ Translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC...ie HS2TFT1/8-2TC  
..ie HS1.3FEP24-0CC48.000

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



B-73

A Hose

B Tubing  
Fluoropolymer

C Coiled Air Hose  
& Fittings

D Transportation

E Fittings

F Tooling, Equipment  
& Accessories

G General Technical

# FEP Heat Shrinkable Tubing

## Series 1.3:1 HS1.3FEP



### Features

- Easier to shrink than PTFE
- Chemically inert
- Low coefficient of friction
- Superior dielectric strength
- Good heat resistance
- Self extinguishing
- Nonwetting

### Certifications

- 1.3:1 - AMS-DTL-23053/11, Class 1
- ASTM D2902 Type II
- ASTM D3296-98
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Protective Cover
- UV Light Covering
- Product Testing
- Rollers

### HS1.3FEP AWG Heat Shrink Tubing (1.3:1)

Part Number	Size (AWG)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS1.3FEP24	24	23053/11-101	.031	0.79	.027	0.69	.008 ± .002	0.20 ± 0.05
HS1.3FEP22	22	23053/11-102	.036	0.91	.032	0.81	.008 ± .002	0.20 ± 0.05
HS1.3FEP20	20	23053/11-103	.045	1.14	.039	0.99	.008 ± .002	0.20 ± 0.05
HS1.3FEP18	18	23053/11-104	.060	1.52	.049	1.25	.008 ± .002	0.20 ± 0.05
HS1.3FEP16	16	23053/11-105	.075	1.90	.061	1.55	.009 ± .002	0.23 ± 0.05
HS1.3FEP14	14	23053/11-106	.092	2.34	.072	1.83	.009 ± .002	0.23 ± 0.05
HS1.3FEP12	12	23053/11-107	.115	2.92	.089	2.26	.009 ± .002	0.23 ± 0.05
HS1.3FEP10	10	23053/11-108	.141	3.58	.114	2.90	.010 ± .003	0.25 ± 0.08
HS1.3FEP09	9	23053/11-109	.158	4.01	.124	3.15	.010 ± .003	0.25 ± 0.08
HS1.3FEP08	8	23053/11-110	.180	4.57	.143	3.63	.010 ± .003	0.25 ± 0.08
HS1.3FEP07	7	23053/11-111	.197	5.00	.158	4.01	.011 ± .004	0.28 ± 0.10
HS1.3FEP06	6	23053/11-112	.225	5.72	.180	4.57	.011 ± .004	0.28 ± 0.10
HS1.3FEP05	5	23053/11-113	.248	6.30	.198	5.03	.011 ± .004	0.28 ± 0.10
HS1.3FEP04	4	23053/11-114	.290	7.37	.226	5.74	.011 ± .004	0.28 ± 0.10
HS1.3FEP03	3	23053/11-115	.310	7.87	.249	6.32	.011 ± .003	0.28 ± 0.08
HS1.3FEP02	2	23053/11-116	.365	9.27	.280	7.11	.012 ± .004	0.31 ± 0.10
HS1.3FEP01	1	23053/11-117	.400	10.2	.311	7.90	.012 ± .004	0.31 ± 0.10
HS1.3FEP00	0	23053/11-118	.440	11.2	.349	8.86	.012 ± .004	0.31 ± 0.10



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## Order Information

**Example: HS1.3FEP24-0CC48.000**

**HS1.3FEP24-0CC48.000 – Heat Shrink**

**HS1.3FEP24-0CC48.000 – Shrink Ratio (1.3:1)**

**HS1.3FEP24-0CC48.000 – FEP**

**HS1.3FEP24-0CC48.000 – Heat Shrink Size in AWG (AWG 24) (For inch size use inch (3/8"))**

**HS1.3FEP24-0CC48.000 – Black**

**HS1.3FEP24-0CC48.000 – Package Quantity in feet (48')**

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

### HS1.3FEP Fractional Heat Shrink Tubing (1.3:1)

Part Number	Size (inch)	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS1.3FEP3/8	3/8	23053/11-119	.500	12.7	.383	9.73	.015 ± .004	0.38 ± 0.10
HS1.3FEP7/16	7/16	23053/11-120	.580	14.7	.448	11.4	.020 ± .004	0.51 ± 0.10
HS1.3FEP1/2	1/2	23053/11-121	.666	16.9	.510	13.0	.020 ± .004	0.51 ± 0.10
HS1.3FEP5/8	5/8	23053/11-122	.830	21.1	.637	16.2	.025 ± .004	0.64 ± 0.10
HS1.3FEP3/4	3/4	23053/11-123	1.000	25.4	.764	19.4	.030 ± .004	0.76 ± 0.10
HS1.3FEP7/8	7/8	23053/11-124	1.170	29.7	.891	22.6	.035 ± .004	0.89 ± 0.10
HS1.3FEP1.00	1	23053/11-126	1.330	33.8	1.020	25.9	.035 ± .004	0.89 ± 0.10
HS1.3FEP1.13	1-1/8	23053/11-133	1.500	38.1	1.145	29.1	.035 ± .004	0.89 ± 0.10
HS1.3FEP1.25	1-1/4	23053/11-134	1.666	42.3	1.270	32.3	.035 ± .004	0.89 ± 0.10
HS1.3FEP1.38	1-3/8	23053/11-135	1.833	46.6	1.390	35.3	.035 ± .004	0.89 ± 0.10
HS1.3FEP1.50	1-1/2	23053/11-136	2.000	50.8	1.520	38.6	.035 ± .004	0.89 ± 0.10

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 400°F (204°C)
- Shrink Temperature  
1" Dia. and below - 410°F/210°C  
Over 1" Dia. - 430°F/221°C
- \*Dielectric Strength: ≥ 2,000 V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

## Colors

○ Translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC ..ie HS1.3FEP24-0CC48.000

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



B-75

A Hose  
 B Tubing Fluoropolymer  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# FEP Heat Shrinkable Tubing

## Series 1.67:1 HS1.6FEP



### Features

- Easier to shrink than PTFE
- Chemically inert
- Low coefficient of friction
- Superior dielectric strength
- Good heat resistance
- Self extinguishing
- Nonwetting

### Certifications

- 1.67:1 - AMS-DTL-23053/11, Class 2
- ASTM D3296-98
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Protective Cover
- UV Light Covering
- Product Testing
- Rollers

### HS1.6FEP Fractional Heat Shrink Tubing (1.67:1)

Part Number	Size	Mil Spec*	Minimum Expanded I.D.		Maximum Recovered I.D.		Nominal Recovered Wall	
			inch	mm	inch	mm	inch	mm
HS1.6FEP3/32	3/32	23053/11-201	.093	2.36	.056	1.42	.008 ± .003	0.20 ± 0.08
HS1.6FEP1/8	1/8	23053/11-202	.125	3.18	.075	1.90	.010 ± .003	0.25 ± 0.08
HS1.6FEP3/16	3/16	23053/11-203	.188	4.78	.115	2.92	.010 ± .003	0.25 ± 0.08
HS1.6FEP1/4	1/4	23053/11-204	.250	6.35	.150	3.81	.010 ± .003	0.25 ± 0.08
HS1.6FEP3/8	3/8	23053/11-205	.375	9.52	.225	5.72	.012 ± .003	0.31 ± 0.08
HS1.6FEP1/2	1/2	23053/11-206	.500	12.7	.300	7.62	.015 ± .004	0.38 ± 0.10
HS1.6FEP3/4	3/4	23053/11-207	.750	19.1	.450	11.4	.020 ± .004	0.51 ± 0.10
HS1.6FEP1.00	1	23053/11-208	1.000	25.4	.600	15.2	.025 ± .005	0.64 ± 0.13
HS1.6FEP1.25	1-1/2	23053/11-209	1.500	38.1	.900	22.9	.030 ± .005	0.76 ± 0.13
HS1.6FEP1.50	2	23053/11-210	2.000	50.8	1.200	30.5	.030 ± .005	0.76 ± 0.13

## Order Information

### Example: HS1.6FEP3/32-NC48.000

HS1.6FEP3/32-NC48.000 – **Heat Shrink**

HS1.6FEP3/32-NC48.000 – **Shrink Ratio (1.67:1)**

HS1.6**FEP**3/32-NC48.000 – **FEP**

HS1.6FEP**3/32**-NC48.000 – **Heat Shrink Size** in inches (**3/32"**)

HS1.6FEP3/32-**NC**48.000 – **Natural**

HS1.6FEP3/32-NC**C**48.000 – **Cut Tubing**

HS1.6FEP3/32-NC**48.000** – **Package Quantity** in feet (**48'**)

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 400°F (204°C)
- Shrink Temperature  
1" Dia. and below - 410°F/210°C  
Over 1" Dia. - 430°F/221°C
- \*Dielectric Strength:  $\geq 2,000$  V/M, per ASTM D 149 short term test of 10 MIL thickness (Volts/MIL)
- Heat Shrink tubing is available in stock packaging of 4-ft. straight lengths
- Minimum quantities may apply
- Custom packaging, sizes, lengths and colors are quoted upon request

## Colors

○ Translucent

See Color Code Table

- Colors available as custom run
- When ordering coiled tubing in colors, the color code is always followed by TC; when ordering cut lengths, the color code is followed by CC....ie HS2TFT1/8-2TC  
..ie HS1.3FEP24-0CC48.000

Color Code		
○	N	Natural
●	0	Black
●	1	Brown
●	2	Red
●	3	Orange
●	4	Yellow
●	5	Green
●	6	Blue
●	7	Violet
●	8	Gray
○	9	White

For detailed ordering information, please consult price list or contact Parflex® Division.



# PFA Tubing

## Series Fractional: 104 Industrial & Heavy Wall



### Features

- Virgin Perfluoroalkoxy
- Translucent
- High purity resins available
- Low permeability
- Exceptional heat resistance
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Non wetting
- Non leaching

### Certifications

- ASTM D 3307 Type II
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Air Sampling
- Gas Sampling
- Fluid Transfer
- Laboratory
- Wetbench
- Flow Monitoring
- Steam Plant

### 104 PFA Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C	
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi
#															
104-0094031	3/32	.094	± .005	2.40	± 0.10	.031	± .002	0.79	± 0.05	.031	0.79	680	47	3400	234
104-0125031	1/8	.125	± .005	3.18	± 0.10	.064	± .004	1.63	± 0.10	.031	0.79	500	34	2500	172
104-0156031	5/32	.157	± .005	3.99	± 0.13	.094	± .004	2.39	± 0.08	.031	0.79	390	27	1950	134
104-0188031	3/16	.188	± .005	4.78	± 0.13	.125	± .005	3.18	± 0.13	.031	0.79	320	22	1600	110
104-0250031	1/4	.250	± .005	6.35	± 0.13	.188	± .005	4.78	± 0.13	.031	0.79	230	16	1150	79
104-0312031	5/16	.312	± .005	7.92	± 0.13	.250	± .005	6.35	± 0.13	.031	0.79	180	12	900	62
104-0375031	3/8	.375	± .005	9.52	± 0.13	.312	± .005	7.92	± 0.13	.031	0.79	140	10	700	48
104-0438031	7/16	.438	± .005	11.13	± 0.13	.375	± .005	9.53	± 0.13	.031	0.79	120	8	600	41
104-0500031	1/2	.500	± .005	12.70	± 0.13	.438	± .005	11.13	± 0.13	.031	0.79	100	7	500	34
104-0563031	9/16	.563	± .006	14.30	± 0.15	.500	± .006	0.79	± 0.15	.031	0.79	80	6	400	28



For detailed ordering information, please consult price list or contact Parflex® Division.

## Order Information

**Example: 104-0188062-NT-100**

**104-0188062-NT-100 – PFA**

104-**0188**062-NT-100 – **Tube O.D.** in inches (**3/16"**)

104-0188**062**-NT-100 – **Tube Wall Thickness** in inches (**.062"**)

104-0188062-**NT**-100 – **Natural**

104-0188062-**NT**-100 – **Bulk Tubing**

104-0188062-NT-**100** – **Package Quantity** in feet (**100'**)

## Fittings

- Fittings available for sizes 3/32" up to 1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™






## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

## Colors

- Translucent

## 104 PFA Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C		
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi	bar
#																
104-0188062	3/16	.188	± .005	4.78	± 0.13	.062	± .005	1.57	± 0.13	.062	1.57	680	47	3400	234	
104-0250040	1/4	.250	± .005	6.35	± 0.13	.170	± .005	4.32	± 0.13	.040	1.02	300	21	1500	103	
104-0250047	1/4	.250	± .005	6.35	± 0.13	.156	± .005	3.96	± 0.13	.047	1.19	370	26	1850	128	
104-0250062	1/4	.250	± .005	6.35	± 0.13	.125	± .005	3.18	± 0.13	.062	1.57	500	34	2500	172	
104-0312062	5/16	.312	± .005	7.92	± 0.13	.188	± .005	4.78	± 0.13	.062	1.57	390	27	1950	134	
104-0375062	3/8	.375	± .005	9.52	± 0.13	.250	± .005	6.35	± 0.13	.062	1.57	320	22	1600	110	
104-0438062	7/16	.438	± .005	11.13	± 0.13	.312	± .005	7.92	± 0.13	.062	1.57	270	19	1350	93	
104-0500062	1/2	.500	± .005	12.70	± 0.13	.375	± .005	9.53	± 0.13	.062	1.57	230	16	1150	79	
104-0750062	3/4	.750	± .006	19.05	± 0.15	.625	± .006	15.88	± 0.15	.062	1.57	140	10	700	48	
104-1000062	1	1.000	± .010	25.40	± 0.25	.875	± .010	22.22	± 0.25	.062	1.57	100	7	500	34	

For detailed ordering information, please consult price list or contact Parflex® Division.



# PFA Tubing

## Series Metric: 204



### Features

- Virgin Perfluoroalkoxy
- Translucent
- High purity resins available
- Low permeability
- Exceptional heat resistance
- Chemically inert
- Long continuous lengths
- Low coefficient of friction
- Self extinguishing
- Non wetting
- Non leaching

### Certifications

- ASTM D 3307 Type II
- FDA Compliant
- USP Class VI Compliant

### Applications/Markets



- Air Sampling
- Gas Sampling
- Fluid Transfer
- Laboratory
- Wetbench
- Flow Monitoring
- Steam Plant

### 204 Metric PFA Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F /23°C		Burst Pressure at 73°F /23°C	
		mm	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	inch	psi	bar	psi
#															
204-0400100	4	4	± 0.11	.157	± .004	2	± 0.11	.079	± .004	1	.039	34	500	172	2500
204-0600100	6	6	± 0.11	.236	± .004	4	± 0.11	.157	± .004	1	.039	22	320	110	1600
204-0800100	8	8	± 0.11	.315	± .004	6	± 0.11	.236	± .004	1	.039	16	230	79	1150
204-1000100	10	10	± 0.11	.393	± .004	8	± 0.11	.315	± .004	1	.039	12	180	62	900
204-1200100	12	12	± 0.15	.472	± .006	10	± 0.15	.393	± .006	1	.039	10	140	48	700

## Order Information

### Example: 204-0400100-NT-100

204-0400100-NT-100 – **Metric PFA**

204-**0400**100-NT-100 – **Tube O.D.** in millimeters (**4 mm**)

204-0400**100**-NT-100 – **Tube Wall Thickness** in millimeters (**1 mm**)

204-0400100-**NT**-100 – **Natural**

204-0400100-**NT**-100 – **Bulk Tubing**

2040400100-NT-**100** – **Package Quantity** in feet (**100'**)

## Fittings

- Fittings available for sizes 4mm up to 12mm

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®
- Fast & Tite
- TrueSeal™

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email [texloc@parker.com](mailto:texloc@parker.com)
- Working Temperature: 500°F (260°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request
- Package quantities are not continuous

## Colors

- Translucent

*For detailed ordering information, please consult price list or contact Parflex® Division.*



# PVDF Tubing Polyvinylidene Fluoride

## Series PVDF Flex: 110



### Features

- Low extractable levels
- High mechanical strength
- Good chemical resistance
- High abrasion resistance
- Exceptional thermal stability
- Low permeability
- Self extinguishing
- Weather resistant

### Certifications

- ASTM D 3222
- FDA Compliant

### Applications/Markets



- Applications with long cycle life
- Gas
- Food
- Thermal cycling
- Outdoor/extreme conditions
- Water systems
- Ground water monitoring
- Fluid and handling

### 110 PVDF Flex™ Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C	
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi
#															
110-0125031	1/8	.125	± .005	3.18	± 0.13	.062	± .005	1.57	± 0.13	.031	0.79	950	65	4750	327
110-0188031	3/16	.188	± .005	4.78	± 0.13	.125	± .005	3.18	± 0.13	.031	0.79	600	41	3000	207
110-0250031	1/4	.250	± .005	6.35	± 0.13	.188	± .005	4.78	± 0.13	.031	0.79	430	30	2150	148
110-0375031	3/8	.375	± .005	9.52	± 0.13	.312	± .005	7.92	± 0.13	.031	0.79	280	19	1400	97
110-0500031	1/2	.500	± .005	12.70	± 0.13	.438	± .005	11.13	± 0.13	.031	0.79	200	14	1000	69



## Order Information

**Example: 110-0312062-NT-100**

110-0312062-NT-100 – **PVDF Flex**

110-0312062-NT-100 – **Tube O.D.** in inches (**5/16"**)

110-0312062-NT-100 – **Tube Wall Thickness** in inches (**.062"**)

110-0312062-NT-100 – **Natural**

110-0312062-NT-100 – **Bulk Tubing**

110-0312062-NT-100 – **Package Quantity** in feet (**100'**)

## Fittings

- Fittings available for sizes 3/32" up to 1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email texloc@parker.com
- Working Temperature: -80°F (-62°C) - 265°F (130°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request

## Colors

- Off-white

### 110 PVDF Flex™ Heavy Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C	
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi
#															
110-0250047	1/4	.250	± .005	6.35	± 0.13	.156	± .005	3.96	± 0.13	.047	1.19	650	45	3250	224
110-0250062	1/4	.250	± .005	6.35	± 0.13	.125	± .005	3.18	± 0.13	.062	1.57	940	65	4700	324
110-0312062	5/16	.312	± .005	7.92	± 0.13	.188	± .005	4.78	± 0.13	.062	1.57	740	51	3700	255
110-0375062	3/8	.375	± .005	9.52	± 0.13	.250	± .005	6.35	± 0.13	.062	1.57	600	41	3000	207
110-0500062	1/2	.500	± .005	12.70	± 0.13	.370	± .005	9.40	± 0.13	.062	1.57	440	30	2200	152
110-0625062	5/8	.625	± .005	15.88	± 0.13	.500	± .005	12.70	± 0.13	.062	1.57	340	23	1700	117
110-0750062	3/4	.750	± .006	19.05	± 0.15	.625	± .006	15.88	± 0.15	.062	1.57	280	19	1400	97
110-1000062	1	1.000	± .010	25.40	± 0.25	.875	± .008	22.22	± 0.25	.062	1.57	200	14	1000	69

For detailed ordering information, please consult price list or contact Parflex® Division.



# PVDF Tubing Polyvinylidene Fluoride

## Series PVDF Super-Flex®: 111



### Features

- Low extractable levels
- High mechanical strength
- Good chemical resistance
- High abrasion resistance
- Exceptional thermal stability
- Low permeability
- Self extinguishing
- Weather resistant

### Certifications

- ASTM D 3222
- FDA Compliant

### Applications/Markets



- Applications with long cycle life
- Gas
- Food
- Thermal cycling
- Outdoor/extreme conditions
- Water systems
- Ground water monitoring
- Fluid and handling

### 111 PVDF Super-Flex® Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F /23°C		Burst Pressure at 73°F /23°C	
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi
#															
111-0188031	3/16	.188	± .005	4.78	± 0.13	.125	± .005	3.18	± 0.13	.031	0.79	600	41	3000	207
111-0250031	1/4	.250	± .005	6.35	± 0.13	.188	± .005	4.78	± 0.13	.031	0.79	440	30	2200	152
111-0375031	3/8	.375	± .005	9.53	± 0.13	.312	± .005	7.92	± 0.13	.031	0.79	280	19	1400	97

## Order Information

**Example: 111-0375031-NT-200**

**111-0375031-NT-200** – PVDF Super-Flex®

111-**0375**031-NT-200 – **Tube O.D.** in inches (**3/8"**)

111-0375**031**-NT-200 – **Tube Wall Thickness** in inches (**.031"**)

111-0375031-**NT**-200 – **Natural**

111-0375031-**NT**-200 – **Bulk Tubing**

111-0375031-NT-**200** – **Package Quantity** in feet (**200'**)

## Fittings

- Fittings available for sizes 3/32" up to 1"

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- Compression
- Compress-Align®

## Notes

- Available from TexLoc Business Unit, Ft. Worth, Texas (817) 625-5081 or email texloc@parker.com
- Working Temperature: -80°F (-62°C) - 265°F (130°C)
- Working pressure calculated using a Design Factor of 5; Other manufacturers may use a Design Factor of 4
- Custom packaging and sizes are quoted upon request

## Colors

- Off-white

### 111 PVDF Super-Flex® Industrial Wall Fractional Size Tubing

Part Number	Order Size	Nominal O.D.				Nominal I.D.				Reference Wall		Working Pressure at 73°F / 23°C		Burst Pressure at 73°F / 23°C	
		inch	inch	Tolerance	mm	Tolerance	inch	Tolerance	mm	Tolerance	inch	mm	psi	bar	psi
#															
111-0250062	1/4	.250	± .005	6.35	± 0.13	.125	± .005	3.18	± 0.13	.062	1.57	950	65	4750	327
111-0375062	3/8	.375	± .005	9.52	± 0.13	.250	± .005	6.35	± 0.13	.062	1.57	600	41	3000	207
111-0500062	1/2	.500	± .005	12.7	± 0.13	.375	± .005	9.52	± 0.13	.062	1.57	440	30	2200	152

For detailed ordering information, please consult price list or contact Parflex® Division.





# Coiled Air Hose and Fittings



Fast-Stor®

NoMar™ Fast-Stor®

Ultra-Lite Superbraid



# Table of Contents

## Hose & Tubing

Introduction .....	C-4
Fast-Stor® Air Hose .....	C-8 : C-9
Fast-Stor® Air Hose Assemblies, A0 .....	C-8
Bulk Air Hose, FS .....	C-9
NoMar™ Fast-Stor® Urethane Coiled Assemblies, AUFS .....	C-14
NoMar™ Fast-Stor® High Durometer Urethane Coiled Assemblies, AHUFS .....	C-17
NoMar™ Fast-Stor® Coils, UFS .....	C-16
Ultra-Lite Superbraid Hose .....	C-20

## Fittings

Fast-Stor® Fittings .....	C-10 : C-12
Fast-Stor® Replacement Parts .....	C-12 : C-13
NoMar™ Fast-Stor® Fittings .....	C-18

## Technical











Assembly Instructions NoMar™ Fast-Stor® Fittings .....	C-19
Assembly Instructions Fast-Stor® Hose .....	C-13
Measuring Fast-Stor® Bulk Hose .....	C-6
Size Selection Procedure .....	C-5








# Coiled Air Hose Visual Index



<b>Fast-Stor® Fittings &amp; Replacement Parts</b>	<b>MC</b> Male Connector	<b>ME</b> Male Elbow	<b>ML</b> Live Male Pipe Swivel
	 C-10	 C-10	 C-11
	<b>FC</b> Female Connector	<b>FL</b> Female Pipe Swivel	<b>UC</b> Union Connector
	 C-11	 C-11	 C-12
	<b>FN</b> Brass Nut	<b>FR</b> Plastic Ferrule	<b>SG</b> Steel Spring Guard
	 C-12	 C-12	 C-13
<b>TS</b> Tube Support	 C-13		



For detailed ordering information, please consult price list or contact Parflex® Division.



# Air Hose

Every hydraulic, pneumatic and lubrication system requires some form of tube line fabrication and fitting installation for completion. Proper fabrication and installation are essential for the overall efficiency, leak free performance, and general appearance of any system.

Start by planning ahead. After sizing the tube lines and selecting the appropriate style of fitting, consider the following in the design of your system:

- Accessibility of joints
- Proper routing of lines
- Adequate tube line supports
- Available fabricating tools

## Routing of Lines

Routing of lines is probably the most difficult, yet most significant, of these system design considerations. Proper routing involves getting a connecting line from one point to another through the most logical path.

Always try to leave fitting joints as accessible as possible. Hard to reach joints are hard to assemble and tighten properly. Inaccessible joints are also more difficult and time consuming to service.








# Size Selection Procedure

Proper size selection is extremely important in choosing any air hose in order to prevent “starvation” of the air tool and to ensure maximum torque and tool speed. Starved tools don’t produce!

Steps in size selection:

1. Determine air flow rate and pressure required by following air-tool manufacturers recommendations.
2. Refer to “Air Flow Characteristics” graphs, shown below. Find air flow requirement in standard cubic feet per minute (SCFM) on vertical line to left of graph. Now follow horizontal line on same graph to determine total extended length of hose required. Follow vertical line above hose length to intersection with the horizontal air flow SCFM line.
3. Note pressure drop above curve nearest to intersection of SCFM and hose length lines. Pressure drop, subtracted from line pressure, equals “available pressure” at the selected SCFM flow rate and hose length.
4. If “available pressure” is below the tool manufacturers’ recommendations, refer to chart for successively larger hose sizes until an acceptable “available pressure” is found. Choose this size Fast-Stor® Air Hose for your application.
5. Refer to “working pressure vs. temperature” chart (pg. B-7) to be sure your application falls within the working range of Fast-Stor® Air Hose.



Actual working pressure charts are located in the tubing section on the specific product page.

For detailed ordering information, please consult price list or contact Parflex® Division.




# Measuring Fast-Stor® Bulk Hose



Measuring Fast-Stor® hose is quick and easy and may be accomplished by either of two accurate methods:

## 1. Counting

Total Length of Hose			Number of Coils Needed to Obtain Required Net Extended Length +3%				
			3/16 I.D. Fast-Stor®	1/4 I.D. Fast-Stor®	3/8 I.D. Fast-Stor®	1/2 I.D. Fast-Stor®	3/4 I.D. Fast-Stor®
ft.	inch	mtr.	coils	coils	coils	coils	coils
3	36	.91	5-1/8	3-1/2	2-1/4	1-5/8	7/8
3	36	.91	5-1/8	3-1/2	2-1/4	1-5/8	7/8
5	60	1.52	8-1/2	5-3/4	3-7/8	2-5/8	1-1/2
7	84	2.13	12	8-1/8	5-3/4	3-3/4	1-1/8
10	120	3.05	17-1/8	11-1/2	7-3/4	5-3/8	3
12	144	3.66	20-1/2	13-7/8	9-1/4	6-1/2	3-1/2
15	180	4.57	25-3/4	17-3/8	11-1/2	8	4-1/2
16	192	4.88	27-3/8	18-1/2	12-3/8	8-5/8	4-3/4
17	204	5.18	29-1/8	19-5/8	13-1/8	9-1/8	5
19	216	5.79	30-7/8	20-3/4	13-7/8	9-5/8	5-3/8
20	240	6.10	34-1/4	23-1/8	15-3/8	10-3/4	6
25	300	7.62	42-7/8	28-7/8	19-1/4	13-3/8	7-1/2
30	360	9.14	51-3/8	34-5/8	23-1/8	16-1/8	8-7/8
33	396	10.06	56-1/2	38-1/8	25-3/8	17-3/4	9-3/4
50	600	15.24	85-5/8	57-3/4	38-1/2	26-7/8	14-7/8



1 Full 360° Coil



For detailed ordering information, please consult price list or contact Parflex® Division.


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

## 2. Division into Even Numbers of Lengths

Bulk retracted lengths of Fast-Stor® hose are always exactly 100 feet long when shipped from the factory. Some diameter expansion of the coils may occur in shipment due to temperature and storage conditions. This may appear to have shortened a given 100 foot retracted length slightly in relation to other 100 foot retracted lengths in the same master carton. The shorter appearance should not be mistaken for any actual shortage in extended length. A bulk retracted length may be easily divided into smaller lengths by first measuring the tightly retracted length in inches, and dividing by 4 to determine the cut-off length for 25 feet, by 3 for 33 feet, by 8 for 12-1/2 feet, etc. Pieces should be tagged with their proper length before returning to storage.

### Cutting Bulk Length Coils

To cut bulk length coils, position coils on work table extending away from you, cut end-up in 12 o'clock position.



*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



C-7

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Fast-Stor® Air Hose



## Features

- Manufactured from tough, abrasion-resistant nylon
- Excellent memory characteristics over a wide temperature range
- Long service life in rugged applications
- Desirable Safety Yellow color per U.S. Government OSHA directives
- Optimal retail packaging available\*

## Applications/Markets



- Blow Guns
- Construction
- Mfg. Air Drops
- Machine Tool Lubrication
- Water Hose

## Fast-Stor® Assemblies

### Popular Stock Assemblies

Assembly Part Number	Hose I.D.		Total Length		Working Length		Nominal Compact Length		Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
	inch	mm	ft.	mtr.	ft.	mtr.	ft.	mtr.	inch	mm	psi	MPa	psi	MPa	
#	○								○		↗		✂		
A0312-MC4-ML4	3/16	5	12	3.7	9	2.7	4.8	1.5	2	51	225	1.55	680	4.69	1/4" NPT
A0325-MC4-ML4	3/16	5	25	7.6	18	5.5	9.6	2.9	2	51	225	1.55	680	4.69	1/4" NPT
A0350-MC4-ML4	3/16	5	50	15.2	38	11.6	20.2	6.2	2	51	225	1.55	680	4.69	1/4" NPT
A0412-MC4-ML4*	1/4	6	12	3.7	9	2.7	4.3	1.3	3	76	225	1.55	680	4.69	1/4" NPT
A0425-MC4-ML4*	1/4	6	25	7.6	18	5.5	8.6	2.6	3	76	225	1.55	680	4.69	1/4" NPT
A0450-MC4-ML4	1/4	6	50	15.2	38	11.6	18.1	5.5	3	76	225	1.55	680	4.69	1/4" NPT
A0612-MC6-ML6*	3/8	10	12	3.7	9	2.7	4.3	1.3	4.5	114	225	1.55	680	4.69	3/8" NPT
A0625-MC6-ML6	3/8	10	25	7.6	18	5.5	8.5	2.6	4.5	114	225	1.55	680	4.69	3/8" NPT
A0650-MC6-ML6	3/8	10	50	15.2	38	11.6	17.9	5.5	4.5	114	225	1.55	680	4.69	3/8" NPT
A0812-MC8-ML8	1/2	13	12	3.7	9	2.7	4.3	1.3	6.5	165	225	1.55	680	4.69	1/2" NPT
A0825-MC8-ML8	1/2	13	25	7.6	18	5.5	8.5	2.6	6.5	165	225	1.55	680	4.69	1/2" NPT
A0850-MC8-ML8	1/2	13	50	15.2	38	11.6	16.8	5.1	6.5	165	225	1.55	680	4.69	1/2" NPT

## Construction

Tube: Yellow PFX Nylon  
Spring Guard: Steel  
Fittings: Brass

## Notes

\*Retail packaging available - Add "R" suffix when ordering

## Operating Parameters

Service temperature range: -40°F to +200°F  
(-40°C to +93°C)

Maximum working pressure based on safety factor of 3:1 over burst



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Fast-Stor® Bulk Air Hose



Assembly Part Number	Hose I.D.		Average Wall Thickness		Coil I.D.		Coil O.D.		Total Length		Working Length		Master Carton Quantity		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C	
	#																	
Black	inch	mm	inch	mm	inch	mm	inch	mm	ft.	mtr.	ft.	mtr.	ft.	mtr.	psi	MPa	psi	MPa
FS-03-100	3/16	5	.023	.58	2	51	2.5	64	100	30.5	75	22.9	600	183	225	160	680	469
FS-04-100	1/4	6	.030	.76	3	76	3.7	94	100	30.5	75	22.9	600	183	225	160	680	469
FS-06-100	3/8	10	.045	1.1	4.5	114	5.5	140	100	30.5	75	22.9	400	122	225	160	680	469
FS-08-100	1/2	13	.062	1.6	6.5	165	7.8	198	100	30.5	75	22.9	400	122	225	160	680	469
FS-12-100	3/4	19	.075	1.9	11	305	13.0	330	100	30.5	75	22.9	100	30	200	140	600	414

## Construction

Tube: Yellow PFX Nylon

## Operating Parameters

Service temperature range: -40°F to +200°F (-40°C to +93°C)

Maximum working pressure based on safety factor of 3:1 over burst

## Order Information

### Example: A0412-MC4-ML4

A0412-MC4-ML4 – Assembly

A0412-MC4-ML4 – Tube ID (1/4")

A0412-MC4-ML4 – Total Length (12')

A0412-MC4-ML4 – End 1 Fitting Size & Type  
(1/4" Male NPT)

A0412-MC4-ML4 – End 2 Fitting Size & Type  
(1/4" Male NPT, Swivel)



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



C-9

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories


G General Technical

# Fast-Stor® Fittings

Fittings for Fast-Stor® hose are constructed from heavy duty brass with built in insert-supports. Fitting bodies are SAE Standard sizes. Hose entry length into the fittings is the longest in the industry due to Parflex's SAE body design and size standardization, assuring a strong grip on the hose.

All fitting part numbers include body, nut, ferrule and spring guard. For body only, use Prefix B.


## MC – Male Connector



Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
		inch	mm	inch	mm	inch	mm	inch	mm
#									
MC-03-2	1/8	3/16	5	1-3/8	35	9/16	14	1/2	13
MC-03-4	1/4	3/16	5	1-9/16	40	9/16	14	1/2	13
MC-04-2	1/8	1/4	6	1-3/8	35	9/16	14	9/16	14
MC-04-4	1/4	1/4	6	1-9/16	40	9/16	14	9/16	14
MC-06-6	3/8	3/8	10	1-13/16	46	11/16	17	13/16	21
MC-08-6	3/8	1/2	13	2-1/8	54	7/8	22	15/16	24
MC-08-8	1/2	1/2	13	2-1/8	54	7/8	22	15/16	24
*MC-12-12	3/4	3/4	19	2-1/4	57	1-1/4	32	1-3/8	35


\*No spring guard required.

## ME – Male 90° Elbow




Part Number	Thread Size	Hose I.D.		L		N		C Hex	
		inch	mm	inch	mm	inch	mm	inch	mm
#									
ME-03-4	1/4	3/16	5	1-1/4	32	15/16	24	9/16	14
ME-04-4	1/4	1/4	6	1-13/16	46	15/16	24	9/16	14
ME-06-6	3/8	3/8	10	1-9/16	40	1-1/8	29	13/16	21
ME-08-8	1/2	1/2	13	1-3/4	44	1-3/8	35	15/16	24

## ML – Live Male Pipe Swivel




Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
		inch	mm	inch	mm	inch	mm	inch	mm
#									
ML-03-4	1/4	3/16	5	1-1/16	27	9/16	14	1/2	13
ML-04-4	1/4	1/4	6	1-9/16	40	9/16	14	9/16	14
ML-06-6	3/8	3/8	10	1-7/8	47	3/4	19	13/16	21
ML-08-8	1/2	1/2	13	2-3/8	60	7/8	22	15/16	24

## FC – Female Connector FPT



Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
		inch	mm	inch	mm	inch	mm	inch	mm
#									
FC-04-4	1/4	1/4	6	1-9/16	40	11/16	17	9/16	14
FC-06-6	3/8	3/8	10	1-3/4	44	13/16	21	13/16	21

## FL – Female Pipe Swivel\*




Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex		Box Quantity
		inch	mm	inch	mm	inch	mm	inch	mm	
#										
FL-04-4	1/4	1/4	6	1-3/4	44	5/8	16	9/16	14	20
FL-06-6	3/8	3/8	10	2-1/8	54	3/4	19	9/16	14	10

For detailed ordering information, please consult price list or contact Parflex® Division.

# Fast-Stor® Union Connector


## UC – Union Connector



Part Number	Thread Size	Hose I.D.		L		B Hex		C Hex	
		inch	mm	inch	mm	inch	mm	inch	mm
#									
UC-04-4	1/4 x 1/4 I.D.	1/4	6	1-7/8	48	1/2	13	9/16	14
UC-06-6	3/8 x 3/8 I.D.	3/8	10	2-5/8	67	11/16	17	13/16	21


## Fast-Stor® Replacement Parts

### FN – Brass Nut



Part Number	Hose I.D.	
	inch	mm
#		
FN-03	3/16	5
FN-04	1/4	6
FN-06	3/8	10
FN-08	1/2	13
FN-12	3/4	19

### FR – Plastic Ferrule



Part Number	Hose I.D.	
	inch	mm
#		
FR-03	3/16	5
FR-04	1/4	6
FR-06	3/8	10
FR-08	1/2	13
FR-12*	3/4	19


\* Brass.

## SG – Steel Spring Guard



Part Number	Hose I.D.	
	inch	mm
#		
SG-03	3/16	5
SG-04	1/4	6
SG-06	3/8	10
SG-08	1/2	13


## TS – Tube Support



Part Number	Hose I.D.	
	inch	mm
#		
TS-03	3/16	5
TS-04	1/4	6
TS-06	3/8	10
TS-08	1/2	13
TS-12	3/4	19

## How to Assemble Fast-Stor® Hose

- Using a Parker Model 316 cutoff tool, Parflex PHC hand cutter or other sharp cutter, cut hose squarely to correct length.
- Install SG spring guard on hose as shown. A guard is not required on size -12 hose.
- Slide FN nut on hose and insert TS tube support.
- Slide FR plastic ferrule over hose with taper side toward cut end of hose. Size -12 hose uses a brass ferrule and requires the hose end to be dipped in clean water for lubrication.
- Push hose into fitting body until bottomed. Slide nut and ferrule up to fitting body and tighten nut by hand. With a wrench, tighten the nut additional 2 to 2-1/2 turns.
- Slide spring guard over nut until the lead coil snaps between the nut and fitting body hex.



For detailed ordering information, please consult price list or contact Parflex® Division.

# Parflex NoMar™ Fast-Stor® Assemblies AUFS



## Features

- Manufactured from durable, abrasion-resistant Polyurethane
- Excellent memory characteristics over a wide temperature range
- Field-attachable fittings
- Available in bulk or factory-made assemblies

## Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

## Urethane Fast-Stor® Assemblies

Includes live male end and rigid male end

Assembly Part Number	Hose O.D.		Hose I.D.		Total Length		Nominal Compact Length		Nominal Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
	inch	mm	inch	mm	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa	
#															
AUFS-32-TBLU-010**	3/16	5	1/8	3	10	3.0	6.6	167	3/4	19	135	.93	405	2.79	1/8" NPT
AUFS-32-TBLU-025**	3/16	5	1/8	3	25	7.6	19	482	3/4	19	135	.93	405	2.79	1/8" NPT
AUFS-42-TBLU-010	1/4	6	1/8	3	10	3.0	8.3	210	3/4	19	175	1.21	525	3.62	1/4" NPT
AUFS-42-TBLU-025	1/4	6	1/8	3	25	7.6	23.9	607	3/4	19	175	1.21	525	3.62	1/4" NPT
AUFS-64-TBLU-010*	3/8	10	1/4	6	10	3.0	5.6	142	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-64-TBLU-015*	3/8	10	1/4	6	15	4.6	9.3	236	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-64-TBLU-020	3/8	10	1/4	6	20	6.1	13	330	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-64-TBLU-025*	3/8	10	1/4	6	25	7.6	16	406	1-3/4	44	180	1.24	540	3.72	1/4" NPT
AUFS-85-TBLU-010	1/2	13	21/64	8	10	3.0	5.5	140	2-1/2	64	150	1.03	450	3.10	3/8" NPT
AUFS-85-TBLU-015	1/2	13	21/64	8	15	4.6	9	229	2-1/2	64	150	1.03	450	3.10	3/8" NPT
AUFS-85-TBLU-020	1/2	13	21/64	8	20	6.1	12.5	317	2-1/2	64	150	1.03	450	3.10	3/8" NPT
AUFS-85-TBLU-025	1/2	13	21/64	8	25	7.6	16	406	2-1/2	64	150	1.03	450	3.10	3/8" NPT
AUFS-86-TBLU-010	1/2	13	3/8	10	10	3.0	5.5	140	2-1/2	64	110	.76	330	2.28	3/8" NPT
AUFS-86-TBLU-020	1/2	13	3/8	10	20	6.1	12.5	317	2-1/2	64	110	.76	330	2.28	3/8" NPT
AUFS-96-TBLU-010	9/16	14	3/8	10	10	3.0	6.1	155	2-1/2	64	140	.97	420	2.90	3/8" NPT
AUFS-96-TBLU-015	9/16	14	3/8	10	15	4.6	9.9	251	2-1/2	64	140	.97	420	2.90	3/8" NPT
AUFS-96-TBLU-020	9/16	14	3/8	10	20	6.1	13.7	348	2-1/2	64	140	.97	420	2.90	3/8" NPT
AUFS-96-TBLU-025	9/16	14	3/8	10	25	7.6	17.5	444	2-1/2	64	140	.97	420	2.90	3/8" NPT



Assembly Part Number	Hose O.D.		Hose I.D.		Total Length		Nominal Compact Length		Nominal Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C		End Fittings
	#														
	inch	mm	inch	mm	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa	
AUFS-128-TBLU-010	3/4	19	1/2	13	10	3.0	7.5	190	3	76	125	.86	375	2.59	1/2" NPT
AUFS-128-TBLU-015	3/4	19	1/2	13	15	4.6	11.2	284	3	76	125	.86	375	2.59	1/2" NPT
AUFS-128-TBLU-020	3/4	19	1/2	13	20	6.1	15	381	3	76	125	.86	375	2.59	1/2" NPT
AUFS-128-TBLU-025	3/4	19	1/2	13	25	7.6	19.5	495	3	76	125	.86	375	2.59	1/2" NPT

## Construction

Tube: Transparent Blue Polyurethane

Fittings: Brass

## Operating Parameters

Service temperature range: -40°F to +180°F (-40°C to +82°C)

## Notes

Pigtail Lengths - 16" swivel end, 8" rigid end

\*Retail packaging available - Add "R" suffix when ordering

\*\*Size -32 comes standard with two rigid ends

Other sizes available upon request

## Colors

Color Code		
	TBLU	Transparent Blue

Other colors available upon request - consult factory

## Order Information

### Example: AUFS-64-TBLU-025

**AUFS-64-TBLU-025** - Assembled Urethane Fast-Stor

AUFS-**64**-TBLU-025 - Tube OD (3/8")

AUFS-64-**TBLU**-025 - Tube ID (1/4")

AUFS-64-**TBLU**-025 - Color (Transparent Blue)

AUFS-64-TBLU-**025** - Total Length (25')

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



C-15

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Parflex NoMar™ Fast-Stor® Coiled Tubing UFS



## Features

- Manufactured from durable, abrasion-resistant Polyurethane
- Excellent memory characteristics over a wide temperature range
- Long service life in rugged applications

## Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Assembly Part Number	Hose O.D.		Hose I.D.		Working Length	Nominal Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C	
	inch	mm	inch	mm		inch	mm	psi	MPa	psi	MPa
#											
UFS-32-TBLU-xxx	3/16	5	1/8	3	010, 025	3/4	19	135	.93	405	2.79
UFS-42-TBLU-xxx	1/4	6	1/8	3	010, 025	3/4	19	175	1.21	525	3.62
UFS-64-TBLU-xxx	3/8	10	1/4	6	010, 015, 020, 025	1-3/4	44	180	1.24	540	3.72
UFS-85-TBLU-xxx	1/2	13	21/64	8	010, 015, 020, 025	2-1/2	64	150	1.03	450	3.10
UFS-86-TBLU-xxx	1/2	13	3/8	10	010, 020	2-1/2	64	110	.76	330	2.28
UFS-96-TBLU-xxx	9/16	17	3/8	10	010, 015, 020, 025	2-1/2	64	140	.97	420	2.90
UFS-128-TBLU-xxx	3/4	19	1/2	13	010, 015, 020, 025	3	76	125	.86	375	2.59

## Construction

Tube: Transparent Blue Polyurethane

## Operating Parameters

Service temperature range: -40°F to +180°F (-40°C to +82°C)

Maximum working pressure based on safety factor of 3:1 over burst

## Notes

xxx- Denotes Hose Length (feet)

Pigtail Lengths - 16" End #1, 8" End #2

Other sizes available upon request

## Colors

Color Code		
	TBLU	Transparent Blue

Other colors available upon request - consult factory

## Order Information

**Example: UFS-86-TBLU-010**

**UFS-86-TBLU-010** – Assembled NoMar™ Fast-Stor

UFS-86-TBLU-010 – Tube OD (1/2")

UFS-86-TBLU-010 – Tube ID (3/8")

UFS-86-TBLU-010 – Color (Transparent Blue)

UFS-86-TBLU-010 – Total Length (10')



For detailed ordering information, please consult price list or contact Parflex® Division.

# Parflex NoMar™ Fast-Stor® Coiled Assembly AHUFS



## Features

- Manufactured from durable, abrasion-resistant 98 Durometer Polyurethane
- Excellent memory characteristics over a wide temperature range
- Long service life in rugged applications

## Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Assembly Part Number	Hose O.D.		Hose I.D.		Working Length		Nominal Compact Length		Coil I.D.		Maximum Working Pressure 73°F/23°C		Minimum Burst at 73°F/23°C	
	inch	mm	inch	mm	ft.	mtr.	inch	mm	inch	mm	psi	MPa	psi	MPa
#														
AHUFS-6-xxx-015	3/8	10	1/4	6	15	4.6	13	330	1-1/4	32	180	1.24	540	3.72
AHUFS-6-xxx-025	3/8	10	1/4	6	25	6.7	22	559	1-1/4	32	180	1.24	540	3.72

## Construction

Tube: 98 Durometer Polyurethane  
Fitting: Brass

## Operating Parameters

Service temperature range: -40°F to +180°F (-40°C to +82°C)

Maximum working pressure based on safety factor of 3:1 over burst.

## Notes

xxx- Denotes Color

Retail packaging available - Add "R" suffix when ordering

Pigtail Lengths - 16" End #1, 8" End #2

Other sizes available upon request

## Colors

Color Code		
	BLK	Black
	BLU	Blue
	RED	Red
	YEL	Yellow

Other colors available upon request - consult factory

## Order Information

**Example: AHUFS-6-BLK-015**

**AHUFS-6-BLK-015 – Assembled High Durometer Urethane Fast-Stor**

AHUFS-6-BLK-015 – **Tube OD (3/8")**

AHUFS-6-BLK-015 – **Color (Black)**

AHUFS-6-BLK-015 – **Total Length (15')**

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)




C-17

A Hose  
B Tubing  
C Coiled Air Hose & Fittings  
D Transportation  
E Fittings  
F Tooling, Equipment & Accessories  
G General Technical

# Parflex NoMar™ Fast-Stor® Fittings


Parflex NoMar™ Fast-Stor® fittings are manufactured from a heavy brass construction utilizing all standards for NPTF pipe threads. The engineered barb design generates the maximum gripping and sealing power when combined with the socket.

## MCB Male Pipe Rigid




Part Number	Hose Part Number	Thread Size	Hose I.D.		L		Cutoff M		C Hex		F Hex	
			inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
#	#											
MCB-3x2-2	UFS-32	1/8 NPT	0.11	2.8	0.94	23.8	0.72	18.3	7/16	11	7/16	11
MCB-4x2-2	UFS-42	1/8 NPT	0.12	3.0	1.00	25.4	0.74	18.8	7/16	11	7/16	11
MCB-4x2-4	UFS-42	1/4 NPT	0.12	3.0	1.16	29.5	0.90	22.9	9/16	14	7/16	11
MCB-6x4-4	UFS-64	1/4 NPT	0.23	5.8	1.16	29.5	0.90	22.9	5/8	16	5/8	16
MCB-6x4-6	UFS-64	3/8 NPT	0.23	5.8	1.20	30.5	0.94	23.9	3/4	19	5/8	16
MCB-8x5-6	UFS-85	3/8 NPT	0.27	6.9	1.29	32.8	0.99	25.1	3/4	19	3/4	19
MCB-8x6-4	UFS-86	1/4 NPT	0.28	7.1	1.29	32.8	1.03	26.1	3/4	19	3/4	19
MCB-8x6-6	UFS-86	3/8 NPT	0.34	6.6	1.30	33.0	1.04	26.4	3/4	19	3/4	19
MCB-9x6-6	UFS-96	3/8 NPT	0.31	7.9	1.47	37.3	1.10	27.9	7/8	22	7/8	22
MCB-9x6-8	UFS-96	1/2 NPT	0.32	8.1	1.61	40.9	1.24	31.5	7/8	22	7/8	22
MCB-12x8-8	UFS-128	1/2 NPT	0.42	10.7	1.98	50.0	0.94	24.0	1	25	1	25

## MLB Male Live Swivel



Part Number	Hose Part Number	Thread Size	Hose I.D.		L		Cutoff M		C Hex		E Hex		F Hex	
			inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
#	#													
MLB-4x2-4	UFS-42	1/4 NPT	0.12	3.0	1.37	34.8	1.11	28.2	9/16	14	7/16	11	9/16	14
MLB-6x4-4	UFS-64	1/4 NPT	0.22	5.6	1.37	34.8	1.11	28.2	9/16	14	5/8	16	5/8	16
MLB-6x4-6	UFS-64	3/8 NPT	0.23	5.8	1.58	40.1	1.32	33.5	3/4	19	5/8	16	5/8	16
MLB-8x5-6	UFS-85	3/8 NPT	0.27	6.9	1.68	42.7	1.38	35.1	3/4	19	3/4	19	3/4	19
MLB-8x6-6	UFS-86	3/8 NPT	0.33	8.4	1.71	43.4	1.45	36.8	3/4	19	3/4	19	3/4	19
MLB-9x6-6	UFS-96	3/8 NPT	0.31	7.9	1.87	47.5	1.50	38.1	3/4	19	7/8	22	7/8	22
MLB-9x6-8	UFS-96	1/2 NPT	0.31	7.9	1.95	49.5	1.58	40.1	15/16	24	7/8	22	7/8	22
MLB-12x8-8	UFS-128	1/2 NPT	0.42	10.7	2.30	56.5	1.26	32.0	7/8	22	1	25	1	25

### Assembly Instructions



- Using an appropriate cut-off tool (Parker 316 Cut-off tool, Parker HTC - Hose & Tubing Cutter or other sharp cutter), cut the air hose squarely to the correct length.
- Install the SG Spring Guard on the hose. (Note: A guard is not required on -12 hose.)
- Slide the FN Nut and FR Plastic Ferrule on the hose. The FR ferrule should be installed with the taper side toward the cut end of the hose. (Note: -12 hose uses a brass ferrule and requires the hose end to be dipped in clean water for lubrication.)
- Insert the TS Tube Support and push the hose into the fitting body until bottomed. Slide the nut and ferrule up to the fitting body and tighten the nut finger tight. With a wrench, tighten the nut an additional 2 to 2-1/2 turns
- Slide the Spring Guard over the nut until the lead coil snaps between the nut and fitting body hex.

For detailed ordering information, please consult price list or contact Parflex® Division.

# Ultra-Lite Superbraid Hose



## Features

- More than 20% lighter than similar braided polyurethane hoses
- Extremely tough and abrasion resistant
- State-of-the-art strain relief system allows the hose to bend freely without kinking at the fitting
- Features lightweight, non-marring jacket

## Applications/Markets



- Auto Repair
- Blow Guns
- Construction
- Carpentry
- Furniture Manufacturing
- Mfg. Air Drops
- Marine
- Water Hose

Part Number	Nominal I.D.		Nominal O.D.		Total Length	Maximum Working Pressure 73°F/23°C		Fitting Size & Type
	inch	mm	inch	mm		psi	MPa	
#								
SB-4-B-xxx-ML4 SB-4-Y-xxx-ML4	1/4	6	3/8	10	025, 050, 100	220	1.52	1/4" Male NPT, Swivel
SB-5-B-xxx-ML6 SB-5-Y-xxx-ML6	5/16	8	15/32	12	025, 050, 100	185	1.28	3/8" Male NPT, Swivel
SB-6-Y-xxx-ML4	3/8	10	.515	13	025, 050, 100	200	1.38	1/4" Male NPT, Swivel
SB-6-Y-xxx-ML6	3/8	10	.515	13	025, 050, 100	200	1.38	3/8" Male NPT, Swivel
SB-6-Y-xxx-MC4	3/8	10	.515	13	025, 050, 100	200	1.38	1/4" Male NPT, Swivel
SB-6-Y-xxx-MC6	3/8	10	.515	13	025, 050, 100	200	1.38	3/8" Male NPT, Swivel

## Construction

Tube: Polyurethane  
 Reinforcement: Polyester  
 Cover: Polyurethane  
 Fittings: Brass  
 O-rings: Buna-N  
 Strain Relief Sleeves: Acetal

## Operating Parameters

Temperature Range: -40°F to +165°F  
 (-40°C to + 74°C)

## Fittings

Parker Fittings available from:  
 Fluid System Connectors Division  
 Otsego, MI  
 (269) 692-6555  
 (269) 694-4614 FAX  
 Field Attachable Part Number:

06244S	06264SU
06254S	06266SU
06256S	06244-HS
06264RU	06226-HSU

## Notes

xxx- Denotes Hose Length



## SB – Bulk Hose Without Fittings

Part Number	Nominal I.D.		Nominal O.D.		Working Length	Maximum Working Pressure	
	inch	mm	inch	mm		psi	MPa
#							
SB-4-B-xxx SB-4-Y-xxx	1/4	6	3/8	10	025, 050, 100, 500	220	1.52
SB-5-B-xxx SB-5-Y-xxx	5/16	8	15/32	12	025, 050, 100, 300	185	1.28
SB-6-Y-xxx	3/8	10	.515	13	025, 050, 100, 500	200	1.38

### Order Information

**Example: SB-4-Y-050-ML4**

**SB-4-Y-050-ML4 – Super Braid**

**SB-4-Y-050-ML4 – Hose ID (1/4")**

**SB-4-Y-050-ML4 – Color (Yellow)**

**SB-4-Y-050-ML4 – Total Length (50')**

**SB-4-Y-050-ML4 – Fittings Size & Type  
(1/4' Male NPT, Swivel)**

Color Code		
	TBLU	Transparent Blue
	YEL	Yellow

For detailed ordering information, please consult price list or contact Parflex® Division.





# Transportation

Air Brake Tubing

Diesel Fuel Tubing

High Temperature Fuel Tubing

Truck Coils


Cut Tubes

Formed Tubes

Jacketed Bundles

Air Brake Harnesses

SCR Hose


















# Table of Contents

Air Brake Tubing .....D-4  
 Quantum® Elastomeric Air Brake Tubing .....D-5  
 PFT-FL Diesel Fuel Tubing .....D-6  
 HTFL Diesel Fuel Tubing, High Temp .....D-7  
 BRAKCoil® .....D-8  
 Duo-Coil™ .....D-9  
 DollyCoil™ .....D-10

SliderCoil™ .....D-11  
 Fifth Wheel Slider .....D-12  
 Cut Tubes .....D-13  
 Formed Tubes and Hoses .....D-13  
 Jacketed Bundles .....D-13  
 Straight Harnesses .....D-13  
 Formed Harnesses .....D-13  
 SCR Hose .....D-14

## Transportation Visual Index

	Air Brake Tubing	Quantum® Tubing	PFT-FL Diesel Fuel Tubing	HTFL High-Temperature Diesel Fuel Tubing	BRAKCoil®
<b>Transportation Products</b>	 D-4	 D-5	 D-6	 D-7	 D-8
	<b>Duo-Coil®</b>	<b>DollyCoil™</b>	<b>SliderCoil™</b>	<b>Fifth Wheel Slider</b>	<b>Cut Tubes</b>
	 D-9	 D-10	 D-11	 D-12	 D-13
	<b>Formed Tubes &amp; Hoses</b>	<b>Jacketed Bundles</b>	<b>Straight Harnesses</b>	<b>Formed Harnesses</b>	<b>SCR Hose</b>
	 D-13	 D-13	 D-13	 D-13	 D-14



# Parflex Transportation Products

Formed Dash Harnesses  
Transmission Air Shift Bundles  
Cab Tilt Lines



Air Brake Tubing  
Air Brake Harnesses



Slider Coils  
Tire Inflation Hoses



**B** Tubing


**C** Coiled Air Hose & Fittings

**D** Transportation

**E** Fittings

**F** Tooling, Equipment & Accessories

**G** General Technical



Brake Coils



Heated SCR Hose  
Fuel Tubing  
High Temp Fuel Lines



Compressor Discharge Lines  
Formed Power Steering Hoses


*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)





# 1120 Nylon Air Brake Tubing



## Features

- 100% Pressure Tested
- Excellent UV Stability
- Abrasion Resistant
- Kink Resistant

## Certifications

- Meets SAE Specification J844
- Meets DOT FMVSS 49CFR 571.106

## Applications



- Air brake lines

Part Number	Tube O.D.		Outside Diameter		Inside Diameter		Nominal Wall Thickness		Burst Pressure at 73°F / 23°C		Minimum Bend Radius		Weight		Standard Reel		Standard Pallet		
	inch	mm	inch	mm	inch	mm	inch	mm	psi	bar	inch	mm	lbs./100 ft.	kg./mtr.	feet	meter	feet	meter	
#																			
1120-2A-XXX-1000	1/8	.125	3.2	.079	2.0	.023	0.6	1000	69.0	.370	9.4	.340	0.51	1000	305	24,000	7315		
1120-2.5A-XXX-1000	5/32	.156	4.0	.092	2.3	.032	0.8	1200	82.7	.500	12.7	.570	0.85	1000	305	24,000	7315		
1120-3A-XXX-1000	3/16	.188	4.8	.118	3.0	.035	0.9	1200	82.7	.750	19.1	.770	1.15	1000	305	24,000	7315		
1120-4A-XXX-1000	1/4	.250	6.4	.170	4.3	.040	1.0	1200	82.7	1.00	25.4	1.21	1.80	1000	305	24,000	7315		
1120-5A-XXX-500	5/16	.313	7.9	.232	5.9	.040	1.0	1000	69.0	1.25	31.8	1.57	2.34	500	152	12,000	3658		
1120-6B-XXX-500	3/8	.375	9.5	.251	6.4	.062	1.6	1400	96.5	1.50	38.1	2.70	4.02	500	152	12,000	3658		
1120-8B-XXX-500	1/2	.500	12.7	.376	9.6	.062	1.6	950	65.5	2.00	50.8	3.90	5.81	500	152	6,000	3658		
1120-10B-XXX-250	5/8	.625	15.9	.441	11.2	.092	2.3	900	62.1	2.50	63.5	7.00	10.43	250	76	3,000	914		
1120-12B-XXX-250	3/4	.750	19.1	.566	14.4	.092	2.3	800	55.2	3.00	76.2	8.60	12.81	250	76	3,000	914		

XXX represents color code.

## Construction

Material:  
Type A - Single-wall extruded Nylon (polyamide)

Type B - Nylon (polyamide) core, fiber reinforcement,  
Nylon (polyamide) jacket/sheath

## Operating Parameters

Temperature Range:  
-40°F to +200°F (-40°C to +93°C)  
Working Pressure: 150 psi (10.3 bar)

## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- NTA
- PMT
- PTC

## Colors


Color Code		
	BLK	Black
	BLU	Blue
	BRN	Brown
	GRN	Green
	ORG	Orange
	PUR	Purple
	RED	Red
	SIL	Silver
	TAN	Tan
	YEL	Yellow
	WHT	White



For detailed ordering information, please consult price list or contact Parflex® Division.



# 1320 Quantum® Elastomeric Air Brake Tubing



## Features

- 100% Pressure Tested
- Excellent UV Stability
- Abrasion Resistant
- Kink Resistant

## Certifications

- Meets or exceeds the performance requirements of DOT 49CFR571.106 and SAE J844

## Applications



- Air brake lines

Part Number	Tube O.D.	Outside Diameter		Inside Diameter		Nominal Wall Thickness		Burst Pressure at 73°F / 23°C		Minimum Bend Radius		Weight		Standard Reel		Standard Pallet	
		inch	mm	inch	mm	inch	mm	psi	bar	inch	mm	lbs./100 ft.	kg./mtr.	feet	meter	feet	meter
1320-6B-XXX-500	3/8	.375	9.5	.251	6.4	.062	1.6	1400	96.5	1.50	38.1	2.70	4.02	500	152	12,000	3658
1320-8B-XXX-500	1/2	.500	12.7	.376	9.6	.062	1.6	950	65.5	2.00	50.8	3.90	5.81	500	152	6,000	3658

XXX represents color code.

## Construction

Material: Proprietary elastomeric material  
Type B - Proprietary, reinforced design

## Operating Parameters

Temperature Range:  
-40°F to +200°F (-40°C to +93°C)  
Working Pressure: 150 psi (10.3 bar)

## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:


- NTA
- PMT
- PTC

## Colors

Color Code		
●	BLK	Black
●	BLU	Blue
●	BRN	Brown
●	GRN	Green
●	ORG	Orange
●	RED	Red
●	SIL	Silver
●	YEL	Yellow

## Order Information

To order 1120 or 1320 Air Brake Tubing, add color code and reel length to specify part number. ie.  
1120-4A-BLK-1000 **Typical order examples:**  
**24,000 feet, 1120-4A-BLK-1000** - Product ordered is 1/4" O.D. Black Air Brake Tubing, (24) 1000-foot reels of tubing on 1 pallet. **500 feet, 1120-10B-RED-250** - Product ordered is 5/8" O.D. Red Air Brake Tubing, (2) 250-foot reels of tubing in boxes.



For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# Parflex Diesel Fuel Tubing



## Features

- Nylon tubing designed for use in tractor, trailer and other mobile fuel systems
- Heat and light stabilized
- 100% quality controlled - 100% pressure tested
- Saves weight and labor in comparison with hose and hard-line tubing

## Approvals

- Compatible with JP-5 (MIL-DTL-5624) and JP-8 (MIL-DTL-83133)
- Compatible with Biodiesel per Parflex PPB PL-18 hard-line tubing

## Applications



- D.O.T. diesel fuel applications

Part Number	Nominal Tube O.D.		Nominal Tube I.D.		Minimum Bend Radius		Weight		Standard Reel	
	inch	mm	inch	mm	inch	mm	lbs./ft.	kg./mtr.	feet	meter
#										
PFT-4A-XXX-1000-FL	1/4	6	.170	4	1	25	.012	.005	1000	305
PFT-6B-XXX-500-FL	3/8	10	.251	6	1-1/2	38	.027	.012	500	152
PFT-8B-XXX-500-FL	1/2	13	.376	10	2	51	.039	.018	500	152
PFT-10B-XXX-250-FL	5/8	16	.441	11	2-1/2	64	.070	.032	250	76
PFT-12B-XXX-250-FL	3/4	19	.566	14	3	76	.086	.039	250	76

XXX represents color code.

## Construction

Heat and light stabilized seamless extruded nylon core reinforced with fibrous reinforcement and bonded with a protective blue nylon cover sheath

## Operating Parameters

Temperature Range:

-40°F to +200°F (-40°C to +93°C)

Maximum Working Pressure: 150 psi (10.3 bar)

Do not exceed temperature and pressure ranges

## Color

- BLU

Blue is standard

Consult division for additional colors

## Fittings

Parker Fittings available from:  
Fluid System Connectors Division  
Otsego, MI  
(269) 692-6555  
(269) 694-4614 FAX

FSC Product Families:

- NTA
- DF (Diesel Fuel Only)

## Notes

Contact Parflex Division for application review

# HTFL Diesel Fuel Line Tubing (High-Temperature)



## Features

- Heat and UV stabilized
- For use in high temperature applications
- 100% Pressure Tested
- Lightweight
- Pre-formed tubes available

## Applications



Part Number	Nominal Tube O.D.		Nominal Tube I.D.		Nominal Wall Thickness		Working Pressure		Minimum Burst at 73°F / 23°C		Minimum Bend Radius		Weight		Standard Reel	
	inch	mm	inch	mm	inch	mm	psi	bar	psi	bar	inch	mm	lbs./ft.	kg./mtr.	feet	meter
#																
HTFL-6B-BRN-500	3/8	10	.251	6	.062	1.6	175	12.1	1,400	96.5	1-1/2	38	.028	.013	500	152
HTFL-8B-BRN-500	1/2	13	.376	10	.062	1.6	155	10.7	950	65.5	2	51	.039	.018	500	152
HTFL-10B-BRN-250	5/8	16	.441	11	.092	1.6	140	9.7	900	62.1	2-7/8	73	.071	.032	250	76
HTFL-12B-BRN-250	3/4	19	.566	14	.092	1.6	150	10.3	800	55.1	3	76	.086	.039	250	76

## Construction

Tube: High-temperature and chemical-resistant special polyamide

Reinforcement: High-strength yarn fiber

Cover: High-temperature and UV-resistant special polyamide

## Operating Parameters

Temperature Range:

-50°F to +266°F (-46°C to +130°C)

Vacuum Rating: 28 inch Hg

## Fittings

Parker Fittings available from:

Fluid System Connectors Division

Otsego, MI

(269) 692-6555

(269) 694-4614 FAX

FSC Product Families:

NTA

## Color

● BRN

Brown is standard

Consult division for additional colors

## Notes

Compatible with JP-5 (MIL-DTL-5624) and JP-8 (MIL-DTL-83133)

Compatible with Biodiesel per Parflex PPB PL-18

For detailed ordering information, please consult price list or contact Parflex® Division.


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



D-7

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# BRAKCOIL®



## Features

- Tractor-to-trailer coiled nylon air-brake connections
- Maintenance-free performance - designed for trouble-free service on your rig
- Years of city delivery and line haul testing
- Heavy-duty plated spring guards are rust-resistant for added protection
- More coils offer you maximum working lengths
- No need for pogo sticks or spring hangers
- Color coding gives you mistake-free hook-ups - blue for service, red for emergency

## Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

## Applications



- Tractor to Trailer

Kit Coil Number	Individual Coil Part Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Working Length		Number of Coils
						Valve		Gladhand				
#	#	⊙										
		inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
731516	731512-Red 731512-Blue	-8	13	12	305	1/2	13	1/2	13	15	4.6	21-1/2
751597	731611-Red 731611-Blue	-8	13	12	305	3/8	10	1/2	13	15	4.6	21-1/2
731522	731513-Red 731513-Blue	-8	13	40	1016	1/2	13	1/2	13	15	4.6	21-1/2
741526	731612-Red 731612-Blue	-8	13	40	1016	3/8	10	1/2	13	15	4.6	21-1/2
751641	741590-Red 741590-Blue	-8	13	6	152	1/2	13	1/2	13	12	3.7	18-1/2
751655	751656-Blk Black Only	-8	13	6	152	3/8	10	1/2	13	12	3.7	18-1/2

## Order Information

BRAKCOIL® kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and male pipe NTA brass fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or assembly necessary. Just attach the gladhands (sold separately or pre-assembled). They are available in kits or as separate lines. A kit consists of both a red and blue tube assembly.

## Construction

Tube: Coiled Nylon Air Brake Tubing

## Operating Parameters

Temperature Range:  
-70°F to +200°F (-57°C to +93°C)

## Options

Extended BRAKCOIL handle available, part no. 771164

Gladhands available

- Blue - Part # GH9211
- Red - Part # GH9212



For detailed ordering information, please consult price list or contact Parflex® Division.

# Duo-Coil™ Features



## Features

- Duo-Coil combines both tractor-to-trailer lines (service and emergency) into a strong single unit
- Designed for quick hook-up and trouble-free service on your rig
- Reverse winding of the coiled air brake lines eliminates the possibility of tangling
- Installation swivel fittings make hook-up a snap
- The inner red emergency coil is wound inside the blue service coil offering added protection to the driver
- The single unit provides clean and neat installation

## Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

## Applications



- Tractor to Trailer

Kit Coil Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Working Length		Number of Coils
					Valve		Gladhand				
#	⊙										
	inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
801048	-8	13	12	305	1/2	13	1/2	13	15	4.6	21-1/2
801632	-8	13	6	152	1/2	13	1/2	13	12	3.7	18-1/2
801595	-8	13	40	1016	1/2	13	1/2	13	15	4.6	21-1/2

## Order Information

Duo-Coil™ kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and pipe end NTA fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or fitting assembly is necessary. Just attach the gladhands (sold separately or pre-assembled).

## Construction

Tube: Coiled Nylon Air Brake Tubing

## Operating Parameters

Temperature Range:  
-70°F to +200°F (-57°C to +93°C)

## Options

Extended BRAKCOIL handle available, part no. 771164

Gladhands available

- Blue - Part # GH9211
- Red - Part # GH9212

For detailed ordering information, please consult price list or contact Parflex® Division.



# DollyCoil™



## Features

- No need to install springs or hangers
- Will retract to its original shape even after long periods of extended use

## Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

## Applications



- Multiple Trailers
- Converter Dollies

Kit Coil Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Standard Working Length		Number of Coils
					Valve 90° End		Gladhand 180° End				
#	⊙										
	inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
751634	-8	13	8	13	1/2	13	1/2	13	6	1.83	12

## Order Information

DollyCoil™ kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and male pipe end NTA fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or assembly necessary. Just attach the gladhands (sold separately or pre-assembled). They are available in kits or as separate lines. A kit consists of both a red and blue tube assembly.

## Construction

Tube: Coiled Nylon Air Brake Tubing

## Operating Parameters

Temperature Range:  
-70°F to +200°F (-57°C to +93°C)

## Options


Extended BRAKCOIL handle available, part no. 771164

Gladhands available

- Blue – Part # GH9211
- Red – Part # GH9212



# SliderCoil™



## Features

- Used between an adjustable rear trailer axle and the final point on a trailer chassis
- No need to install springs or hangers
- Will retract to its original shape even after long periods of extended use

## Certifications

- Meets or exceeds SAE J844 and D.O.T. FMVSS 106 Specifications at -70°F to +200°F

## Applications



- Tractor Trailers (Sliding)
- Tractor Trailers (Axles)

Kit Coil Number	Individual Coil Part Number	Tube O.D.		Valve Tail Length		Brass Male Ends (NPT)				Working Length		Number of Coils
						Valve 90° End		Gladhand 180° End				
#	#	⊙										
		inch	mm	inch	mm	inch	mm	inch	mm	feet	meter	
751657	751658-BLU, RED	-8	13	8	13	1/4	6	1/4	6	14-1/2	4.5	6' - 8'
751659	751660-BLU, RED	-8	13	8	13	3/8	10	3/8	10	14-1/2	4.5	6' - 8'

## Order Information

SliderCoil™ kits are supplied complete – **Parker pre-assembled**, with everything needed, including spring guards and male pipe end NTA fittings, **ready to install**. Special pipe thread sealant is factory applied. No cutting or assembly necessary. They are available in kits or as separate lines. A kit consists of both a red and blue coil assemblies.

## Construction

Tube: Coiled Nylon Air Brake Tubing

## Operating Parameters

Temperature Range: -70°F to +200°F (-57°C to +93°C)

## Color

- Blue
- Red

## Options

Extended BRAKCOIL handle available, part no. 771164

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Fifth Wheel Slider Coil



## Features

- Clutter-free hook-up and maintenance-free performance of adjustable length pneumatic tubing for fifth wheel sliding action
- Self-adjusts from 10" to fully extended 54" working length
- Universal, ready for immediate installation
- No maintenance required - stays on the job at peak performance through years of trouble-free life
- Coil set is strong and permanent - Even after prolonged use in fully extended position, coils will retract to shorter length without sagging and eliminating hazards of chafing and wear

## Applications



- Double Trailers
- Covert, Dollies

## Certifications

- Conforms to SAE Specification J844 Type A
- Meets D.O.T. FMVSS 106

Part Number	Fittings	Pigtail Length		Max. Extended Length		Retracted Length	
		inch	mm	inch	mm	inch	mm
#							
811537	(2)68NTA-4-4	2	51	74	1880	10	254
811537-NF-BLK	-	2	51	74	1880	10	254

## Order Information

Fifth Wheel Slider Coil part# 811537 comes complete with fittings. Part# 811537-NF-BLK does not include fittings.

## Construction

Tube: 1/4" O.D. extruded Nylon, heat and light stabilized, single wall

## Operating Parameters

Temperature Range: -40°F to +200°F (-40°C to +93°C)

## Color

- SIL

## Options

Available with or without fittings

# Custom Harness, Bundles & Tubing

## Order Information

Several different harnesses may be required on a single unit depending upon the model of the vehicle, wheel base and options available. To determine your harness application needs:

- 1. Recognize the cost savings** available to you through the use of harnesses. How many dollars will be saved on tubing installation alone? On scrap reduction?
- 2. Call Parker.** Have one of our application engineers study your application.
- 3. Have Parker engineers design and build a prototype** harness for your approval.
- 4. Approve the prototype** as our basis to engineer your production model harness.
- 5. Implement the harness** into your Purchasing and Production systems – one harness, one part number instead of multiple part numbers you once had for each air brake line.




## Cut Tubes

Any tube offered by Parflex can be cut-to-length, with options for additional marking



## Formed Tubes

Tubes can be formed into shapes for ease of installation



## Jacketed Bundles

Two or more tubes can be bundled together with an extruded thermoplastic jacket

## Features

- Preformed, pre-bundled tubing or hose custom designed to reduce installation time and improve throughput
- Your production line will run faster and be virtually free from tubing scrap
- Individual tubes are pre-cut and assembled into a single unit

## Certifications

- Designed and engineered to meet the exacting requirements of each bus or truck manufacturer for each vehicle
- The air brake tubing used in a Parflex Harness conforms to SAE J844 type 3A and 3B and also D.O.T. FMVSS 106

## Tubing

### Construction

Tube: Nylon Air Brake Tubing

### Operating Parameters

Temperature Range: -40°F to +200°F (-40°C to +93°C)

Working Pressure: 150 psi (10.3 bar)

### Options


Each tube can be color-coded and/or numbered

Each harness may contain any number of tube sizes ranging from 1/8" O.D. to 3/4" O.D.

The harness can be supplied with special clamps, brackets and fittings to meet any need required by the customer

## Hose

Contact Parflex Customer Service for custom formed hoses and hose assemblies



## Straight Harnesses

Combine multiple cut tubes into a harness built specifically for your application



## Formed Harnesses

Combine multiple formed tubes to create a repeatable tubing routing solution



## Formed Assemblies

Most Parflex thermoplastic hoses can be formed into application specific shapes

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



D-13

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

# SCR Hose Assemblies for Tier IV Compliance



## Features

- Consistent thaw - more reliable than coolant heated lines
- Multiple options available to fit every application
- Protective Overmolding
  - Protection against water ingress and damage of electrical components
  - Bolsters fitting strength and impact resistance
- Corrugated heat shield offers abrasion and heat resistance
- Assembled and designed in USA

## Certifications

- Parflex Division is third party certified for ISO 14001 and TS 16949

## Applications



- Diesel Exhaust Fluid Conveyance

## Keeping the Air We Breath Clean

With Electrically Heated SCR Hose Assemblies from Parker's Parflex Division, a cleaner exhaust system means a cleaner environment. Designed for heating and conveying DEF (Diesel Exhaust Fluid) throughout the SCR system on commercial vehicles, Parflex hoses are made to handle both on-road and off-road applications while helping you stay Tier IV and EPA '10 compliant. Combine these hoses with other high value Parflex fluid conveyance products (pilot lines, grease lines, hydraulic hoses, etc.) so your customer can enjoy best in class durability and performance.

Unlike the competition's electrically heated hose, Parflex SCR hoses encapsulate the heating elements with an extruded sheath for added protection and long-lasting uniform heating. The overmold on the fittings provide impact and water resistance, making the hoses suitable for multiple environments.

Each configuration utilizes materials specifically formulated for their application. All Parflex SCR hose assemblies have multiple options, allowing customization by the equipment manufacturer/end user.

*Both styles available with 6mm I.D.  
Please contact Parflex for other hose internal diameters, custom requirements or non-purge systems.*

**Contact Parflex for 3mm or 4mm I.D. nylon lines, or 4mm or 5.5mm EPDM lines. Other custom designs available!**

*Check [www.scrhose.com](http://www.scrhose.com) for product updates*

# S0/S1

## Suction/Throttle Line Design



### Parflex SCR Hose Assembly Polyamide Suction/Throttle Line


- Polyamide core tube with fabric reinforcement
- Extruded thermoplastic jacket
- Optional heat/abrasion shield

### Certifications

- TS 16949
- ISO 14001

Base Part Number	Nominal I.D.		O.D.		with Shield (opt)		Max. Oper. Pressure		Min. Burst Pressure		Vacuum Resistance		Bend Radius		Standard Lengths*
	mm	inch	mm	inch	mm	inch	psi	bar	psi	bar	inch	Hg/bar	inch	mm	mtr
S0	6	.24	14	.55	NA	NA	145	10	600	40	8.9	300m	2	51	1/2, 1, 1-1/2 or 2
S1	6	.24	14	.55	21	.827	145	10	600	40	8.9	300m	2	51	1/2, 1, 1-1/2 or 2

\*Please contact Parflex for overall lengths other than those listed. Nonstandard lengths are available.



# P1

## Pressure Line Design



### Parflex SCR Hose Assembly Polyamide Pressure Line

- Specialty high temperature polyamide core with fabric reinforcement
- Stainless steel heating wire
- Extruded high temperature thermoplastic jacket
- Heat/abrasion shield

### Operating Parameters

- Temperature Range: -40°F to 248°F (-40°C to 120°C) Spikes to 284°F (140°C)
- Available in 12VDC or 24VDC design

Base Part Number	Nominal I.D.		w/ Heat Shield		Max. Oper. Pressure		Min. Burst Pressure		Bend Radius		Standard Lengths*
	mm	inch	mm	inch	psi	bar	psi	bar	inch	mm	mtr
P1	6	.24	21	.82	189	13	600	40	2	51	1, 2 or 3

\*Please contact Parflex for overall lengths other than those listed. Nonstandard lengths are available.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical





# Hose Fittings



Permanent/Crimp

Field Attachable/Reusable



# Table of Contents

## Intro

Hose Fitting Nomenclature.....	E-3
Fitting Configurations by Connection and End Code .....	E-4

## Permanent/Crimp

54 Series .....	E-8
55/58 Series .....	E-12
57 Series .....	E-37
58H Series .....	E-41
91N/91 Series .....	E-52
92 Series .....	E-65
93N Series .....	E-67
94/95 Series .....	E-70
PAGE Fittings .....	E-71
CY Series .....	E-81
SF Series .....	E-85
HY Series .....	E-87
LV Series .....	E-104
MS Series .....	E-105
SQ Series .....	E-107

## Field Attachable/Reuseable

51 Series .....	E-5
90 Series .....	E-45
BA Series .....	E-79
BU Series .....	E-80
MS Series .....	E-105



# Parflex Fittings

Parflex has expanded the Fitting Section to include new products such as 54 Series Rapid Assembly fittings and also, CY Series, SF Series and PAGE Fittings, that were previously omitted.

The new PAGE fittings, which are designed for use with traditional PAGE fluoropolymer hoses only, are a two piece crimp connection and need to be combined with the corresponding crimp collars located on page E-72. As demonstrated below, the

nomenclature associated with the PAGE fitting is also not consistent with the traditional Parker products, as the end size and hose I.D. are reversed and located at the front of the part construction.

The Table of Content is broken out by style: Permanent/Crimp and Field Attachable/Reusable. Each fitting series has its own Visual Index preceding the series with the fittings in a numerical picture index.

## Parker Fitting Nomenclature

### Example: 10355-8-6

This example describes a permanent crimp 1/2" Male JIC 37° with a 3/8" I.D. hose size. This fitting is constructed of steel since the designated material is blank.

- 10355-8-6 – **Fitting Type** (1 = Permanent/Crimp)  
(2 = Field Attachable Fitting)
- 10355-8-6 – **End Configuration Code** (Male JIC 37°)
- 10355-8-6 – **Fitting Series** (Series 55)
- 10355-8-6 – **End Size** (1/2")
- 10355-8-6 – **Hose I.D.** (3/8")
- 10355-8-6C – **Alternate Material**

Fitting part numbers that start with a "2" are field attachable fittings

### Parker Fitting Material Selection

- Blank = Steel (unless otherwise noted)
- B = All Brass
- C = Stainless Steel
- S = All Carbon Steel – Used only with PTFE Fittings

## PAGE Fitting Nomenclature

### Example: 08-16SAN-S

This example describes a permanent sanitary flange step down, 1/2" I.D. hose with a 1" sanitary flange. This fitting is constructed of stainless steel since the designated material is -S.

- 08-16SAN-S – **Hose I.D.** (1/2")
- 08-16SAN-S – **End Size** (1")
- 08-16SAN-S – **End Configuration Code**  
(Sanitary Flange)

### PAGE Fitting Material Selection

- B = All Brass
- C = Carbon Steel

For detailed ordering information, please consult price list or contact Parflex® Division.

# Standard Fitting Configurations by Connection and End Code






	Description	End Code	
Pipe	Male NPTF Pipe - Rigid - Straight	01	
	Male NPTF Pipe - Swivel - Straight	13	
	Male NPTF Pipe - Swivel - 90° Elbow	1L	
	Female NPTF Pipe - Rigid - Straight	02	
	Female NPSM Pipe - Swivel - Straight (60° Cone)	07	
SAE Str. Thr.	Male SAE Straight Thread with O-Ring - Rigid - Straight	05	
	Male SAE Straight Thread with O-Ring - Swivel - Straight	0G	
	Male SAE Straight Thread with O-Ring - Swivel - 90° Elbow	0L	
	Male SAE Straight Thread with O-Ring - Adjustable - 90° Elbow	35	
	Male JIC 37° - Rigid - Straight	03	
Flare	Male JIC 37° - Bulkhead without Locknut - Straight	LB	
	Female JIC 37° - Swivel - Straight	06	
	Female JIC 37° - Swivel - 45° Elbow - Short Drop	37	
	Female JIC 37° - Swivel - 45° Elbow - Medium Drop	L7	
	Female JIC 37° - Swivel - 90° Elbow - Short Drop	39	
	Female JIC 37° - Swivel - 90° Elbow - Medium Drop	L9	
	Female JIC 37° - Swivel - 90° Elbow - Long Drop	41	
	Male SAE 45° - Rigid - Straight	04	
	Female SAE 45° - Swivel - Straight	08	
	Female SAE 45 / Swivel - 45° Elbow	77	
	Female SAE 45 / Swivel - 90° Elbow	79	
	Female SAE 45 / Swivel - 90° Elbow - Long Drop	81	
	Female JIC 37°/SAE 45° Dual Flare - Swivel - Straight	06	
	Inverted Flare	Male Inverted SAE 45° - Swivel - Straight	28
		Male Inverted SAE 45° - Swivel - 45° Elbow	67
Male Inverted SAE 45° - Swivel - 90° Elbow		69	
Female Inverted SAE 45° - Rigid - Straight		29	
Seal-Lok	Male Seal-Lok - Rigid - Straight (with O-Ring)	J0	
	Male Seal-Lok - Bulkhead without Locknut-Straight (with O-Ring)	JB	
	Female Seal-Lok - Swivel - Straight - Long	JS	
	Female Seal-Lok - Swivel - Straight - Short	JC	
	Female Seal-Lok - Swivel - 221/2° Elbow	J6	
	Female Seal-Lok - Swivel - 45° Elbow	J7	
	Female Seal-Lok - Swivel - 90° Elbow - Short Drop	J9	
	Female Seal-Lok - Swivel - 90° Elbow - Medium Drop	J5	
	Female Seal-Lok - Swivel - 90° Elbow - Long Drop	J1	
	JIS	Female Metric Swivel - Straight (30° Flare)	MU
Female BSP Parallel Pipe - Swivel - Straight (30° Flare)		FU	
Male BSP Taper Pipe - Rigid - Straight (60° Cone)		UT	
Female BSP Parallel Pipe - Swivel - Straight (60° Cone)		GU	
Female BSP Parallel Pipe - Swivel - 45° Elbow (60° Cone)		G1	
Female BSP Parallel Pipe - Swivel - 90° Elbow (60° Cone)		G2	
Metric		Male Metric L - Rigid - Straight (24° Cone)	D0
	Male Standpipe Metric L - Rigid - Straight	1D	
	Female Metric L - Swivel - Straight (Ball Nose)	C3	

	Description	End Code	
Metric	Female Metric L - Swivel - 45° Elbow (Ball Nose)	C4	
	Female Metric L - Swivel - 90° Elbow (Ball Nose)	C5	
	Female Metric L - Swivel - Straight (24° Cone with O-Ring)	CA	
	Female Metric L - Swivel - 45° Elbow (24° Cone with O-Ring)	CE	
	Female Metric L - Swivel - 90° Elbow (24° Cone with O-Ring) -	CF	
	Male Metric S - Rigid - Straight (24° Cone)	D2	
	Male Standpipe Metric S - Rigid - Straight	3D	
	Female Metric S - Swivel - Straight (Ball Nose)	C6	
	Female Metric S - Swivel - 45° Elbow (Ball Nose)	C7	
	Female Metric S - Swivel - 90° Elbow (Ball Nose)	C8	
	Female Metric S - Swivel - Straight (24° Cone with O-Ring)	C9	
	Female Metric S - Swivel - 45° Elbow (24° Cone with O-Ring)	0C	
	Female Metric S - Swivel - 90° Elbow (24° Cone with O-Ring)	1C	
	BSP	Male BSP Taper Pipe - Rigid - Straight	91
		Female BSP Parallel Pipe - Swivel - Straight (60° Cone)	92
Male BSP Parallel Pipe - Rigid - Straight (60° Cone)		D9	
Female BSP Parallel Pipe - Swivel - 45° Elbow (60° Cone)		B1	
Female BSP Parallel Pipe - Swivel - 90° Elbow (60° Cone)		B2	
Female BSP Parallel Pipe - Swivel - 90° Elbow Block Type (60° Cone)		B4	
Female BSP Parallel Pipe - Swivel - Straight (Flat Seat)		B5	
Male BSP Taper Pipe - Rigid - 45° Elbow		BV	
Male BSP Taper Pipe - Rigid - 90° Elbow or Side Outlet		BZ	
Fr. Gaz		Male French Gaz Series - Rigid - Straight (24° Cone)	FG
	Female French Gaz Series - Swivel - Straight (Ball Nose)	F4	
	DIN Metric Banjo - Straight	49	
	Male Standpipe - Rigid - Straight (Inch Size Tube O.D.)	34	
	Male Standpipe - Rigid - Straight with V-Notch	TW	
	Male Ferulok Flareless-Rigid-Straight (24° Cone with Nut & Ferrule)	11	
	Female Ferulok Flareless - Swivel - Straight (24° Cone)	12	
	Male Rapid Assembly, Straight	WU	
	Male Rapid Assembly, 45° Elbow	WW	
	Male Rapid Assembly, 90° Elbow	WY	
	Bulkhead w/Zerk Port Integrated	GK	
	Female A-Lok® Compression	AL	
	Female Cam & Groove	FC	
	Flange Retainer	4K	
	Specialty	Male I-Line® Sanitary	H1
Female I-Line® Sanitary		H2	
Male Sanitary Bevel Seat		H4	
Female Sanitary Bevel Seat		H5	
Sanitary Flange & Step Downs		FN	
Mini Sanitary Flange		FV	








For detailed ordering information, please consult price list or contact Parflex® Division.

# 51 Series Visual Index

<b>51 Series</b> <b>FIELD ATTACHABLE</b>	<b>201</b>	Male Taper Pipe Rigid	<b>203</b>	Male [JIC] 37°	<b>206</b>	SAE [JIC] 37° Swivel	<b>208</b>	SAE 45° Swivel	<b>239</b>	[JIC] 37° Swivel 90° Elbow
										
	E-5		E-6		E-6		E-7		E-7	

## 20151 Male Taper Pipe Rigid



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
<b>#</b>									
20151-2-3	1/8-27	3/16	5	1.71	43	1	25	7/16	5/8
20151-4-3	1/4-18	3/16	5	1.90	48	1-1/8	29	9/16	5/8
20151-2-4	1/8-27	1/4	6	1.90	48	1	25	1/2	5/8
20151-4-4	1/4-18	1/4	6	2.08	53	1-3/16	30	9/16	5/8
20151-4-5	1/4-18	5/16	8	2.17	55	1-7/16	37	9/16	3/4
20151-6-5	3/8-18	5/16	8	2.17	55	1-7/16	37	3/4	3/4
20151-4-6	1/4-18	3/8	10	2.61	66	1-7/16	37	3/4	7/8
20151-6-6	3/8-18	3/8	10	2.61	66	1-7/16	37	3/4	7/8
20151-8-6	1/2-14	3/8	10	2.80	71	1-9/16	40	7/8	7/8
20151-6-8	3/8-18	1/2	13	2.99	76	1-1/2	38	7/8	1-1/16
20151-8-8	1/2-14	1/2	13	3.17	81	1-11/16	43	7/8	1-1/16
20151-12-12	3/4-14	3/4	19	3.42	87	1-3/4	44	1-1/8	1-3/8
20151-16-16	1-11-1/2	1	25	3.74	95	2-1/4	57	1-3/8	1-9/16


Construction: Steel.  
Add "C" for Stainless Steel.

51 series field attachable couplings are not intended for use on hose that has previously been in service.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 5-1  
 F Tooling, Equipment & Accessories  
 G General Technical


A  
Hose**20351 Male (JIC) 37° - Rigid**

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
20351-4-3	7/16-20	3/16	5	1.88	48	1-1/8	29	1/2	5/8
20351-5-4	1/2-20	1/4	6	2.06	52	1-1/8	29	9/16	5/8
20351-6-5	9/16-18	5/16	8	2.16	55	1-5/16	33	5/8	3/4
20351-6-6	9/16-18	3/8	10	2.61	66	1-7/16	37	3/4	7/8
20351-8-6	3/4-16	3/8	10	2.71	69	1-7/16	37	13/16	7/8
20351-8-8	3/4-16	1/2	13	3.08	78	1-5/8	41	7/8	1-1/16

Construction: Steel.

Add "C" for Stainless Steel.

51 series field attachable couplings are not intended for use on hose that has previously been in service.

B  
TubingC  
Coiled Air Hose  
& FittingsD  
Transportation**20651 SAE (JIC) 37° Swivel**

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
#										
20651-4-3	7/16-20	3/16	5	1.99	51	1-1/4	32	9/16	9/16	5/8
20651-4-4	7/16-20	1/4	6	2.18	55	1-1/4	32	9/16	9/16	5/8
20651-5-4	1/2-20	1/4	6	2.24	57	1-7/16	37	5/8	5/8	5/8
20651-6-4	9/16-18	1/4	6	2.34	59	1-7/16	37	11/16	11/16	5/8
20651-6-5	9/16-18	5/16	8	2.37	60	1-1/2	38	11/16	11/16	3/4
20651-6-6	9/16-18	3/8	10	2.74	70	1-7/16	37	11/16	11/16	7/8
20651-8-6	3/4-16	3/8	10	2.88	73	1-5/8	41	7/8	7/8	7/8
20651-8-8	3/4-16	1/2	13	3.25	83	1-3/4	44	7/8	7/8	1-1/16
20651-10-8	7/8-14	1/2	13	3.37	86	1-7/8	48	1	1	1-1/16
20651-12-12	1-1/16-12	3/4	19	3.75	95	2-1/8	54	1-1/4	1-1/4	1-3/8
20651-16-16	1/5/16-12	1	25	3.93	100	2-7/16	62	1-1/2	1-1/2	1-9/16


Construction: Steel.

Add "C" for Stainless Steel.

E  
Fittings  
Series 51F  
Tooling, Equipment  
& AccessoriesG  
General Technical



## 20851 SAE 45° Swivel




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
#										
20851-6-6	5/8-18	3/8	10	2.82	72	1-9/16	40	3/4	3/4	7/8

Construction: Steel.  
Add "C" for Stainless Steel.

51 series field attachable couplings are not intended for use on hose that has previously been in service.

## 23951 JIC 37° Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch	inch
#												
23951-4-3	7/16-20	3/16	5	1.77	45	1	25	0.83	21	3/8	9/16	5/8
23951-6-6	9/16-18	3/8	10	2.70	69	1-7/16	37	0.85	22	9/16	11/16	7/8
23951-8-6	3/4-16	3/8	10	2.90	74	1-5/8	41	1.09	28	11/16	7/8	7/8










Construction: Steel.  
Add "C" for Stainless Steel.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 51  
 F Tooling, Equipment & Accessories  
 G General Technical


A Hose

# 54 Series Visual Index

B Tubing

<b>54 Series</b> <b>PERMANENT</b>	<b>106</b> Female SAE (JIC) 37° Swivel  E-9	<b>137</b> Female (JIC) 37° Swl, 45° Elbow  E-10	<b>139</b> Female (JIC) 37° Swl, 90° Elbow  E-10	<b>1J7</b> Female Seal-Lok™ 45° Elbow  E-9	<b>1J9</b> Female Seal-Lok™ 90° Elbow  E-9
	<b>1JC</b> Female Seal-Lok™ Str. Short O-Ring  E-8	<b>1WW</b> Male Rapid Assembly, 45° Elb.  E-10	<b>1WY</b> Male Rapid Assembly, 90° Elb.  E-11	<b>1WU</b> Male Rapid Assembly, Straight  E-11	


C Coiled Air Hose & Fittings




<b>54 Series Adapter</b> <b>PERMANENT</b>	<b>685RA</b> Female Rapid Assy. Adapter Male SAE  E-11
--	---

D Transportation

E Fittings Series 54

## 1JC54 Female Seal-Lok™ Straight Short O-Ring Face Seal ISO 12151-1 SWSA



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1JC54-4-4	9/16-18	1/4	6	1.38	35	5/8	16	11/16
1JC54-6-6	11/16-16	3/8	10	1.58	40	9/16	14	13/16


Construction: Steel.  
Add "C" for Stainless Steel

F Tooling, Equipment & Accessories

G General Technical



## 1J754 Female Seal-Lok™ 45° Elbow O-Ring Face Seal ISO 12151-1 SWE45




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1J754-4-4	9/16-18	1/4	6	2.16	55	1-3/8	35	11/16

Construction: Steel.

Add "C" for Stainless Steel.

## 1J954 Female Seal-Lok™ 90° Elbow O-Ring Face Seal Short Drop ISO 12151-1 SWE90




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J954-4-4	9/16-18	1/4	6	2.14	54	1-3/8	35	0.83	21	11/16
1J954-6-6	11/16-16	3/8	10	2.32	59	1-3/8	35	0.90	23	13/16

Construction: Steel.

Add "C" for Stainless Steel.

## 10654 Female SAE (JIC) 37° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
10654-4-4	7/16-20	1/4	6	1.75	45	1	25	9/16	9/16
10654-6-6	9/16-18	3/8	10	2.13	54	1-3/16	30	11/16	11/16


Construction: Steel.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose

### 13754 Female JIC 37° Swivel 45° Elbow




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
13754-4-4	7/16-20	1/4	6	2.08	53	1-1/4	32	.33	8	9/16

Construction: Steel.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

### 13954 Female JIC 37° Swivel 90° Elbow Short Drop




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
13954-4-4	7/16-20	1/4	6	1.97	50	1-3/16	30	.68	17	9/16
13954-6-6	9/16-18	3/8	10	2.30	59	1-5/8	41	.85	22	11/16

Construction: Steel.  
Add "C" for Stainless Steel.

D Transportation

E Fittings Series 54

### 1WW54 Male Rapid Assembly - 45° Elbow



Part Number	Stem O.D.		Hose I.D.		A		Cutoff Allow. B		E	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
#										
1WW54-4-4	1/4	6	1/4	6	1.97	50	1-3/16	30	.67	17
1WW54-6-6	3/8	10	3/8	10	2.19	56	1-3/16	30	.69	18

Construction: Brass nipple, steel plated shell, Nitrile o-ring.


NOTE: Use with mating adapter PN 685RA.

F Tooling, Equipment & Accessories

G General Technical



## 1WY54 Male Rapid Assembly - 90° Elbow




Part Number	Stem O.D.		Hose I.D.		A		Cutoff Allow. B		E	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
#										
1WY54-4-4	1/4	6	1/4	6	1.27	32	1/2	13	.90	23
1WY54-6-6	3/8	10	3/8	10	1.49	38	1/2	13	1.00	25

Construction: Brass nipple, steel plated shell, Nitrile o-ring.

NOTE: Use with mating adapter PN 685RA.

## 1WU54 Male Rapid Assembly - Straight




Part Number	Stem O.D.		Hose I.D.		A		Cutoff Allow. B	
	inch	mm	inch	mm	inch	mm	inch	mm
#								
1WU54-4-4	1/4	6	1/4	6	1.85	47	1-1/16	27
1WU54-6-6	3/8	10	3/8	10	2.13	54	1-1/8	29

Construction: Brass nipple, steel plated shell, Nitrile o-ring.

NOTE: Use with mating adapter PN 685RA.

## 685RA Adapter Female Rapid Assembly - Male SAE Straight Thread ORB






































Part Number	Tube O.D.		Thread Size	A		H Hex
	inch	mm		inch	mm	
#						
685RA-4-4	1/4	6	7/16-20	1.85	47	11/16
685RA-6-4	3/8	10	7/16-20	2.13	54	3/4
685RA-4-6	1/4	6	9/16-18	1.12	28	3/4
685RA-6-6	3/8	10	9/16-18	2.13	54	3/4










Construction: Brass nipple, Nitrile o-ring.

NOTE: Use with mating fittings 1WU54, 1WV54, 1WY54.


# 55/58 Series Visual Index




<b>A</b> Hose	<b>B</b> Tubing	<b>C</b> Coiled Air Hose & Fittings	<b>D</b> Transportation	<b>E</b> Fittings Series 55/58	<b>F</b> Tooling, Equipment & Accessories	<b>G</b> General Technical	<b>101</b> Male Taper Pipe Rigid  E-13	<b>102</b> Female Taper Pipe Rigid  E-14	<b>103</b> Male (JIC) 37°  E-14	<b>104</b> Male SAE 45°  E-15	<b>105</b> Male Str. Thread O-Ring  E-16
							<b>106</b> SAE (JIC) 37° Swivel  E-17	<b>107</b> Female Pipe Swivel  E-18	<b>108</b> Female SAE 45° Swivel  E-18	<b>111</b> Ferrul-Fix  E-19	<b>112</b> SAE Flareless Swivel  E-19
<b>113</b> Male Pipe Swivel  E-20	<b>11D</b> Standpipe Light METRIC  E-34	<b>11L</b> Male Pipe Swivel 90° Elbow  E-20	<b>137</b> FM JIC 37° Swivel 45° Elbow  E-21	<b>139</b> FM JIC 37° Swivel 90° Elbow  E-22							
<b>13D</b> Standpipe Heavy METRIC  E-35	<b>13E</b> Male (JIC) 37° Long  E-15	<b>141</b> FM JIC 37° Swivel 90° Lg Elbow  E-23	<b>155</b> Hose Splicer  E-24	<b>167</b> SAE Male Inverted 45° Elbow  E-24							
<b>169</b> SAE Male Inverted 90° Elbow  E : 25	<b>192</b> Female BSP Pipe Swivel - Str. (60° Cone)  E : 35	<b>1AL</b> A-Lok® Compression  E : 29	<b>1B1</b> Female BSP Pipe Swivel 45° Elb. (60° Cone)  E : 36	<b>1B2</b> Female BSP Pipe Swivel 90° Elb. (60° Cone)  E : 36							
<b>1C6</b> Female Swivel DIN 20078 HW w/o O-Ring METRIC  E-32	<b>1C9</b> Female Swivel DIN 20078 HW O-Ring METRIC  E-32	<b>1D0</b> Male Stud DIN 20078 Light METRIC  E-33	<b>1D2</b> Male Stud DIN 20078 Heavy METRIC  E-33	<b>1D9</b> Male BSPP METRIC  E-34							
<b>1FU</b> (JIS)/BSP 30° Flare Female Swivel  E-30	<b>1G1</b> (JIS)/BSP 60° Cone FM Swivel 45° Elb.  E-31	<b>1G2</b> (JIS)/BSP 60° Cone FM Swivel 90° Elb.  E-31	<b>1GU</b> (JIS)/BSP 60° Cone Female Swivel  E-30	<b>1J0</b> Male Seal-Lok™ Rigid Str. w/O-Ring  E-26							



<b>55/58 Series</b>  <b>PERMANENT</b>	<b>1J1</b>	Female Seal-Lok™ 90° Elbow Long	<b>1J7</b>	Female Seal-Lok™ 45° Elbow	<b>1J9</b>	Female Seal-Lok™ 90° Elbow	<b>1JC</b>	Female Seal-Lok™ Straight Short	<b>1JS</b>	Female Seal-Lok™ Straight
										
	E-27		E-27		E-28		E-26		E-25	
<b>1L9</b>	FM JIC 37° Swivel 90° Elbow, SPL Drop	<b>1MU</b>	(JIS) Metric 30° Flare Female Swivel	<b>1TU</b>	Universal Tube Stub End	<b>1UT</b>	Male (JIS)/BSPT			
										
E-23		E-30		E-28		E-29				

## 10155/10158 Male Taper Pipe Rigid



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
#	#								
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch
10155-2-3	—	1/8-27	3/16	5	1.94	49	1	25	9/16
10155-2-4	10158-2-4	1/8-27	1/4	6	2.13	54	1	25	5/8
10155-4-3	—	1/4-18	3/16	5	2.12	54	1-3/16	30	11/16
10155-4-4	10158-4-4	1/4-18	1/4	6	2.31	59	1-3/16	30	11/16
10155-4-5	—	1/4-18	5/16	8	2.37	60	1-3/16	30	11/16
10155-4-6	10158-4-6	1/4-18	3/8	10	2.66	68	1-5/16	33	3/4
10155-6-3	—	3/8-18	3/16	5	2.21	56	1-3/16	30	3/4
10155-6-4	10158-6-4	3/8-18	1/4	6	2.41	61	1-5/16	33	3/4
10155-6-5	—	3/8-18	5/16	8	2.47	63	1-5/16	33	3/4
10155-6-6	10158-6-6	3/8-18	3/8	10	2.66	68	1-5/16	33	3/4
10155-6-8	10158-6-8	3/8-18	1/2	13	2.85	72	1-5/16	33	7/8
10155-8-6	10158-8-6	1/2-14	3/8	10	2.91	74	1-9/16	40	15/16
10155-8-8	10158-8-8	1/2-14	1/2	13	3.09	78	1-9/16	40	15/16
10155-8-10	10158-8-10	1/2-14	5/8	16	3.20	81	1-1/2	38	1
10155-12-10	—	3/4-14	5/8	16	3.20	81	1-1/2	38	1-1/8
10155-12-12	10158-12-12	3/4-14	3/4	19	3.29	84	1-9/16	40	1-1/8
10155-16-16	10158-16-16	1-11-1/2	1	1	3.97	101	1-3/4	44	1-3/8

Construction: Steel.

Add "B" for Brass.

Add "C" for Stainless Steel.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

# 10255/10258 Female Taper Pipe Rigid




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	inch
#	#								
55 Series	58 Series								
10255-4-4	10258-4-4	1/4-18	1/4	6	2.39	61	1-1/4	32	3/4
10255-6-4	—	3/8-18	1/4	6	2.60	66	1-1/2	38	7/8
10255-6-6	10258-6-6	3/8-18	3/8	10	2.84	72	1-1/2	38	7/8
10255-8-6	—	1/2-14	3/8	10	2.87	73	1-3/8	35	1-1/16
10255-8-8	10258-8-8	1/2-14	1/2	13	2.87	73	1-3/8	35	1-1/16

Construction: Steel.  
 Add "B" for Brass.  
 Add "C" for Stainless Steel.

B  
Tubing

C  
Coiled Air Hose & Fittings

# 10355/10358 Male (JIC) 37° - Rigid



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	inch
#	#								
55 Series	58 Series								
10355-4-3	—	7/16-20	3/16	5	2.17	55	1-3/16	30	9/16
10355-4-4	10358-4-4	7/16-20	1/4	6	2.31	58	1-3/16	30	5/8
10355-5-4	—	1/2-20	1/4	6	2.30	58	1-3/16	30	5/8
10355-5-5	—	1/2-20	5/16	8	2.30	58	1-3/16	30	5/8
10355-6-4	—	9/16-18	1/4	6	2.30	58	1-3/16	30	11/16
10355-6-5	—	9/16-18	5/16	8	2.30	58	1-3/16	30	11/16
10355-6-6	10358-6-6	9/16-18	3/8	10	2.65	67	1-1/4	32	3/4
10355-8-6	10358-8-6	3/4-16	3/8	10	2.68	68	1-3/8	35	13/16
10355-8-8	10358-8-8	3/4-16	1/2	13	2.87	73	1-3/8	35	7/8
10355-8-10	10358-8-10	3/4-16	5/8	16	3.10	79	1-7/16	36	1
10355-10-8	10358-10-8	7/8-14	1/2	13	3.03	77	1-9/16	40	15/16
—	10358-10-10	7/8-14	5/8	16	3.20	81	1-9/16	40	1
10355-12-10	10358-12-10	1-1/16-12	5/8	16	3.31	84	1-5/8	41	1-1/8
10355-12-12	10358-12-12	1-1/16-12	3/4	19	3.32	84	1-11/16	43	1-1/8
10355-16-16	10358-16-16	1-5/16-12	1	25	3.93	100	1-3/4	44	1-3/8

Construction: Steel.  
 Add "B" for Brass.  
 Add "C" for Stainless Steel.

D  
Transportation


E  
Fittings Series 55/58

F  
Tooling, Equipment & Accessories

G  
General Technical



## 13E55/13E58 Male (JIC) 37° Long



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	inch
#	#								
55 Series	58 Series								
13E55-4-4	—	7/16-20	1/4	6	2.93	74	1-13/16	46	5/8
13E55-6-6	—	9/16-18	3/8	10	3.38	86	2	51	3/4
13E55-8-8	—	3/4-16	1/2	13	3.72	95	2-1/8	54	7/8


Construction: Steel.

Add "B" for Brass.

Add "C" for Stainless Steel.

**NOTE:** Bulkhead Locknut sold separately. WLN Locknuts are Manufactured by the Tube Fittings Division. Refer to Catalog 4300 for additional information.

## 10455/10458 Male SAE 45° - Rigid



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	inch
#	#								
55 Series	58 Series								
10455-4-3	—	7/16-20	3/16	5	2.06	52	1-1/8	29	9/16
10455-5-4	—	1/2-20	1/4	6	2.34	59	1-1/8	29	5/8
10455-6-5	—	5/8-18	5/16	8	2.55	65	1-1/4	32	3/4
10455-6-6	10458-6-6	5/8-18	3/8	10	2.74	70	1-1/4	32	3/4
10455-6-8	—	5/8-18	1/2	13	2.90	74	1-1/4	32	7/8
10455-8-8	10458-8-8	3/4-16	1/2	13	3.04	77	1-3/8	35	7/8
10455-12-12	10458-12-12	1-1/16-14	3/4	19	3.54	90	1-11/16	43	1-1/4


Construction: Steel.

Add "B" for Brass.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose**10555/10558 Male Straight Thread O-Ring (BUNA N O-Ring included)**

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	inch
#	#								
55 Series	58 Series								
10555-4-3	—	7/16-20	3/16	4	1.98	50	1-1/8	29	9/16
10555-4-4	—	7/16-20	1/4	6	2.11	54	1	25	5/8
10555-4-5	—	7/16-20	5/16	8	2.11	54	1	25	5/8
10555-5-4	10558-5-4	1/2-20	3/8	10	2.11	54	1	25	5/8
10555-5-5	—	1/2-20	5/16	8	2.11	54	1	25	5/8
10555-6-3	—	9/16-18	3/8	10	1.89	48	1	25	11/16
10555-6-4	10558-6-4	9/16-18	3/8	10	2.14	54	1	25	11/16
10555-6-6	10558-6-6	9/16-18	3/8	10	2.42	61	1-1/8	29	3/4
10555-8-6	—	3/4-16	1/2	13	2.46	62	1-1/8	29	7/8
10555-8-8	10558-8-8	3/4-16	1/2	13	2.65	67	1-3/16	30	7/8
10555-10-8	10558-10-8	7/8-14	5/8	16	2.77	70	1-5/16	33	1


Construction: Steel.

Add "B" for Brass.

Add "C" for Stainless Steel.

B  
TubingC  
Coiled Air Hose  
& FittingsD  
TransportationE  
Fittings  
Series 55/58F  
Tooling, Equipment  
& AccessoriesG  
General Technical

# 10655/10658 SAE (JIC) 37° Swivel



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	inch
10655-3-3	—	3/8-24	3/16	5	2.23	57	1-5/16	33	9/16	9/16
10655-4-3	—	7/16-20	3/16	5	2.23	57	1-1/4	32	9/16	9/16
10655-5-3	—	1/2-20	3/16	5	2.24	57	1-1/4	32	9/16	5/8
10655-4-4	10658-4-4	7/16-20	1/4	6	2.36	60	1-3/16	30	5/8	9/16
10655-5-4	10658-5-4	1/2-20	1/4	6	2.43	62	1-1/4	32	5/8	5/8
10655-6-4	10658-6-4	9/16-18	1/4	6	2.45	62	1-5/16	33	5/8	11/16
10655-5-5	10658-5-5	1/2-20	5/16	8	2.46	62	1-1/4	32	5/8	5/8
10655-6-5	10658-6-5	9/16-18	5/16	8	2.48	63	1-1/4	32	5/8	11/16
10655-6-6	10658-6-6	9/16-18	3/8	10	2.70	69	1-5/16	33	11/16	11/16
10655-8-6	10658-8-6	3/4-16	3/8	10	2.89	73	1-1/2	38	11/16	7/8
10655-6-8	10658-6-8	9/16-18	1/2	13	2.96	75	1-3/8	35	7/8	11/16
10655-8-8	10658-8-8	3/4-16	1/2	13	3.08	78	1-1/2	38	7/8	7/8
10655-8-10	10658-8-10	3/4-16	5/8	16	3.30	84	1-5/8	41	1	15/16
10655-10-8	10658-10-8	7/8-14	1/2	13	3.12	79	1-5/8	41	7/8	1-1/16
10655-12-8	10658-12-8	1-1/16-12	1/2	13	3.21	82	1-3/4	44	1	1-1/4
10655-10-10	10658-10-10	7/8-14	5/8	16	3.30	84	1-5/8	41	1	1-1/16
10655-12-10	10658-12-10	1-1/16-12	5/8	16	3.40	86	1-3/4	44	1-1/8	1-5/16
10655-10-12	10658-10-12	7/8-14	3/4	19	3.36	85	1-11/16	43	1-1/8	1-1/16
10655-12-12	10658-12-12	1-1/16-12	3/4	19	3.40	86	1-3/4	44	1-1/8	1-1/4
—	10658-16-12	1-5/16-12	3/4	19	3.55	90	1-13/16	46	1-3/8	1-1/2
10655-16-16	10658-16-16	1-5/16-12	1	25	4.02	102	1-3/4	44	1-3/8	1-1/2

Construction: Steel.

Add "B" for Brass.

Add "C" for Stainless Steel.

NOTE: Sizes -4, -5, -8 and -10 incorporate a dual seat.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



E-17

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation


E  
Fittings  
Series 55/58

F  
Tooling, Equipment  
& Accessories

G  
General Technical

A Hose

# 10755/10758 Female Pipe Swivel



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#	#									
55 Series	58 Series									
10755-4-4	10758-4-4	1/4-18	1/4	6	2.43	62	1-1/4	32	5/8	11/16
10755-4-5	—	1/4-18	5/16	8	2.39	61	1-3/16	30	11/16	11/16
10755-6-6	10758-6-6	3/8-18	3/8	10	2.61	66	1-3/16	30	11/16	7/8
10755-8-8	10758-8-8	1/2-14	1/2	13	2.93	74	1-5/16	33	7/8	1
—	10758-12-12	3/4-14	3/4	19	3.48	88	1-3/4	44	1-1/8	1-1/4
10755-16-16	10758-16-16	1-11-1/2	1	25	4.00	102	1-13/16	46	1-3/8	1-1/2

Construction: Steel.

Add "B" for Brass.


Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

# 10855/10858 Female SAE 45° Swivel



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#	#									
55 Series	58 Series									
10855-6-4	—	5/8-18	1/4	6	2.55	65	1-3/8	35	5/8	3/4
10855-6-5	—	5/8-18	5/16	8	2.61	66	1-3/8	35	5/8	3/4
10855-6-6	10858-6-6	5/8-18	3/8	10	2.75	70	1-5/16	33	3/4	3/4
10855-12-12	10858-12-12	1-1/16-14	3/4	19	3.40	86	1-11/16	43	1-1/8	1-1/4

Construction: Steel.

Add "B" for Brass.

Add "C" for Stainless Steel.

E Fittings Series 55/58


F Tooling, Equipment & Accessories

G General Technical





## 11155/11158 Ferrul-Fix (Nut and Sleeve included)



Part Number	Part Number	Thread Size	Tube O.D.		Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
11155-6-4	—	9/16-18	3/8	10	1/4	6	2.34	59	1-1/8	32	11/16	11/16
11155-6-6	—	9/16-18	3/8	10	3/8	10	2.53	64	1-1/8	32	3/4	11/16
11155-8-6	—	3/4-16	1/2	13	3/8	10	2.63	67	1-5/16	33	7/8	7/8

Construction: Steel.


Add "C" for Stainless Steel.

"Ferrul-Fix" affords salvaging of bent tube section of combination tube-hose assemblies and quick, easy repair on the job. See page G-29 for Ferrule-Fix installation instructions.

**NOTE:** Nut Part Number is 111-size.  
Sleeve Part Number is 110-size.

Nut and Sleeve are Manufactured by the Tube Fittings Division. Refer to Catalog 4300 for additional information.

## 11255/11258 SAE Flareless Swivel



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	inch
11255-6-4	—	9/16-18	1/4	6	2.62	67	1-1/2	38	11/16	3/4
11255-6-6	—	9/16-18	3/8	10	2.82	72	1-1/2	38	3/4	3/4
11255-8-6	—	3/4-16	3/8	10	2.92	74	1-5/8	41	7/8	15/16

Construction: Steel.


Add "B" for Brass.

Add "C" for Stainless Steel.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

# 11355/11358 Male Pipe Swivel\*



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	inch
11355-4-3	—	1/4-18	3/16	5	2.72	69	1-3/4	44	5/8	11/16
11355-4-4	11358-4-4	1/4-18	1/4	6	2.84	72	1-3/4	44	5/8	11/16
11355-4-5	—	1/4-18	5/16	8	2.84	72	1-3/4	44	5/8	11/16
11355-6-6	11358-6-6	3/8-18	3/8	10	3.12	79	1-13/16	46	3/4	3/4
11355-8-6	—	1/2-14	3/8	10	3.37	86	2-1/16	52	3/4	15/16
11355-8-8	11358-8-8	1/2-14	1/2	13	3.56	90	2-1/16	52	7/8	15/16
11355-12-12	11358-12-12	3/4-14	3/4	19	3.81	97	2-1/8	54	1-1/8	1-1/8
11355-16-16	11358-16-16	1-11-1/2	1	25	5.06	129	2-13/16	71	1-1/2	1-1/2

Construction: Steel.

Add "C" for Stainless Steel.

**NOTE:** \*For use with petroleum based fluids.

**WARNING:** Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling. Not recommended for use in CNG applications.


B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings Series 55/58

# 11L55/11L58 Male Pipe Swivel 90° Elbow\*



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	inch
11L55-4-4	—	1/4-18	1/4	6	1.94	49	13/16	21	11/16	11/16

Construction: Steel.

Add "C" for Stainless Steel.

\*For use with petroleum based fluids.

**NOTE:** Use crimp Die Ring 80C-R1L with Parkrimp 1 Machine; crimp Die Ring 82C-R1L with KarryKrimp or Minikrimp.



**WARNING:** Fittings allow minor movement under pressure to relieve stress on hose but are not recommended for continued or extensive swiveling. Fittings not recommended for use in CNG applications.

F Tooling, Equipment & Accessories

G General Technical



# 13755/13758 Female JIC 37° Swivel 45° Elbow



\*13755-6-6, 13755-8-6, 13755-8-8 and 13758-8-8

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series											
13755-4-3	—	7/16-20	3/16	5	2.49	63	1-1/2	38	0.33	8	9/16	9/16
13755-4-4	13758-4-4	7/16-20	1/4	6	2.49	63	1-1/2	38	0.33	8	5/8	9/16
13755-5-4	—	1/2-20	1/4	6	2.49	63	1-1/2	38	0.36	9	5/8	5/8
13755-6-5	—	9/16-18	5/16	8	2.73	69	1-9/16	40	0.39	10	5/8	11/16
13755-6-6*	13758-6-6	9/16-18	3/8	10	2.91	74	1-9/16	40	0.39	10	3/4	11/16
13755-8-6*	13758-8-6	3/4-16	3/8	10	3.18	81	1-13/16	46	0.55	14	3/4	7/8
13755-8-8*	13758-8-8*	3/4-16	1/2	13	3.37	86	1-13/16	46	0.55	14	7/8	7/8
13755-10-8	13758-10-8	7/8-14	1/2	13	3.42	87	1-7/8	48	0.63	16	7/8	1
—	13758-10-10	7/8-14	5/8	16	3.44	87	1-3/4	44	0.64	16	1-1/16	1
13755-12-12	13758-12-12	1-1/16-12	3/4	19	4.05	103	2-3/8	60	0.78	20	1-1/8	1-1/4
13755-16-16	13758-16-16	1-5/16-12	1	25	4.57	116	2-5/16	59	0.89	23	1-3/8	1-1/2

Construction: Steel.

Add "C" for Stainless Steel.

NOTE: \*Part number 13755-6-6, 13755-8-6, 13755-8-8 and 13758-8-8 do not have a "H" hex.

A  
Hose

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

E  
Fittings Series 55/58

F  
Tooling, Equipment & Accessories



G  
General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



A  
Hose

# 13955/13958 Female JIC 37° Swivel 90° Elbow Short Drop



\*13955-6-6, 13955-8-6, 13955-8-8 and 13958-8-8

B  
Tubing

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series											
13955-4-3	—	7/16-20	3/16	5	2.49	63	1-3/8	35	0.68	17	9/16	9/16
13955-4-4	13958-4-4	7/16-20	1/4	6	2.49	63	1-3/8	35	0.68	17	5/8	9/16
13955-5-4	—	1/2-20	1/4	6	2.49	63	1-9/16	40	0.77	20	5/8	5/8
13955-6-4	—	9/16-18	1/4	6	2.57	65	1-9/16	36	0.85	22	5/8	11/16
13955-6-5	—	9/16-18	5/16	8	2.73	69	1-1/2	38	0.85	22	5/8	11/16
13955-6-6*	13958-6-6	9/16-18	3/8	10	2.91	74	1-1/2	38	0.91	23	11/16	11/16
13955-8-6*	13958-8-6	3/4-16	3/8	10	3.18	81	1-9/16	40	1.14	29	3/4	7/8
13955-8-8*	13958-8-8*	3/4-16	1/2	13	3.37	86	1-5/8	41	1.09	28	7/8	7/8
13955-10-8	13958-10-8	7/8-14	1/2	13	3.42	87	1-3/4	44	1.23	31	7/8	1
—	13958-10-10	7/8-14	5/8	16	3.28	83	1-5/8	41	1.23	31	1-1/16	1
13955-12-12	13958-12-12	1-1/16-12	3/4	19	4.05	103	2-1/4	57	1.81	46	1-1/8	1-1/4
13955-16-16	13958-16-16	1-5/16-12	1	25	4.57	116	2-9/16	65	2.14	54	1-3/8	1-1/2

Construction: Steel.

Add "C" for Stainless Steel.

NOTE: \*Part number 13955-6-6, 13955-8-6, 13955-8-8 and 13958-8-8 do not have a "H" hex.

C  
Coiled Air Hose & Fittings

D  
Transportation



E  
Fittings Series 55/58

F  
Tooling, Equipment & Accessories

G  
General Technical



# 14155/14158 Female JIC 37° Swivel 90° Elbow Long Drop





\*14155-6-6, 14155-8-6, 14155-8-8 and 14158-8-8

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
14155-4-3	—	7/16-20	3/16	5	2.37	60	1-3/8	35	1.80	46	9/16	9/16
14155-4-4	—	7/16-20	1/4	6	2.57	65	1-7/16	36	1.80	46	5/8	9/16
14155-5-4	—	1/2-20	1/4	6	2.51	64	1-3/8	35	1.80	46	5/8	5/8
14155-6-5	—	9/16-18	5/16	8	2.73	69	1-9/16	40	2.18	55	5/8	11/16
14155-6-6*	14158-6-6	9/16-18	3/8	10	2.92	74	1-9/16	40	2.13	54	11/16	11/16
14155-8-6*	14158-8-6	3/4-16	3/8	10	3.00	76	1-5/8	41	2.52	64	3/4	7/8
14155-8-8*	14158-8-8*	3/4-16	1/2	13	3.18	81	1-5/8	41	2.43	62	7/8	7/8
14155-10-8	14158-10-8	7/8-14	1/2	13	3.39	86	1-13/16	46	2.57	65	7/8	1
14155-12-12	14158-12-12	1-1/16-12	3/4	19	3.91	99	2-3/16	56	3.73	95	1-1/8	1-1/4
14155-16-16	14158-16-16	1-5/16-12	1	25	4.62	117	2-3/8	60	4.33	110	1-3/8	1-1/2

Construction: Steel. Add "C" for Stainless Steel.

NOTE: \*Part number 14155-6-6, 14155-8-6, 14155-8-8 and 14158-8-8 do not have a "H" hex.

# 1L955/1L958 Female JIC 37° Swivel 90° Elbow Special Drop



\*1L955-6-6, 1L955-8-6, 1L955-8-8 and 1L958-8-8

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1L955-4-3	—	7/16-20	3/16	5	2.31	59	1-3/8	35	0.88	22	9/16	9/16
1L955-4-4	—	7/16-20	1/4	6	2.47	63	1-3/8	35	0.88	22	5/8	9/16
1L955-5-4	—	1/2-20	1/4	6	2.53	64	1-7/16	36	0.88	22	5/8	5/8
1L955-6-5	—	9/16-18	5/16	8	2.69	68	1-1/2	38	1.12	28	5/8	11/16
1L955-6-6*	1L958-6-6	9/16-18	3/8	10	2.88	73	1-7/16	36	1.50	38	11/16	11/16
1L955-8-6*	1L958-8-6	3/4-16	3/8	10	3.00	76	1-5/8	41	1.61	41	3/4	7/8
1L955-8-8*	1L958-8-8*	3/4-16	1/2	13	3.19	81	1-5/8	41	1.38	35	7/8	7/8
1L955-10-8	1L958-10-8	7/8-14	1/2	13	3.68	93	2-1/8	54	1.75	44	7/8	1
1L955-12-12	1L958-12-12	1-1/16-12	3/4	19	4.29	109	2-1/2	64	2.06	52	1-1/8	1-1/4
1L955-16-16	1L958-16-16	1-5/16-12	1	25	5.14	131	2-3/4	70	2.50	64	1-3/8	1-1/2

Construction: Steel. Add "C" for Stainless Steel.

NOTE: \*Part number 1L955-6-6, 1L955-8-6, 1L955-8-8 and 1L958-8-8 do not have a "H" hex.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

# 15555/15558 Hose Splicer



55 Series	58 Series	Hose I.D.		A		W Hex
#	#	⊙				⬡
Part Number	Part Number	inch	mm	inch	mm	inch
15555-4-4	15558-4-4	1/4	6	3.25	83	11/16
15555-5-5	15558-5-5	5/16	8	3.25	83	3/4
15555-6-6	15558-6-6	3/8	10	3.62	92	13/16
15555-8-8	15558-8-8	1/2	13	4.00	102	1
15555-12-12	15558-12-12	3/4	19	4.50	114	1-5/16
15555-16-16	15558-16-16	1	25	5.54	141	1-9/16


Construction: Steel

B Tubing

C Coiled Air Hose & Fittings

D Transportation

# 16755/16758 SAE Male Inverted Swivel 45° Elbow



55 Series	58 Series	Thread Size	Tube O.D.		Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#	#	⌘	⊙		⊙								⬡	⬡
Part Number	Part Number		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
16755-6-6	—	5/8-18	3/8	10	3/8	10	3.48	88	2-1/8	54	0.94	24	3/4	5/8

Construction: Steel.

Add "C" for Stainless Steel.

E Fittings Series 55/58


F Tooling, Equipment & Accessories

G General Technical





## 16955/16958 SAE Male Inverted Swivel 90° Elbow




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
16955-6-6	—	5/8-18	3/8	10	3.48	88	1-3/4	27	1.69	43	3/4	5/8

Construction: Steel.

Add "C" for Stainless Steel.

## 1JS55/1JS58 Female Seal-Lok™ Straight ISO 12151-1-SWSB



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	inch
1JS55-4-3	—	9/16-18	3/16	5	2.23	57	1-1/4	32	9/16	11/16
1JS55-4-4	—	9/16-18	1/4	6	2.42	61	1-1/4	32	5/8	11/16
1JS55-6-4	—	11/16-16	1/4	6	2.48	63	1-1/4	32	11/16	13/16
1JS55-6-5	—	11/16-16	5/16	8	2.54	65	1-5/16	33	11/16	13/16
1JS55-6-6	1JS58-6-6	11/16-16	3/8	10	2.73	69	1-5/16	33	11/16	13/16
1JS55-8-6	—	13/16-16	3/8	10	3.00	76	1-5/8	41	7/8	15/16
1JS55-8-8	1JS58-8-8	13/16-16	1/2	13	3.20	81	1-5/8	41	7/8	15/16
1JS55-10-10	1JS58-10-10	1-14	5/8	16	3.53	90	1-7/8	48	1-1/8	1-1/8
1JS55-12-12	1JS58-12-12	1-3/16-12	3/4	19	3.75	95	2	51	1-1/4	1-3/8

Construction: Steel.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



A  
Hose

# 1JC55/1JC58 Female Seal-Lok™ Straight - Swivel - Short

## ISO 12151-1-SWSA

B  
Tubing

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch (mm)	inch (mm)
#	#									
55 Series	58 Series									
1JC55-4-3	—	9/16-18	3/16	5	1.88	48	15/16	24	9/16	11/16
1JC55-4-4	1JC58-4-4	9/16-18	1/4	6	2.16	55	1-1/16	25	5/8	11/16
1JC55-6-4	1JC58-6-4	11/16-16	1/4	6	2.22	56	1-1/16	27	11/16	13/16
1JC55-4-5	1JC58-4-5	9/16-18	5/16	8	2.22	56	1	27	5/8	11/16
1JC55-6-5	1JC58-6-5	11/16-16	5/16	8	2.28	58	1-1/16	27	11/16	13/16
1JC55-6-6	1JC58-6-6	11/16-16	3/8	10	2.47	63	1-1/16	27	11/16	13/16
1JC55-6-6-SM	1JC58-6-6-SM	11/16-16	3/8	10	2.47	63	1-1/16	27	(19)	(22)
1JC55-8-6	1JC58-8-6	13/16-16	3/8	10	2.56	65	1-3/16	30	7/8	15/16
1JC55-8-6-SM	1JC58-8-6-SM	13/16-16	3/8	10	2.56	65	1-3/16	30	(24)	(24)
1JC55-8-8	1JC58-8-8	13/16-16	1/2	13	2.75	70	1-3/16	30	7/8	15/16
1JC55-10-8	1JC58-10-8	1-14	1/2	13	2.95	75	1-3/8	35	1-1/8	1-1/8
—	1JC58-10-10	1-14	5/8	16	3.05	77	1-3/8	35	1-1/8	1-1/8
1JC55-10-12	1JC58-10-12	1-14	3/4	19	3.15	80	1-3/8	35	1-1/8	1-1/8
1JC55-12-8	—	1-3/16-12	1/2	13	3.00	76	1-7/16	36	1-1/4	1-3/8
1JC55-12-10	1JC58-12-10	1-3/16-12	5/8	16	3.10	79	1-7/16	36	1-1/4	1-3/8
1JC55-12-12	1JC58-12-12	1-3/16-12	3/4	19	3.20	81	1-7/16	36	1-1/4	1-3/8
1JC55-16-16	1JC58-16-16	1-7/16-12	1	25	3.74	95	1-1/2	38	1-1/2	1-5/8
—	1JC58-20-16	1-11/16-12	1	25	3.78	96	1-9/16	40	1-5/8	1-3/8


Construction: Steel.

Add "C" for Stainless Steel.

C  
Coiled Air Hose  
& FittingsD  
TransportationE  
Fittings  
Series 55/58

# 1J055/1J058 Male Seal-Lok™ Rigid Straight (with Buna N O-Ring)

## ISO 12151-1-S





Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	inch (mm)
#	#								
55 Series	58 Series								
1J055-4-4	—	9/16-18	1/4	6	2.20	56	1-1/16	27	5/8
1J055-4-4-SM	—	9/16-18	1/4	6	2.20	56	1-1/16	27	(19)
1J055-6-6	1J058-6-6	11/16-16	3/8	10	2.53	63	1-1/8	29	3/4
1J055-6-6-SM	1J058-6-6-SM	11/16-16	3/8	10	2.47	63	1-1/8	29	(19)
1J055-8-6	—	13/16-16	3/8	10	2.56	65	1-1/4	32	7/8
1J055-8-6-SM	—	13/16-16	3/8	10	2.56	65	1-1/4	32	(24)
1J055-8-8	1J058-8-8	13/16-16	1/2	13	2.75	70	1-1/4	32	15/16
1J055-8-8-SM	1J058-8-8-SM	13/16-16	1/2	13	2.75	70	1-1/4	32	(24)

Construction: Steel.

Add "C" for Stainless Steel.

F  
Tooling, Equipment  
& AccessoriesG  
General Technical

# 1J155/1J158 Female Seal-Lok™ Swivel 90° Elbow Long Drop ISO 12151-1-SWEL90



\*1J155-6-6, 1J155-8-6, 1J155-8-8 and 1J158-8-8



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1J155-4-3	—	9/16-18	3/16	5	2.30	58	1-5/16	33	1.80	46	9/16	11/16
1J155-4-4	—	9/16-18	1/4	6	2.45	62	1-5/16	46	1.80	46	9/16	11/16
1J155-6-6*	1J158-6-6	11/16-16	3/8	10	2.94	75	1-3/4	44	2.13	54	11/16	13/16
1J155-8-6*	—	13/16-16	3/8	10	2.94	75	1-5/8	41	2.52	64	3/4	15/16
1J155-8-8*	1J158-8-8*	13/16-16	1/2	13	3.21	82	1-11/16	43	2.52	64	7/8	15/16
—	1J158-10-10	1-14	5/8	16	3.35	85	1-11/16	43	2.76	70	1-1/16	1-1/8
1J155-12-12	1J158-12-12	1-3/16-12	3/4	19	3.86	98	2-1/8	54	3.78	96	1-1/8	1-3/8
1J155-16-16	1J158-16-16	1-7/16-12	1	25	4.42	112	2-3/8	60	4.50	114	1-3/8	1-5/8

Construction: Steel.

Add "C" for Stainless Steel.

NOTE: \*Part number 1J155-6-6, 1J155-8-6, 1J155-8-8 and 1J158-8-8 do not have a "H" hex.

# 1J755/1J758 Female Seal-Lok™ Swivel 45° Elbow ISO 12151-1-SWE45



\*1J755-6-6, 1J755-8-6, 1J755-8-8 and 1J758-8-88

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1J755-4-4	1J758-4-4	9/16-18	1/4	6	2.66	68	1-1/2	38	0.41	10	5/8	11/16
1J755-6-4	—	11/16-16	1/4	6	2.74	70	1-5/8	41	0.43	11	5/8	13/16
1J755-6-6*	1J758-6-6	11/16-16	3/8	10	2.98	76	1-5/8	43	0.43	11	3/4	13/16
1J755-8-6*	—	13/16-16	3/8	10	3.23	82	1-7/8	48	0.59	15	3/4	15/16
1J755-8-8*	1J758-8-8*	13/16-16	1/2	13	3.43	87	1-15/16	49	0.59	15	7/8	15/16
—	1J758-10-10	1-14	5/8	16	3.56	90	1-7/8	48	0.65	17	1-1/16	1
1J755-12-12	1J758-12-12	1-3/16-12	3/4	19	3.67	93	2	51	0.81	21	1-1/8	1-3/8
1J755-16-16	1J758-16-16	1-7/16-12	1	25	5.10	130	2-7/8	73	0.94	24	1-3/8	1-5/8

Construction: Steel.

Add "C" for Stainless Steel.

NOTE: \*Part number 1J755-6-6, 1J755-8-6, 1J755-8-8 and 1J758-8-8 do not have a "H" hex.



For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

# 1J955/1J958 Female Seal-Lok™ Swivel 90° Elbow Short Drop ISO 12151-1-SWES90



\*1J955-6-6, 1J958-8-6 and 1J958-8-8

B  
Tubing

Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series											
1J955-4-4	—	9/16-18	1/4	6	2.49	63	1-3/8	35	0.82	21	5/8	11/16
1J955-6-4	—	11/16-16	1/4	6	2.59	66	1-7/16	36	0.90	23	5/8	13/16
1J955-6-5	—	11/16-16	5/16	8	2.66	68	1-1/2	38	0.90	23	5/8	13/16
1J955-6-6*	1J958-6-6	11/16-16	3/8	10	2.85	72	1-1/2	38	0.91	23	3/4	13/16
1J955-8-6*		13/16-16	1/2	13	3.15	80	1-5/8	41	1.14	29	3/4	15/16
—	1J958-8-8*	13/16-16	1/2	13	3.15	80	1-5/8	41	1.14	29	7/8	15/16
—	1J958-10-10	1-14	5/8	16	3.26	83	1-5/8	41	1.27	32	1-1/16	1
1J955-12-12	1J958-12-12	1-3/16-12	3/4	19	3.82	89	2-1/8	54	1.85	47	1-3/8	1-3/8
1J955-16-16	1J958-16-16	1-7/16-12	1	25	5.03	128	2-15/16	75	2.21	56	1-3/8	1-5/8

Construction: Steel.


Add "C" for Stainless Steel.

NOTE: \*Part number 1J955-6-6, 1J958-8-6 and 1J958-8-8 does not have a "H" hex.

C  
Coiled Air Hose & Fittings

D  
Transportation

# 1TU55/1TU58 Universal Inch Tube Stub End



Part Number	Part Number	Diameter R	Hose I.D.		A		Cutoff Allow. B		C		H Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch
#	#										
55 Series	58 Series										
1TU55-4-4	1TU58-4-4	1/4	1/4	6	2.60	66	1-1/2	38	0.72	18	5/8
1TU55-6-6	1TU58-6-6	3/8	3/8	10	2.91	74	1-1/2	38	0.78	20	3/4
1TU55-8-8	1TU58-8-8	1/2	1/2	13	3.35	85	1-13/16	46	1.03	26	7/8
1TU55-12-12	1TU58-12-12	3/4	3/4	19	3.66	93	1-15/16	49	1.03	26	1-1/8
1TU55-16-16	1TU58-16-16	1	1	25	4.41	112	2-3/16	56	1.29	33	1-3/8

Construction: Steel.

Add "C" for Stainless Steel.


NOTE: Use with A-Lok & CPI nuts, sleeves and adapters. These components are manufactured by Parker's Instrumentation Connectors Division. Refer to catalogs 4230 & 4233 for additional information.

F  
Tooling, Equipment & Accessories

G  
General Technical



# 1AL55/1AL58 A-LOK® Compression (With Nut and Ferrule)




Part Number	Part Number	Thread Size	Tube O.D.		Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#	#											
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
1AL55-4-4	1AL58-4-4	7/16-20	1/4	6	1/4	6	2.16	55	11/16	17	5/8	9/16
1AL55-6-6	1AL58-6-6	9/16-20	3/8	10	3/8	10	2.56	65	13/16	21	3/4	11/16
1AL55-8-8	1AL58-8-8	3/4-20	1/2	13	1/2	13	2.81	71	3/4	19	15/16	7/8

Construction: 316 Stainless nipple and shell.

**NOTE:** Nut part No. is **XNUX** or **XNUX-316** for stainless steel.  
 Front ferrule part No. is **XFFX** or **XFFX-316** for stainless steel.  
 Back ferrule part No. is **XBFX** or **XBFX-316** for stainless steel.  
**X** denotes dash size.

Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4300 for additional information.

# 1UT55/1UT58 Male Rigid (JIS)/BSPT



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	mm
#	#								
55 Series	58 Series		inch	mm	inch	mm	inch	mm	mm
1UT55-4-3	—	PT 1/4-19	3/16	5	2.20	56	1-1/4	32	19
1UT55-4-4	—	PT 1/4-19	1/4	6	2.36	60	1-1/4	32	19


Construction: Steel.

Add "C" for Stainless Steel.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

## 1FU55/1FU58 (JIS)/BSP 30° Flare Female Swivel ISO 228-1




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	mm	mm
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	mm	mm
1FU55-4-4	1FU58-4-4	PF 1/4-19	1/4	6	2.48	63	1-9/16	40	19	19
1FU55-6-6	1FU58-6-6	PF 3/8-19	3/8	10	2.88	73	1-11/16	43	22	22
1FU55-8-8	1FU58-8-8	PF 1/2-14	1/2	13	3.27	83	1-7/8	48	27	27
1FU55-12-12	1FU58-12-12	PF 3/4-14	3/4	19	3.58	91	1-3/16	31	36	36
1FU55-16-16	1FU58-16-16	PF 1-11	1	25	4.22	107	1-3/8	35	41	41

Construction: Steel.

Add "C" for Stainless Steel.

B  
TubingC  
Coiled Air Hose  
& Fittings

## 1GU55/1GU58 (JIS)/BSP 60° Cone Female Swivel ISO 228-1




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	mm	mm
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	mm	mm
1GU55-4-4	—	PF 1/4-19	1/4	6	2.44	62	1-1/4	32	19	19
1GU55-6-6	1GU58-6-6	PF 3/8-19	3/8	10	2.76	70	1-3/8	35	22	22
1GU55-8-8	—	PF 1/2-14	1/2	13	3.24	82	1-11/16	43	27	27
1GU55-12-12	—	PF 3/4-14	3/4	19	3.46	88	1-13/16	46	27	36

Construction: Steel.

Add "C" for Stainless Steel.

D  
TransportationE  
Fittings  
Series 55/58

## 1MU55/1MU58 (JIS) Metric 30° Flare Female Swivel



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	mm	mm
#	#									
55 Series	58 Series		inch	mm	inch	mm	inch	mm	mm	mm
1MU55-4-4	—	M14 x 1,5	1/4	6	2.41	61	1-5/16	33	19	19
1MU55-4-6	—	M14 x 1,5	3/8	10	2.75	70	1-3/8	35	19	19
1MU55-6-6	—	M18 x 1,5	3/8	10	2.86	73	1-1/2	38	22	24
1MU55-8-8	—	M22 x 1,5	1/2	13	3.19	81	1.63	41	27	27


Construction: Steel.

Add "C" for Stainless Steel.

F  
Tooling, Equipment  
& AccessoriesG  
General Technical



# 1G155/1G158 (JIS)/BSP 60° Cone Female Swivel 45° Elbow ISO 228-1




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	mm
#	#										
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	mm
1G155-4-4	—	PF 1/4-19	1/4	6	3.30	84	2-3/16	56	0.79	20	19
1G155-6-6	—	PF 3/8-19	3/8	10	3.48	88	2-1/8	54	0.82	21	22
1G155-8-8	—	PF 1/2-14	1/2	13	4.27	108	2-11/16	68	1.16	30	27

Construction: Steel.

Add "C" for Stainless Steel.

# 1G255/1G258 (JIS)/BSP 60° Cone Female Swivel 90° Elbow ISO 228-1



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch	mm	mm
#	#										
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	mm
1G255-4-4	—	PF 1/4-19	1/4	6	2.57	65	1-7/16	37	0.94	24	19
1G255-6-6	—	PF 3/8-19	3/8	10	3.06	78	1-9/16	40	1.50	38	22
1G255-8-8	—	PF 1/2-14	1/2	13	3.26	83	1-11/16	43	1.81	46	27

Construction: Steel.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation


E Fittings Series 55/58

F Tooling, Equipment & Accessories

G General Technical

A  
Hose

## 1C655/1C658 Female Metric Swivel DIN 20078 Heavy Series (Without O-Ring) ISO 8434-1




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	mm	mm
#	#									
55 Series	58 Series									
1C655-8-3	—	M16 x 1,5	3/16	5	2.25	57	1-3/8	35	19	19
1C655-10-4	1C658-10-4	M18 x 1,5	1/4	6	2.50	64	1-3/8	35	19	22
1C655-12-5	—	M20 x 1,5	5/16	8	2.57	65	1-7/16	37	24	24
1C655-14-6	—	M22 x 1,5	3/8	10	3.02	77	1-5/8	41	27	27
1C655-16-8	1C658-16-8	M24 x 1,5	1/2	13	3.19	81	1-5/8	41	27	30
1C655-20-12	—	M30 x 2	3/4	19	3.46	88	1-11/16	43	36	36
—	1C658-25-12	M36x2	3/4	19	3.64	92	1-7/8	48	41	46
1C655-30-16	—	M42 x 2	1	25	4.81	122	2-9/16	65	40	50

Construction: Steel.

Add "C" for Stainless Steel.

B  
TubingC  
Coiled Air Hose  
& FittingsD  
TransportationE  
Fittings Series 55/58F  
Tooling, Equipment  
& AccessoriesG  
General Technical

## 1C955/1C958 Female Metric Swivel DIN 20078 Heavy Series (With O-Ring) ISO 12151-2-SWS




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	mm	mm
#	#									
55 Series	58 Series									
1C955-8-3	—	M16 x 1,5	3/16	5	2.15	55	1-1/4	32	19	19
1C955-10-4	1C958-10-4	M18 x 1,5	1/4	6	2.46	63	1-5/16	33	19	22
1C955-12-5	1C958-12-5	M20 x 1,5	5/16	8	2.54	65	1-7/16	37	24	24
1C955-14-6	1C958-14-6	M22 x 1,5	3/8	10	2.95	75	1-9/16	40	27	27
1C955-16-8	1C958-16-8	M24 x 1,5	1/2	13	3.18	81	1-9/16	40	24	30
1C955-20-12	1C958-20-12	M30 x 2	3/4	19	3.33	85	1-9/16	40	36	36
1C955-25-12	1C958-25-12	M36 x 2	3/4	19	3.55	90	1-13/16	46	41	46

Construction: Steel.

Add "C" for Stainless Steel.

# 1D055/1D058 Male Stud DIN 20078 Light Series

ISO 8434-1




Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	mm
#	#								
55 Series	58 Series								
1D055-6-3	—	M12 x 1,5	3/16	5	1.93	49	1	25	15
1D055-8-4	—	M14 x 1,5	1/4	6	2.17	55	1	25	19
1D055-10-5	—	M16 x 1,5	5/16	8	2.28	58	1	25	19
1D055-12-5	—	M18 x 1,5	5/16	8	2.32	59	1-1/16	27	22
1D055-10-6	1D058-10-6	M16 x 1,5	3/8	10	2.52	64	1	26	22
1D055-12-6	1D058-12-6	M18 x 1,5	3/8	10	2.52	64	1-1/16	27	22
1D055-15-8	1D058-15-8	M22 x 1,5	1/2	13	2.80	71	1-3/16	30	27
1D055-18-12	—	M26 x 1,5	3/4	19	3.03	77	1-3/16	30	32
—	1D058-22-12	M30x2	3/4	19	3.11	79	1-1/4	32	36
—	1D058-28-16	36x2	1	25	3.54	90	1-1/4	32	41

Construction: Steel.

Add "C" for Stainless Steel.

# 1D255/1D258 Male Stud DIN 20078 Heavy Series

ISO 8434-1



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	mm
#	#								
55 Series	58 Series								
1D255-10-4	1D258-10-4	M18 x 1,5	1/4	6	2.28	58	1-1/8	29	22
1D255-12-5	—	M20 x 1,5	5/16	8	2.44	62	1-3/16	30	24
1D255-12-6	—	M20 x 1,5	3/8	10	2.64	67	1-3/16	30	24
1D255-14-6	1D258-14-6	M22 x 1,5	3/8	10	2.72	69	1-1/4	32	27
1D255-16-8	1D258-16-8	M24 x 1,5	1/2	13	2.87	73	1-1/4	32	27
1D255-20-12	1D258-20-12	M30 x 2	3/4	19	3.19	81	1-5/16	33	36
—	1D258-25-12	M36x2	3/4	19	3.27	83	1-3/8	35	41
—	1D258-30-16	M42x2	1	25	3.90	99	1-3/8	35	46


Construction: Steel.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose

# 1D955/1D958 Male BSPP - Rigid ISO 228-1



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch	mm	mm
#	#								
55 Series	58 Series								
1D955-4-4	—	PF 1/4-19	1/4	6	2.30	59	1-1/8	29	19
1D955-6-6	—	PF 3/8-19	3/8	10	2.52	64	1-1/16	27	22
1D955-8-8	—	PF 1/2-14	1/2	12	2.87	73	1-1/4	32	27
—	1D958-16-16	PF 1-11	1	25	3.74	95	1-3/8	35	41

Construction: Steel.

Add "C" for Stainless Steel.


NOTE: When used in a port, a bonded seal must be used. Purchase from Parker's Tube Fittings Division. Ref. P/N D9DT-SIZE.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

# 11D55/11D58 Metric Standpipe Light Series ISO 8434-1



Part Number	Part Number	Diameter R		Hose I.D.		A		Cutoff Allow. B		C		H Hex
		mm	inch	inch	mm	inch	mm	inch	mm	inch	mm	mm
#	#											
55 Series	58 Series											
11D55-6-3	—	6	.236	3/16	5	2.28	58	1-1/4	32	0.79	20	14
11D55-8-4	—	8	.315	1/4	6	2.64	67	1-1/2	38	0.87	22	17
11D55-10-5	—	10	.394	5/16	8	2.76	70	1-7/16	36	0.91	23	17
11D55-10-6	11D58-10-6	10	.394	3/8	10	2.95	75	1-9/16	40	0.91	23	19
11D55-12-6	—	12	.472	3/8	10	3.15	80	1-3/4	45	1.02	26	19
11D55-15-8	11D58-15-8	15	.591	1/2	13	3.23	82	1-11/16	43	0.98	25	22
11D55-18-12	11D58-18-12	18	.709	3/4	19	3.66	93	1-7/8	48	0.98	25	30
11D55-22-12	11D58-22-12	22	.866	3/4	19	3.66	93	1-7/8	48	1.10	28	30
11D55-28-16	11D58-28-16	28	1.10	1	25	4.21	107	1-5/16	33	1.18	30	36

Construction: Steel.

Add "C" for Stainless Steel.

NOTE: Mates with Parker's Tube Fittings Division EO "L" Series Adapters.

E Fittings Series 55/58


F Tooling, Equipment & Accessories

G General Technical



# 13D55/13D58 Metric Standpipe Heavy Series

## ISO 8434-1




Part Number	Part Number	Diameter R		Hose I.D.		A		Cutoff Allow. B		C		H Hex
#	#	Ø		⊙								Hexagon
55 Series	58 Series	mm	inch	inch	mm	inch	mm	inch	mm	inch	mm	mm
13D55-8-3	—	8	.315	3/16	5	2.45	62	1-1/2	38	0.94	24	14
13D55-10-4	—	10	.394	1/4	6	2.80	71	1-11/16	43	0.94	24	17
13D55-12-5	—	12	.472	5/16	8	2.86	73	1-11/16	43	1.02	26	17
13D55-12-6	—	12	.472	3/8	10	3.05	77	1-11/16	43	1.02	26	19
13D55-14-6	—	14	.551	3/8	10	3.17	81	1-13/16	46	1.02	26	19
13D55-16-8	—	16	.630	1/2	13	3.44	87	1-7/8	48	1.18	30	22

Construction: Steel.

Add "C" for Stainless Steel.

NOTE: Mates with Parker's Tube Fittings Division EO "S" Series Adapters.

# 19255/19258 Female BSP Parallel Pipe Swivel Straight (60° Cone)



Part Number	Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
#	#	⌀	⊙						Hexagon	Hexagon
55 Series	58 Series		inch	mm	inch	mm	inch	mm	mm	mm
19255-4-3	—	PF 1/4-19	3/16	5	2.16	55	1-5/16	33	17	19
19255-4-4	19258-4-4	PF 1/4-19	1/4	6	2.41	61	1-5/16	33	17	19
19255-6-5	—	PF 3/8-19	5/16	8	2.45	62	1-5/16	33	19	22
19255-6-6	19258-6-6	PF 3/8-19	3/8	10	2.63	67	1-5/16	33	19	22
19255-8-8	19258-8-8	PF 1/2-14	1/2	13	3.00	76	1-1/2	38	27	27
19255-12-12	19258-12-12	PF 3/4-14	3/4	19	3.42	87	1-3/8	35	36	36
19255-16-16	19258-16-16	PF 1-11	1	25	4.16	106	1-5/16	38	33	41

Construction: Steel.

Add "C" for Stainless Steel.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 55/58  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

## 1B155/1B158 Female BSP Parallel Pipe Swivel 45° Elbow (60° Cone) ISO 228-1



B Tubing


Part Number	Part Number	Thread Size	Tube O.D.		Hose I.D.		A		Cutoff Allow. B		E		J Hex
#	#												
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	
1B155-4-4	—	PF 1/4-19	1/4	6	1/4	6	3.03	77	1-7/8	48	.61	16	19
1B155-6-5	—	PF 3/8-19	3/8	10	5/16	8	3.60	91	2-1/4	57	.67	17	22
1B155-6-6	—	PF 3/8-19	3/8	10	3/8	10	3.60	91	2-1/4	57	.67	17	22
1B155-8-8	—	PF 1/2-14	1/2	13	1/2	13	4.28	109	2-11/16	68	.79	20	27

Construction: Steel.  
Add "C" for Stainless Steel.

C Coiled Air Hose & Fittings

D Transportation

## 1B255/1B258 Female BSP Parallel Pipe Swivel 90° Elbow (60° Cone) ISO 228-1



E Fittings Series 55/58

Part Number	Part Number	Thread Size	Tube O.D.		Hose I.D.		A		Cutoff Allow. B		E		J Hex
#	#												
55 Series	58 Series		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	
1B255-4-4	—	PF 1/4-19	1/4	6	1/4	6	2.39	61	1-1/4	32	1.14	29	19
1B255-6-5	—	PF 3/8-19	3/8	10	5/16	8	2.72	69	1-3/8	35	1.34	34	22
1B255-6-6	—	PF 3/8-19	3/8	10	3/8	10	2.81	71	1-1/2	38	1.37	35	22
1B255-8-8	—	PF 1/2-14	1/2	13	1/2	13	3.27	83	1-9/16	40	1.57	40	27
1B255-10-8	—	PF 5/8-14	1/2	13	1/2	13	3.28	83	1-11/16	43	1.89	48	30
1B255-12-12	—	PF 3/4-14	3/4	19	3/4	19	4.20	107	2-7/16	62	2.54	65	36

Construction: Steel.  
Add "C" for Stainless Steel.









F Tooling, Equipment & Accessories

G General Technical





# 57 Series Visual Index

<b>57 Series</b> <b>PERMANENT</b>	<b>101</b> Male Taper Pipe Rigid  E-38	<b>106</b> Female SAE (JIC) 37° Swivel  E-38	<b>113</b> Male Pipe Swivel  E-38	<b>137</b> FM (JIC) 37° Swivel 45° Elbow  E-39	<b>139</b> FM (JIC) 37° Swivel 90° Elbow  E-39	
	<b>1J7</b> Seal-Lok™ 45° Elbow  E-39	<b>1J9</b> Seal-Lok™ 90° Elbow  E-40	<b>1JC</b> Seal-Lok™ Straight Short  E-40			

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings Series 57

F Tooling, Equipment & Accessories


G General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose

## 10157 Male Taper Pipe Rigid




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
10157-2-2	1/8-27	1/8	3	1.35	34	3/4	19	1/2
10157-4-2	1/4-18	1/8	3	1.56	40	15/16	24	5/8

Construction: Steel.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

## 10657 SAE (JIC) 37° Swivel




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
10657-2-2	5/16-24	1/8	3	1.63	41	1	25	1/2	1/2
10657-3-2	3/8-24	1/8	3	1.60	41	1	25	1/2	9/16
10657-4-2	7/16-20	1/8	3	1.68	43	1	25	1/2	5/8

Construction: Steel.  
Add "C" for Stainless Steel.  
NOTE: Size -4 incorporates a dual seat.

D Transportation

E Fittings Series 57

## 11357 Male Pipe Swivel\*



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
11357-2-2	1/8-27	1/8	3	1.96	50	1-5/16	33	1/2	1/2


Construction: Steel.  
Add "C" for Stainless Steel.  
NOTE: \*For use with petroleum based fluids.

**WARNING:** Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling.

F Tooling, Equipment & Accessories

G General Technical


## 13757 Female JIC 37° Swivel 45° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
13757-4-2	7/16-20	1/8	3	1.98	50	1-5/16	33	0.33	8	9/16

Construction: Steel.  
Add "C" for Stainless Steel.


## 13957 Female JIC 37° Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
13957-4-2	7/16-20	1/8	3	1.87	48	1-1/4	32	0.68	17	9/16

Construction: Steel.  
Add "C" for Stainless Steel.

## 1J757 Seal-Lok™ 45° Elbow ISO 12151-1-SWE45




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J757-4-2	9/16-18	1/8	3	2.07	53	1-7/16	36	0.39	10	11/16

Construction: Steel.  
Add "C" for Stainless Steel.

A Hose

# 1J957 Seal-Lok™ 90° Elbow

## ISO 12151-1-SWE90



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J957-4-2	9/16-18	1/8	3	2.04	52	1-7/16	36	0.83	21	11/16


Construction: Steel.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

# 1JC57 Seal-Lok™ Straight-Short

## ISO 12151-1-SWSA



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1JC57-4-2	9/16-18	1/8	3	1.34	34	3/4	19	5/8	11/16

Construction: Steel.  
Add "C" for Stainless Steel.

D Transportation










E Fittings Series 57

F Tooling, Equipment & Accessories

G General Technical



# 58H Series Visual Index

<b>58H Series</b> <b>PERMANENT</b>	<b>101</b> Male Taper Pipe Rigid	<b>106</b> SAE (JIC) 37° Swivel	<b>137</b> Female JIC 37° Swivel 45° Elbow	<b>139</b> Female JIC 37° Swivel 90° Elbow	<b>1J1</b> Seal-Lok™ 90° Elbow Long
					
	E-42	E-42	E-42	E-43	E-44
	<b>1J7</b> Seal-Lok™ 45° Elbow	<b>1J9</b> Seal-Lok™ 90° Elbow	<b>1JC</b> Seal-Lok™ Straight Short	<b>1JS</b> Seal-Lok™ Straight	
					
	E-44	E-44	E-43	E-43	

A  
Hose

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

E  
Fittings Series 58H

F  
Tooling, Equipment & Accessories


G  
General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose

# 10158H Male Taper Pipe Rigid




Part Number	NPTF Thread	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
10158H-12-12	3/4-14	3/4	19	3.91	99	1-11/16	43	1-1/4
10158H-16-16	1-11-1/2	1	1	4.76	121	1-13/16	46	1-3/4

Construction: Steel.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

# 10658H (JIC) 37° Swivel




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
10658H-12-12	1-1/16-12	3/4	19	4.14	105	1-13/16	46	1-1/4	1-5/16
10658H-16-16	1-5/16-12	1	25	4.89	124	1-15/16	49	1-3/4	1-5/8

Construction: Steel.  
Add "C" for Stainless Steel.

D Transportation

E Fittings Series 58H

# 13758H Female JIC 37° Swivel 45° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#											
13758H-16-16	1-5/16-12	1	25	5.46	139	2-1/2	64	0.90	23	1-3/4	1-1/2

Construction: Steel.  
Add "C" for Stainless Steel.


F Tooling, Equipment & Accessories

G General Technical






## 13958H Female JIC 37° Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#											
13958H-12-12	1-1/16-12	3/4	19	4.57	116	2-3/8	60	1.81	46	1-1/4	1-1/4
13958H-16-16	1-5/16-12	1	25	5.42	138	2-1/2	64	2.14	54	1-3/4	1-1/2

Construction: Steel.  
Add "C" for Stainless Steel.


## 1JS58H Seal-Lok™ Straight - Long ISO 12151-1-SWSB



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1JS58H-12-12	1-3/16-12	3/4	19	4.29	109	2-1/16	52	1-1/4	1-3/8
1JS58H-16-16	1-7/16-12	1	25	4.97	126	1-15/16	49	1-3/4	1-5/8

Construction: Steel.  
Add "C" for Stainless Steel.

## 1JC58H Seal-Lok™ Straight-Short ISO 12151-1-SWSA




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1JC58H-12-12	1-3/16-12	3/4	19	3.86	98	1-1/2	38	1-1/4	1-3/8
1JC58H-16-16	1-7/16-12	1	25	4.66	119	1-11/16	43	1-3/4	1-5/8

Construction: Steel.  
Add "C" for Stainless Steel.

A Hose

## 1J158H Seal-Lok™ 90° Elbow - Long Drop

### ISO 12151-1-SWEL90



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#											
1J158H-12-12	1-3/16-12	3/4	19	4.38	111	1-7/8	48	3.78	96	1-1/4	1-3/8
1J158H-16-16	1-7/16-12	1	25	5.35	136	1-7/8	48	4.50	114	1-3/4	1-5/8


Construction: Steel.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

## 1J758H Seal-Lok™ 45° Elbow

### ISO 12151-1-SWE45



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#											
1J758H-12-12	1-3/16-12	3/4	19	4.51	115	2-5/16	59	0.81	21	1-1/4	1-3/8
1J758H-16-16	1-7/16-12	1	25	5.75	146	2-13/16	71	0.94	24	1-3/4	1-5/8


Construction: Steel.  
Add "C" for Stainless Steel.

D Transportation

E Fittings Series 58H

## 1J958H Seal-Lok™ 90° Elbow - Short Drop

### ISO 12151-1-SWE90















Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch	inch
#											
1J958H-12-12	1-3/16-12	3/4	19	4.40	112	2-3/16	56	1.85	47	1-1/4	1-3/8
1J958H-16-16	1-7/16-12	1	25	5.70	145	2-3/4	70	2.21	56	1-3/4	1-5/8





Construction: Steel.  
Add "C" for Stainless Steel.

F Tooling, Equipment & Accessories

G General Technical

# 90 Series Visual Index

<b>90 Series</b> FIELD ATTACHABLE	<b>201</b> Male Taper Pipe Rigid  E-46	<b>206</b> SAE (JIC) 37° Swivel  E-46	<b>208</b> SAE 45° Swivel  E-47	<b>228</b> SAE Male Inverted Swivel Straight  E-47	<b>234</b> Straight Tube  E-47
	<b>237</b> JIC 37° Swivel 45° Elbow  E-48	<b>239</b> JIC 37° Swivel 90° Elbow  E-48	<b>261</b> SAE Compression Air Brake  E-49	<b>267</b> SAE Male Inverted Swivel 45° Elbow  E-49	<b>269</b> SAE Male Inverted Swivel 90° Elbow  E-50
	<b>277</b> 45° Swivel 45° Elbow  E-50	<b>279</b> 45° Swivel 90° Elbow  E-50			

<b>90 Series</b> REPLACEMENT COMPONENTS	<b>200</b> Replacement Socket  E-51	<b>090</b> Replacement Ferrule  E-51	<b>60HAB</b> Compression Airbrake Sleeve  E-51	<b>61HAB</b> Compression Airbrake Nut  E-51
--	--	---	---	--


A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 90  
 F Tooling, Equipment & Accessories  
 G General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose

## 20190 Male Taper Pipe Rigid



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch
#							
20190-2-4	1/8-27	-4	1.33	34	7/8	22	9/16
20190-4-4	1/4-18	-4	1.58	40	1-1/16	27	9/16
20190-4-5	1/4-18	-5	1.66	42	1-1/8	29	5/8
20190-4-6	1/4-18	-6	1.66	42	1-1/8	29	11/16
20190-6-6	3/8-18	-6	1.66	42	1-1/8	29	11/16
20190-6-8	3/8-18	-8	1.77	45	1-3/16	30	7/8
20190-8-8	1/2-14	-8	1.97	50	1-7/16	37	7/8
20190-8-10	1/2-14	-10	2.13	54	1-7/16	37	1
20190-12-12	3/4-14	-12	2.26	57	1-9/16	40	1-1/8
20190-12-16	3/4-14	-16	2.29	58	1-5/8	41	1-3/8
20190-16-16	1-11-1/2	-16	2.46	62	1-7/8	48	1-3/8
20190-20-20	1-1/4-11-1/2	-20	2.69	68	2-1/16	52	2

Construction: Brass nipple and ferrule, steel socket.


Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

## 20690 SAE (JIC) 37° Swivel



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
20690-4-4	7/16-20	-4	1.58	40	1-1/8	29	9/16	9/16
20690-5-5	1/2-20	-5	1.66	42	1-1/8	29	5/8	5/8
20690-6-6	9/16-18	-6	1.74	44	1-3/16	35	11/16	11/16
20690-8-6	3/4-16	-6	1.85	47	1-5/16	33	7/8	7/8
20690-8-8	3/4-16	-8	1.98	50	1-3/8	35	7/8	7/8
20690-8-10	3/4-16	-10	2.07	53	1-7/16	37	1	7/8
20690-10-10	7/8-14	-10	2.22	56	1-1/2	38	1	1
20690-12-12	1-1/16-12	-12	2.33	59	1-5/8	41	1-1/4	1-1/4
20690-16-16	1-5/16-12	-16	2.52	64	1-15/16	49	1-3/8	1-1/2
20690-20-20	1-5/8-12	-20	2.99	76	2-5/16	59	2	2

Construction: Brass nipple and ferrule, steel nut and socket.

Add "C" for Stainless Steel.


NOTE: Sizes -4, -5, -8 and -10 incorporate a dual seat.

E Fittings Series 90

F Tooling, Equipment & Accessories

G General Technical

## 20890 SAE 45° Swivel




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
20890-6-6	5/8-18	-6	1.77	45	1-1/4	32	11/16	3/4
20890-12-12	1-1/16-14	-12	2.34	59	1-11/16	43	1-1/8	1-1/4

Construction: Brass nipple and ferrule, steel nut and socket.

Add "C" for Stainless Steel.

## 22890 SAE Male Inverted Swivel-Straight




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
22890-4-4	7/16-24	-4	2.15	55	1-11/16	43	9/16	7/16
22890-5-5	1/2-20	-5	2.21	56	1-11/16	43	5/8	1/2
22890-5-6	1/2-20	-6	2.20	56	1-11/16	43	11/16	1/2
22890-6-6	5/8-18	-6	2.22	56	1-11/16	43	11/16	5/8
22890-8-8	3/4-18	-8	2.34	59	1-13/16	46	13/16	3/4
22890-10-10	7/8-18	-10	2.53	64	1-7/8	48	15/16	7/8
22890-12-12	1-1/16-16	-12	3.01	76	2-3/8	60	1-1/8	1-1/16

Construction: Brass ferrule, steel tube, nut and socket.

Add "C" for Stainless Steel.

## 23490 Straight Tube



Part Number	Hose Size	Tube Size		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
23490-8-8	-8	1/2	6	3.06	78	2-1/2	64	13/16
23490-8-10	-10	1/2	8	3.15	80	2-1/2	64	1
23490-10-8	-8	5/8	8	3.26	83	2-5/8	67	13/16
23490-10-10	-10	5/8	10	3.28	83	2-5/8	67	1
23490-12-12	-12	3/4	13	3.28	83	2-11/16	68	1-1/8


Construction: Brass nipple and ferrule, steel socket.

Add "C" for Stainless Steel.

NOTE: 26T90 fitting includes 23490 with the 60HAB sleeve and 61HAB nut.

A Hose

## 23790 JIC 37° Swivel 45° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#										
23790-4-4	7/16-20	-4	1.79	45	1-3/8	35	0.33	8	9/16	9/16
23790-5-5	1/2-20	-5	1.86	47	1-3/8	35	0.36	9	5/8	5/8
23790-6-6	9/16-18	-6	1.96	50	1-7/16	37	0.39	10	11/16	11/16
23790-8-6	3/4-16	-6	2.11	54	1-11/16	43	0.55	14	11/16	7/8
23790-8-8	3/4-16	-8	2.40	61	1-3/4	44	0.55	14	13/16	7/8
23790-10-10	7/8-14	-10	2.45	62	1-7/8	48	0.63	16	15/16	1
23790-12-12	1-1/16-12	-12	3.04	77	2-7/16	62	0.78	20	1-1/8	1-1/4
23790-16-16	1-5/16-12	-16	3.28	83	2-11/16	68	0.90	23	1-3/8	1-1/2
23790-20-20	1-5/8-12	-20	3.70	94	3-1/16	78	1.18	30	1-3/4	2

Construction: Brass ferrule, steel tube, nut and socket.


Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

## 23990 JIC 37° Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#										
23990-4-4	7/16-20	-4	1.67	41	1-1/4	32	0.68	17	9/16	9/16
23990-5-5	1/2-20	-5	1.75	44	1-1/4	32	0.77	20	5/8	5/8
23990-6-6	9/16-18	-6	1.86	47	1-3/8	35	0.85	22	11/16	11/16
23990-8-6	3/4-16	-6	1.95	50	1-7/16	37	1.09	28	11/16	7/8
23990-8-8	3/4-16	-8	2.15	55	1-1/2	38	1.09	28	13/16	7/8
23990-10-10	7/8-14	-10	2.38	60	1-3/4	44	1.23	31	15/16	1
23990-12-12	1-1/16-12	-12	2.95	75	2-5/16	59	1.82	46	1-1/8	1-1/4
23990-16-16	1-5/16-12	-16	3.13	80	2-1/2	64	2.14	54	1-3/8	1-1/2
23990-20-20	1-5/8-12	-20	3.54	90	2-7/8	73	2.57	65	1-3/4	2

Construction: Brass ferrule, steel tube, nut and socket.

Add "C" for Stainless Steel.


E Fittings Series 90

F Tooling, Equipment & Accessories

G General Technical



## 26190 SAE Compression Air Brake




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch
#							
26190-8-8	11/16-20	-8	1.69	43	1-1/16	27	13/16
26190-8-10	11/16-20	-10	1.86	47	1-3/16	30	1
26190-10-10	13/16-18	-10	1.92	49	1-1/4	32	1
26190-12-10	1-18	-10	2.09	53	1-7/16	37	1
26190-12-12	1-18	-12	2.09	53	1-7/16	37	1-1/8

Construction: Brass nipple and ferrule, steel socket.

Add "B" for Brass nipple and socket.

Add "C" for Stainless Steel.

## 26790 SAE Male Inverted Swivel 45° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#										
26790-4-4	7/16-24	-4	2.11	54	1-11/16	43	0.63	16	9/16	7/16
26790-5-5	1/2-20	-5	2.51	64	2	51	0.94	24	5/8	1/2
26790-5-6	1/2-20	-6	2.55	65	2-1/16	52	0.94	24	11/16	1/2
26790-6-6	5/8-18	-6	2.61	66	2-1/8	54	0.94	24	11/16	5/8
26790-8-8	3/4-18	-8	2.97	75	2-3/8	60	0.94	24	13/16	3/4
26790-8-10	3/4-18	-10	3.05	77	2-7/16	62	0.94	24	15/16	3/4
26790-10-10	7/8-18	-10	3.43	87	2-11/16	68	1.02	26	15/16	7/8
26790-12-12	1-1/16-16	-12	3.83	97	3-3/16	81	1.15	29	1-1/8	1-1/16

Construction: Brass ferrule, steel tube, nut and socket.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.

A  
Hose

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation


E  
Fittings Series 90

F  
Tooling, Equipment & Accessories

G  
General Technical

A Hose

## 26990 SAE Male Inverted Swivel 90° Elbow




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#										
26990-4-4	7/16-24	-4	1.79	45	1-5/16	33	1.19	30	9/16	7/16
26990-5-5	1/2-20	-5	2.01	51	1-1/2	38	1.65	42	5/8	1/2
26990-5-6	1/2-20	-6	2.05	52	1-9/16	40	1.65	42	11/16	1/2
26990-6-6	5/8-18	-6	2.03	52	1-1/2	38	1.70	43	11/16	5/8
26990-8-8	3/4-18	-8	2.30	58	1-11/16	43	1.78	45	13/16	3/4
26990-8-10	3/4-18	-10	2.39	61	1-3/4	44	1.78	45	15/16	3/4
26990-10-10	7/8-18	-10	3.16	80	2-1/2	64	2.18	55	15/16	7/8
26990-12-12	1-1/16-16	-12	3.56	90	2-15/16	75	2.51	64	1-1/8	1-1/16

Construction: Brass ferrule, steel tube, nut and socket.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

## 27790 SAE 45° Swivel 45° Elbow




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#										
27790-6-6	5/8-18	-6	1.72	44	1-3/16	30	0.39	10	11/16	3/4
27790-12-12	1-1/16-14	-12	3.03	77	2-3/8	60	0.78	20	1-1/8	1-1/4

Construction: Brass ferrule, steel tube, nut and socket.  
Add "C" for Stainless Steel.

D Transportation

E Fittings Series 90

## 27990 SAE 45° Swivel 90° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		H Hex	J Hex
			inch	mm	inch	mm	inch	mm	inch	inch
#										
27990-4-4	7/16-20	-4	1.67	42	1-1/4	32	.68	17	9/16	9/16
27990-5-5	1/2-20	-5	1.75	44	1-1/4	32	.77	20	5/8	5/8
27990-6-6	5/8-18	-6	1.86	47	1-3/8	35	.85	22	11/16	3/4
27990-8-8	3/4-16	-8	2.09	53	1-1/2	38	1.09	28	13/16	7/8
27990-12-12	1-1/16-14	-12	2.95	75	2-5/16	39	1.82	46	1-1/8	1-1/4


Construction: Brass ferrule, steel tube, nut and socket.  
Add "C" for Stainless Steel.

F Tooling, Equipment & Accessories

G General Technical




## 20090 Replacement Socket for Field Attachable Fittings



Part Number	H Hex
#	
	inch
20090-4	9/16
20090-5	5/8
20090-6	11/16
20090-8	7/8
20090-10	1
20090-12	1-1/8
20090-16	1-3/8
20090-20	1-3/4

Construction: Steel or Stainless Steel.  
Add "C" for Stainless Steel.


## 60 HAB SAE Compression Airbrake Sleeve



Part Number	Tube Size		L
	inch	mm	
#			
60HAB-4	1/4	6	.250
60HAB-6	3/8	10	.313
60HAB-8	1/2	13	.375
60HAB-10	5/8	16	.438
60HAB-12	3/4	19	.500

Construction: Brass.  
NOTE: To be used with 13491N & 23490.


## 090 Replacement Ferrule for 90 Series Field Attachable Fittings



Part Number	Hose Size
#	
090-4B	-4
090-5B	-5
090-6B	-6
090-8B	-8
090-10B	-10
090-12B	-12
090-16B	-16
090-20B	-20

Construction: Brass.  
Replace "B" with "C" for Stainless Steel.

## 61 HAB SAE Compression Airbrake Nut



Part Number	Thread Size	Tube Size		L		W Hex
		inch	mm	inch	mm	
#						
61HAB-4	7/16-24	1/4	6	0.75	19	9/16
61HAB-6	7/32-24	3/8	10	1.13	29	5/8
61HAB-8	11/16-20	1/2	13	1.25	32	13/16
61HAB-10	13/16-18	5/8	16	1.38	35	15/16
61HAB-12	1-18	3/4	19	1.56	40	1-1/8

Construction: Brass.  
NOTE: To be used with 13491N & 23490 Fittings.

A  
Hose

# 91N/91 Series Visual Index

B  
Tubing




























C  
Coiled Air Hose & Fittings

D  
Transportation

E  
Fittings Series 91


F  
Tooling, Equipment & Accessories

G  
General Technical

<b>91N/91 Series</b> <b>PERMANENT</b>	<b>101</b> Male Taper Pipe Rigid  E-53	<b>103</b> Male JIC 37°  E-53	<b>106</b> JIC 37° Female Swivel  E-54	<b>106 RD</b> JIC 37° Female Swivel w/o Nip. Hex  E-54	<b>107</b> Female Pipe Swivel  E-55
	<b>108</b> Female SAE 45° Swivel  E-55	<b>128</b> Male Inverted Swivel Straight  E-55	<b>134</b> Straight Tube  E-56	<b>137</b> Female JIC 37° Swivel 45° Elbow  E-56	<b>139</b> Female JIC 37° Swivel 90° Elbow  E-57
<b>141</b> Female JIC 37° Swivel 90° Elb Long  E-57	<b>161</b> Compression Air Brake  E-58	<b>167</b> SAE Male Inverted 45° Elbow  E-58	<b>169</b> SAE Male Inverted 90° Elbow  E-59	<b>177</b> SAE 45° Swivel 45° Elbow  E-59	
<b>179</b> Female SAE 45° Swivel 90° Elbow  E-59	<b>192</b> Female BSP Pipe Swivel - Str. (60° Cone)  E-64	<b>1AL</b> A-Lok® Compression  E-60	<b>1B2</b> Female BSP Pipe Swivel 45° Elb. (60° Cone)  E-64	<b>1FN</b> Sanitary Flange  E-60	
<b>1J1</b> Female Seal-Lok™ 90° Elbow Long  E-61	<b>1J7</b> Female Seal-Lok™ 45° Elbow  E-61	<b>1J9</b> Female Seal-Lok™ 90° Elbow  E-62	<b>1JC</b> Female Seal-Lok™ Swive lStraight Short  E-62	<b>1P6</b> CPI® Compression w/nut and ferrule  E-60	
<b>1Q1</b> Female Ultra Seal  E-63	<b>1TU</b> Universal Tube Stub End  E-63				



# 10191N Male Taper Pipe Rigid




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch
#							
10191N-2-4	1/8-27	-4	1.27	32	3/4	19	7/16
10191N-4-4	1/4-18	-4	1.50	38	15/16	24	9/16
10191N-4-5	1/4-18	-5	1.55	39	15/16	24	9/16
10191N-4-6	1/4-18	-6	1.60	41	15/16	24	9/16
10191N-6-6	3/8-18	-6	1.65	58	1	25	11/16
10191N-6-8	3/8-18	-8	1.71	43	1	25	11/16
10191N-8-8	1/2-14	-8	1.94	49	1-1/4	32	7/8
10191N-8-10	1/2-14	-10	1.96	50	1-1/4	32	7/8
10191N-8-12	1/2-14	-12	2.42	61	1-1/4	32	1
10191N-12-12	3/4-14	-12	2.19	56	1-3/8	35	1-1/8
10191N-16-16	1-11-1/2	-16	2.46	62	1-1/2	38	1-3/8
10191-20-20	1-1/4-11-1/2	-20	3.05	77	2-1/16	52	1-3/4

Construction: Brass nipple, steel shell.

Add "B" for Brass nipple and shell.

Add "C" for Stainless Steel.

# 10391N Male (JIC) 37°



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex
			inch	mm	inch	mm	inch
#							
10391N-4-4	7/16-20	-4	1.37	35	13/16	21	1/2
10391N-5-5	1/2-20	-5	1.48	38	7/8	22	9/16
10391N-6-6	9/16-18	-6	1.64	42	1	25	11/16
10391N-8-8	3/4-16	-8	1.79	35	1-1/8	29	7/8
10391N-8-6	3/4-16	-6	1.73	44	1-1/16	27	7/8
10391N-10-10	7/8-14	-10	2.07	53	1-3/8	35	1
10391N-12-12	1-1/16-12	-12	2.10	53	1-5/16	33	1-1/8
10391N-16-16	1-5/16-12	-16	2.43	62	1-1/2	38	1-3/8


Construction: Brass nipple, steel shell.

Add "B" for Brass nipple and shell.

Add "C" for Stainless Steel.

A Hose

## 10691N SAE (JIC) 37° Swivel



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
10691N-4-4	7/16-20	-4	1.43	36	7/8	22	3/8	9/16
10691N-5-5	1/2-20	-5	1.56	40	15/16	24	7/16	5/8
10691N-6-6	9/16-18	-6	1.63	41	1	25	1/2	11/16
10691N-6-8	9/16-18	-8	1.69	43	1	25	9/16	11/16
10691N-8-8	3/4-16	-8	1.89	48	1-3/16	30	11/16	7/8
10691N-8-10	3/4-16	-10	1.86	58	1-1/8	29	3/4	7/8
10691N-10-10	7/8-14	-10	2.03	52	1-5/16	33	13/16	1
10691N-12-12	1-1/16-12	-12	2.12	54	1-5/16	33	1	1-1/4
10691N-16-16	1-5/16-12	-16	2.45	62	1-9/16	40	1-1/4	1-1/2
10691-20-20	1-5/8-12	-20	2.98	76	1-13/16	46	1-11/16	2


Construction: Brass nipple, steel nut and shell.  
 Add "B" for Brass nipple, nut and shell.  
 Add S for Steel nipple, nut and shell.  
 Add "C" for Stainless Steel.  
 NOTE: Sizes -4, -5, -8 and -10 incorporate a dual seat.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

## 10691NRD SAE (JIC) 37° Swivel



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
			inch	mm	inch	mm	inch
#							
10691N-4-4-RD	7/16-20	-4	1.34	34	13/16	21	9/16
10691N-5-5-RD	1/2-20	-5	1.51	38	7/8	22	5/8
10691N-6-6-RD	9/16-18	-6	1.60	41	15/16	24	11/16
10691N-8-8-RD	3/4-16	-8	1.79	45	1-1/16	27	7/8
10691N-10-10-RD	7/8-14	-10	1.91	49	1-3/16	30	1
10691N-12-12-RD	1-1/16-12	-12	2.09	58	1-5/16	33	1-1/4
10691N-16-16-RD	1-5/16-12	-16	2.27	58	1-5/16	33	1-1/2

Construction: Brass nipple, steel nut and shell.  
 Add "B" for Brass nipple, nut and shell.  
 Add "C" for Stainless Steel.  
 NOTE: Sizes -4, -5, -8 and -10 incorporate a dual seat.

E Fittings Series 91


F Tooling, Equipment & Accessories

G General Technical





## 10791N Female Pipe Swivel




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
10791N-4-4	1/4-18	-4	1.50	38	15/16	24	9/16	11/16
10791N-6-6	3/8-18	-6	1.67	42	1	25	5/8	7/8
10791N-8-8	1/2-14	-8	1.83	46	1-1/8	29	3/4	1
10791N-10-10	3/4-14	-12	2.09	53	1-5/16	33	1	1-1/4
10791N-12-12	1-1/11-1/2	-12	2.26	57	1-5/16	33	1-3/16	1-3/8

Construction: Brass nipple, steel nut and shell.

Add "B" for Brass nipple, nut and shell.

Add "C" for Stainless Steel.

## 10891N SAE 45° Swivel




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
10891N-6-6	5/8-18	-6	1.69	43	1-1/16	27	5/8	3/4
10891N-12-12	1-1/16-14	-12	2.12	54	1-5/16	33	1	1-1/4

Construction: Brass nipple, steel nut and shell.

Add S for Steel nipple, nut and shell.

Add "C" for Stainless Steel.

## 12891N Male Inverted Swivel–Straight



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
			inch	mm	inch	mm	inch
#							
12891N-4-4	7/16-24	-4	2.09	53	1-1/2	38	7/16
12891N-5-5	1/2-20	-5	2.15	55	1-9/16	40	1/2
12891N-5-6	1/2-20	-6	2.23	57	1-9/16	40	1/2
12891N-6-6	5/8-18	-6	2.23	57	1-9/16	40	5/8
12891N-8-8	3/4-18	-8	2.31	59	1-5/8	41	3/4
12891N-10-10	7/8-18	-10	2.43	58	1-3/4	44	7/8
12891N-12-12	1-1/16-16	-12	2.50	64	1-11/16	43	1-1/16


Construction: Steel nipple, tube, nut and shell.

Add "C" for Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.

A  
Hose

# 13491N Straight Tube



Part Number	Hose Size	Diameter R	A		Cutoff Allow. B	
			inch	mm	inch	mm
#						
13491N-8-8	-8	1/2	2.80	71	2-1/8	54
13491N-8-10	-10	1/2	2.81	71	2-1/8	54
13491N-10-10	-10	5/8	2.96	75	2-1/4	58
13491N-12-12	-12	3/4	3.37	86	2-9/16	65

Construction: Brass nipple, steel shell.

Add "B" for Brass nipple and shell.


Add "C" for Stainless Steel.

NOTE: The 16T91N fitting includes 13491N with the 60HAB sleeve and 61HAB nut.

B  
Tubing

C  
Coiled Air Hose & Fittings

# 13791N JIC 37° Swivel 45° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
13791N-4-4	7/16-20	-4	1.74	44	1-3/16	30	0.33	8	9/16
13791N-5-5	1/2-20	-5	1.87	47	1-1/4	32	0.36	9	5/8
13791N-6-6	9/16-18	-6	1.94	49	1-5/16	33	0.43	11	11/16
13791N-8-8	3/4-16	-8	2.28	58	1-9/16	37	0.55	14	7/8
13791N-10-10	7/8-14	-10	2.42	61	1-11/16	43	0.64	43	1
13791N-12-12	1-1/16-12	-12	2.83	58	2-1/16	52	0.78	20	1-1/4
13791N-16-16	1-5/16-12	-16	3.18	81	2-1/4	57	0.89	23	1-1/2
13791-20-20	1-5/8-12	-20	3.67	93	2-9/16	65	1.10	28	2

Construction: Steel tube, nipple, nut and shell.

Add "C" for Stainless Steel.

D  
Transportation

E  
Fittings Series 91

F  
Tooling, Equipment & Accessories


G  
General Technical

Non Standard. See page ii for information on non-standard products.



For detailed ordering information, please consult price list or contact Parflex® Division.


## 13991N JIC 37° Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
13991N-4-4	7/16-20	-4	1.62	41	1-1/16	37	0.68	17	9/16
13991N-5-5	1/2-20	-5	1.71	43	1-1/8	29	0.77	20	5/8
13991N-6-6	9/16-18	-6	1.91	49	1-1/4	32	0.91	23	11/16
13991N-8-8	3/4-16	-8	2.03	52	1-5/16	33	1.09	28	7/8
13991N-10-10	7/8-14	-10	2.27	58	1-9/16	37	1.23	43	1
13991N-12-12	1-1/16-12	-12	2.75	58	1-15/16	49	1.82	46	1-1/2
13991N-16-16	1-5/16-12	-16	3.15	80	2-3/16	56	2.14	52	1-1/2
13991-20-20	1-5/8-12	-20	3.53	90	2-7/16	62	1.18	30	2

Construction: Steel tube, nipple, nut and shell.  
Add "C" for Stainless Steel.

## 14191N JIC 37° Swivel 90° Elbow Long Drop



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
14191N-4-4	7/16-20	-4	1.66	42	1-1/8	29	1.80	46	9/16
14191N-5-5	1/2-20	-5	1.72	44	1-1/8	29	1.77	45	5/8
14191N-6-6	9/16-18	-6	1.93	49	1-5/16	33	2.13	54	11/16
14191N-8-8	3/4-16	-8	2.11	54	1-3/8	35	2.43	62	7/8
14191N-10-10	7/8-14	-10	2.34	59	1-5/8	41	2.57	65	1
14191N-12-12	1-1/16-12	-12	2.63	67	1-7/8	48	3.73	95	1-1/4
14191N-16-16	1-5/16-12	-16	3.15	80	2-3/16	56	4.33	110	1-1/2
14191-20-20	1-5/8-12	-20	4.00	102	2-15/16	75	5.28	134	2

Construction: Steel tube, nipple, nut and shell.  
Add "C" for Stainless Steel.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 91  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

## 16191N Compression Air Brake



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	
			inch	mm	inch	mm	inch	mm
#								
16191N-8-8	11/16-20	-8	1.61	41	15/16	24		3/4
16191N-8-10	11/16-20	-10	1.61	41	15/16	24		7/8
16191N-10-10	13/16-18	-10	1.82	46	1-1/8	29		15/16
16191N-12-12	1-18	-12	1.93	49	1-1/8	29		1-1/4

Construction: Brass nipple, steel shell.

Add "B" for Brass nipple and shell.


Add "C" for Stainless Steel.

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

## 16791N Male Inverted Swivel 45° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
16791N-4-4	7/16-24	-4	2.05	52	1-1/2	38	0.63	16	7/16
16791N-5-5	1/2-20	-5	2.48	63	1-7/8	48	0.71	18	1/2
16791N-6-6	5/8-18	-6	2.60	66	1-15/16	49	0.96	24	5/8
16791N-8-8	3/4-18	-8	2.85	72	2-1/8	54	0.90	23	3/4
16791N-10-10	7/8-18	-10	3.30	84	2-5/8	67	1.02	43	7/8
16791N-12-12	1-1/16-16	-12	3.64	58	2-13/16	71	1.15	29	1-1/16

Construction: Steel tube, nipple, nut and shell.


Add "C" for Stainless Steel.

E  
Fittings Series 91

F  
Tooling, Equipment & Accessories

G  
General Technical


## 16991N Male Inverted Swivel 90° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
16991N-4-4	7/16-24	-4	1.72	44	1-3/16	30	1.19	30	7/16
16991N-5-5	1/2-20	-5	1.98	50	1-3/8	35	1.65	42	1/2
16991N-5-6	1/2-20	-6	2.03	52	1-7/16	37	1.65	42	1/2
16991N-6-6	5/8-18	-6	2.08	53	1-7/16	37	1.70	43	5/8
16991N-8-8	3/4-18	-8	2.18	55	1-1/2	38	1.87	43	3/4
16991N-10-10	7/8-18	-10	3.02	58	2-5/16	59	2.18	55	7/8
16991N-12-12	1-1/16-16	-12	3.36	85	2-9/16	64	2.51	64	1-1/16

Construction: Steel tube, nipple, nut and shell.  
Add "C" for Stainless Steel.


## 17791N SAE 45° Swivel 45° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
17791N-6-6	5/8-18	3/8	10	2.06	52	1-5/16	33	0.39	10	3/4
17791N-12-12	1-1/16-14	3/4	19	3.07	78	2-7/16	62	0.78	20	1-1/4

Construction: Steel tube, nipple, nut and shell.  
Add "C" for Stainless Steel.

## 17991N SAE 45° Swivel 90° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
17991N-6-6	5/8-18	3/8	10	2.06	52	1-5/16	49	1.19	30	3/4
17991N-12-12	1-1/16-14	3/4	19	2.92	74	2-1/8	54	1.82	46	1-1/4

Construction: Steel tube, nipple, nut and shell.  
Add "C" for Stainless Steel.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 91  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

# 1AL91N A-LOK® Compression



Part Number	Part Number	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#	#							
w/nut & ferrule	w/o nut & ferrules							
1AL91N-4-4C	1AL91N-4-4NC	-4	1.30	33	7/16	11	1/2	9/16
1AL91N-4-5C	1AL91N-4-5NC	-5	1.35	34	7/16	11	1/2	9/16
1AL91N-6-6C	1AL91N-6-6NC	-6	1.53	39	1/2	13	5/8	11/16
1AL91N-8-8C	1AL91N-8-8NC	-8	1.61	41	7/16	11	13/16	7/8
1AL91N-12-12C	1AL91N-12-12NC	-12	1.86	47	1/2	13	1-1/8	1-1/8
1AL91N-16-16C	1AL91N-16-16NC	-16	2.11	58	7/16	11	1-3/8	1-1/2

Construction: Stainless steel nipple, nut, ferrules and shell.


**Note:** Nut part No. is **XNUX-316**;  
Front ferrule part No. is **XFFX-316**;  
Back ferrule part No. is **XBFX-316**.  
X denotes dash size.

Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4230/4233 for Installation Instructions and Replacement Components.

B  
Tubing

C  
Coiled Air Hose & Fittings

# 1P691N CPI® Compression (With Nut and Ferrule)



Part Number	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	inch
#							
w/nut & ferrules							
1P691N-4-4C	-4	1.30	33	7/16	11	1/2	9/16
1P691N-6-6C	-6	1.53	39	1/2	13	5/8	11/16
1P691N-8-8C	-8	1.61	41	7/16	11	13/16	7/8

Construction: Stainless steel nipple and shell.


**Note:** Nut part No. is **XBZ-SS**;  
Ferrule part No. is **XTZ-SS**;  
X denotes dash size.

Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4230/4233 for Installation Instructions and Replacement Components.

D  
Transportation

E  
Fittings Series 91

# 1FN91N Sanitary Flange



Part Number	Hose Size	A		Cutoff Allow. B		C		Flange Size D	
		inch	mm	inch	mm	inch	mm	inch	mm
#									
1FN91N-16-16C	-16	1.96	50	1-1/16	27	0.87	22	1.98	50

Construction: Stainless steel nipple and shell.


F  
Tooling, Equipment & Accessories

G  
General Technical





# 1J191N Female Seal-Lok™ Swivel 90° Elbow Long Drop




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
1J191N-4-4	9/16-18	-4	1.66	42	1-1/16	27	1.80	46	11/16
1J191N-4-5	9/16-18	-5	1.78	45	1-1/16	27	1.80	46	11/16
1J191N-6-5	11/16-16	-5	1.92	49	1-3/16	30	2.13	54	13/16
1J191N-6-6	11/16-16	-6	1.92	49	1-3/16	30	2.13	54	13/16
1J191N-8-6	13/16-16	-6	2.00	51	1-9/16	40	2.51	43	15/16
1J191N-8-8	13/16-16	-8	2.15	58	1-7/16	37	2.51	64	15/16
1J191N-10-10	1-14	-10	1.25	32	1-9/16	40	2.76	70	1-1/8
1J191N-12-12	1-3/16-12	-12	2.65	67	1-13/16	46	3.78	96	1-3/8
1J191N-16-16	1-7/16-12	-16	3.15	80	2-1/4	57	4.50	114	1-1/2

Construction: Steel tube, nipple, nut and shell.

Add "C" for Stainless Steel.

# 1J791N Female Seal-Lok™ Swivel 45° Elbow



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
1J791N-4-4	9/16-18	-4	1.73	44	1-1/4	32	0.41	10	11/16
1J791N-4-6	9/16-18	-6	1.91	49	1-5/16	33	0.41	10	11/16
1J791N-6-6	11/16-16	-6	2.02	51	1-3/8	35	0.43	11	13/16
1J791N-8-8	13/16-16	-8	2.18	55	1-1/2	38	0.59	15	15/16
1J791N-8-10	13/16-16	-8	2.39	61	1-11/16	43	0.59	15	15/16
1J791N-10-10	1-14	-10	2.47	63	1-3/4	44	0.59	43	1-1/8
1J791N-12-12	1-3/16-12	-12	2.74	58	1-15/16	49	0.81	21	1-3/8
1J791N-16-16	1-7/16-12	-16	3.50	89	2-1/2	64	0.94	24	1-5/8

Construction: Steel tube, nipple, nut and shell.

Add "C" for Stainless Steel.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 91  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

## 1J991N Female Seal-Lok™ Swivel 90° Elbow Short Drop




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
1J991N-4-4	9/16-18	-4	1.73	44	1-1/4	32	0.82	21	11/16
1J991N-6-6	11/16-16	-6	1.91	49	1-5/16	33	0.91	23	13/16
1J991N-8-8	13/16-16	-6	2.02	51	1-3/8	35	1.15	29	15/16
1J991N-10-10	1-14	-8	2.18	55	1-1/2	38	1.27	32	1-1/8
1J991N-12-12	1-3/16-12	-8	2.39	61	1-11/16	43	1.85	43	1-3/8
1J991N-16-16	1-7/16-12	-10	2.47	63	1-3/4	44	2.21	56	1-5/8

Construction: Steel tube, nipple, nut and shell.

Add "C" for Stainless Steel.

B  
TubingC  
Coiled Air Hose  
& FittingsD  
Transportation

## 1JC91N Female Seal-Lok™ Swivel Straight



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
1JC91N-4-4	9/16-18	-4	1.46	37	5/8	16	9/16	11/16
1JC91N-6-6	11/16-16	-6	1.62	41	11/16	17	5/8	13/16
1JC91N-8-8	13/16-16	-8	1.93	49	13/16	21	3/4	15/16
1JC91N-10-10	1-14	-10	2.05	52	7/8	22	15/16	1-1/8
1JC91N-12-10	1-3/16-12	-10	2.05	52	1-1/4	32	15/16	1-3/8
1JC91N-12-12	1-3/16-12	-12	2.05	58	1-1/4	32	15/16	1-3/8
1JC91N-16-16	1-7/16-12	-16	2.56	65	1-1/16	27	1-3/8	1-5/8
1JC91N-20-16	1-11/16-12	-16	2.30	58	1-3/8	35	1-5/8	1-7/8
1JC91-20-20	1-11/16-12	-20	2.68	68	1-11/16	43	1-11/16	1-7/8


Construction: Steel nipple, nut and shell.

Add "B" for Brass nipple, nut and shell.

Add "C" for Stainless Steel.

E  
Fittings  
Series 91F  
Tooling, Equipment  
& AccessoriesG  
General Technical


# 1Q191N Ultra Seal



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
			inch	mm	inch	mm	inch
#							
1Q191N-8-8C	7/8-20	-8	1.62	41	15/16	24	1

Construction: Stainless Steel.

# 1TU91N Universal Tube Stub



Part Number	Hose Size	Diameter R	A		Cutoff Allow. B	
			inch	mm	inch	mm
#						
1TU91-2-3C	-3	1/8	1.33	34	7/8	22
1TU91-3-3C	-3	3/16	1.33	34	7/8	22
1TU91N-4-4C	-4	1/4	1.63	41	1-1/16	27
1TU91N-4-5C	-5	1/4	1.70	43	1-1/16	27
1TU91N-6-6C	-6	3/8	1.81	46	1-3/16	30
1TU91N-8-8C	-8	1/2	2.72	58	1-7/16	37
1TU91N-8-10C	-10	1/2	2.14	54	1-7/16	37
1TU91N-10-10C	-10	5/8	2.14	54	1-7/16	37
1TU91N-12-12C	-12	3/4	2.24	57	1-7/16	37
1TU91N-16-16C	-16	1	2.73	69	1-3/4	44

Construction: Stainless Steel.

**NOTE:** Use with A-Lok & CPI nuts, sleeves and adapters. These components are manufactured by Parker's Instrumentation Connectors Division. Refer to catalogs 4230 & 4233 for additional information.

A  
Hose

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

E  
Fittings Series 91


F  
Tooling, Equipment & Accessories

G  
General Technical



A  
Hose

## 19291N Female BSP Parallel Pipe Swivel Straight (60° Cone)




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		H Hex	J Hex
			inch	mm	inch	mm	inch	inch
#								
19291N-8-8	PF-1/2-14	-8	1.99	51	1-5/16	33	27	27
19291N-12-12	PF-3/4-14	-12	2.35	60	1-9/16	40	36	36

Construction: Steel nipple, nut and shell.  
 Add "B" for Brass nipple, nut and shell.  
 Add "C" for Stainless Steel.

B  
Tubing

C  
Coiled Air Hose  
& Fittings

## 1B291N Female BSP Parallel Pipe Swivel - 90° Elbow (60° Cone)



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
1B291N-8-8	PF-1/2-14	-8	2.04	52	1-3/8	35	1.57	40	27
1B291N-12-12	PF-3/4-14	-12	2.93	74	2-1/8	54	2.54	65	36

Construction: Steel nipple, nut and shell.  
 Add "C" for Stainless Steel.

D  
Transportation

E  
Fittings  
Series 91

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# 92 Series Visual Index

A  
Hose

B  
Tubing





C  
Coiled Air Hose & Fittings

D  
Transportation


E  
Fittings Series 92





F  
Tooling, Equipment & Accessories

G  
General Technical

<b>92 Series</b> PERMANENT	<b>111</b>	Ferrule Fix	<b>128</b>	Male Inverted Swivel Straight	<b>167</b>	SAE Male Inverted 45° Elbow	<b>169</b>	SAE Male Inverted 90° Elbow
	 E-65		 E-65		 E-66		 E-66	

## 11192 Ferrule-Fix (Nut and Sleeve Included)



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
<b>#</b>									
11192-3-3	3/8-24	3/16	5	1.37	35	15/16	24	5/8	7/16

Construction: Steel.


Add "C" for Stainless Steel.




"Ferrul-Fix" affords salvaging of bent tube section of combination tube-hose assemblies and quick, easy repair on the job. See page G-29 for Ferrule-Fix installation instructions.

**NOTE:** Nut Part Number is 111-size.  
Sleeve Part Number is 110-size.

Nuts and Ferrules are Manufactured by the Instrumentation Products Division. Refer to Catalog 4230/4233 for additional information.

## 12892 SAE Male Inverted Swivel Straight



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		C		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
<b>#</b>										
12892-3-3C	3/8-24	3/16	5	2.01	55	1-1/2	38	1.25	32	7/16


Construction: Stainless Steel.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose

## 16792 SAE Male Inverted Swivel 45° Elbow




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
16792-3-3C	3/8-24	3/16	5	2.36	60	1-15/16	50	0.62	16	3/8

Construction: Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

## 16992 SAE Male Inverted Swivel 90° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
16992-3-3C	3/8-24	3/16	5	1.45	37	1	25	1.25	32	3/8

Construction: Stainless Steel.

D Transportation









E Fittings Series 92

F Tooling, Equipment & Accessories


G General Technical






# 93N Series Visual Index

<b>93N Series</b> PERMANENT	<b>101</b>	Male Taper Pipe Rigid	<b>106</b>	Female JIC 37° Swivel	<b>137</b>	Female JIC 37° Swivel 45° Elbow	<b>139</b>	Female JIC 37° Swivel 90° Elbow	<b>14K</b>	ANSI B16.5 Flange
										
	E-67		E-67		E-68		E-68		E-68	
<b>1J7</b>		Female Seal-Lok™ 45° Elbow	<b>1J9</b>		Female Seal-Lok™ 90° Elbow	<b>1JC</b>		Female Seal-Lok™ Swivel Straight Short		
										
E-69		E-69		E-69						

## 10193N Female Taper Pipe Rigid








Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
10193N-8-8	1/2-14	1/2	13	2.09	53	1-1/2	38	7/8
10193N-12-12	3/4-14	3/4	19	2.70	69	1-5/8	41	1-1/8
10193N-16-16	1-11-1/2	1	25	3.03	77	1-13/16	46	1-3/8
10193N-20-20	1-1/4-11-1/2	1-1/4	32	3.20	58	1-7/8	48	1-11/16
10193N-24-24	1-1/2-11-1/2	1-1/2	38	3.76	96	2-1/16	52	2
10193N-32-32	2-11-1/2	2	51	3.97	101	2-5/16	59	2-1/2

Construction: Steel nipple, nut and shell.

Add "C" for Stainless Steel.

## 10693N (JIC) 37° Female Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
10693N-6-6	9/16-8	3/8	10	1.69	43	1-3/32	28	3/4	11/16
10693N-8-8	3/4-16	1/2	13	2.02	51	1-3/8	35	7/8	7/8
10693N-10-10	7/8-14	5/8	16	2.51	64	1-11/16	43	1	1
10693N-12-12	1-1/16-12	3/4	19	2.86	73	1-3/4	44	1-1/8	1-1/4
10693N-16-16	1-5/16-12	1	25	3.11	79	1-13/16	46	1-3/8	1-1/2
10693N-20-20	1-5/8-12	1-1/4	32	3.28	83	2	51	1-3/4	2
10693N-24-24	1-7/8-12	1-1/2	38	3.92	58	2-1/4	57	2	2-1/4
10693N-32-32	2-1/2-12	2	51	4.12	105	2-7/16	62	2-1/2	2-7/8

Construction: Steel nipple, nut and shell.

Add "C" for Stainless Steel.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 93  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

### 13793N JIC 37° Swivel 45° Elbow




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
13793N-12-12	1-1/16-12	-12	3.37	86	2-1/4	57	.78	20	1-1/4
13793N-16-16	1-5/16-12	-16	3.71	94	2-5/8	67	.90	23	1-1/2
13793N-20-20	1-5/8-12	-20	4.06	103	2-3/4	70	1.18	43	2
13793N-24-24	1-7/8-12	-24	5.76	146	4-1/4	108	1.47	37	2-1/4

Construction: Steel nipple, nut and shell.  
Add "C" for Stainless Steel.

B Tubing

C Coiled Air Hose & Fittings

### 13993N JIC 37° Swivel 90° Elbow Short Drop




Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		E		J Hex
			inch	mm	inch	mm	inch	mm	inch
#									
13993N-8-8	3/4-16	-8	2.20	56	1-9/16	40	1.09	28	7/8
13993N-10-10	7/8-14	-10	2.41	61	1-11/16	43	1.23	31	1
13993N-12-12	1-1/16-12	-12	3.28	83	2-3/16	56	1.82	46	1-1/4
13993N-16-16	1-5/16-12	-16	3.71	94	2-1/2	64	2.14	54	1-1/2
13993N-20-20	1-5/8-12	-20	3.89	99	2-9/16	65	2.57	43	2
13993N-24-24	1-7/8-12	-24	5.72	58	4-1/4	108	3.17	81	2-1/4

Construction: Steel nipple, nut and shell.  
Add "C" for Stainless Steel.

D Transportation

E Fittings Series 93

### 14K93N ANSI B16.5 Flange



Part Number	Hose I.D.		Flange Diameter		A		Cutoff Allow. B		Bolt Spacing E	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
#										
14K93N-8-8	1/2	13	3-1/2	89	2.03	52	1-3/8	35	2-3/8	60
14K93N-12-12	3/4	19	3-7/8	98	2.70	69	1-3/4	44	2-3/4	70
14K93N-16-16	1	25	4-1/4	108	2.84	72	1-5/8	41	3-1/8	79
14K93N-20-20	1-1/4	32	4-5/8	117	2.98	76	1-5/8	41	3-1/2	89
14K93N-24-24	1-1/2	38	5	127	3.45	88	1-3/4	44	3-7/8	98
14K93N-32-32	2	51	6	152	3.62	58	2	51	4-3/4	121


Construction: Steel nipple and shell, stainless steel flange.  
NOTE: Also available in PAGE Fittings.

F Tooling, Equipment & Accessories

G General Technical



# 1JC93N Seal-Lok™ Swivel Straight Short




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex		J Hex	
		inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
#											
1JC93N-12-12	1-3/16-12	3/4	19	2.30	58	1-3/8	35	1-3/8		1-3/8	
1JC93N-16-16	1-7/16-12	1	25	2.61	66	1-3/8	35	1-3/8		1-5/8	
1JC93N-20-20	1-11/16-12	1-1/4	32	2.65	67	1-5/16	33	1-7/8		1-7/8	

Construction: Steel nipple, nut and shell.

Add "C" for Stainless Steel.

NOTE: Also available in PAGE Fittings.

# 1J793N Seal-Lok™ 45° Elbow




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J793N-20-20	1-11/16-12	1-1/4	32	4.25	108	2-15/16	75	1.00	25	1-7/8

Construction: Steel nipple, tube, nut and shell.

Add "C" for Stainless Steel.

NOTE: Also available in PAGE Fittings.

# 1J993N Seal-Lok™ 90° Elbow Short Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J993N-20-20	1-11/16-12	1-1/4	32	4.36	111	3-1/16	78	2.51	64	1-7/8

Construction: Steel nipple, tube, nut and shell.

Add "C" for Stainless Steel.

NOTE: Also available in PAGE Fittings.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series 94/95  
 F Tooling, Equipment & Accessories  
 G General Technical


# 94/95 Series Visual Index

**94 Series**

PERMANENT

**106**

SAE (JIC) 37° Female Swivel




E-70

**95 Series**

PERMANENT


**106**




SAE (JIC) 37° Female Swivel



E-70


## 10694 SAE (JIC) 37° Female Swivel






Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
			inch	mm	inch	mm	
#							
10694-6-6	9/16-18	-6	1.76	45	15/16	24	11/16
10694-8-8	3/4-16	-8	2.09	53	1-3/16	30	7/8
10694-10-10	7/8-14	-10	2.30	58	1-5/16	33	1
10694-12-12	1-1/16-12	-12	2.45	62	1-5/16	33	1-1/4
10694-16-16	1-5/16-12	-16	2.72	69	1-7/16	37	1-1/2

Construction: Steel nipple, nut and shell.  
 Add "C" for Stainless Steel.

















## 10695 SAE (JIC) 37° Female Swivel



Part Number	Thread Size	Hose Size	A		Cutoff Allow. B		J Hex
			inch	mm	inch	mm	
#							
10695-4-4	7/16-20	-4	1.76	45	15/16	24	11/16
10695-6-6	9/16-18	-6	2.09	53	1-3/16	30	7/8
10695-8-8	3/4-16	-8	2.30	58	1-5/16	33	1
10695-12-12	1-1/16-12	-12	2.45	62	1-5/16	33	1-1/4
10695-16-16	1-5/16-12	-16	2.72	69	1-7/16	37	1-1/2

Construction: Steel nipple, nut and shell.  
 Add "C" for Stainless Steel.

# PAGE Fittings Visual Index

<b>PAGE Fittings</b> <b>PERMANENT</b>	<b>CL-S</b> Female Cam & Groove  E-73	<b>E-S</b> Male Cam & Groove  E-73	<b>FBS-S</b> Female Sanitary Bevel Seat  E-73	<b>FIL-S</b> Female I-Line® Sanitary  E-74	<b>FJX-S</b> Female JIC 37° Swivel  E-76
	<b>FORFS-S</b> Female Seal-Lok™ Swivel Short  E-76	<b>FP-S</b> Female NPTF Pipe Rigid  E-75	<b>MBS-S</b> Male Sanitary Bevel Seat  E-74	<b>MIL-S</b> Male I-Line® Sanitary  E-74	<b>MP-S</b> Male NPTF Pipe Rigid  E-75
	<b>MSAN-S</b> Mini Sanitary Flange  E-78	<b>PF</b> ANSI Flange  E-77	<b>PLCF-S</b> Female A-Lok® Compression  E-76	<b>SAN-S</b> Sanitary Flange & Step Downs  E-78	<b>SFR-S</b> Flange Retainer  E-77
	<b>TUBE-S</b> A-Lok® Male Stand pipe-Rigid "V" Notch  E-77				

**NOTE:**

**The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed.**

Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

*For detailed ordering information, please consult price list or contact Parflex® Division.*



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series PAGE  
 F Tooling, Equipment & Accessories  
 G General Technical

# PAGE Fitting Collars - Size & Style

<b>PAGE</b> <b>COLLARS</b>  <b>By Size</b>	Hose	Collar # Size	04	06	08	12	16	20	24	32	40	48	64	
	STW STB	ST300	ST300	ST300	ST300	ST300	ST300	ST300	ST300	ST300				
	SCW SCB	SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300				
	PCW PCB	PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300				
	SCWV SCBV	SC300			SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300	SC300	
	PCWV PCBV	PC300			PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300	PC300	
	SBFW SBFB	SBF300		SBF300	SBF300	SBF300	SBF300		SBF300					
	RCTW RCTB	RC300			RC300	RC300	RC300	RC300	RC300	RC300	RC300	RC300	RC300	

**Inserts & Collars Sold Separately**

Examples:

If you need a Female JIC Swivel Fitting for a 08-SCW Hose (1/2" Convoluted), place an order for (1) 08-08 FJX-S and (1) 08-SC300.

If you need a Male Pipe Fitting for a 12-RCTW Hose, place an order for (1) 12-12 MP-S and (1) 12-RC300.

**By Style**

Size	ST300	SC300	PC300	SBF300	RC300
	For use with STW/STB	For use with SCW/SCB, SCWV/SCBV	For use with PCW/PCB, PCWV/PCBV	For use with SBFW/SBFB	For use with RCTW/RCTB
1/4"	04-ST300	04-SC300	04-PC300	—	—
3/8"	06-ST300	06-SC300	06-PC300	06-SBF300	—
1/2"	08-ST300	08-SC300	08-PC300	08-SBF300	08-RC300
3/4"	12-ST300	12-SC300	12-PC300	12-SBF300	12-RC300
1"	16-ST300	16-SC300	16-PC300	16-SBF300	16-RC300
1-1/4"	20Z-ST300	20-SC300	20-PC300	—	20-RC300
1-1/2"	24Z-ST300	24-SC300	24-PC300	24-SBF300	24-RC300
2"	—	32-SC300	32-PC300	—	32-RC300
3"	—	48-SC300	48-PC300	—	48-RC300
4"	—	64-SC300	64-PC300	—	64-RC300

Construction: Stainless Steel.  
 Note: also available in carbon steel "CS".

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.




For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series PAGE  
 F Tooling, Equipment & Accessories  
 G General Technical



## CL-S Female Cam & Groove




Part Number	Hose I.D.		A		E	
	inch	mm	inch	mm	inch	mm
#	⊙					
16-16CL-S	1	25	2.64	67	1.44	37
20-20CL-S	1-1/4	32	3.00	76	1.78	45
24-24CL-S	1-1/2	38	3.39	86	2.10	53
32-32CL-S	2	51	3.85	98	2.48	63
48-48CL-S	3	76	5.25	133	3.60	91
64-64CL-S	4	102	7.00	178	4.70	119

Construction: Stainless Steel.

Note: Also available as encapsulated female cam under part number TEC-S and TECL-S.


## E-S Male Cam & Groove



Part Number	Hose I.D.		A		E	
	inch	mm	inch	mm	inch	mm
#	⊙					
12-12E-S	3/4	19	2.60	66	1.26	32
16-16E-S	1	25	2.91	74	1.44	37
20-20E-S	1-1/4	32	3.64	93	1.78	45
24-24E-S	1-1/2	38	4.03	102	2.10	53
32-32E-S	2	51	4.75	121	2.48	63
48-48E-S	3	76	5.75	146	3.60	91
64-64E-S	4	102	5.88	149	4.70	119

Construction: Stainless Steel.

## FBS-S Female Sanitary Bevel Seat



Part Number	Acme Thread	Hose I.D.		A	
		inch	mm	inch	mm
#		⊙			
16-16FBS-S	1-1/2-8	1	25	2.74	70
24-24FBS-S	2-8	1-1/2	38	3.41	87
32-32FBS-S	2-1/2-8	2	51	3.94	100
40-40FBS-S	3-8	2-1/2	64	4.37	110
48-48FBS-S	3-1/2-8	3	76	4.85	123
64-64FBS-S	4-5/8-6	4	102	5.24	133

Construction: Stainless Steel.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



E-73

A  
Hose

B  
Tubing


C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings Series PAGE


F  
Tooling, Equipment  
& Accessories

G  
General Technical

A  
Hose**MBS-S Male Sanitary Bevel Seat**


Part Number	Acme Thread	Hose I.D.		A	
		inch	mm	inch	mm
<b>#</b>					
16-16MBS-S	1-1/2-8	1	25	2.74	70
24-24MBS-S	2-8	1-1/2	38	3.41	87
32-32MBS-S	2-1/2-8	2	51	3.94	100
40-40MBS-S	3-8	2-1/2	64	4.37	110
48-48MBS-S	3-1/2-8	3	76	4.85	123
64-64MBS-S	4-5/8-6	4	102	5.24	133

Construction: Stainless Steel.

B  
TubingC  
Coiled Air Hose  
& Fittings**FIL-S Female I-Line® Sanitary**

Part Number	Hose I.D.		A		Flange Size C		D	
	inch	mm	Inch	mm	Inch	mm	Inch	mm
<b>#</b>								
16-16FIL-S	1	25	2.60	66	1.25	32	2.00	51
24-24FIL-S	1-1/2	38	3.43	87	1.76	45	2.00	51
32-32FIL-S	2	51	4.23	107	2.26	57	2.64	67
40-40FIL-S	2-1/2	64	4.42	112	2.76	70	3.31	84
48-48FIL-S	3	76	4.84	123	3.31	84	3.87	98

Construction: Stainless Steel.

D  
TransportationE  
Fittings  
Series PAGE**MIL-S Male I-Line® Sanitary**

Part Number	Hose I.D.		A		Flange Size C		D	
	inch	mm	Inch	mm	Inch	mm	Inch	mm
<b>#</b>								
16-16MIL-S	1	13	2.60	66	1.25	32	2.00	51
24-24MIL-S	1-1/2	19	3.43	87	1.76	45	2.00	51
32-32MIL-S	2	25	4.23	107	2.26	57	2.64	67
40-40MIL-S	2-1/2	64	4.42	112	2.76	70	3.31	84
48-48MIL-S	3	76	4.84	123	3.31	84	3.87	98

Construction: Stainless Steel.


F  
Tooling, Equipment  
& AccessoriesG  
General Technical

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.



For detailed ordering information, please consult price list or contact Parflex® Division.


## FP-S Female NPTF Pipe-Rigid



Part Number	Thread Size	Hose I.D.		A		H Hex
		inch	mm	inch	mm	inch
#						
04-04FP-S	1/4-18	1/4	6	1.63	41	3/4
06-06FP-S	3/8-18	3/8	10	1.73	44	7/8
08-08FP-S	1/2-14	1/2	13	2.25	57	1-1/16
12-12FP-S	3/4-14	3/4	19	2.60	66	1-5/16
16-16FP-S	1-11 1/2	1	25	2.85	72	1-5/8
20-20FP-S	1 1/4-11 1/2	1-1/4	32	3.50	89	2
24-24FP-S	1 1/2-11 1/2	1-1/2	38	3.63	92	2-3/8
32-32FP-S	2-11 1/2	2	51	4.25	108	2-7/8

Construction: Stainless Steel.

## MP-S Male NPTF Pipe-Rigid



Part Number	Thread Size	Hose I.D.		A		H Hex
		inch	mm	inch	mm	inch
#						
04-04MP-S	1/4-18	1/4	6	1.63	41	9/16
06-06MP-S	3/8-18	3/8	10	1.76	45	11/16
08-08MP-S	1/2-14	1/2	13	2.34	59	7/8
12-12MP-S	3/4-14	3/4	19	2.59	66	1-1/8
16-16MP-S	1-11 1/2	1	25	3.00	76	1-3/8
20-20MP-S	1 1/4-11 1/2	1-1/4	32	3.39	86	1-3/4
24-24MP-S	1 1/2-11 1/2	1-1/2	38	3.89	99	2
32-32MP-S	2-11 1/2	2	51	4.58	116	2-1/2
40-40MP-S	2-1/2 8	2-1/2	64	5.28	134	3
48-48MP-S	3-8	3	76	5.93	151	3-3/4
64-64MP-S	4-8	4	102	6.82	173	4-5/8

Construction: Stainless Steel.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



E-75

A  
Hose

B  
Tubing


C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings  
Series PAGE


F  
Tooling, Equipment  
& Accessories

G  
General Technical

A  
Hose**FJX-S Female JIC 37° Swivel**


Part Number	Thread Size	Hose I.D.		A		H Hex
		inch	mm	inch	mm	inch
#						
04-04FJX-S	7/16-20	1/4	6	1.44	37	9/16
06-06FJX-S	9/16-18	3/8	10	1.65	42	11/16
08-08FJX-S	3/4-16	1/2	13	2.13	54	7/8
12-12FJX-S	1-1/16-12	3/4	19	2.54	65	1-1/4
16-16FJX-S	1-5/16-12	1	25	2.76	70	1-1/2
20-20FJX-S	1-5/8-12	1-1/4	32	3.25	83	2
24-24FJX-S	1-7/8-12	1-1/2	38	3.73	95	2-1/4
32-32FJX-S	2-1/2-12	2	51	4.55	116	2-7/8
40-40FJX-S	3-12	2-1/2	64	4.76	121	3-3/8

Construction: Stainless Steel.

B  
TubingC  
Coiled Air Hose  
& Fittings**FORFS-S Female Seal-Lok® Swivel-Short**

Part Number	Thread Size	Hose I.D.		A		H Hex	J Hex
		inch	mm	inch	mm	inch	inch
#							
04-04FORFS-S	9/16-18	1/4	6	1.50	38	9/16	11/16
06-06FORFS-S	11/16-16	3/8	10	1.85	47	11/16	13/16
08-08FORFS-S	13/16-16	1/2	13	2.00	51	13/16	15/16
12-12FORFS-S	1-3/16-12	3/4	19	2.30	58	1-1/8	1-3/8
16-16FORFS-S	1-7/16-12	1	25	2.50	64	1-3/8	1-5/8
24-24FORFS-S	2-12	1-1/2	38	3.98	101	2	2-1/4

Construction: Stainless Steel.

D  
TransportationE  
Fittings  
Series PAGE**PLCF-S Female A-LOK® Compression (With Nut & Ferrules)**


Part Number	Thread Size	Hose I.D.		A		H Hex	J Hex
		inch	mm	inch	mm	inch	inch
#							
04-04PLCF-S	7/16-20	1/4	6	1.52	39	9/16	9/16
06-06PLCF-S	9/16-20	3/8	10	1.63	41	11/16	11/16
08-08PLCF-S	3/4-20	1/2	13	2.05	52	7/8	7/8
12-12PLCF-S	1-20	3/4	19	2.30	58	1-1/8	1-1/8
16-16PLCF-S	1-5/16-20	1	25	2.57	65	1-3/8	1-1/2

Construction: Stainless Steel.

F  
Tooling, Equipment  
& AccessoriesG  
General Technical

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.


## TUBE-S A-LOK® Male Standpipe-Rigid with “V” Notch



Part Number	Diameter R		Hose I.D.		A		C		D		H Hex
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch
<b>#</b>	/		⊙								⬡
04-04TUBE-S	1/4	6	1/4	6	1.75	45	.18	5	.66	17	7/16
06-06TUBE-S	3/8	10	3/8	10	2.06	52	.25	6	.85	2	5/8
08-08TUBE-S	1/2	13	1/2	13	2.56	65	.34	9	.97	25	3/4
12-12TUBE-S	3/4	19	3/4	19	2.86	73	.40	10	1.02	26	1-1/8
16-16TUBE-S	1	25	1	25	3.34	85	.52	13	1.30	33	1-3/8
20-20TUBE-S	1-1/4	32	1-1/4	32	4.05	10	.50	13	1.75	45	1-3/4

Construction: Stainless Steel.


## PF ANSI B16.5 Flange



Carbon Steel (Epoxy Coated)	316 Stainless Steel	304 Stainless Steel	Flange Diameter A		Hose I.D.		Bolt Spacing B	
<b>#</b>	<b>#</b>	<b>#</b>	/		⊙			
Flange	Flange	Flange	inch	mm	inch	mm	inch	mm
08-PF150	08-PF156	08-PF154	3-1/2	89	1/2	13	2-3/8	60
12-PF150	12-PF156	12-PF154	3-7/8	98	3/4	19	2-3/4	70
16-PF150	16-PF156	16-PF154	4-1/4	108	1	25	3-1/8	79
20-PF150	20-PF156	20-PF154	4-5/8	117	1-1/4	32	3-1/2	89
24-PF150	24-PF156	24-PF154	5	127	1-1/2	38	3-7/8	98
32-PF150	32-PF156	32-PF154	6	152	2	51	4-3/4	120
40-PF150	40-PF156	40-PF154	7	178	2-1/2	64	5-1/2	140
48-PF150	48-PF156	48-PF154	7-1/2	191	3	76	6	152
64-PF150	64-PF156	64-PF154	9	229	4	102	7-3/4	197

Note: Also available in 300 lb. flange and other materials. Contact Customer Service for options.

## SFR-S Flange Retainer



Part Number	Flange Diameter		Hose I.D.		A		Bolt Spacing E	
<b>#</b>	⊙		⊙					
	inch	mm	inch	mm	inch	mm	inch	mm
08-08SFR-S	3-1/2	89	1/2	13	2.30	58	2-3/8	60
12-12SFR-S	3-7/8	98	3/4	19	2.60	66	2-3/4	70
16-16SFR-S	4-1/4	108	1	25	3.00	76	3-1/8	79
20-20SFR-S	4-5/8	117	1-1/4	32	3.25	83	3-1/2	89
24-24SFR-S	5	127	1-1/2	38	3.65	93	3-7/8	98
32-32SFR-S	6	152	2	51	4.25	108	4-3/4	120
40-40SFR-S	7	178	2-1/2	64	5.00	127	5-1/2	140
48-48SFR-S	7-1/2	191	3	76	5.50	140	6	152
64-64SFR-S	9	229	4	102	7.00	178	7-3/4	197

Construction: Stainless Steel.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

For detailed ordering information, please consult price list or contact Parflex® Division.


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

E-77

A  
HoseB  
TubingC  
Coiled Air Hose  
& FittingsD  
TransportationE  
Fittings  
Series PAGEF  
Tooling, Equipment  
& AccessoriesG  
General Technical

A Hose

# MSAN-S Mini Sanitary Flange



Part Number	Hose I.D.		A		Flange Size D	
	inch	mm	inch	mm	inch	mm
#	⊙					
04-04MSAN-S	1/4	6	1.47	37	.98	25
04-08MSAN-S	1/4	6	1.50	38	.98	25
06-06MSAN-S	3/8	10	1.53	39	.98	25
06-08MSAN-S	3/8	10	1.53	39	.98	25
06-12MSAN-S	3/8	10	1.66	42	.98	25
08-08MSAN-S	1/2	13	1.90	48	.98	25
08-12MSAN-S	1/2	13	1.94	49	.98	25
12-12MSAN-S	3/4	19	2.16	55	.98	25
16-16MSAN-S	1	25	2.27	58	.98	25

Construction: Stainless Steel. Meets ASME-BPE-2009.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed.


NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed. Length calculations for PAGE hose assemblies are typically made sealing surface to sealing surface per the NAHAD Fluoropolymer Hose Assembly Specification Guidelines unless otherwise requested by customer at time of order.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

# SAN-S Sanitary Flange & Step-Downs



Part Number	Hose I.D.		A		Flange Size D	
	inch	mm	inch	mm	inch	mm
#	⊙					
08-08SAN-S	1/2	13	2.11	54	1.98	50
08-16SAN-S	1/2	13	2.11	54	1.98	50
08-24SAN-S	1/2	13	2.11	54	1.98	50
12-12SAN-S	3/4	19	2.32	59	1.98	50
16-16SAN-S	1	25	2.45	62	1.98	50
20-20SAN-S	1-1/2	38	3.10	79	1.98	50
06-24SAN-S	3/8	10	1.34	34	1.98	50
12-24SAN-S	3/4	19	2.32	59	1.98	50
16-24SAN-S	1	25	2.32	59	1.98	50
24-24SAN-S	2	51	3.67	93	2.50	64
24-32SAN-S	1-1/4	32	3.10	80	2.50	64
32-40SAN-S	2	51	3.74	95	3.00	76
32-32SAN-S	2-1/2	64	4.00	102	3.00	76
32-40SAN-S	2	51	3.74	95	3.00	76
48-48SAN-S	3	76	4.50	114	3.50	89
40-48SAN-S	2-1/2	64	4.09	104	3.50	89
64-64SAN-S	4	102	4.75	121	4.70	119
48-64SAN-S	3	76	4.21	107	4.70	119,4

Construction: Stainless Steel. Meets ASME-BPE-2009.

NOTE: The PAGE fitting call-out does not follow traditional Parker fitting nomenclature. The end size and hose size are reversed.

E Fittings Series PAGE



F Tooling, Equipment & Accessories

G General Technical










# BA Series Visual Index

<b>BA Series</b>  FIELD ATTACHABLE	<b>201</b>	Male Taper Pipe Rigid	<b>206</b>	SAE (JIC) 37° Swivel
	 E-79		 E-79	


## 201BA Male Taper Pipe Rigid








Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
201BA-4-4	1/4-18	1/4	6	2.43	62	1-1/4	32	5/8	3/4
201BA-6-6	3/8-18	3/8	10	2.62	67	1-1/4	32	3/4	7/8

Construction: Steel.

## 206BA Female SAE (JIC) 37° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
#										
206BA-6-4	9/16-18	1/4	6	2.62	67	1-3/8	35	11/16	11/16	3/4
206BA-6-6	9/16-18	3/8	10	2.76	70	1-3/8	35	3/4	3/4	7/8
206BA-8-8	3/4-16	1/2	13	3.26	83	1-11/16	43	7/8	7/8	1-1/16

Construction: Steel.




NOTE: Size -8 incorporate a dual seat.

For detailed ordering information, please consult price list or contact Parflex® Division.








A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series BA  
 F Tooling, Equipment & Accessories  
 G General Technical

# BU Series Visual Index

<b>BU Series</b>  <b>FIELD ATTACHABLE</b>	<b>201</b> Male Taper Pipe Rigid	<b>206</b> SAE (JIC) 37° Swivel	<b>213</b> Male Taper Pipe Swivel
	 E-80	 E-80	 E-80


## 201BU Male Taper Pipe Rigid








Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
<b>#</b>									
201BU-2-2	1/8-27	1/8	3	1.50	38	1	25	7/16	7/16

Construction: Steel.

## 206BU Female SAE (JIC) 37° Swivel









Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
<b>#</b>										
206BU-3-2	3/8-24	1/8	3	1.72	44	1-3/16	30	1/2	9/16	7/16
206BU-4-2	7/16-20	1/8	3	1.77	45	1-3/16	30	9/16	9/16	7/16
206BU-4-3	7/16-20	1/8	3	1.89	48	1-1/16	27	9/16	9/16	7/16

Construction: Steel.

NOTE: Size -4 incorporate a dual seat.

## 213BU Male Taper Pipe Swivel












Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
<b>#</b>										
213BU-2-2	1/8-27	1/8	3	2.07	53	1-1/2	38	1/2	1/2	7/16

Construction: Steel.

**WARNING:** Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling. Not recommended for use in CNG applications.

# CY Series Visual Index

<b>CY Series</b> <b>PERMANENT</b>	<b>101</b> Male Taper Pipe Rigid  E-82	<b>102</b> Female Pipe Thread  E-82	<b>106</b> JIC 37° Female Swivel  E-82	<b>113</b> Male Pipe Swivel  E-83	<b>139</b> Female JIC 37° Swivel 90° Elbow  E-83	
	<b>1GK</b> Bulkhead w/Zerk Port Integrated  E-83	<b>1J9</b> Female Seal-Lok™ 90° Elbow  E-84	<b>1JC</b> Female Seal-Lok™ Swivel Straight Short  E-84	<b>1LM</b> Male Grease  E-84		

A  
Hose

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

E  
Fittings Series CY

F  
Tooling, Equipment & Accessories


G  
General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



A  
Hose

## 101CY Male Taper Pipe Rigid




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
101CY-2-2	1/8-27	1/8	3	1.31	33	13/16	21	7/16
101CY-2-3	1/8-27	3/16	5	1.72	44	15/16	24	1/2
101CY-4-2	1/4-18	1/8	3	1.51	38	1	25	9/16
101CY-4-3	1/4-18	3/16	5	1.91	49	1-1/8	29	9/16

Construction: Steel.  
Add "C" for Stainless Steel.

B  
Tubing

C  
Coiled Air Hose & Fittings

## 102CY Female Pipe Thread




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
102CY-2-3	1/8-27	3/16	5	1.97	50	1-1/16	27	1/2

Construction: Steel.  
Add "C" for Stainless Steel.

D  
Transportation

## 106CY Female SAE (JIC) 37° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
106CY-2-2	Flare 5/16-24	1/8	3	1.52	39	15/16	24	7/16	7/16
106CY-3-2	Flare 3/8-24	1/8	3	1.55	39	1	25	1/2	1/2
106CY-4-2	Flare 7/16-20	1/8	3	1.58	40	1	25	7/16	9/16
106CY-4-3	Flare 7/16-20	3/16	5	1.98	50	1-1/16	27	9/16	9/16


Construction: Steel.  
Add "C" for Stainless Steel.  
NOTE: Sizes -4 incorporate a dual seat.

E  
Fittings Series CY

F  
Tooling, Equipment & Accessories

G  
General Technical

## 113CY Male Pipe Swivel\*



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
113CY-2-2	1/8-27	1/8	3	1.89	48	1-5/16	33	1/2	1/2
113CY-2-3	1/8-27	3/16	3	2.29	58	1-3/8	35	1/2	1/2


Construction: Steel.

Add "C" for Stainless Steel.

\*NOTE: For use with petroleum based fluids.

**WARNING:** Fittings allow minor movement to relieve stress on hose but are not recommended for continued or extensive swiveling. Not recommended for use in CNG applications.

## 139CY Female JIC 37° Swivel 90° Elbow Short Drop




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
139CY-4-2	7/16-20	1/8	3	1.61	41	1-1/8	29	0.83	21	9/16
139CY-4-3	7/16-20	3/16	5	1.90	48	1	25	0.83	21	9/16

Construction: Steel.

Add "C" for Stainless Steel.

## 1GKCY Bulkhead with Integrated Zerk Port



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1GKCY-2-2	1/8-27 NPSM Male w/1/4-28 UNF Female	1/8	3	1.45	37	7/8	22	1/2
1GKCY-2-3	1/8-27 NPSM Male w/1/4-28 UNF Female	3/16	5	1.86	47	15/16	24	1/2
1GKCY-2-2-L77*	1/8-27 NPSM Male w/1/4-28 UNF Female	1/8	3	1.71	43	1-1/4	32	1/2
1GK91N-2-4**	1/8-27 NPSM Male w/1/4-28 UNF Female	3/16	5	1.46	37	15/16	24	1/2


Construction: Steel.

Add "C" for Stainless Steel.

**NOTE:** \*Long bulkhead for use with plates under 3/4" thick. Uses 2GK-NUT, sold separately.  
\*\*Use with 919 hoses.

A  
Hose

## 1JCCY Female Seal-Lok™ Swivel Straight Short




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1JCCY-4-2	9/16-18	1/8	3	1.29	33	3/4	19	9/16	11/16

Construction: Steel.  
Add "C" for Stainless Steel.

B  
Tubing

C  
Coiled Air Hose & Fittings

## 1J9CY Female O-Ring Face Seal Swivel Short Drop




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		J Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J9CY-4-2	9/16-18	1/8	3	1.81	46	1-1/4	32	.83	21	11/16

Construction: Steel.  
Add "C" for Stainless Steel.

D  
Transportation

E  
Fittings Series CY

## 1LMCY Male Grease



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1LMCY-2-2	1/4-28	1/8	3	1.26	32	11/16	17	3/8





Construction: Steel.  
Add "C" for Stainless Steel.

F  
Tooling, Equipment & Accessories


G  
General Technical






# SF Series Visual Index

<b>SF Series</b>  <b>PERMANENT</b>	<b>101</b>	Male Taper Pipe Rigid	<b>106</b>	JIC 37° Swivel	<b>1JS</b>	Female Seal-Lok™ Swivel Long	<b>1JB</b>	Male Seal-Lok™ Bulkhead w/O-Ring
	 E-85		 E-85		 E-86		 E-86	


## 101SF Male Taper Pipe Rigid







Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
<b>#</b>								
101SF-2-1	1/8-27	.090	2.3	1.13	29	3/4	19	7/16

Construction: Steel

## 106SF JIC 37° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
<b>#</b>									
106SF-2-1	5/16-24	.090	2.3	1.37	35	15/16	24	7/16	1/2

Construction: Steel


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series SF  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

# 1JSSF Female Seal-Lok™ Swivel Long



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1JSSF-4-1	9/16-18	.090	2.3	1.50	88	3/4	19	11/16


Construction: Steel

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

# 1JBSF Male Seal-Lok™ Bulkhead with O-Ring



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1JBSF-4-1	9/16-18	.090	2.3	2.06	52	1-11/16	43	5/8

Construction: Steel

**NOTE:** Bulkhead Locknut sold separately.


































WLNL Locknuts are Manufactured by the Tube Fittings Division. Refer to Catalog 4300 for additional information.

E  
Fittings Series SF

F  
Tooling, Equipment & Accessories

G  
General Technical

# HY Series Visual Index

<b>HY Series</b> <b>PERMANENT</b>	<b>101</b> Male NPTF Pipe Rigid  E-88	<b>102</b> Female NPTF Pipe Rigid  E-89	<b>103</b> Male (JIC) 37°  E-89	<b>105</b> Male SAE Str. Thread Rigid w/o-ring  E-90	<b>106</b> SAE (JIC) 37° Swivel  E-91
	<b>107</b> Female NPSM Pipe Swivel (60° cone)  E-92	<b>108</b> Female SAE 45° Swivel  E-92	<b>10G</b> Male SAE Str. Thread Swivel w/o-ring  E-93	<b>10L</b> Male SAE Str. Thread Swivel 90° Elbow  E-93	<b>111</b> Male Ferulok Flare-less Rigid  E-94
	<b>113</b> Male NPTF Pipe Swivel  E-94	<b>11L</b> Male NPTF Pipe Swivel 90° Elbow  E-95	<b>128</b> Male Inverted SAE 45° Swivel  E-95	<b>129</b> Male Inverted SAE 90° Swivel  E-96	<b>134</b> Male Standpipe Rigid  E-96
	<b>137</b> FM SAE (JIC) 37° Swivel 45° Elbow  E-96	<b>139</b> FM SAE (JIC) 37° Swivel 90° Elbow  E-97	<b>13D</b> Male Standpipe Metric S Rigid  E-100	<b>141</b> JIC 37° Swivel 90° Elbow Long  E-97	<b>167</b> SAE Male Inverted 45° Elbow  E-98
	<b>169</b> SAE Male Inverted 90° Elbow  E-98	<b>177</b> SAE 45° Swivel 45° Elbow  E-98	<b>179</b> SAE 45° Swivel 90° Elbow  E-99	<b>193</b> Female (JIC) 37° Swivel 90° Elbow BT  E-99	<b>1D0</b> Male Metric L Rigid  E-99
	<b>1D9</b> Male BSPP  E-100	<b>1GJ</b> Female Grease Connection - SPL  E-100	<b>1J0</b> Male Seal-Lok™ Rigid Str. w/O-Ring  E-103	<b>1J1</b> Seal-Lok™ 90° Elbow Long  E-101	<b>1J7</b> Seal-Lok™ 45° Elbow  E-101
	<b>1J9</b> Seal-Lok™ 90° Elbow  E-102	<b>1JC</b> Seal-Lok™ Swivel Short  E-102	<b>1JS</b> Seal-Lok™ Swivel Long  E-103		


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

# 101HY Male NPTF Pipe Rigid



B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings Series HY

F Tooling, Equipment & Accessories

G General Technical

Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
101HY-2-4	1/8x27	1/4	6	2.34	59	1.00	25	5/8
101HY-4-4	1/4x18	1/4	6	2.53	64	1.19	30	9/16
101HY-4-5	1/4x18	5/16	8	2.56	65	1.22	31	11/16
101HY-4-6	1/4x18	3/8	10	2.55	65	1.19	30	11/16
101HY-6-4	3/8x18	1/4	6	2.53	64	1.19	30	3/4
101HY-6-5	3/8x18	5/16	8	2.56	65	1.22	31	3/4
101HY-6-6	3/8x18	3/8	10	2.55	65	1.19	30	3/4
101HY-6-8	3/8x18	1/2	13	2.72	69	1.38	35	7/8
101HY-8-4	1/2x14	1/4	6	2.72	69	1.38	35	7/8
101HY-8-6	1/2x14	3/8	10	2.73	69	1.38	35	7/8
101HY-8-7	1/2x14	13/32	10	2.73	69	1.38	35	7/8
101HY-8-8	1/2x14	1/2	13	2.91	74	1.41	40	7/8
101HY-8-10	1/2x14	5/8	16	2.94	75	1.59	40	1-1/8
101HY-8-12	1/2x14	3/4	19	3.08	78	1.50	38	1-1/4
101HY-12-8	3/4x14	1/2	13	2.91	74	1.56	40	1-1/16
101HY-12-10	3/4x14	5/8	16	2.98	76	1.59	40	1-1/8
101HY-12-12	3/4x14	3/4	19	3.08	78	1.50	38	1-1/4
101HY-12-16	3/4x14	1	25	3.23	82	1.63	41	1-3/8
101HY-16-12	1x11-1/2	3/4	19	3.27	83	1.69	43	1-3/8
101HY-16-14	1x11-1/2	7/8	22	3.27	83	1.78	43	1-3/8
101HY-16-16	1x11-1/2	1	25	3.42	87	1.81	46	1-3/8
101HY-20-20	1-1/4x11-1/2	1-1/4	32	3.84	98	2.00	51	1-3/4

Construction: Steel

Add "C" for Stainless Steel.


**NOTE:** Stainless steel fittings must be assembled with Karrykrimp 2, Phastkrimp™, Superkrimp or Parkrimp 2. See CrimpSource for more information.



For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)


# 102HY Female NPTF Pipe Rigid



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
102HY-2-4	1/8x27	1/4	6	2.34	59	1.00	25	5/8
102HY-4-4	1/4x18	1/4	6	2.47	63	1.13	29	11/16
102HY-4-6	1/4x18	3/8	10	2.48	63	1.13	29	11/16
102HY-6-4	3/8x18	1/4	6	2.47	63	1.13	29	7/8
102HY-6-6	3/8x18	3/8	10	2.48	63	1.13	29	7/8
102HY-8-6	1/2x14	3/8	10	2.75	70	1.41	36	1
102HY-8-8	1/2x14	1/2	13	2.84	72	1.50	38	1
102HY-12-12	3/4x14	3/4	19	2.83	72	1.25	32	1-1/4
102HY-16-16	1x11-1/2	1	25	3.27	83	1.66	42	1-1/2

Construction: Steel

# 103HY Male JIC 37° Rigid



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
103HY-4-4	7/16x20	1/4	6	2.52	64	1.19	30	5/8
103HY-5-4	1/2x20	1/4	6	2.52	64	1.19	30	5/8
103HY-6-4	9/16x18	1/4	6	2.53	64	1.19	30	11/16
103HY-6-5	9/16x18	5/16	8	2.56	65	1.22	31	11/16
103HY-6-6	9/16x18	3/8	10	2.54	65	1.19	30	11/16
103HY-6-8	9/16x18	1/2	13	2.72	69	1.38	35	7/8
103HY-8-6	3/4x16	3/8	10	2.64	67	1.28	33	13/16
103HY-8-8	3/4x16	1/2	13	2.81	71	1.47	37	7/8
103HY-10-6	7/8x14	3/8	10	2.81	71	1.47	37	1
103HY-10-8	7/8x14	1/2	13	2.91	74	1.56	40	1
103HY-10-10	7/8x14	5/8	16	2.98	76	1.59	40	1-1/8
103HY-10-12	7/8x14	3/4	19	3.08	78	1.50	38	1-1/4
103HY-12-8	1-1/16x12	1/2	13	3.02	77	1.66	42	1-1/8
103HY-12-10	1-1/16x12	5/8	16	3.09	78	1.72	44	1-1/8
103HY-12-12	1-1/16x12	3/4	19	3.19	81	1.63	41	1-1/4
103HY-14-12	1-3/16x12	3/4	19	3.19	81	1.63	41	1-1/4
103HY-16-12	1-5/16x12	3/4	19	3.23	82	1.66	42	1-3/8
103HY-16-16	1-5/16x12	1	25	3.39	86	1.78	45	1-3/8
103HY-20-16	1-5/8x12	1	25	3.44	87	1.81	46	1-3/4
103HY-20-20	1-5/8x12	1-1/4	32	3.83	97	2.00	51	1-3/4

Construction: Steel


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

# 105HY Male SAE Straight Thread Rigid (with O-Ring)



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
105HY-4-4	7/16x20	1/4	6	2.33	59	0.97	25	9/16
105HY-5-4	1/2x20	1/4	6	2.33	59	0.97	25	5/8
105HY-6-4	9/16x18	1/4	6	2.42	61	1.06	27	11/16
105HY-6-6	9/16x18	3/8	10	2.38	60	1.03	26	11/16
105HY-8-6	3/4x16	3/8	10	2.42	61	1.06	27	7/8
105HY-8-8	3/4x16	1/2	13	2.59	66	1.25	32	7/8
105HY-10-6	7/8x14	3/8	10	2.55	65	1.19	30	1
105HY-10-8	7/8x14	1/2	13	2.66	68	1.31	33	1
105HY-10-10	7/8x14	5/8	16	2.80	71	1.41	36	1-1/8
105HY-12-8	1-1/16x12	1/2	13	2.81	71	1.47	37	1-1/4
105HY-12-10	1-1/16x12	5/8	16	2.83	72	1.44	37	1-1/4
105HY-12-12	1-1/16x12	3/4	19	2.92	74	1.34	34	1-1/4
105HY-16-12	1-5/16x12	3/4	19	2.92	74	1.34	34	1-1/2
105HY-16-16	1-5/16x12	1	25	3.08	78	1.47	37	1-1/2

Construction: Steel

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation


E  
Fittings  
Series HY

F  
Tooling, Equipment  
& Accessories

G  
General Technical



## 106HY Female JIC 37°Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
106HY-3-4	3/8x24	1/4	6	2.58	66	1.22	31	9/16	1/2
106HY-4-4	7/16x20	1/4	6	2.60	66	1.25	32	9/16	9/16
106HY-4-6	7/16x20	3/8	10	2.67	68	1.31	33	3/4	9/16
106HY-5-4	1/2x20	1/4	6	2.65	67	1.31	33	9/16	5/8
106HY-5-5	1/2x20	5/16	8	2.69	68	1.34	34	5/8	5/8
106HY-5-6	1/2x20	3/8	10	2.73	69	1.38	35	3/4	5/8
106HY-6-4	9/16x18	1/4	6	2.67	68	1.31	33	9/16	11/16
106HY-6-5	9/16x18	5/16	8	2.70	69	1.34	34	5/8	11/16
106HY-6-6	9/16x18	3/8	10	2.69	68	1.34	34	11/16	11/16
106HY-8-6	3/4x16	3/8	10	2.72	69	1.38	35	7/8	7/8
106HY-8-8	3/4x16	1/2	13	2.90	74	1.41	40	7/8	7/8
106HY-8-10	3/4x16	5/8	16	2.98	76	1.59	40	1-1/8	7/8
106HY-8-12	3/4x16	3/4	19	3.08	78	1.53	39	1-1/4	7/8
106HY-10-6	7/8x14	3/8	10	2.81	71	1.47	37	7/8	1
106HY-10-8	7/8x14	1/2	13	2.98	76	1.63	41	1	1
106HY-10-10	7/8x14	5/8	16	3.06	78	1.69	43	1-1/8	1
106HY-10-12	7/8x14	3/4	19	3.16	80	1.59	40	1-1/4	1
106HY-12-6	1-1/16x12	3/8	10	3.00	76	1.66	42	1-1/8	1-1/4
106HY-12-8	1-1/16x12	1/2	13	3.05	77	1.69	43	1-1/8	1-1/4
106HY-12-10	1-1/16x12	5/8	16	3.12	79	1.75	44	1-1/8	1-1/4
106HY-12-12	1-1/16x12	3/4	19	3.22	82	1.66	42	1-1/4	1-1/4
106HY-12-16	1-1/16x12	1	25	3.38	86	1.75	44	1-3/8	1-1/4
106HY-14-12	1-3/16x12	3/4	19	3.23	82	1.66	42	1-1/4	1 3/8
106HY-16-12	1-5/16x12	3/4	19	3.30	84	1.72	44	1-3/8	1-1/2
106HY-16-14	1-5/16x12	7/8	22	3.30	84	1.72	44	1-3/8	1-1/2
106HY-16-16	1-5/16x12	1	25	3.45	88	1.84	47	1-3/8	1-1/2
106HY-16-20	1-5/16x12	1-1/4	32	3.84	98	2.00	51	1-3/4	1-1/2
106HY-20-16	1-5/8x12	1	25	3.70	94	2.09	53	1-3/4	2
106HY-20-20	1-5/8x12	1-1/4	32	4.09	104	2.25	57	2	2

Construction: Steel

For detailed ordering information, please consult price list or contact Parflex® Division.


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)

E-91

A  
HoseB  
TubingC  
Coiled Air Hose  
& FittingsD  
TransportationE  
Fittings  
Series HYF  
Tooling, Equipment  
& AccessoriesG  
General Technical

A Hose

## 107HY Female NPSM Pipe Swivel (60° Cone)



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
107HY-4-4	1/4x18	1/4	6	2.66	68	1.31	33	9/16	11/16
107HY-6-4	3/8x18	1/4	6	2.72	69	1.38	35	3/4	7/8
107HY-6-6	3/8x18	3/8	10	2.55	65	1.19	30	3/4	7/8
107HY-8-8	1/2x14	1/2	13	2.91	74	1.56	40	1	1
107HY-12-8	3/4x14	1/2	13	3.05	77	1.69	43	1-1/4	1-1/4
107HY-12-12	3/4x14	3/4	19	3.22	82	1.66	42	1-1/4	1-1/4
107HY-16-16	1x11-1/2	1	25	3.39	86	1.78	45	1-3/8	1-1/2


Construction: Steel

B Tubing

C Coiled Air Hose & Fittings

D Transportation

## 108HY Female SAE 45° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
108HY-4-4	7/16x20	1/4	6	2.60	66	1.26	32	9/16	9/16
108HY-5-4	1/2x20	1/4	6	2.66	68	1.31	33	9/16	5/8
108HY-5-5	1/2x20	5/16	8	2.68	68	1.34	34	5/8	5/8
108HY-6-4	5/8x18	1/4	6	2.73	69	1.38	35	11/16	3/4
108HY-6-5	5/8x18	5/16	8	2.76	70	1.41	36	5/8	3/4
108HY-6-6	5/8x18	3/8	10	2.75	70	1.41	36	11/16	3/4
108HY-8-6	3/4x16	3/8	10	2.73	69	1.38	35	13/16	7/8
108HY-8-8	3/4x16	1/2	13	2.90	74	1.56	40	7/8	7/8
108HY-8-12	3/4x16	3/4	19	3.17	81	1.59	40	1-1/4	7/8
108HY-10-8	7/8x14	1/2	13	2.98	76	1.63	41	1	1
108HY-10-10	7/8x14	5/8	16	3.06	78	1.69	43	1-1/8	1
108HY-12-10	1-1/16x12	5/8	16	3.33	85	1.94	49	1-1/8	1-1/4
108HY-12-12	1-1/16x12	3/4	19	3.41	87	1.84	47	1-1/4	1-1/4


Construction: Steel

E Fittings Series HY

F Tooling, Equipment & Accessories

G General Technical

## 10GHY Male SAE Straight Thread Swivel (with O-Ring)




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	D
		inch	mm	inch	mm	inch	mm	inch	inch
#									
10GHY-4-4*	7/16x20	1/4	6	3.21	82	1.94	49	5/8	1/2
10GHY-5-4*	1/2x20	1/4	6	3.60	91	2.33	59	3/4	5/8
10GHY-6-4	9/16x18	1/4	6	3.16	80	1.81	46	11/16	5/8
10GHY-6-6	9/16x18	3/8	10	3.14	80	1.78	45	11/16	11/16
10GHY-6-8*	9/16x18	3/8	10	3.80	97	2.51	64	3/4	7/8
10GHY-8-6	3/4x16	3/8	10	3.24	82	1.88	48	7/8	13/16
10GHY-8-8	3/4x16	1/2	13	3.36	85	2.00	51	7/8	7/8
10GHY-10-8	7/8x14	1/2	13	3.44	87	2.09	53	1	1
10GHY-12-8	1-1/16x12	1/2	13	3.66	93	2.31	59	1-1/4	1-1/4
10GHY-12-12	1-1/16x12	3/4	19	3.89	99	2.31	59	1-1/4	1-1/4
10GHY-16-16	1-5/16x12	1	25	3.95	100	2.34	59	1-1/2	1-3/8

Construction: Steel

**NOTE:** \*Fittings "D" dimension is round rather than hex. Fitting allows minor movement under pressure to relieve stress on hose but is not to be used on extensive or continuous swiveling.

## 10LHY Male SAE Straight Thread Swivel 90° Elbow (with O-Ring)



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
10LHY-4-4	7/16x20	1/4	6	2.31	59	0.97	25	1.63	41	11/16
10LHY-6-4	9/16x18	1/4	6	2.31	59	0.97	25	1.66	42	7/8
10LHY-6-6	9/16x18	3/8	10	2.33	59	0.97	25	1.66	42	11/16
10LHY-8-4	3/4x16	1/4	6	2.31	59	0.94	24	1.75	44	7/8
10LHY-8-6	3/4x16	3/8	10	2.33	59	0.97	25	1.73	44	7/8
10LHY-8-8	3/4x16	1/2	13	3.00	76	1.09	28	1.80	46	7/8
10LHY-10-8	7/8x14	1/2	13	3.00	76	1.09	28	1.88	48	1
10LHY-12-12	1-1/16x12	3/4	19	2.77	70	1.19	30	2.23	57	1-1/4


Construction: Steel

**NOTE:** Fitting allows minor movement under pressure to relieve stress on hose but is not to be used on extensive or continuous swiveling.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

# 111HY Male Ferulok Flareless Rigid (24° Cone w/Nut and Ferrule)



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
111HY-4-4	7/16x20	1/4	6	2.42	61	1.06	27	9/16	9/16
111HY-4-6	7/16x20	3/8	10	2.44	62	1.09	28	3/4	9/16
111HY-5-6	1/2x20	3/8	10	2.44	62	1.09	28	3/4	5/8
111HY-6-4	9/16x18	1/4	6	2.44	62	1.09	28	5/8	11/16
111HY-6-6	9/16x18	3/8	10	2.45	62	1.09	28	11/16	11/16
111HY-8-6	3/4x16	3/8	10	2.61	66	1.25	32	7/8	7/8
111HY-8-8	3/4x16	1/2	13	2.72	69	1.38	35	7/8	7/8
111HY-10-8	7/8x14	1/2	13	2.78	71	1.44	37	1	1
111HY-12-12	1-1/16x12	3/4	19	3.02	77	1.44	37	1-1/4	1-1/4

Construction: Steel


**NOTE:** The Parker Ferrule-Fix fitting makes it possible to salvage the bent tube section from a hose assembly for quick, easy on the job repairs. See page G-29 for Ferrule-Fix installation instructions.

B Tubing

C Coiled Air Hose & Fittings

D Transportation

# 113HY Male NPTF Pipe Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	D
		inch	mm	inch	mm	inch	mm	inch	inch
#									
113HY-2-4	1/8x27	1/4	6	3.61	92	2.34	59	5/8	9/16
113HY-4-4	1/4x18	1/4	6	3.35	85	2.08	53	5/8	1/2
113HY-4-6	1/4x18	3/8	10	3.36	85	2.08	53	5/8	11/16
113HY-6-4	3/8x18	1/4	6	3.46	89	2.19	56	3/4	5/8
113HY-6-6	3/8x18	3/8	10	3.47	89	2.19	56	3/4	11/16
113HY-6-8	3/8x18	1/2	13	3.63	92	2.34	59	3/4	7/8
113HY-8-4	1/2x14	3/8	10	3.66	93	2.39	61	7/8	13/16
113HY-8-6	1/2x14	3/8	10	3.68	93	2.40	61	7/8	13/16
113HY-8-8	1/2x14	1/2	13	3.80	97	2.51	64	7/8	7/8
113HY-12-12*	3/4x14	3/4	25	3.95	100	2.38	60	1-1/4	1-1/4
113HY-16-16*	1x11-1/2	1	25	4.23	107	2.63	67	1-1/2	1-1/2

Construction: Steel

**NOTE:** \* Fittings "D" dimension is a hex rather than round.

Fitting allows minor movement under pressure to relieve stress on hose but is not to be used for continuous swiveling. See Hose Products Catalog 4400 for pressure limitations.


E Fittings Series HY

F Tooling, Equipment & Accessories

G General Technical




# 11LHY Male NPTF Pipe Swivel 90° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
11LHY-2-4	1/8x27	1/4	6	2.31	59	0.97	25	1.50	38	5/8
11LHY-4-4	1/4x18	1/4	6	2.31	59	0.97	25	1.69	43	11/16
11LHY-4-6	1/4x18	3/8	10	2.33	59	0.97	25	1.69	43	11/16
11LHY-6-4	3/8x18	1/4	6	2.31	59	0.97	25	1.63	41	11/16
11LHY-6-6	3/8x8	3/8	10	2.33	59	0.97	25	1.63	41	11/16
11LHY-8-6	1/2x14	3/8	10	2.73	69	0.97	25	1.88	48	7/8
11LHY-8-8	1/2x14	1/2	13	3.00	76	1.09	28	1.93	49	7/8

Construction: Steel

# 128HY Male Inverted SAE 45° Swivel



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		W Hex
		inch	mm	inch	mm	inch	mm	inch
#								
128HY-3-4	3/8x24	1/4	6	3.09	78	1.75	44	3/8
128HY-4-4	7/16x24	1/4	6	3.28	83	1.94	49	7/16
128HY-5-4	1/2x20	1/4	6	3.34	85	2.00	51	1/2
128HY-5-6	1/2x20	3/8	10	3.17	81	1.81	46	1/2
128HY-6-5	5/8x18	5/16	8	3.75	95	2.41	61	5/8
128HY-6-6	5/8x18	3/8	10	3.73	95	2.38	60	5/8
128HY-7-6	11/16x18	3/8	10	3.73	95	2.38	60	11/16
128HY-8-6	3/4x18	3/8	10	3.42	87	2.06	52	3/4
128HY-8-8	3/4x18	1/2	13	3.66	93	2.31	59	3/4

Construction: Steel


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

## 129HY Female Inverted SAE 45° Rigid




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
129HY-5-4	1/2x20	1/4	6	2.25	57	0.91	23	5/8
129HY-6-6	5/8x18	3/8	10	2.25	57	0.91	23	7/8

Construction: Steel

B Tubing

## 134HY Male Standpipe Rigid (Inch Size Tube O.D.)




Part Number	Diameter R		Hose I.D.		A		Cutoff Allow. B	
	inch	mm	inch	mm	inch	mm	inch	mm
#								
134HY-6-6	3/8	10	3/8	10	3.17	81	1.81	46
134HY-8-6	1/2	13	3/8	10	3.33	85	1.97	50
134HY-12-12	3/4	19	3/4	19	3.89	99	2.31	59

Construction: Steel

C Coiled Air Hose & Fittings

D Transportation

## 137HY Female JIC 37° Swivel 45° Elbow Short Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
137HY-4-4	7/16x20	1/4	6	2.59	66	1.32	34	0.39	10	9/16
137HY-5-4	1/2x20	1/4	6	3.27	83	1.91	49	0.36	9	5/8
137HY-6-4	9/16x18	1/4	6	2.70	69	1.43	36	0.43	10	3/4
137HY-6-5	9/16x18	5/16	8	3.34	85	2.00	51	0.39	11	11/16
137HY-6-6	9/16x18	3/8	10	2.72	69	1.44	37	0.43	11	11/16
137HY-8-6	3/4x16	3/8	10	2.88	73	1.60	41	0.58	15	7/8
137HY-8-8	3/4x16	1/2	13	3.10	79	1.81	46	0.59	15	7/8
137HY-10-8	7/8x14	1/2	13	3.20	81	1.91	49	0.63	16	1
137HY-10-10	7/8x14	5/8	16	3.29	84	1.93	49	0.63	16	1
137HY-12-10	1-1/16x12	5/8	16	3.94	100	2.56	65	0.77	20	1-1/8
137HY-12-12	1-1/16x12	3/4	19	3.82	97	2.29	58	0.83	21	1-1/4
137HY-16-12	1-5/16x12	3/4	19	4.35	110	2.78	71	0.89	23	1-1/2
137HY-16-16	1-5/16x12	1	25	4.31	109	2.69	68	0.89	23	1-1/2


Construction: Steel

E Fittings Series HY

F Tooling, Equipment & Accessories

G General Technical


## 139HY Female JIC 37° Swivel 90° Elbow Short Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
139HY-4-4	7/16x20	1/4	6	2.40	61	1.13	29	0.83	21	9/16
139HY-5-4	1/2x20	1/4	6	2.50	64	1.23	31	0.83	21	5/8
139HY-6-4	9/16x18	1/4	6	2.65	67	1.38	35	0.91	23	11/16
139HY-6-5	9/16x18	5/16	8	3.25	83	1.91	49	0.86	22	11/16
139HY-6-6	9/16x18	3/8	10	2.57	65	1.29	33	0.91	23	11/16
139HY-6-8	9/16x18	1/2	13	3.41	87	2.06	52	0.86	22	11/16
139HY-8-6	3/4x16	3/8	10	2.64	67	1.37	35	1.14	29	7/8
139HY-8-8	3/4x16	1/2	13	2.85	72	1.56	40	1.14	29	7/8
139HY-10-8	7/8x14	1/2	13	3.01	76	1.72	44	1.26	32	1
139HY-10-10	7/8x14	5/8	16	3.09	78	1.73	44	1.26	32	1
139HY-10-12	7/8x14	3/4	19	3.25	83	1.69	43	1.23	31	1
139HY-12-8	1-1/16x12	1/2	13	3.61	92	2.25	57	1.83	46	1-1/4
139HY-12-10	1-1/16x12	5/8	16	3.61	92	2.25	57	1.89	48	1-1/4
139HY-12-12	1-1/16x12	3/4	19	3.68	93	2.15	55	1.89	48	1-1/4
139HY-16-12	1-5/16x12	3/4	19	4.33	110	2.78	71	2.14	54	1-1/2
139HY-16-16	1-5/16x12	1	25	4.31	109	2.69	68	2.31	59	1-1/2

Construction: Steel

## 141HY Female JIC 37° Swivel 90° Elbow Long Drop



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
141HY-4-4	7/16x20	1/4	6	2.68	68	1.41	36	1.81	46	9/16
141HY-5-4	1/2x20	1/4	6	3.16	80	1.81	46	1.77	45	5/8
141HY-6-4	9/16x18	1/4	6	2.89	73	1.62	41	2.13	54	11/16
141HY-6-6	9/16x18	3/8	10	2.76	70	1.49	39	2.13	54	11/16
141HY-8-6	3/4x16	3/8	10	2.85	72	1.58	40	2.52	64	7/8
141HY-8-8	3/4x16	1/2	13	2.89	73	1.60	41	2.52	64	7/8
141HY-10-8	7/8x14	1/2	13	3.01	76	1.72	44	2.76	70	1
141HY-12-12	1-1/16x12	3/4	19	3.59	91	2.03	52	3.73	95	1-1/4
141HY-16-16	1-5/16x12	1	25	4.56	116	2.94	75	4.33	110	1-1/2

Construction: Steel


For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical



A Hose

## 167HY Male Inverted SAE 45° Swivel 45° Elbow




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
167HY-4-4	7/16x24	1/4	6	3.31	84	1.97	50	0.78	20	7/16
167HY-5-4	1/2x20	1/4	6	3.55	90	2.19	56	0.88	22	1/2
167HY-5-6	1/2x20	3/8	10	3.38	86	2.03	52	0.88	22	1/2
167HY-6-6	5/8x18	3/8	10	4.16	106	2.81	71	0.94	24	5/8
167HY-8-8	3/4x18	1/2	13	4.22	107	2.88	73	1.06	27	3/4

Construction: Steel

B Tubing

C Coiled Air Hose & Fittings

## 169HY Male Inverted SAE 45° Swivel 90° Elbow




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
169HY-3-4	3/8x24	1/4	6	3.09	78	1.75	44	1.38	35	3/8
169HY-4-4	7/16x24	1/4	6	3.28	83	1.94	49	1.47	37	7/16
169HY-4-6	7/16x24	3/8	10	3.11	79	1.75	44	1.47	37	7/16
169HY-5-4	1/2x20	1/4	6	3.52	89	2.16	55	1.66	42	1/2
169HY-5-6	1/2x20	3/8	10	3.34	85	2.00	51	1.66	42	1/2
169HY-6-5	5/8x18	5/16	8	4.05	103	2.69	68	1.69	43	5/8
169HY-6-6	5/8x18	3/8	10	4.03	102	2.69	68	1.69	43	5/8
169HY-7-6	11/16x18	3/8	10	4.16	106	2.81	71	1.69	43	11/16
169HY-8-8	3/4x18	1/2	13	4.09	104	2.75	70	1.88	48	3/4

Construction: Steel

D Transportation

E Fittings Series HY

## 177HY Female SAE 45° Swivel 45° Elbow




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
177HY-6-6	5/8x18	3/8	10	3.33	85	1.97	50	0.39	10	3/4
177HY-12-12	1-1/16x14	3/4	19	4.03	102	2.44	62	0.77	20	1-1/4

Construction: Steel

F Tooling, Equipment & Accessories

G General Technical


## 179HY Female SAE 45° Swivel 90° Elbow



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
179HY-6-5	5/8x18	5/16	8	3.25	83	1.91	49	0.86	22	3/4
179HY-6-6	5/8x18	3/8	10	3.23	82	1.88	48	0.86	22	3/4
179HY-12-12	1-1/16x14	3/4	19	3.98	101	2.39	61	1.83	46	1-1/4

Construction: Steel


## 193HY Female JIC 37° Swivel 90° Elbow (Block Type)



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
193HY-6-6	9/16x18	3/8	10	2.33	59	0.97	25	0.78	20	11/16
193HY-8-6	3/4x16	3/8	10	2.33	59	0.97	25	0.82	21	7/8
193HY-8-8	3/4x16	1/2	13	3.00	76	1.09	28	0.85	22	7/8
193HY-12-12	1-1/16x12	3/4	19	3.33	85	1.19	30	0.99	25	1-1/4

Construction: Steel

## 1D0HY Male Metric L Rigid (24° Cone) ISO 8434-1



Part Number	Thread Size		Hose I.D.		A		Cutoff Allow. B		H Hex
	mm		inch	mm	inch	mm	inch	mm	inch
#									
1D0HY-6-4	6	M12x1.5	1/4	6	2.36	60	1.00	25	14
1D0HY-8-4	8	M14x1.5	1/4	6	2.36	60	1.00	25	17
1D0HY-10-4	10	M16x1.5	1/4	6	2.40	61	1.03	26	19
1D0HY-10-6	10	M16x1.5	3/8	10	2.42	61	1.06	27	19
1D0HY-12-6	12	M18x1.5	3/8	10	2.42	61	1.06	27	22
1D0HY-15-6	15	M22x1.5	3/8	10	2.52	64	1.16	29	24
1D0HY-15-8	15	M22x1.5	1/2	13	2.63	67	1.28	33	24
1D0HY-18-10	18	M26x1.5	5/8	16	2.71	69	1.31	33	27


Construction: Steel

For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

## 13DHY Male Standpipe Metric S Rigid ISO 8434-1




Part Number	Diameter R		Hose I.D.		A		Cutoff Allow. B	
	mm	inch	inch	mm	inch	mm	inch	mm
#	Ø		⊙					
13DHY-16-8	16	0.63	1/2	13	3.53	90	2.16	55
13DHY-30-16	30	1.18	1	25	4.15	105	2.53	64

Construction: Steel

B Tubing

C Coiled Air Hose & Fittings

## 1D9HY Male BSP Parallel Pipe Rigid (60° Cone) ISO 228-1



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#	⌀	⊙						⬡
1D9HY-4-4	1/4x19	1/4	6	2.40	61	1.03	26	13/16
1D9HY-6-6	3/8x19	3/8	10	2.55	65	1.19	30	7/8
1D9HY-8-6	1/2x14	3/8	10	2.65	67	1.28	33	1-1/16
1D9HY-8-8	1/2x14	1/2	13	2.83	72	1.47	37	1-1/16


Construction: Steel

NOTE: When used in a port, a bonded seal must be used.

D Transportation

E Fittings Series HY

## 1GJHY Female Grease Connection -SPL- PTF Taper Thread Rigid 1/2 x 27




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#	⌀	⊙						⬡
1GJHY-8-4	1/2x27	1/4	6	2.41	61	1.06	27	3/4

Construction: Steel

F Tooling, Equipment & Accessories

G General Technical


# 1J1HY Female Seal-Lok™ Swivel 90° Elbow Long Drop ISO 12151-1 - SWEL90



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J1HY-4-4	9/16x18	1/4	6	2.68	68	1.41	36	1.81	46	11/16
1J1HY-6-4	11/16x16	1/4	6	2.89	73	1.62	41	2.13	54	13/16
1J1HY-6-6	11/16x16	3/8	10	2.76	70	1.49	38	2.13	54	13/16
1J1HY-8-6	13/16x16	3/8	10	2.85	72	1.58	40	2.52	64	15/16
1J1HY-8-8	13/16x16	1/2	13	2.94	75	1.65	42	2.52	64	15/16
1J1HY-10-8	1x14	1/2	13	3.01	76	1.72	44	2.76	70	1-1/8
1J1HY-10-10	1x14	5/8	16	3.42	87	2.03	52	2.76	70	1-1/8
1J1HY-12-12	1-3/16x12	3/4	19	3.68	93	2.15	55	3.78	96	1-3/8
1J1HY-16-16	1-7/16x12	1	25	4.45	113	2.84	72	4.50	114	1-5/8

Construction: Steel

# 1J7HY Female Seal-Lok™ Swivel 45° Elbow ISO 12151-1 - SWE45



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J7HY-4-4	9/16x18	1/4	6	2.59	66	1.32	34	0.39	10	11/16
1J7HY-6-4	11/16x16	1/4	6	2.70	69	1.43	36	0.43	11	13/16
1J7HY-6-6	11/16x16	3/8	10	2.72	69	1.44	37	0.43	11	13/16
1J7HY-6-8	11/16x16	1/2	13	3.41	87	2.06	52	0.44	11	13/16
1J7HY-8-4	13/16x16	1/4	6	2.95	75	1.68	43	0.59	15	15/16
1J7HY-8-6	13/16x16	3/8	10	2.89	73	1.62	41	0.59	15	15/16
1J7HY-8-8	13/16x16	1/2	13	3.10	79	1.81	46	0.59	15	15/16
1J7HY-10-8	1x14	1/2	13	3.20	81	1.91	49	0.63	16	1-1/8
1J7HY-10-10	1x14	5/8	16	3.29	84	1.93	49	0.63	16	1-1/8
1J7HY-10-12	1x14	3/4	19	3.69	94	2.13	54	0.69	18	1-1/8
1J7HY-12-10	1-3/16x12	5/8	16	3.74	104	2.38	60	0.83	21	1-3/8
1J7HY-12-12	1-3/16x12	3/4	19	3.82	97	2.29	58	0.83	21	1-3/8
1J7HY-16-12	1-7/16x12	3/4	19	4.39	112	2.84	72	0.97	25	1-5/8
1J7HY-16-16	1-7/16x12	1	25	4.55	116	2.94	75	0.97	25	1-5/8

Construction: Steel

For detailed ordering information, please consult price list or contact Parflex® Division.




A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical

A Hose

# 1J9HY Female Seal-Lok™ Swivel 90° Elbow Short Drop ISO 12151-1 - SWES90

B Tubing



C Coiled Air Hose & Fittings


Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		E		W Hex
		inch	mm	inch	mm	inch	mm	inch	mm	inch
#										
1J9HY-4-4	9/16x18	1/4	6	2.40	61	1.13	29	0.83	21	11/16
1J9HY-4-6	9/16x18	3/8	10	3.08	78	1.72	44	0.83	21	11/16
1J9HY-6-4	11/16x16	1/4	6	2.65	67	1.38	35	0.91	23	13/16
1J9HY-6-5	11/16x16	5/16	8	3/14	80	1.72	44	0.91	23	13/16
1J9HY-6-6	11/16x16	3/8	10	2.57	65	1.29	33	0.91	23	13/16
1J9HY-6-8	11/16x16	1/2	13	2.77	70	1.48	38	0.91	23	13/16
1J9HY-8-6	13/16x16	3/8	10	2.64	67	1.37	35	1.14	29	15/16
1J9HY-8-8	13/16x16	1/2	13	2.85	72	1.56	40	1.14	29	15/16
1J9HY-10-8	1x14	1/2	13	3.01	76	1.72	44	1.26	32	1-1/8
1J9HY-10-10	1x14	5/8	16	3.09	78	1.73	44	1.26	32	1-1/8
1J9HY-10-12	1x14	3/4	19	3.52	89	1.97	50	1.33	34	1-1/8
1J9HY-12-8	1-3/16x12	1/2	13	3.84	98	2.39	61	1.89	48	1-3/8
1J9HY-12-10	1-3/16x12	5/8	16	3.61	92	2.25	57	1.89	48	1-3/8
1J9HY-12-12	1-3/16x12	3/4	19	3.68	93	2.15	55	1.89	48	1-3/8
1J9HY-16-12	1-7/16x12	3/4	19	4.27	108	2.69	68	2.25	57	1-5/8
1J9HY-16-16	1-7/16x12	1	25	4.45	113	2.84	72	2.25	57	1-5/8
1J9HY-20-16	1-11/16x12	1	25	4.77	121	3.16	80	2.51	64	1-7/8

Construction: Steel

D Transportation

E Fittings Series HY

# 1JCHY Female Seal-Lok™ Swivel Short ISO 12151-1 - SWSA



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1JCHY-4-4	9/16x18	1/4	6	2.61	66	0.94	24	9/16	11/16
1JCHY-6-6	11/16x16	3/8	10	2.69	68	0.94	24	11/16	13/16
1JCHY-8-8	13/16x16	1/2	13	2.91	74	1.13	29	7/8	15/16
1JCHY-12-12	1-3/16x12	3/4	19	3.31	84	1.13	29	1-1/4	1-3/8


Construction: Steel

F Tooling, Equipment & Accessories

G General Technical




# 1JOHY Male Seal-Lok™ Rigid (with O-Ring) ISO 1215-1 - S



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex
		inch	mm	inch	mm	inch	mm	inch
#								
1JOHY-4-4	9/16x18	1/4	6	2.36	60	1.00	25	5/8
1JOHY-6-6	11/16x16	3/8	10	2.49	63	1.13	29	3/4
1JOHY-8-8	13/16x16	1/2	13	2.69	68	1.34	34	7/8
1JOHY-12-8	1-3/16x12	1/2	13	2.91	74	1.56	40	1-1/4

Construction: Steel

# 1JSHY Female Seal-Lok™ Swivel Long ISO 12151-1 - SWSB



Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1JSHY-4-4	9/16x18	1/4	6	2.59	66	1.25	32	9/16	11/16
1JSHY-6-4	11/16x16	1/4	6	2.67	68	1.31	33	5/8	13/16
1JSHY-6-5	11/16x16	5/16	8	2.70	69	1.34	34	5/8	13/16
1JSHY-6-6	11/16x16	3/8	10	2.75	70	1.34	34	11/16	13/16
1JSHY-8-6	13/16x16	3/8	10	2.84	72	1.50	38	7/8	15/16
1JSHY-8-8	13/16x16	1/2	13	2.95	75	1.59	40	7/8	15/16
1JSHY-10-8	1x14	1/2	13	3.16	80	1.81	46	15/16	1-1/8
1JSHY-10-10	1x14	5/8	16	3.17	81	1.78	45	1-1/8	1-1/8
1JSHY-10-12	1x14	3/4	19	3.27	83	1.69	43	1-1/4	1-1/8
1JSHY-12-10	1-3/16x12	5/8	16	3.20	81	1.81	46	1-1/8	1-3/8
1JSHY-12-12	1-3/16x12	3/4	19	3.30	84	1.72	44	1-1/4	1-3/8
1JSHY-16-12	1-7/16x12	3/4	19	3.44	87	1.88	48	1-3/8	1-5/8
1JSHY-16-16	1-7/16x12	1	25	3.59	91	1.97	50	1-3/8	1-5/8
1JSHY-20-16	1-11/16x12	1	25	3.47	88	1.75	59	1-5/8	1-7/8
1JSHY-20-20	1-11/16x12	1-1/4	32	3.98	101	2.16	55	1-3/4	1-7/8

Construction: Steel

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series HY  
 F Tooling, Equipment & Accessories  
 G General Technical


A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series LV  
 F Tooling, Equipment & Accessories  
 G General Technical

# LV Series Visual Index

**LV Series**


PERMANENT





**106** SAE (JIC) 37° Swivel



E-104

## 106LV SAE (JIC) 37° Swivel






Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
106LV-4-3	7/16-20	3/16	6	1.93	49	15/16	24	9/16	9/16
106LV-12-12	1-1/16-12	3/4	19	4.12	105	1-13/16	46	1-1/8	1-1/4
106LV-16-16	1-5/16-12	1	25	4.81	122	1-13/16	46	1-3/8	1-1/2



Construction: Steel nipple, nut and shell.

Add "C" for Stainless Steel.








# MS Series Visual Index

<b>MS Series</b> FIELD ATTACHABLE	<b>108</b> SAE 45° Swivel	<b>134</b> Straight Tube	<b>1TF</b> Marine Tube Connector
	 E-105	 E-105	 E-106

<b>MS Series</b> FIELD ATTACHABLE	<b>208</b> SAE 45° Swivel	<b>2TF</b> Marine Tube Connector
	 E-106	 E-106


## 108MS Permanent SAE 45° Swivel (Brass)






Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		H Hex	J Hex
		inch	mm	inch	mm	inch	mm	inch	inch
<b>#</b>									
108MS-6-5B	5/8-18	5/16	8	1.72	44	1-1/8	29	5/8	13/16
108MS-6-6B	5/8-18	3/8	10	1.82	46	1-1/16	27	3/4	13/16

Construction: Brass.

## 134MS Permanent Straight Tube (Brass)



Part Number	Diameter R		Hose I.D.		A		Cutoff Allow. B		H Hex
	inch	mm	inch	mm	inch	mm	inch	mm	inch
<b>#</b>									
134MS-6-5B	3/8	10	5/16	8	2.00	51	1-3/8	35	5/8
134MS-6-6B	3/8	10	3/8	10	2.08	53	1-3/8	35	3/4

Construction: Brass.


For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series MS  
 F Tooling, Equipment & Accessories  
 G General Technical

A  
Hose

## 1TFMS Permanent Marine Tube Connector (Brass)




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex	H Hex
		inch	mm	inch	mm	inch	mm	inch	inch
#									
1TFMS-6-5B	9/16-24	5/16	8	1.70	43	1 1/16	27	3/4	5/8

Construction: Brass.

**NOTE:** Connector Mates are Manufactured by the Fluid Systems Connection Division. Refer to Catalog 3501E for Ordering, Installation Instructions and Replacement Components.

B  
TubingC  
Coiled Air Hose  
& Fittings

## 208MS Field-Attachable SAE 45° Swivel (Brass)




Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex	H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
#										
208MS-6-5B	5/8-18	5/16	8	2.06	52	1 5/16	33	13/16	5/8	13/16
208MS-6-6B	5/8-18	3/8	10	2.37	60	1 7/16	37	13/16	5/8	13/16

Construction: Brass.

D  
TransportationE  
Fittings  
Series MS

## 2TFMS Field-Attachable Marine Tube Connector (Brass)





Part Number	Thread Size	Hose I.D.		A		Cutoff Allow. B		J Hex	H Hex	W Hex
		inch	mm	inch	mm	inch	mm	inch	inch	inch
#										
2TFMS-6-5B	9/16-24	5/16	8	2.02	51	1 5/16	33	3/4	5/8	3/4

Construction: Brass.


**NOTE:** Connector Mates are Manufactured by the Fluid Systems Connection Division. Refer to Catalog 3501E for more information.

F  
Tooling, Equipment  
& AccessoriesG  
General Technical

# SQ Series Visual Index

<b>SQ Series</b>  <b>PERMANENT</b>	<b>101</b>	Male Taper Pipe Rigid	<b>1HU</b>	SQ Mender
	 E-107		 E-107	


## 1HUSQ Mender



Part Number		Hose I.D.		A		Cutoff Allow. B	
#		⊙					
Hose		inch	mm	inch	mm	inch	mm
S410	1HUSQ-10-10	5/8	16	3.90	100	5/16	8
S612	1HUSQ-12-12	3/4	19	3.70	94	9/16	14
S616	1HUSQ-16-16	1	25	3.99	101	9/16	14
S620	1HUSQ-20-20	1-1/4	32	4.53	115	9/16	14
S912	1HUSQ-12-12	3/4	19	3.70	94	9/16	14
S916	1HUSQ-16-16	1	25	3.99	101	9/16	14

Construction: Steel  
 NOTE: See pg. G-41 for swage die selection.

## 101SQ Male Taper Pipe Rigid



Part Number		Hose I.D.		A		Cutoff Allow. B	
#		⊙					
Hose		inch	mm	inch	mm	inch	mm
S612	101SQ-12-12	3/4	19	3.08	78	1-1/2	38
S616	101SQ-16-16	1	25	3.42	87	1-13/16	46
S620	101SQ-20-20	1-1/4	32	3.84	98	2	51
S912	101SQ-12-12	3/4	19	3.08	78	1-1/2	38
S916	101SQ-16-16	1	25	3.42	87	1-13/16	46

Construction: Steel  
 NOTE: See pg. G-41 for swage die selection.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings Series SQ  
 F Tooling, Equipment & Accessories  
 G General Technical



# Tooling Equipment & Accessories



MiniKrimp™

Karrykrimp

Parkrimp

PHastkrimp™

Superkrimp

Pumps

Accessories



# Table of Contents

## Crimpers

Karrykrimp .....	F-12
Karrykrimp 2 .....	F-12
MiniKrimp™ .....	F-6
Parkrimp 1 .....	F-12
Parkrimp 2 .....	F-13
PHastkrimp™ .....	F-13
Superkrimp .....	F-13

## Pumps

Air Over Hydraulic Pumps .....	F-14 : F-15
Electric Pumps .....	F-15
Hand Pumps.....	F-14

<b>Conversion Kits</b> - Hydraulic Press, Gates, Weatherhead.....	F-16
---	------

## Sewer Hose Swager & Swage Tooling

SQ-101-SW Swager/Mender .....	F-17
-------------------------------	------

## Accessories

Cut-off Tools .....	F-18 : F-19
Dies (Parkrimp) .....	F-20
Die Racks .....	F-20
Hose Guards/Sleeves.....	F-21 : F-26
Vise Blocks .....	F-17



## Technical



Minikrimp Assembly Detail.....	F-10 : F-11
Spring/Armor/PVC Guard Selection Tables.....	F-24 : F-25



# Tooling, Equipment & Accessories Visual Index








<b>MiniKrimp™</b>	94C-001-PFD	94C-002-PFD	Hose Stand 94C-MKS
	 F-6	 F-7	 F-9

<b>Karrykrimp</b>	Karrykrimp 82C-061L-PFD	Karrykrimp 2 85C-061L-PFD
	 F-12	 F12

<b>Parkrimp</b>	Parkrimp 1 80C-061-PFD	Parkrimp 2 83C-081-PFD
	 F-12	 F-13

<b>PHastkrimp™</b>	PHastkrimp 89C-061-PFD
	 F-13

<b>Superkrimp</b>	Superkrimp 88C-082-PFD
	 F-13

<b>Pumps</b>	Hand Pump 015301	Hand Pump 82C-0HP-PFD	Hand Pump 85C-0HP-PFD	Air/Hydraulic Pump 025399	Air/Hydraulic Pump 82C-0AP
	 F-14	 F-14	 F-14	 F-14	 F-15
	Electric Pump 82C-0EP-PFD	Electric Pump 85C-0EP-PFD			
	 F-15	 F-15			








For detailed ordering information, please consult price list or contact Parflex® Division.





# Tooling, Equipment & Accessories Visual Index




	Dies	Die Storage Racks
<b>Parkrimp Dies</b>		
	F20	F-20

<b>Cutoff Tools</b>	Hose Cutoff Machine 332T-115V	Karrykut H631075	Hose Cutoff Tool 316-PFD	Push-Lok Cut-Off 885140	Hose Cutter HTC
					
	F-18	F-18	F-19	F-19	F-19
	Hose Cutter TH11-1	Plastic Tube Cutter PTC			
					
	F-19	F-19			

<b>Hose Guards &amp; Sleeves</b>	AG Flat Steel Armor	AS Partek Sleeve	CNG CNGG Guard Kit	FS Fire Sleeve	HBR Bend Restrictor
					
	F-22	F-23*	F-21	F-23*	F-21
	MG External Anti-Kink Casing	PSG and SSG Pre-Made Spring	PSG Parker Spiral Guard	PV Clear Vinyl	SG Steel Spring Guard
					
	F-23	F-22	F-26	F-21	F-22
	2613 Internal Flat Spring	2625 External Round Spring	2740 External Flat Spring	2799 Internal Round Spring	
					
	F-23*	F-23*	F-23*	F-23*	

\* Items on page F-23 are for PTFE hose.





<b>Additional Accessories Available</b>		
<b>Components, Accessories</b>	<b>Division</b>	<b>Contact Information</b>
Tube Fitting Adaptors	Tube Fitting Division	Phone: (614) 279-7070 Fax: (614) 279-7685 www.parker.com/tfd
Seal-Lok™ O-Rings		
Hose Protective Sleeving	Hose Products Division	Phone: (440) 943-5700 Fax: (440) 943-3129 www.parker.com/hpd
Hose Clamps		
Flange Kits (Code 61, 62, DIN & ISO)		
Protection Shields		

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
B Tubing  
C Coiled Air Hose & Fittings  
D Transportation  
E Fittings  
F Tooling, Equipment & Accessories  
G General Technical

# MiniKrimp™ Crimping Machines



## Hand Pump Model

Part No. 94C-001-PFD

The Parker Hannifin MiniKrimp is the best portable crimper on the market. By utilizing a one-piece, high-strength cast aluminum frame, the MiniKrimp is light, robust and highly corrosion resistant.

## Features

- Lightweight, portable, compact all-in-one unit
- Unit with pump weighs only 42 pounds
- 10,000 psi and 30+ tons of force
- No gauges to set - exclusive Parkalign™ feature positions the fitting correctly every time
- Removable pusher design for easy die change
- Hand pump easily removed for use with jumper hose for bench-mounted units (Part No.- 015309)
- No additional power source required for operation
- Capable of crimping a majority of thermoplastic, rubber, PTFE and specialty hoses up to 3/4" I.D.

### Specifications

Approximate Size (with Pump)	6" Deep, 13" Wide, 15" High
Weight (w/o die set)	42 lbs with hand pump
Rating	30 tons force @ 10,000 psi maximum
Full Cycle Time	Approximately 30 seconds

### Standard Equipment (Model 94C-001-PFD)

Part Description	Individual Part Number
MiniKrimp Portable Crimping Machine	94C-080-PFD
Hand Pump	015301
Die Ring – Color Coded Silver	82C-R01-PFD

## Operating Parameters

Reference Crimpsource™ online or appropriate catalog (4660 or 4400) of the Parker division that supplies the hose for detailed crimp specifications as exceptions do occur based on the particular hose type, size, and fitting material.

[www.parker.com/crimpsource](http://www.parker.com/crimpsource)



For detailed ordering information, please consult price list or contact Parflex® Division.



## Air Over Hydraulic Model

### Part No. 94C-002-PFD

- The Parker Hannifin MiniKrimp is the best portable crimper on the market. By utilizing a one-piece, high-strength cast aluminum frame, the MiniKrimp is light, robust and highly corrosion resistant.

## Features

- Lightweight, portable, compact all-in-one unit
- Unit with pump weighs only 45 pounds
- 10,000 psi and 30+ tons of force
- No gauges to set - exclusive Parkalign™ feature positions the fitting correctly every time
- Removable pusher design for easy die change
- Air pump utilizes a rugged activation and release lever for greater durability
- Can operate with as little as 60 psi air pressure (60-100 psi, 9 CFM recommended)
- Capable of crimping a majority of thermoplastic, rubber, PTFE and specialty hoses up to 3/4" I.D.

Specifications	
Approximate Size (with Pump)	6" Deep, 12" Wide, 15" High
Weight	45 lbs. with air/hydraulic pump
Rating	30 tons force @ 10,000 psi maximum
Full Cycle Time	approximately 30 seconds

Standard Equipment (Model 94C-002-PFD)	
Part Description	Part Number
MiniKrimp Portable Crimping Machine	94C-080-PFD
Air-Over-Hydraulic Pump (includes tubing and adaptors)	025399
Die Ring – Color Coded Silver	82C-R01-PFD

## Operating Parameters

Reference Crimpsource™ online or appropriate catalog (4660 or 4400) of the Parker division that supplies the hose for detailed crimp specifications as exceptions do occur based on the particular hose type, size, and fitting material.

[www.parker.com/crimpsource](http://www.parker.com/crimpsource)

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



F-7

A  
Hose

B  
Tubing

C  
Coiled Air Hose & Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment & Accessories

G  
General Technical

# MiniKrimp™ Crimping Machine Accessories



## Upright Vise Mount

Part No. 015307

- Machined and bent from 1/4" thick 1018 steel
- Mount connects to the bottom of the MiniKrimp using four 3/8-16 bolts (not included)
- Once connected, MiniKrimp can be clamped into a vise for operation



## Table Mount

Part No. 015306

- Machined and bent from 1/4" thick 1018 steel
- Mount connects to the bottom of the MiniKrimp using four 3/8-16 bolts (not included)
- MiniKrimp can then be mounted to a table using the four 3/8" clearance holes on the other side of the plate (bolts not included)



## High Pressure Hose Assembly

Part No. 015309

- Parker 10,000 psi, 1/4" I.D. hose with 3/8" female JIC connections on both ends (PN HP0606060604-72")
- Hose is 6' long
- Hose is used when a flexible connection is required between the MiniKrimp and a hydraulic pressure source



## Replacement Connector

Part No. 015308

- Replacement stainless-steel bent tube rigid connector
- For use with 94C-001-PFD (MiniKrimp Hand Pump Model)



## Replacement Connector

Part No. 025349

- Replacement stainless-steel bent tube rigid connector
- For use with 94C-002-PFD (MiniKrimp Air Over Hydraulic Model)

**Note:** The hydraulic connectors shown on this page are designed exclusively for use with the MiniKrimp. No other connectors are approved for use with the MiniKrimp without expressed written consent from Parker Parflex Division's technical support. Any worn connectors should be replaced immediately.



## High Pressure Hose Assembly

Part No. 045234

- Parker 10,000 psi, 1/4" I.D. hose with quick coupler
- Hose is designed to be used when mounting a hand pump to the 94C-MKS MiniKrimp stand's base

ie: HP Hose Assembly with applicable quick connects  
 PN HP0101040604-36 (12" guard)



## Folding Stand

Part No. 94C-MKS

(See pictures below for configuration examples)

- Lightweight folding stand designed exclusively for the MiniKrimp portable crimper (works for all versions)
- Fold up design is easy to store
- Mounting hardware and safety instructions are included
- Patented design



MiniKrimp™  
with Hand Pump

Hand Pump  
MiniKrimp™

Air Over Hydraulic  
MiniKrimp™

Air Over Hydraulic  
MiniKrimp™ and  
Folding Stand

For detailed ordering information, please consult price list or contact Parflex® Division.


Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Assembly Detail & Parts List

## MiniKrimp™ Hand Pump Model

Part No.	Description	Qty.
015301	2 Speed Light Weight Hand Pump	1
015302	Hardened Steel Sleeve	1
015303	Custom Cylinder	1
015304	Aluminum Frame	1
015305	Cup Pusher	1
015306	Bent Tube Assembly	1
015310	3/8" x 3/8" Shoulder Bolt	1
015415	Spring Plunger	1
6 CTX-S	3/8" 37° to 1/4" NPT Elbow	1
6-6 CTX-S	3/8" 37° to 3/8" NPT Elbow	1
822011	Die Separator	1
822012	Spring	1
822031	Retention Ring	1
82C-R01-PFD	Silver Die Ring	1
015411	3/8-16 18-8 SS SHCS 2.5" Long	2
015413	1/4-20 18-8 SS Lock Washer	2
015414	1/4-20 18-8 SS Flat Washer	2
015412	1/4-20 18-8 SS SHCS .75" Long	4




Minikrimp Serial Number




For detailed ordering information, please consult price list or contact Parflex® Division.



# MiniKrimp™ Air Over Hydraulic Model



Part No.	Description	Qty.
015302	Hardened Steel Sleeve	1
015303	Custom Cylinder	1
015304	Aluminum Frame	1
015305	Cup Pusher	1
015310	3/8" x 3/8" Shoulder Bolt	1
015415	Spring Plunger	1
6-2 CTX-S	3/8" 37° to 1/8" NPT Elbow	1
6-6 CTX-S	3/8" 37° to 3/8" NPT Elbow	1
822011	Die Separator	1
822012	Spring	1
822031	Retention Ring	1
82C-R01-PFD	Silver Die Ring	1
015411	3/8-16 18-8 SS SHCS 2.5" Long	2
015413	1/4-20 18-8 SS Lock Washer	2
015414	1/4-20 18-8 SS Flat Washer	2
015412	1/4-20 18-8 SS SHCS .75" Long	4
025349	Bent Tube Assembly	1
025399	Air Powered Pump	1



Minikrimp Serial Number

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# Karrykrimp, Karrykrimp 2, Parkrimp 1



## Karrykrimp

Karrykrimp, with crimping capability for SAE 100R1, 100R2, 100R7, 100R8 and 100R14 hose, gives you true field-crimping capability. Utilizing Parker's patented unitized dies (the same as Parkrimp 1 and 2), this lightweight machine is easily carried to the job site for quick, easy field assemblies – when downtime is critical. The Karrykrimp unit puts hose assembly fabrication where you need and want it, on the spot.

### Part Number

82C-061L-PFD.....Karrykrimp, two-piece stand, silver die ring, black die ring, connection hose with coupling, no dies, no pump

82C-R01-PFD.....Karrykrimp silver die ring

### Features

- Crimps most hoses up to 1-1/4" I.D. (Check Crimpsource™ for details)
- Rating: 30 ton force @ 10,000 psi maximum
- Full Cycle Time: 30 seconds with electric pump
- Portable
- Approved for use with SAE 100R1, 100R2, 100R7, 100R8 and 100R14 hose
- Also available in bench mounted construction (82C-KKB-PFD)

## Karrykrimp 2

Karrykrimp 2 is portable, compact and ruggedly built. Model 85C-061L-PFD includes crimping machine, collapsible stand, die rings, and connection hose with quick coupling. Select the power unit that meets your needs.

### Part Number

85C-061L-PFD.....Karrykrimp 2, two-piece stand, silver die ring, black die ring, connection hose with coupling, no dies, no pump

85C-R01-PFD.....Karrykrimp 2 silver die ring

### Features

- Crimps most hoses 1/4" up to 1-1/4" I.D. (Check Crimpsource™ for details)
- Rating: 60 ton force @ 10,000 psi maximum
- Full Cycle Time: 20 seconds with electric pump
- Collapsible stand
- Portable
- Also available in bench mounted construction (85C-KKB-PFD)

## Parkrimp 1

Parkrimp 1 offers hose assembly capability for SAE 100R1, 100R2, 100R7, 100R8 and 100R14 hose. Its patented design provides you with the ability to crimp straight – as well as bent tube hose ends; a full power return cycle allows quick, easy size and hose type changes, while the die pusher automatically moves out of the way for easy die insertion: Bench mounted at a 20° angle lets you load and unload hydraulic assemblies as easily as possible. Parkrimp 1 gives you the ease and flexibility to manufacture hydraulic hose assemblies you require – and in less than ten seconds.

### Part Number

80C-061-PFD.....Parkrimp 1 crimper, silver die ring, black die ring, no dies

80C-R01-PFD.....Parkrimp 1 silver die ring

### Features

- Crimps most hoses up to 1-1/4" I.D. (Check Crimpsource™ for details)
- Rating: 30 ton force @ 3,000 psi maximum
- Full Cycle Time: 20 seconds
- Crimps straight or bent tube hose ends
- Full power return cycle
- Approved for use with SAE 100R1, 100R2, 100R7, 100R8 and 100R14 hose



# Parkrimp 2, Superkrimp, PHastkrimp



## PHastkrimp

PHastkrimp is a fast, benchmounted crimper for braided and multispiral hoses.

### Part No.

89C-061-PFD..... Parkrimp 2 head assembly, Parkrimp 2 stand assembly with 230/460 volt 3 phase power unit wired for 230 volt, adaptor bowl, spacer ring, no dies

## Features

- Crimps most hoses up to 2" I.D. (Check Crimpsource™ for details)
- Rating: 60 ton force @ 4,200 psi maximum
- Full Cycle Time: 6 seconds



## Parkrimp 2

Parkrimp 2's advanced design - with capacity to handle 100R1 through 100R14 hose types, coupled with straight or bent tube ends - is the industry's leading edge in the manufacture of hydraulic hose assemblies. Unparalleled in its design, Parkrimp 2 needs no special adjustments or gauge settings. Simply insert the unitized or split die train for the appropriate size - and with push button ease you have factory-quality assemblies in just seconds.

### Part No.

83C-081-PFD..... Parkrimp 2 head assembly, Parkrimp 2 stand assembly with 230/460 volt 3 phase power unit wired for 230 volt, adaptor bowl, spacer ring, no dies.

## Features

- Crimps hoses up to 2" I.D.
- Rating: 125 ton force @ 5,000 psi maximum
- Full Cycle Time: 30 sec. w/o adaptor bowl, 20 sec. with adaptor bowl
- Approved for use with SAE 100R1, 100R2, 100R7, 100R8 and 100R14 hose
- Crimps straight or bent tube hose ends
- Push button, easy operation



## Superkrimp

Superkrimp can handle all Parflex thermoplastic and PTFE hose assemblies up through 2" I.D. Its design - with capacity to handle 100R7, 100R8, and 100R14 hose types, coupled with straight or bent tube ends - is the industry's leading edge in the manufacture of hose assemblies. Unparalleled in its design, Superkrimp needs no special adjustments or gauge settings. Simply insert the unitized or split die train for the appropriate size, and with push-button ease you have factory quality assemblies in just seconds.

### Part Number

88C-082-PFD..... Superkrimp, 230/240-volt single phase power unit wired for 230 volts, adaptor bowl, spacer ring, spacer plate, no dies. Order appropriate dies from the crimp die selection chart in the General Technical Section, pgs. G-30 : G-41.

## Features

- Crimps thermoplastic or fluoropolymer hose up to 2" I.D.
- Rating: 70 ton force @ 5,000 psi maximum
- Full Cycle Time: 20 sec. w/o adaptor bowl, 15 sec. with adaptor bowl
- Bench-top design
- Push button, easy operation
- Stainless steel crimping
- Push button ease
- Approved for use with 100R7, 100R8 and 100R14 hose

For detailed ordering information, please consult price list or contact Parflex® Division.

# Parflex Hand Pumps



## Hand Pump Part No. 015301

For use with MiniKrimp Hand Pump Model  
Easy-to-use hand pump delivers 10,000 psi

Length.....13-3/8"  
Width.....3-1/4"  
Height.....3-5/8"  
Port Size.....1/4" NPTF  
Weight.....4.7 lbs.  
Hydraulic Fluid.....Enerpac Oil only



## Hand Pump Part No. 82C-0HP-PFD

For use with Karrykrimp, KarryKrimp 2 & MiniKrimp  
Attach with hose. Easy-to-use hand pump delivers 10,000 psi

Length.....23"  
Width.....4"  
Height.....5"  
Port Size.....3/8" NPTF  
Weight.....9 lbs.  
Hydraulic Fluid.....Enerpac Oil only



## Hand Pump Part No. 85C-0HP-PFD

For use with Karrykrimp, Karrykrimp 2 & MiniKrimp  
Attach with hose. Easy-to-use hand pump delivers 10,000 psi

Length.....28-15/16"  
Width.....13"  
Height.....11"  
Port Size.....3/8" NPTF  
Weight.....61 lbs.  
Hydraulic Fluid.....Enerpac Oil only



## Air/Hydraulic Pump Part No. 025399

For use with MiniKrimp Air-over-Hydraulic Model  
Lightweight pump operates with 60 - 100 psi shop air pressure

Length.....13"  
Width.....4-1/2"  
Height.....5"  
Intake Port Size.....1/4" NPTF  
Output Port Size.....1/8" NPTF  
Weight.....12 lbs.  
Hydraulic Fluid.....Enerpac Oil only

All pumps are supplied to Parker by ENERPAC. For repair or warranty work to any of the cylinders or pumps, contact your nearest ENERPAC Service Center. For the ENERPAC Service Center nearest you, call 1-800-558-0530 or visit the ENERPAC web site at [www.Enerpac.com](http://www.Enerpac.com).



For detailed ordering information, please consult price list or contact Parflex® Division.



## Air/Hydraulic Pump

### Part No. 82C-0AP-PFD

For use with MiniKrimp, Karrykrimp and Karrykrimp 2  
Lightweight, operates with 80-150 psi shop air  
Pump delivers 10,000 psi

Length.....15"  
Width.....6"  
Height.....6"  
Port Size..... 1/4" NPTF  
Weight..... 14 lbs.  
Hydraulic Fluid .....Enerpac Oil only



## Electric Pump

### Part No. 82C-0EP-PFD

For use with MiniKrimp, Karrykrimp and Karrykrimp 2  
Lightweight. Pump delivers 10,000 psi

Length.....13"  
Width.....13"  
Height.....15"  
Port Size..... 3/8" NPTF  
Weight..... 31 lbs.  
Hydraulic Fluid .....Enerpac Oil only  
115 volt, 1 phase, 50/60 Hz, 9 amp



## Electric Pump

### Part No. 85C-0EP-PFD

Heavy duty pump delivers 1,000 psi at a faster cycle time

Length.....19"  
Width.....11"  
Height.....17"  
Port Size..... 3/8" NPTF  
Weight..... 59 lbs.  
Hydraulic Fluid .....Enerpac Oil only  
115 volt, 1 phase, 50/60 Hz, 20 amp

All pumps are supplied to Parker by ENERPAC. For repair or warranty work to any of the cylinders or pumps, contact your nearest ENERPAC Service Center. For the ENERPAC Service Center nearest you, call 1-800-558-0530 or visit the ENERPAC web site at [www.Enerpac.com](http://www.Enerpac.com).

For detailed ordering information, please consult price list or contact Parflex® Division.

# Conversion Kits



## Hydraulic Press Kit

Specifications	
Required height from press base to press ram	10"
Required width of bowl diameter	5"
Bowl Rating	30 tons force maximum
Minimum required press capacity	Hose size 1/4" - 1/2" - 20 ton press Hose size 5/8" - 1-1/4" - 30 ton press

Part Description	Individual Part Number
Bowl Assembly	8PC-030-PFD
Pusher	8PC-00P-PFD
Silver Die Ring	81C-R01-PFD

Each component for press kit must be ordered separately.



## Weatherhead Conversion Kit

Convert Weatherhead T-400 crimper to utilize Parker Parkimp No-Skive fittings.

Part Description	Individual Part Number
Bowl Assembly	8PC-030-PFD
Pusher	8WC-00P-PFD
Silver Die Ring	81C-R01-PFD

Each component for press kit must be ordered separately.



## Gates Conversion Kit

Convert Gates 701, 703 and 707 bottom loading crimpers to utilize Parker Parkimp No-Skive fittings.

Part Description	Individual Part Number
Bowl Assembly	8PC-030-PFD
Silver Die Ring	81C-R01-PFD

Each component for press kit must be ordered separately.

# Swagers



## SQ-101-SW Swager/Mender

- Used for field assembly or repair on Predator S6 and S9 hoses

# Vise Blocks



## Vise Blocks for Parflex Hose

**For Hose Sizes  
Part Number**

-3, -4, -5, -6, and -8; 3/16", 1/4", 5/16",  
3/8" and 1/2" I. D. ....VBS

-12 and -16; 3/4" and 1" I. D. ....VBL

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

*For detailed ordering information, please consult price list or contact Parflex® Division.*



# Cutoff Tools



## Hose Cutoff Machine

Part No. 332T-115V-PFD

- Recommended for PTFE Hose
- Power unit for quick, easy cutting of cotton or rubber-covered fabric braid or wire reinforced hose
- Equipped with 1-1/2 HP, 3650 RPM, 115/230V single phase electric motor wired for 115V
- Belt-driven cutting wheel of high-speed steel, hardened and ground for smooth, dust-free, long-lasting service
- Moving parts shielded by guards
- Includes a smooth cutting blade (8" with 5/8" arbor size)

Model 332T-115V will cut:

- Two wire braid, 1-1/4" I.D. maximum
- One wire braid, 2" I.D. maximum
- Four spiral, 1-1/4" I.D. maximum

Replacement Blades	Part Number
--------------------	-------------

Smooth Cutting (8" with 5/8" arbor size).....	580661
Scallop Cutting .....	24398



## Karrykut

Part No. 631075-PFD

- Portable power saw
- Clean cutoff of rubber or cotton covered, wire or fabric reinforced hose -4 through -32
- Hardened steel blade powered
- 110V (13 amp) universal AC-DC motor
- Hand grip, trigger control
- Unique clamp which spreads hose as it is cut to prevent binding of blade

Description	Part Number
-------------	-------------

Universal Clamp Attachment* .....	631076
Replacement Blade (8" with 5/8" arbor size).....	580661
Replacement Power Saw (less clamp and Blade).....	631140

\*May be used with any portable power saw unit having a 5/8" arbor, 8" blade capacity



## Hose Cutoff Tool

Part No. 316-PFD

- Cuts hose up to 1" O.D.
- Small
- Easy to use
- Manually operated unit for quick cutting of Parflex hoses (not recommended for wire reinforced)



## Push-Lok Cut-Off & Assembly Tool

Part No. 881540-PFD

- Combines hose cutter and toggle action press
- Cuts and assembles Parker 83FR in sizes 1/4" through 3/4" I.D.



## Hose & Tubing Cutter

Part No. HTC

- Special V-block design with easy adjustable blade ensures a straight, clean cut
- Minimal flattening of hose/tubing during cutting - Straight, square cut enhances fitting retention
- Cuts up to 1" O.D. hose or tubing (Non-wire reinforced thermoplastic hose and tubing and rubber hose and tubing)
- Replacement blades: HTC-RB



## Hose Cut-Off Tool

Part No. TH11-1-PFD

- Designed for quick, easy cutting of textile reinforced hose
- Squarely cuts fiber reinforced hoses in sizes 1/4" through 3/4" I.D.



## Plastic Tube Cutter

Part No. PTC

- Razor-edged tube cutter
- Closes automatically, assuring clean and square cuts
- May be used with most plastic tubing up to 5/8" I.D.

Description	Part Number
Replacement Blades.....	PTC-001-RB

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

# Parflex Parkrimp Dies



Parkrimp dies, specifically engineered for thermoplastic and fluoropolymer hose:

- Linked die segments
- Pre-matched and assembled
- Fitting size color coded

Color Code	
Size	Color
-1.5	GR
-2	BR
-3	GR
-4	R
-5	P

Color Code	
Size	Color
-6	Y
-8	BL
-10	O
-12	G
-16	B

Color Code	
Size	Color
-20	W
-24	R
-32	G

Parkrimp Approved Silver Die Rings	
Machine	Approved Die
Parkrimp 2 and Superkrimp	NA*
Parkrimp 1	80C-R01-PFD
Karrykrimp and MiniKrimp	82C-R01-PFD
Karrykrimp 2 and PHastkrimp	85C-R01-PFD

\*No additional silver die rings required.

## Note:

- 1) Parflex dies have been designed for use with the silver die ring. Silver die rings are to be used with all Parflex hoses unless otherwise specified.
- 2) See Die Selection and Crimp Specification Charts in the General Technical Section of this catalog (pgs. G-30 : G-41) for proper die selection and crimp specifications.
- 3) Visit Crimpsource™ Online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource) for the latest and most up to date crimping information such as dies and crimp specifications for all your favorite Parflex hoses.

## Die Racks



### Die Storage Rack

Part No. 80C-0DR-PFD/83C-0DR-PFD

- Holds small and large Parkrimp dies
- Can be bolted together to a work bench

Description	Part No.
Storage 3 small dies	80C-0DR-PFD
Storage 2 large dies	83C-0DR-PFD



### Swivel Die Rack

Part No. 80C-SDR-XXXX-PFD


- Holds up to 30 Parkrimp dies
- Powder coated, heavy duty steel construction
- Consist of base unit and up to 5 circular holders
- Floor or bench mounted

Description	Part No.
Swivel Die Rack and Small Die Holder	80C-SDR-SM-PFD
Swivel Die Rack and Large Die Holder	80C-SDR-LG-PFD
Swivel Die Rack Base	80C-SDR-BASE-PFD

# Hose Guards


Parker hose guards prolong the life of hoses that are exposed to rugged operating conditions. In addition to protecting the hose from abrasion and cutting, they limit the bending radius which prevents kinking.

## PV - Clear Vinyl Hose Guard



Part Number	Guard I.D.		Standard Length	
	inch	mm	feet	mtr.
#	⊙			
PV97-1	0.44	11	100	30.5
PV139-1	0.56	14	100	30.5
PV1611-1	0.68	17	100	30.5
PV2014-1	0.87	22	50	15.2
PV2420-1	1.25	32	50	15.2
PV3224-1	1.50	38	50	15.2

## HBR - Hose Bend Restrictor (Black Elastomer)



Part Number	Hose Size		L		D1		D2	
	inch	mm	inch	mm	inch	mm	inch	mm
#	⊙							
HBR-4	1/4	6	5	127	.600	15	.500	13
HBR-6	3/8	10	6	152	.640	16	.625	16

Parker reserves the right to change dimensions and performance parameters without notice.

## 5CNG/CNGLT - Black Vinyl CNG Hose Guard



Hose Part Number	Hose Guard Part Number
#	#
5CNG/CNGLT-3	CNGG5-3
5CNG/CNGLT-4	CNGG5-4
5CNG/CNGLT-6	HBR-6
5CNG/CNGLT-8	CNGG5-8
5CNG/CNGLT-12	CNGG5-12
5CNG/CNGLT-16	CNGG5-16



- Use with Parflex CNG hose
- Contact Parflex Division for information on Hose Guard Kits.

For detailed ordering information, please consult price list or contact Parflex® Division.

# Metallic Spring Guards

Use Spring Guards for protection from abrasion and extreme physical abuse.

## SSG & PSG - Pre-made Spring Guards (Plated, hard-drawn steel wire)



### Standard


Part Number	Guard I.D.		Standard Length	
	inch	mm	inch	mm
#	⊙			
55SSG-3	0.44	11	5	127
55SSG-4	0.55	14	5	127
55SSG-5	0.61	15	5	127
55SSG-6	0.68	17	5	127
55SSG-8	0.83	21	5	127
55SSG-12	1.09	28	7	178

### For CNG Hose (Stainless Steel)


Part Number	Guard I.D.		Standard Length	
	inch	mm	inch	mm
#	⊙			
3PSG-3	0.46	12	5.30	135
5PSG-4	0.63	16	6.25	159
5PSG-6	0.78	20	6.50	165
5PSG-8	0.90	23	6.50	165

Special configurations available upon request.  
Contact factory.

## SG - Steel Spring Guards (Plated, hard-drawn steel wire)




## AG - Flat Steel Armor Guards



Part Number	Guard I.D.		Standard Length	
	inch	mm	feet	mtr.
#	⊙			
55SG-3	0.47	12	25	7.6
55SG-4	0.55	14	25	7.6
55SG-5	0.61	16	25	7.6
55SG-6	0.67	17	25	7.6
55SG-8	0.83	21	25	7.6
55SG-12	1.09	28	10	3
55SG-16	1.35	34	10	3
58SG-12	1.18	30	10	3
58SG-16	1.51	38	10	3

Part Number	Guard I.D.		Standard Length	
	inch	mm	inch	mm
#	⊙			
55AG-3	0.47	12	25	7.6
55AG-4	0.55	14	25	7.6
55AG-5	0.61	16	25	7.6
55AG-6	0.67	17	25	7.6
55AG-8	0.83	21	25	7.6
55AG-12	1.09	28	10	3
55AG-16	1.35	34	10	3
58AG-12	1.18	30	10	3
58AG-16	1.51	38	10	3

# Guards for PTFE Hoses



AS

2625, 2799

2740, 2613

FS

MG

PV



Hose		Max. O.D.	Partek Sleeve	External Round Spring	Internal Round Spring	External Flat Spring	Internal Flat Spring	Fire Sleeve	External Anti-Kink Casing	Clear Vinyl Sleeve
919/929	-3	0.25	-	2625-10	-	2740-10	-	-	-	PV75-1
	-4	0.32	-	2625-11	-	2740-11	-	FS-F-5	MG-038-015C	PV86-1
	-5	0.40	-	2625-14	-	2740-14	-	FS-F-7	MG-044-015C	PV97-1
	-6	0.46	AS-Y-11/AS-B-11	2625-15	-	2740-16	-	FS-F-8	MG-050-015C	PV108-1
	-8	0.56	AS-Y-11/AS-B-11	2625-19	-	2740-19	2613-13CR	FS-F-10	MG-062-015C	PV1310-1
	-10	0.66	AS-Y-13/AS-B-13	2625-22	-	2740-22	2613-16CR	FS-F-12	MG-075-015C	PV1411-1
	-12	0.79	AS-Y-15/AS-B-15	2625-26	-	2740-26	2613-20CR	FS-F-14	MG-081-015C	PV1814-1
	-16	1.05	AS-Y-17/AS-B-17	2625-34	-	2740-34	2613-28CR	FS-F-20	MG-112-015C*	PV2218-1
	-20	1.32	AS-Y-22/AS-B-22	2625-44	-	2740-44	2613-37CR	FS-F-24	MG-144-015C	-
	936	-4	0.56	AS-Y-11/AS-B-11	2625-20	-	2740-20	-	FS-F-11	-
-6		0.69	AS-Y-13/AS-B-13	2625-24	-	2740-24	-	FS-F-14	-	-
-8		0.86	AS-Y-15/AS-B-15	2625-29	-	2740-31	-	FS-F-16	-	-
-10		0.96	AS-Y-17/AS-B-17	2625-35	-	2740-35	-	FS-F-18	-	-
-12		1.12	AS-Y-19/AS-B-19	2625-38	-	2740-38	-	FS-F-20	-	-
-16		1.43	AS-Y-27/AS-B-27	2625-50	2799-16CR	2740-50	-	FS-F-24	-	-
-20		1.80	AS-Y-35/AS-B-35	2625-70	2799-20CR	2740-60	-	FS-F-32	-	-
-24		2.05	AS-Y-37/AS-B-37	2625-72	2799-24CR	2740-70	-	FS-F-38	-	-
-32		2.60	AS-Y-45/AS-B-45	2625-87	2799-32CR	2740-83	-	FS-F-48	-	-
939		-4	0.48	AS-Y-11/AS-B-11	2625-16	-	2740-18	-	FS-F-10	-
	-6	0.59	AS-Y-13/AS-B-13	2625-20	-	2740-20	-	FS-F-11	-	-
	-8	0.75	AS-Y-15/AS-B-15	2625-25	-	2740-25	-	FS-F-14	-	-
	-10	0.88	AS-Y-17/AS-B-17	2625-29	-	2740-30	-	FS-F-16	-	-
	-12	1.09	AS-Y-19/AS-B-19	2625-36	-	2740-36	-	FS-F-20	-	-
	-16	1.33	AS-Y-27/AS-B-27	2625-44	2799-16CR	2740-44	-	FS-F-24	-	-
	-20	1.75	AS-Y-35/AS-B-35	2625-58	2799-20CR	2740-58	-	FS-F-32	-	-
	-24	2.05	AS-Y-39/AS-B-39	2625-67	2799-24CR	2740-70	-	FS-F-38	-	-
	-32	2.56	AS-Y-47/AS-B-47	2625-83	2799-32CR	2740-83	-	FS-F-48	-	-
	943	-6	0.49	AS-Y-11/AS-B-11	2625-17	-	2740-18	-	FS-F-10	-
-8		0.62	AS-Y-13/AS-B-13	2625-21	-	2740-21	2613-13CR	FS-F-11	-	-
-10		0.73	AS-Y-15/AS-B-15	2625-24	-	2740-23	2613-16CR	FS-F-14	-	-
-12		0.99	AS-Y-17/AS-B-17	2625-33	-	2740-35	2613-20CR	FS-F-18	-	-
	-16	1.39	AS-Y-27/AS-B-27	2625-45	-	2740-46	2613-28CR	FS-F-24	-	-

NOTE: \*MG-112-015C to be used on 919-16 only.  
 Partek sleeves come in yellow and black.  
 All internal guards are fabricated from 300 series stainless steel.  
 All external guards are plated steel.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Spring Guards & Armor Guards



Hose Style	Armor Guards/Spring Guards								
	55AG-3 55SG-3	55AG-4 55SG-4	55AG-5 55SG-5	55AG-6 55SG-6	55AG-8 55SG-8	55AG-12 55SG-12	55AG-16 55SG-16	58AG-12 58SG-12	58AG-16 58SG-16
510A/510C/518C	-2, -3	-4	-5	-6	-8			-12	
515H	-3, -4	-5	-6		-8				
520N/528N	-3	-4	-5	-6	-8	-10			
526BA	-3	-4		-6					
527BA	-3	-4							
53DM	-3	-4	-5	-6	-8	-10		-12	
538DM	-3	-4	-5	-6	-8	-10			
540N	-2, -3	-4	-5	-6	-8	-12			
540P		-4		-6	-8	-12			
548N				-6					
55LT	-2, -3	-4	-5	-6	-8	-12			
560	-3	-4	-5	-6	-8	-10		-12	
563		-4		-6	-8				
56DH/568DH	1.5, -2								
575X	-3	-4		-6	-8			-12	-16
580N/588N				-4	-6	-8, -10		-12	-16
H580N									-16
590	-3	-4		-6	-8	-10		-12	-16
593								-12	-16
83FR		-4		-6	-8	-12			
1035A		-4		-6					
1035HT	-3	-4		-6					
B9	-3	-4	-5	-6	-8	-10			
D6			-4		-6	-8, -10	-12		-16
H6		-4	-5	-6	-8	-10		-12	
R6			-4		-6	-8	10, -12		-16
HFS		-4	-5	-6	-8	-12	-16		
HFS2			-4		-6, -8	-10		-12	-16
HJK			-4						
HTB				-4	-6	-8, -10	-12		-16
M8					-6	-8, -10			
XDH	-4			-6	-8				



# PVC Guards



Hose Style	PVC Guards						
	PV97-1	PV139-1	PV1611-1	PV2014-1	PV2218-1	PV2420-1	PV3224-1
510A/510C/518C	-2	-3, -4	-5, -6	-8	-12		
515H	-3	-4, -5	-6	-8			
520N/528N		-3, -4	-5, -6	-8	-10		
526BA		-3, -4	-6				
527BA		-3, -4			-8		
53DM		-3, -4	-5	-6	-8		
538DM		-3, -4	-5	-6	-8		
540N	-2	-3, -4	-5, -6	-8	-12		
540P		-4		-6	-8	-12	
548N				-6			
55LT	-2	-3, -4	-5, -6	-8	-12		
560		-3, -4	-5, -6	-8	-10	-12	
563		-4	-6	-8			
573X	-3						-16
575X		-4	-6	-8		-12	
580N/588N			-4	-6	-8, -10	-12	-16
590		-3, -4	-6	-8	-10	-12	-16
593						-12	-16
83FR		-4	-6	-8		-12	
1035A		-4	-6				
1035HT		-3, -4	-6				
B9		3, -4	-5, -6	-8	-10		
CNG		-3, -4		-6	-8, -10	-12	-16
D6		-4	-6	-8	-10	-12	-16
H6		-4	-5, -6	-8	-10	-12	
R6		-4	-6	-8	-10	-12	
HFS		-4	-5, -6	-8	-12		-16
HFS2			-4	-6, -8	-10	-12	-16
HJK			-4				
HLB	-2, -3						
HTB			-4	-6	-8, -10	-12	-16
M8				-6	-8, -10		
MSH		-5	-6				
MSXL		-5					
PTH		-3					
XDH		-4	-6	-8			

For detailed ordering information, please consult price list or contact Parflex® Division.



# PSG – Parker Spiral Guard



## Features

- High-strength and resilient, Spiral Guard protects hose and cable with superior anti-crush performance
- Exceptionally smooth facing and rounded edges prevent Spiral Guard from getting caught on rough surfaces
- Easy installation and routing
- Low friction interior minimizes wear on hose
- For bundling, organizing and protecting hose and cable, Parflex Spiral Guard is the superior solution for mining operations - In fact, it delivers more advantages than cut pipe or sleeving at a competitive price or less
- Spiral Guard is available in:
  - An MSHA/FRAS approved version for underground mining
  - A standard version (with yellow stripe) for surface applications not requiring fire-resistant, anti-static properties

## Applications



- Mining
- Automotive
- Mobile Equipment

Part Number	Hose O.D. Range		Package Qty.		1-Wire Braid Size		2-Wire Braid Size		Multi-Spiral Size		Weight	
	#		mtr.	feet	inch	mm	inch	mm	inch	mm	lbs./ft.	kg./mtr.
PSG 12	10 – 13	.394-.512	20	65.6	-		-		-		.034	.015
PSG 16 FRAS or PSG 16	12 – 17	.472-.669	20	65.6	1/4	6	1/4	6	-		.040	.018
PSG 20 FRAS or PSG 20	16 – 22	.630-.866	20	65.6	3/8	10	1/4 3/8	6 10	3/8	10	.060	.027
PSG 25 FRAS or PSG 25	22 – 28	.866-1.10	20	65.6	1/2 5/8	13 16	1/2 5/8	13 16	1/2 5/8	13 16	.101	.046
PSG 32 FRAS or PSG 32	27 – 33	1.06-1.30	20	65.6	3/4	19	5/8 3/4	16 19	5/8 3/4	16 19	.151	.068
PSG 40 FRAS or PSG 40	33 – 42	1.30-1.65	20	65.6	1	25	1	25	1	25	.235	.107
PSG 50 FRAS or PSG 50	42 – 55	1.65-2.17	20	65.6	1-1/4 1-1/2	32 38	1-1/4	32	1-1/4	32	.268	.122
PSG 63 FRAS or PSG 63	52 – 65	2.05-2.56	20	65.6	2	51	1-1/2	38	1-1/2	38	.402	.182
PSG 75 FRAS or PSG 75	65 – 80	2.56-3.15	10	32.8	-		2	51	2	51	.637	.289
PSG 90 FRAS or PSG 90	80 – 150	3.15-5.91	10	32.8	-		-		-		.771	.350
PSG 110 FRAS or PSG 110	150 – above	5.91-above	10	32.8	-		-		-		1.00	.454



For detailed ordering information, please consult price list or contact Parflex® Division.

# General Technical


Hose Assembly Instructions

Hose Selection, Installation  
& Maintenance

Die Selection & Crimp Charts

Materials

Government Agency  
& Specifications



# Table of Contents

## Hose Selection, Installation & Maintenance

Intro .....	G-3
Selection of Hose Diameter.....	G-4
Calculation of Hose Length.....	G-5
Volumetric Expansion of Hose .....	G-6
Hose Permeation Data (510/510A).....	G-8
Selection, Installation & Maintenance .....	G-9

## Hose Assembly & Crimping

Permanent Crimp Assembly Instructions.....	G-10 : G-12
MiniKrimp™ Fitting Assembly Procedures.....	G-13 : G-15
Field Attachable Fitting Series Assembly Instructions .....	G-16 : G-17
PTFE Permanent Crimp Assembly Instructions .....	G-18 : G-20
PTFE Field Attachable Assembly Instructions .....	G-21 : G-23
Sewer Hose SQ-Swage Assembly Instructions .....	G-24 : G-26
Twin/Multi-Line Separation.....	G-27 : G-28
Ferrul-Fix Installation Instructions .....	G-29

## Technical Data

Die Selection/Crimp/Swage .....	G-30 : G-41
Karrykrimp .....	G-36 : G-38
Karrykrimp 2 .....	G-33 : G-35
Minikrimp™ .....	G-39 : G-40
Parkrimp 1 .....	G-36 : G-38
Parkrimp 2 .....	G-30 : G-32
PHASTkrimp .....	G-33 : G-35
Superkrimp .....	G-30 : G-32
Die Selection & Swage Specification Chart (Sewer Hose).....	G-41
Hose Fitting Insertion Values.....	G-42
Hose Fitting Thread Guide .....	G-43
Media to Fitting & Seal Compatibility Guide .....	G-44
Metal Tube & Fitting Material Compatibility Guide.....	G-46
O-Ring Material Selection Guide.....	G-48

Metals Corrosion Scale .....	G-49
Materials to Parflex Part Number .....	G-50
Media to Hose Material Compatibility Guide .....	G-51 : G-54
Media to Plastic Tubing Material Compatibility Guide .....	G-55 : G-57
Metric Conversion Chart .....	G-58

## Other

Government Agency & Specifications.....	G-59
Parker Safety Guide .....	G-60 : G-63
ENERPAC Warranty.....	G-64
Offer of Sale .....	G-65
Part Number Index .....	i
Key Word Index .....	v

# General Technical Introduction

## Hose Assembly Tutorial

### Crimping

- **Steps for crimping** are clearly marked with sequences showing product distinctions between products lines.
  - Crimping section as well as universal preparations for all hoses appear first.
  - Field attachable assemblies appear next.

### Twin/Multi-Line Hose

- Review **twin/multi-line hose separation**, pg. G-27 if applicable – this will give you information before proceeding to the assembly pages – Not following this procedure may cause permanent damage to hoses.

\*The Hose Products Division Parkrimp 1 is used as an example in this section for illustration and instruction purposes. The PARKRIMP crimping system is the same for all standard Parker portable or bench style crimpers.

Please note: You must become familiar with your own specific crimper to determine its operational features. Please review thoroughly and understand your operator's manual included with your machine. Never use a crimper beyond its recommended published capacities. Crimp specifications can be found in this catalog and on line by accessing Crimp Source. [www.parker.com/crimpsource](http://www.parker.com/crimpsource)

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



# Selection of Hose Diameter

## From Flow Rate and Velocity

The Fluid Velocity Nomogram gives the velocity of a liquid as a function of flow rate and inside diameter of the fluid line. The commonly recommended maximum velocities for hydraulic oil systems at 200°F or less are indicated for guidance.

Example: At 10 gpm, what is the minimum size within the recommended velocity range for a hydraulic pressure line?

The dashed line drawn from the 10 gpm mark on the left hand line to the maximum velocity of 20 fps intersects the middle line at .438" (7/16" I. D. hose or tubing). For a hose application, use 1/2" I. D., the nearest common standard size.


This chart is based on the following formulas:

$$v_{fps} = \frac{.321Q}{bd^2}$$

Q = gal per min  
d = hose or tube I. D. (inch)

$$cu. ft./min. = .1337 Q$$

The cu. ft. per min. value is the actual volume flow rate under flowing conditions. For air, standard cfm of free air = 7.81 actual cfm when the inlet air is at 100 PSIG, 68°F.




# Calculation of Hose Length

## For Over-the-Sheave Applications

The exact cutoff length for an optimum over-the-sheave assembly depends on the particular mechanical arrangement of the machine. A method for finding an approximate starting point is as follows:

1. Assemble hose with one coupling as shown in diagram.
2. Measure hose length from point 1 to point 2 with hose taut (.985 accounts for 1.56 stretch).  
LO = length
3. Calculation of insert allowance (x) may be found from the coupling dimension tabulations in the fittings section or from direct measurement on the coupling. A 1.5% stretch allowance is provided in this formula.
4. Calculate hose cutoff or free length LF:  
LF = 0.985 LO + 2x  
Where LF includes coupling, insert allowance on both ends.
5. Couple the remaining hose end, check crimp, and assemble on the machine.



For detailed ordering information, please consult price list or contact Parflex® Division.



# Volumetric Expansion of Hose

## Volumetric Expansion of Parker Hoses

Hydraulic hoses expand under pressure. On some applications, customers can use the differences in expansion between hoses to tune systems for better performance or even noise reduction. Parflex has tested a select list of hoses and determined the rate of expansion in cubic centimeters per foot of hose (cc/ft).

To calculate the volumetric expansion of a hose, substitute the desired pressure into the "X" values in the appropriate equation. For other hoses, please contact the division.

Hose Part Number	Volumetric Expansion at Maximum Working Pressure		Equation for Volumetric Expansion
	(psi)	(cc/ft)	Y=(cc/ft) X=(psi)
510C-3/518C-3	3250	2.33	Y=0.0007X+0.0581
510C-4/518C-4	3000	2.71	Y=0.0009X+0.0059
510C-5/518C-5	2500	3.41	Y=0.0013X+0.1647
510C-6/518C-6	2250	4.32	Y=0.0019X+0.0471
510C-8/518C-8	2250	7.36	Y=0.0032X+0.1637
510C-12/518C-12	1250	8.99	Y = 0.00745x - 0.29910
510C-16/518C-16	1000	15.33	Y = 0.01573x - 0.44928
520N-3/528N-3	5000	1.13	Y = 0.0002x + 0.1621
520N-4/528N-4	5000	2.05	Y = 0.00031x + 0.47589
520N-5/528N-5	4500	2.63	Y = 0.00048x + 0.48415
520N-6/528N-6	4000	2.87	Y = 0.00053x + 0.75151
520N-8/528N-8	3500	3.64	Y = 0.00086x + 0.64994
520N-10/528N-10	2750	4.25	Y = 0.001x + 1.505
53DM-3/538DM-3	3000	1.36	Y = 0.00039x + 0.13035
53DM-4/538DM-4	3000	1.90	Y = 0.00062x + 0.02373
53DM-5/538DM-5	3000	2.78	Y = 0.0009x + 0.0403
53DM-6/538DM-6	3000	3.19	Y = 0.0010x + 0.0647
53DM-8/538DM-8	3000	4.68	Y = 0.0016x + 0.0384
53DM-10/538DM-10	3000	9.82	Y = 0.0033x - 0.2254
540N-2/548N-2	3000	1.11	Y = 0.00036x + 0.04607
540N-3/548N-3	3000	1.75	Y = 0.00057x + 0.03059
540N-4/548N-4	2750	2.33	Y = 0.00079x + 0.14354
540N-5/548N-5	2500	3.46	Y = 0.00124x + 0.31870
540N-6/548N-6	2250	4.06	Y = 0.00174x + 0.15045
540N-8/548N-8	2000	6.05	Y = 0.0030x + 0.0928
540N-12/548N-12	1250	10.26	Y = 0.0081x - 0.2671
560-3	3500	0.575	Y = 0.00017x + 0.00875
560-4	3250	0.757	Y = 0.0002x + 0.1172
560-5	3000	0.729	Y = 0.00021x + 0.09887
560-6	2750	1.33	Y = 0.0004x + 0.1918
560-8	2500	1.98	Y = 0.0007x + 0.2093
560-10	2000	3.04	Y = 0.0012x + 0.5704
560-12	1750	3.07	Y = 0.0015x + 0.4449

Continued on next page

# Volumetric Expansion of Hose (cont.)

Hose Part Number	Volumetric Expansion at Maximum Working Pressure		Equation for Volumetric Expansion
	(psi)	(cc/ft)	Y=(cc/ft) X=(psi)
575X-3	5000	1.69	Y = 0.0003x + 0.2119
575X-4	5000	2.05	Y = 0.0003x + 0.5601
575X-6	5000	2.71	Y = 0.0004x + 0.8412
575X-8	5000	4.59	Y = 0.00064x + 1.41795
575X-12	5000	12.52	Y = 0.00192x + 2.92038
575X-16	5000	16.81	Y = 0.0028x + 2.9560
590-3	5000	0.646	Y = 0.00013x + 0.01692
590-4	5000	0.888	Y = 0.00016x + 0.09821
590-6	4000	1.87	Y = 0.00038x + 0.32317
590-8	3500	2.17	Y = 0.00049x + 0.43765
590-10	3000	3.69	Y = 0.00095x + 0.82449
590-12	2500	4.20	Y = 0.0013x + 0.8216
590-16	2000	6.21	Y = 0.0026x + 1.0558
D604	3000	1.80	Y = 0.00044x + 0.51607
D606	3000	2.00	Y = 0.0006x + 0.2892
D608	3000	2.88	Y = 0.00057x + 1.20744
D610	3000	2.08	Y = 0.00061x + 0.23127
D612	3000	5.53	Y = 0.00142x + 1.21743
D616	3000	7.33	Y = 0.00205x + 1.24905
H604	3000	1.80	Y = 0.00044x + 0.51607
H605	3000	1.35	Y = 0.00036x + 0.26536
H606	3000	2.00	Y = 0.0006x + 0.2892
H608	3000	2.88	Y = 0.00057x + 1.20744
H610	3000	2.08	Y = 0.00061x + 0.23127
H612	3000	5.53	Y = 0.00142x + 1.21743

The actual volumetric expansion achieved is influenced by multiple variables including fluid properties, hose routing and application temperature. The volumetric expansion calculation is only a general guideline and must be verified by actual testing in the end-use application. No performance warranty in design is expressed or implied by this calculation. Parker recommends that the user review and understand all the precautions listed in the Parker Safety Guide for Selecting and Using Hose, Fittings and Accessories, bulletin BUL. 4400-b.1.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Hose Permeation Data (510A)

## Permeation Rate at 120°F (Pound per Linear Hose Foot per Year)

Hose Size	R12	R22	R507	R404A	R502	R134A
-2	-	.28	-	-	.03	-
-3	-	.30	.08	.07	-	-
-4	-	.71	.15	.10	-	-
-6	-	1.11	-	-	.87	-

## Permeation Rate at 212°F (Pound per Linear Hose Foot per Year)

Hose Size	R12	R22	R507	R404A	R502	R134A
-2	-	-	-	-	-	-
-3	-	1.25	-	-	-	-
-4	.08	2.32	-	-	-	.07
-6	-	-	-	-	-	-

### Notes:

1. Data is for comparison only. Actual results may vary due to differences in application temperature and pressure.
2. Data is collected in highly controlled tests per UL1963.
3. Parker Safety Guide for Selecting and Using Hose, Tubing, Fittings and Related Accessories, Section 2.6:

**Permeation:** Permeation (that is, seepage through the Hose) will occur from inside the Hose to outside when Hose is used with gases, liquid and gas fuels, and refrigerants (including but not limited to such materials as helium, diesel fuel, gasoline, natural gas, or LPG). This permeation may result in high concentrations of vapors which are potentially flammable, explosive, or toxic, and in loss of fluid. Dangerous explosions, fires, and other hazards can result when using the wrong Hose for such applications.

The system designer must take into account the fact that this permeation will take place and must not use Hose if this permeation could be hazardous. The system designer must take into account all legal, government, insurance, or any other special regulations which govern the use of fuels and refrigerants. Never use a Hose even though the fluid compatibility is acceptable without considering the potential hazardous effects that can result from permeation through the Hose Assembly.

Permeation of moisture from outside the Hose to inside the Hose will also occur in Hose assemblies, regardless of internal pressure. If this moisture permeation would have detrimental effects (particularly, but not limited to refrigeration and air conditioning systems), incorporation of sufficient drying capacity in the system or other appropriate system safeguards should be selected and used.

*For detailed ordering information, please consult price list or contact Parflex® Division.*

**Parker Hannifin Corporation** | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Hose Assembly and Crimping

## Permanent Crimp

Series 54, 55, 58, 58H, 92, CY, HY, LV, MS, SF

**CAUTION:** There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See Table of Contents for listing.

1

### Inspection



**Hose** – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



**Fittings** – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

2

### Assembly Prep



**Insertion Depth** – Shown is a 55 series fitting. See Hose Fitting Insertion Values, pg. G-42 for insertion depths of fitting series that do not incorporate an insertion depth. Mark hose end with proper insertion depth line.



**Lubrication (as required)** – Using an SAE 20 weight lubricating oil, lightly lubricate inside of hose end.

#### Warning


Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service, lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.

3

### Assembly



**Assemble hose** – Push hose into fitting all the way to depth insertion mark. (If fitting does not readily slide onto hose, perform the next step.)



Using Parker VBS or VBL (vise blocks) and a rubber mallet, tap fitting onto hose until bottom of fitting shell is aligned with depth insertion mark.


# Hose Assembly and Crimping

## Permanent Crimp (cont.)

Series 43, 54, 55, 58, 58H, 92, CY, HY, LV, MS, SF

4

### Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

5


### Lubricate Bowl



Grease frequently using a premium, quality, lithium-base grease. Apply a thin layer of grease on bowl of crimper base plate.

6

### Die & Spacer Ring



**Crimp Die** – Place die set into bowl.



**Die Ring** – Place applicable die ring on top of die. Position ring so it is centered on die.


(Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

7

### Crimp



**Assemble hose** – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

#### Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

#### Note

Pump on crimper must not exceed the rated pressure of the crimper being used. Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-11

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

# Hose Assembly and Crimping

## Permanent Crimp (cont.)

Series 54, 55, 58, 58H, 92, CY, HY, LV, MS, SF

8


### Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))




# MiniKrimp™ Fitting Assembly Procedures

**CAUTION:** There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See **Table of Contents** for listing.

1

## Inspection



**Hose** – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



**Fittings** – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

2

## Assembly Prep



**Insertion Depth** – Mark hose end with proper insertion depth line. See Hose Fitting Insertion Values, pg. G-42 for insertion depths of fitting series that do not incorporate an insertion depth.



**Lubrication (as required)** – Using an SAE 20 weight lubricating oil, lightly lubricate inside of hose end.

### Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.

3

## Assembly



**Assemble hose** – Push hose into fitting all the way to depth insertion mark. (If fitting does not readily slide onto hose, perform the next step.)



Using Parker VBS or VBL (vise blocks) and a rubber mallet, tap fitting onto hose until bottom of fitting shell is aligned with depth insertion mark.

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical


For detailed ordering information, please consult price list or contact Parflex® Division.

# MiniKrimp™ Fitting Assembly Procedures

(cont.)

4

## Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

5

## Lubricate Bowl



Remove pusher from shoulder bolt.

Using a premium, quality, lithium-base grease, apply a thin layer of grease on bowl of crimper base plate.

6

## Die & Spacer Ring



**Crimp Die** – Place die set into bowl.



**Die Ring** – Place applicable die ring on top of die. Position ring so it is centered on die.

(Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))




Replace pusher onto shoulder bolt.

7

## Crimp



**Assemble hose** – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on the step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

### Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

### Note

Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

# MiniKrimp™ Fitting Assembly Procedures

(cont.)

8


## Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.

# Hose Assembly & Crimping


## Field Attachable

Series 51, BU & MS (Do not use these fittings on oxygen service lines)

**CAUTION:** There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See **Table of Contents** for listing.

1

### Inspection



**Hose** – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.




**Fittings** – Inspect socket for damaged or missing threads. Do not use if conditions exist.



Inspect nipple for a through-hole, damaged or missing threads and improperly crimped nut (if applicable). Do not use if these conditions exist.

2

### Assembly




Using the Parker VBS or VBL vise block, place hose in proper hole of the vise block and then clamp in a bench vise. Ensure enough hose extends from the vise block to install socket.

#### Caution

Ensure hose is installed in correct size hole of vise block. Clamping hose in a smaller hole will crush hose.

3

### Assembly



Using a wrench, screw socket onto hose counterclockwise until it bottoms. Ensure end of hose is against inside shoulder. Back off socket 1/4 turn clockwise.

Socket should be firm when tightened but not difficult to turn. If socket is difficult to install, apply lubricant that is compatible with the hose material. Do not use a lubricant with MS series.


# Hose Assembly & Crimping

## Field Attachable (cont.)

Series 51, BU & MS (Do not use these fittings on oxygen service lines)

4

### Assembly




Place hex portion of socket into vise and tighten vise. Ensure socket extends past vise jaws enough to allow for installation of nipple.

#### Caution


When tightening socket in vise, do not over tighten vise jaws. Over tightening vise jaws will distort internal threads of socket and hamper installation of nipple.

5

### Assembly



Using an SAE 20 weight lubricating oil, generously lubricate nipple and socket, threads and hose I.D.



Using a wrench on the nipple hex, screw nipple into socket clockwise until nipple bottoms against socket shoulder.

#### Caution

Nipple should be firm when tightened but not difficult to turn. If nipple is difficult to install, check hose for proper lubrication. Re-apply lubricating oil as necessary. Installation of nipple without proper lubrication will damage core tube.

6

### Inspection



Measure and verify hose assembly length.

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-17

# Hose Assembly & Crimping


## PTFE Permanent Crimp

### Series 91, 91N & 93N

**CAUTION:** There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See **Table of Contents** for listing.

1

### Cut




Using a power hose cutoff saw, cut hose squarely.

### Note

PTFE Hose should be taped prior to cutting. Hose should be cut at center point of taped section.

2

### Inspection




**Hose** – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



**Fittings** – Verify fitting series corresponds to the selected hose. Visually inspect fitting(s) for a through-hole, threads and damage.

3

### Assembly Prep



**Insertion Depth** – Mark hose end with proper insertion depth line. See Hose Fitting Insertion Values, pg. G-42 for insertion depths of fitting series that do not incorporate an insertion depth. For jacketed PTFE hoses, use a sharp knife and light pressure to cut back the cover at least the length of the insertion depth of the fitting.

### Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service, lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.



**Assemble hose** – Push fitting onto hose slightly and then remove tape. Continue pushing fitting onto hose until fitting reaches depth insertion mark.




# Hose Assembly & Crimping

## PTFE Permanent Crimp (cont.)

Series 91, 91N & 93N

4

### Die Selection



Select proper Parkrimp die set. (Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

5

### Lubricate Bowl



Using a premium, quality, lithium-base grease, apply a thin layer of grease on bowl of crimper base plate.

6

### Die & Spacer Ring



**Crimp Die** – Place die set into bowl.



**Die Ring** – Place applicable die ring on top of die. Position ring so it is centered on die.


(Parflex hoses utilize silver die ring with the exception of HTB hose. Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

7

### Crimp



**Assemble hose** – Insert hose and fitting from bottom of crimper and up through die set. Position fitting so bottom of fitting skirt rests on die step (PARKALIGN® feature).



While holding hose and fitting in position on die step, crimp fitting onto hose until die ring contacts base plate.

### Warning

Keep fingers and hands away from die-pusher area. Failure to do so may result in personal injury.

### Note

Pump on crimper must not exceed the rated pressure of the crimper being used. Parker Hannifin will not accept responsibility for the operation of or provide warranty coverage for a crimper that is operated by a power unit other than equipment supplied by Parker Hannifin for the express purpose of operating the crimper.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Hose Assembly & Crimping

## PTFE Permanent Crimp (cont.)


Series 91, 91N & 93N

8

### Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure crimp diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify crimp diameter is within tolerances.

(Reference Crimp Die Selection Charts - pgs. G-30 : G-41 or Crimpsource online at [www.parker.com/crimpsource](http://www.parker.com/crimpsource))

# Hose Assembly & Crimping

## PTFE Field Attachable Series 90

**CAUTION:** There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See **Table of Contents** for listing.

1

### Inspection




**Hose** – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



**Fittings** – Inspect each component for possible damage. In addition, inspect socket and nipple for a through-hole and threads.

2

### Assembly




Slide two sockets over end of hose with bottom of sockets back to back. Position sockets at each end of hose.

#### Note

When installing sockets on hose, check hose ends to determine if wire braid “necks down” (bends inward). If one end “necks down” use this end to slide sockets onto hose.

3

### Assembly



Mount nipple hex in vise. Ensure nipple end extends beyond vise jaws sufficiently to allow installation of hose.



Push hose bore onto nipple to size tube and to aid in separating braid before assembling ferrule onto hose.

Once completed, remove hose from nipple.

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.

# Hose Assembly & Crimping

## PTFE Field Attachable (cont.)

Series 90

4

### Assembly




By hand, push sleeve over end of PTFE core tube and under wire braid.




To complete positioning of sleeve, push hose end with sleeve against a solid flat surface.

5

### Assembly



Verify tube butts against inside shoulder of ferrule.



Using a tapered punch, push punch into end of sleeve and tube to set sleeve bars into tube.

6

### Assembly



Using SAE 20 weight oil, lubricate nipple and socket threads. For stainless steel fittings use Parker ThreadMate™ or a molybdenum type lubricant.

### Warning

Do not use lubricating oil when installing fittings on hose used in oxygen service. When installing fittings on hose used in oxygen service lubricate with a non-oil based soap solution. Failure to do so may result in an explosion and personal injury when hose is used.



**Assemble hose** – Using a twisting motion, push hose over nipple until hose is seated against nipple chamfer.


# Hose Assembly & Crimping

## PTFE Field Attachable (cont.)

Series 90

7


### Assembly



Push socket forward and hand-start threading of socket to nipple.

#### Caution

When tightening socket in vise, do not over tighten vise jaws. Over tightening vise jaws will distort internal threads of socket.




Remove assembly from vise and reposition with socket in vise jaws. Ensure socket extends beyond vise jaws far enough to allow nipple to be completely tightened.

8

### Assembly



Wrench tighten nipple hex until clearance between hex and socket hex is 1/32" or less.



Tighten further to align corners of nipple and socket hexes if necessary.

9

### Measure & Inspect



Measure and verify hose assembly length.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-23

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical


# SQ-Swage Instructions

## Sewer Hose

**CAUTION:** There are several different sections for Hose Assembly and Crimping. Be sure you are in the section that corresponds to the fitting series you are using. See [Table of Contents](#) for listing.

1

### Inspection




**Hose** – Visually inspect both ends of hose for square cut. Remove any burrs, loose fibers or wires.



**Fittings** – Visually inspect fitting for properly crimped shells, internal barbs, a through-hole and damage.

2


### Assembly



**Insertion Depth** – Mark hose end with proper insertion depth line.




**Lubricate** – Using an SAE 20 weight oil, lightly lubricate inside of both hose ends.




**Assemble hose** – Push each hose end into fitting to the depth insertion mark.

3

### Assembly



Remove both die securing bolts and nuts.




Place hose and fitting assembly into position on swager.


# SQ-Swage Instructions (cont.)

4

## Assembly



Insert both die halves around hose in each end of swager.




Install both die securing bolts with nuts positioned in opening of swager plates. Tighten die securing bolts 1/4 turn past finger tight.

### Caution


When swaging stainless steel fittings, lubricate through-hole of dies with ThreadMate™. Failure to do so may result in damage to fittings.

5

## Assembly



**Lubricate** – Using an SAE 20 weight oil, lightly lubricate inside of both hose ends.




**Assemble hose** – Align swager plates in parallel and tighten nuts on swaging bolts uniformly until dies touch.

### Caution


Ensure swager plates remain in parallel when tightening swager bolts. Failure to do so will result in an improperly swaged fitting.

6


## Assembly



Loosen swaging bolts to release pressure on dies.



Remove die securing bolts and nuts. Then remove dies.



**Assemble hose** – Remove completed hose assembly.

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)




G-25

G General Technical


# SQ-Swage Instructions (cont.)

7


## Measure & Inspect



Measure and verify hose assembly length.



Inspect insertion depth mark at fitting ends. Insertion mark must be visible but not exceed 1/8" from end of crimped fitting shell.



Measure swage diameter of each fitting at top, middle and bottom of shell. Take measurements at a minimum of three places around shell circumference. Verify swage diameter is within tolerances.


(Reference Swage Specification & Tool Selection Chart on pg. G-41 for proper swage diameters.)



# Twin/Multi-Line Separation


Factory-built assemblies are available using twin/multi-line hoses. When field-built assemblies are preferred, the following steps must be taken.

1




**Set-Up** – Position twinned or multi-line hose assembly so that it lies flat on work surface without tendency to twist or turn.

2



**Measure** hose to length – Measure and mark the length that the hoses are to be separated (commonly referred to as Split-back Length).

3



**Lubricate** – Lightly lubricate the web area between the hoses. Distribute the lubricant uniformly along the web of the assembly to be separated. Any lightweight oil will suffice (SAE 10 or 20). The function of the oil is to reduce the friction of the knife blade so that it naturally seeks the center of the valley formed by the hoses. This eliminates the need for the operator to steer the knife.

*For detailed ordering information, please consult price list or contact Parflex® Division.*

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-27

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation


E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Twin/Multi-Line Separation (cont.)

4




**Cut Hose to Length** – Press the multi-line hose assembly firmly and flat against the work surface with your free hand so that it does not move. Using a sharp utility knife, carefully draw the knife toward you with constant light to moderate pressure, and a smooth stroke. Multiple strokes will be necessary to separate the hoses.

## Note

It is important that the knife blade be perpendicular to the hose during this procedure so that the blade cuts only the center line of the web. Extreme care must be taken to avoid cutting through the cover of the hoses and thereby exposing the hose reinforcement. If this occurs, the hose assembly must be discarded (See Figure 1). If the separation length is greater than that which can be accomplished with one continuous, smooth stroke, then the procedure should be repeated over shorter distances always cutting toward the free end of the hoses.

5




**Measure Separation** – It is suggested that the separation length be sufficiently long so that the swaging or crimping operation can be accomplished without risk of kinking the hoses or tearing the web which could result in exposure of the hose reinforcement (See Figure 2).

6




**Apply Tape** – At the option of the assembler, as dictated by the installation, a nylon lashing strap or tape may be applied at the termination of the separated length to provide protection against tearing of the web or hose covers.

## INCORRECT HANDLING



**Figure 1** – Extreme care must be taken to avoid cutting through the cover of the hoses and thereby exposing the hose reinforcement. If this occurs, the hose assembly must be discarded.



**Figure 2** – The separation length must allow for the swaging or crimping operation without damaging the hose.

# Ferrul-Fix Installation Instructions


Fast, on-the-job repair for ruptured bent tube hose assemblies and power steering lines.

The life of the combination tube-hose assembly is often limited to the service life of the hose alone. A replacement assembly may not be available, since equipment dealers are unable to stock all of the many odd tube configurations.

Parker Ferrul-Fix hose end fitting now makes it possible to salvage the bent tube section of the original assembly for replacement. Most importantly, it gets you back into operation FAST!

## Features

- Gets you back in operation fast - No costly delays while replacement assemblies are rushed from the factory.
- Lets you reuse expensive bent tube ends - You can replace the hose at a fraction of the cost of complete assembly.
- Eliminates need for emergency brazing or welding in the field - Ferrul-Fix can be assembled without special tools or equipment.
- 3-Piece Design - Body, nut, ferrule. Wedging action of ferrule, when drawn down by nut, forms seal between body and ferrule, while cutting edge of ferrule bites into tube wall forming another positive seal.
- Visible Bite - Extent of bite at cutting edge of ferrule is completely visible when fitting is disassembled, an important safety feature. Self-centering action assures an even bite around circumference of tube.
- Parkerized Finish - Ferrul-Fix fittings have the Parkerized black finish, providing built-in torque in make-up.



## Assembly

1. **Cut** the formed tube off squarely next to the permanent hose fitting. Lightly **deburr** the end of the tube internally and externally.
2. **Disassemble** the Ferrul-Fix fitting, and **lubricate** threads and both ends of the ferrule with Parker Ferulube.
3. **Slide** nut and ferrule onto tubing with the long, straight end of the ferrule pointing toward the tube end.
4. **Insert** tube end into the Ferrul-Fix body until it bottoms against the shoulder. **Slide** ferrule inside body, and screw nut down finger tight.
5. **Wrench** nut down 1-3/4 turns to preset the ferrule.
6. **Disconnect** nut and **inspect** lead edge of ferrule to make certain that the biting edge has turned up a shoulder to a height of at least 50% of the ferrule and completely around the tube.
7. **Assemble** Ferrul-Fix fitting to hose. **Refer** to assembly instructions listed in appropriate fittings section. Do not assemble to hose before steps 1-6.
8. **Reassemble** tubing into Ferrul-Fix end and **turn** nut down easily until a sudden increase in force is evident. **Turn** bent tube to proper position if required. Using two wrenches, one on the fitting nipple hex and the other on the nut, **tighten** nut an additional 1/6 turn (one wrench flat).

Ferrule-Fix is Manufactured by the Tube Fittings Division. Refer to Catalog 4300 for Ferulok® instructions.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-29

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Die Selection & Crimp Specification Charts

## Superkrimp and Parkrimp 2

Hose	Fittings	Die Selection and Crimping Diameters												
		Hose Dash Size												
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32
Die	54 Series				80C-544F		80C-546F							
515H					0.480 0.490		0.620 0.630							
Die	55 Series				80C-P04		80C-P06							
1035A 1035HT					0.560 0.580		0.675 0.695							
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08						
510A				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860						
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16			
510C 518C				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365			
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08	80C-P10					
520N 528N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860	0.950 0.970					
Die				80C-P03	80C-P04		80C-P06							
526BA				0.480 0.500	0.560 0.580		0.675 0.695							
Die				80C-P03	80C-P04									
527BA				0.480 0.500	0.560 0.580									
Die				80C-P03	80C-P0550		80C-P0705	80C-P0870						
53DM 538DM				0.480 0.500	0.540 0.560		0.695 0.715	0.860 0.880						
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12				
540N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120				
Die					80C-P04		80C-P06	80C-P08		80C-P12				
540P					0.560 0.580		0.675 0.695	0.840 0.860		1.100 1.120				
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16			
55LT				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365			
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08J	80C-P10					
560				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.815 0.835	0.950 0.970					
Die				80C-P03	80C-P04		80C-P06	80C-P08						
575X				0.480 0.500	0.560 0.580		0.675 0.695	0.840 0.860						
Die				80C-P03	80C-P04		80C-P06	80C-P08J						
590				0.480 0.500	0.560 0.580		0.675 0.695	0.815 0.835						
Die				80C-P04		80C-P06	80C-P08J		80C-P12					
83FR				0.560 0.580		0.675 0.695	0.815 0.835		1.100 1.120					
Die				80C-P04J	80C-P0625	80C-P0705	80C-P0845	80C-P10H						
B9				0.535 0.555	0.615 0.635	0.695 0.715	0.835 0.855	1.000 1.020						
Die							80C-P08							
S5							0.840 0.860							
Die	57 Series		80C-P02H											
510A 510C 518C 540N 55LT			0.396 0.410											

(Cont.) Refer to notes on pg. G-32 at end of Superkrimp and Parkrimp 2 charts.



# Die Selection & Crimp Specification Charts

## Superkrimp and Parkrimp 2

Hose	Fittings	Die Selection and Crimping Diameters												
		Hose Dash Size												
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32
Die	58 Series								80C-P10H					
510C 518C									1.000 1.020					
Die						80C-P05R	80C-P0715	80C-P0885	80C-P1045					
53DM 538DM						0.650 0.670	0.705 0.725	0.875 0.895	1.035 1.055					
Die									80C-P10H					
55LT									1.000 1.020					
Die										80C-P12H				
560										1.150 1.170				
Die					80C-P04H		80C-P06H	80C-P08H	80C-P10H	80C-P12H	80C-P16H			
580N 588N					0.668 0.688		0.785 0.805	0.900 0.920	1.000 1.020	1.150 1.170	1.475 1.495			
Die									80C-P10H	80C-P12H	80C-P16J			
590									1.000 1.020	1.150 1.170	1.450 1.470			
Die							80C-P0715	80C-P08	80C-P1015					
D6							0.705 0.725	0.840 0.860	1.005 1.025					
Die							80C-P0705	80C-P08J						
H6							0.695 0.715	0.815 0.835						
Die							80C-P0725	80C-P08J						
HFS							0.715 0.735	0.815 0.835						
Die							80C-P0725	80C-P08						
HFS2							0.715 0.735	0.840 0.860						
Die							80C-P0725	80C-P08J						
HR1C							0.715 0.735	0.815 0.835						
Die							80C-P0725	80C-P08						
HR2C							0.715 0.735	0.840 0.860						
Die							80C-P0730	80C-P08						
R6							0.720 0.740	0.840 0.860						
Die								80C-P08H						
S4								0.900 0.920						
Die									80C-P10S					
S5									1.060 1.080					
Die										80C-P12H	80C-P16J			
S6 S9										1.150 1.170	1.450 1.470			
Die							80C-P08J							
SLH							0.815 0.835							

(Cont.) Refer to notes on pg. G-32 at end of Superkrimp and Parkrimp 2 charts.

For detailed ordering information, please consult price list or contact Parflex® Division.



A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# Die Selection & Crimp Specification Charts

## Superkrimp and Parkrimp 2 (cont.)

Hose	Fittings	Die Selection and Crimping Diameters												
		Hose Dash Size												
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	-24	-32
Die	58H Series									83C-P1258H				
53DM 538DM										1.200 1.220				
Die										83C-P1258H	83C-P1658H			
575X										1.200 1.220	1.605 1.625			
Die											83C-P1658H			
H580N											1.605 1.625			
Die	71 Series <sup>3</sup>												83C-D24	
S6													2.290 2.310	
Die	91 Series			80C-T03									80C-T20	
919				0.295 0.305									1.415 1.435	
Die	91N Series				80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16N			
919 919B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065			
Die					80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16N			
929 929B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120			
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16J			
929BJ					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120			
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16J			
919J 919U					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065			
Die		92 Series			80C-T05									
PTH					0.450 0.470									
Die	93N Series							83C-T08	83C-T10	83C-T12	83C-T16	83C-T20	83C-T24	83C-T32
939 939B								0.750 0.770	0.910 0.930	1.090 1.110	1.295 1.315	1.580 1.600	1.845 1.865	2.410 2.430
Die	CY Series			80C-P0368										
56DH 568DH				0.361 0.375										
Die				80C-P0368	80C-P0505									
HLB			0.361 0.375	0.495 0.515										
Die	LV Series									80C-P12L	83C-P16L			
593										1.150 1.170	1.450 1.470			
Die	MS Series					80C-M05	80C-M06							
MSH						0.535 0.555	0.640 0.660							
Die						80C-M05								
MSXL						0.535 0.555								
Die	SF Series			80C-T03										
56DH 568DH				0.295 0.315										

**Notes:**

1. The Silver Split Die Ring (Part # 83C-R02) is used for all crimping operations listed in the table
2. Crimp values applicable for steel, brass & stainless Parflex fittings
3. The 83C-OCB Adapter Bowl is required for all 80C-dies and also for the 83C-T08, 83C-T10, 83C-T12, 83C-T16
4. Refer to [www.parker.com/crimpsource](http://www.parker.com/crimpsource) for updates, assembly instructions and other crimping options



# Die Selection & Crimp Specification Charts

## Karrykrimp 2 and Phastkrimp

Hose	Fittings	Die Selection and Crimping Diameters											
		Hose Dash Size											
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	
Die	54 Series				80C-544F		80C-546F						
515H					0.480 0.490		0.620 0.630						
Die	55 Series				80C-P04		80C-P06						
1035A 1035HT					0.560 0.580		0.675 0.695						
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08					
510A				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860					
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16		
510C 518C				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365		
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08	80C-P10				
520N 528N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860	0.950 0.970				
Die				80C-P03	80C-P04		80C-P06						
526BA				0.480 0.500	0.560 0.580		0.675 0.695						
Die				80C-P03	80C-P04								
527BA				0.480 0.500	0.560 0.580								
Die				80C-P03	80C-P0550		80C-P0705	80C-P0870					
53DM 538DM				0.480 0.500	0.540 0.560		0.695 0.715	0.860 0.880					
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12			
540N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120			
Die					80C-P04		80C-P06	80C-P08		80C-P12			
540P					0.560 0.580		0.675 0.695	0.840 0.860		1.100 1.120			
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16		
55LT				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365		
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08J	80C-P10				
560				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.815 0.835	0.950 0.970				
Die				80C-P03	80C-P04		80C-P06	80C-P08					
575X				0.480 0.500	0.560 0.580		0.675 0.695	0.840 0.860					
Die				80C-P03	80C-P04		80C-P06	80C-P08J					
590				0.480 0.500	0.560 0.580		0.675 0.695	0.815 0.835					
Die					80C-P04		80C-P06	80C-P08J		80C-P12			
83FR					0.560 0.580		0.675 0.695	0.815 0.835		1.100 1.120			
Die					80C-P04J	80C-P0625	80C-P0705	80C-P0845	80C-P10H				
B9					0.535 0.555	0.615 0.635	0.695 0.715	0.835 0.855	1.000 1.020				
Die								80C-P08					
S5								0.840 0.860					

(Cont.) Refer to notes on pg. G-35 at end of Karrykrimp 2 and Phastkrimp charts.

For detailed ordering information, please consult price list or contact Parflex® Division.





# Die Selection & Crimp Specification Charts

## Karrykrimp 2 and Phastkrimp (cont.)

Hose	Fittings	Die Selection and Crimping Diameters										
		Hose Dash Size										
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20
Die	57 Series		80C-P02H									
510A 510C 518C 540N 55LT			0.396 0.410									
Die									80C-P10H			
510C 518C									1.000 1.020			
Die						80C-P05R	80C-P0715	80C-P0885	80C-P1045			
53DM 538DM					0.650 0.670	0.705 0.725	0.875 0.895	1.035 1.055				
Die								80C-P10H				
55LT								1.000 1.020				
Die									80C-P12H			
560									1.150 1.170			
Die				80C-P04H		80C-P06H	80C-P08H	80C-P10H	80C-P12H	80C-P16H		
580N 588N				0.668 0.688		0.785 0.805	0.900 0.920	1.000 1.020	1.150 1.170	1.475 1.495		
Die								80C-P10H	80C-P12H	80C-P16J		
590								1.000 1.020	1.150 1.170	1.450 1.470		
Die						80C-P0715	80C-P08	80C-P1015				
D6						0.705 0.725	0.840 0.860	1.005 1.025				
Die						80C-P0705	80C-P08J					
H6						0.695 0.715	0.815 0.835					
Die						80C-P0725	80C-P08J					
HFS						0.715 0.735	0.815 0.835					
Die						80C-P0725	80C-P08					
HFS2						0.715 0.735	0.840 0.860					
Die						80C-P0725	80C-P08J					
HR1C						0.715 0.735	0.815 0.835					
Die						80C-P0725	80C-P08					
HR2C						0.715 0.735	0.840 0.860					
Die						80C-P0730	80C-P08					
R6						0.720 0.740	0.840 0.860					
Die							80C-P08H					
S4							0.900 0.920					
Die								80C-P10S				
S5								1.060 1.080				
Die									80C-P12H	80C-P16J		
S6 S9									1.150 1.170	1.450 1.470		
Die							80C-P08J					
SLH							0.815 0.835					
Die	91 Series		80C-T03								80C-T20	
919			0.295 0.305								1.415 1.435	

(Cont.) Refer to notes on pg. G-35 at end of Karrykrimp 2 and Phastkrimp charts.



# Die Selection & Crimp Specification Charts

## Karrykrimp 2 and Phastkrimp (cont.)

Hose	Fittings	Die Selection and Crimping Diameters											
		Hose Dash Size											
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	
Die	91N Series				80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16N		
919 919B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065		
Die					80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16H		
929 929B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120		
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16HJ		
929BJ					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120		
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16J		
919J 919U					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065		
Die		92 Series			80C-T05								
PTH					0.450 0.470								
Die	93N Series							83C-T08	83C-T10	83C-T12	83C-T16		
939 939B								0.750 0.770	0.910 0.930	1.090 1.110	1.295 1.315		
Die	CY Series		80C-P0368										
56DH 568DH			0.361 0.375										
Die			80C-P0368	80C-P0505									
HLB			0.361 0.375	0.495 0.515									
Die	MS Series					80C-M05	80C-M06						
MSH						0.535 0.555	0.640 0.660						
Die						80C-M05							
MSXL						0.535 0.555							
Die	SF Series	80C-T03											
56DH 568DH			0.295 0.315										

### Notes:

- The Silver Spacer Ring (Part # 85C-R01) is required for all crimping operations listed in the table unless otherwise noted
- Crimp values applicable for steel, brass & stainless Parflex fittings except 93N stainless steel fittings in sizes -12 & -16. These require the Superkrimp or Parkrimp 2 machines
- Refer to [www.parker.com/crimpsource](http://www.parker.com/crimpsource) for updates, assembly instructions and other crimping options

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-35

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

# Die Selection & Crimp Specification Charts

## Karrykrimp and Parkrimp 1

Hose	Fittings	Die Selection and Crimping Diameters										
		Hose Dash Size										
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20
Die	54 Series				80C-544F		80C-546F					
515H					0.480 0.490		0.620 0.630					
Die	55 Series				80C-P04		80C-P06					
1035A 1035HT					0.560 0.580		0.675 0.695					
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08				
510A				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860				
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16	
510C 518C				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365	
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08	80C-P10			
520N 528N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860	0.950 0.970			
Die				80C-P03	80C-P04		80C-P06					
526BA				0.480 0.500	0.560 0.580		0.675 0.695					
Die				80C-P03	80C-P04							
527BA				0.480 0.500	0.560 0.580							
Die				80C-P03	80C-P0550		80C-P0705	80C-P0870				
53DM 538DM				0.480 0.500	0.540 0.560		0.695 0.715	0.860 0.880				
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12		
540N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120		
Die					80C-P04		80C-P06	80C-P08		80C-P12		
540P					0.560 0.580		0.675 0.695	0.840 0.860		1.100 1.120		
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16	
55LT				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365	
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08J	80C-P10			
560				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.815 0.835	0.950 0.970			
Die				80C-P03	80C-P04		80C-P06	80C-P08				
575X				0.480 0.500	0.560 0.580		0.675 0.695	0.840 0.860				
Die				80C-P03	80C-P04		80C-P06	80C-P08J				
590				0.480 0.500	0.560 0.580		0.675 0.695	0.815 0.835				
Die					80C-P04		80C-P06	80C-P08J		80C-P12		
83FR					0.560 0.580		0.675 0.695	0.815 0.835		1.100 1.120		
Die				80C-P04J	80C-P0625	80C-P0705	80C-P0845	80C-P10H				
B9				0.535 0.555	0.615 0.635	0.695 0.715	0.835 0.855	1.000 1.020				
Die							80C-P08					
S5							0.840 0.860					
Die	57 Series		80C-P02H									
510A 510C 518C 540N 55LT			0.396 0.410									

(Cont.) Refer to notes on pg. G-38 at end of Karrykrimp and Parkrimp 1 charts.



# Die Selection & Crimp Specification Charts

## Karrykrimp and Parkrimp 1 (cont.)

Hose	Fittings	Die Selection and Crimping Diameters										
		Hose Dash Size										
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20
Die	58 Series								80C-P10H			
510C 518C									1.000 1.020			
Die						80C-P05R	80C-P0715	80C-P0885	80C-P1045			
53DM 538DM						0.650 0.670	0.705 0.725	0.875 0.895	1.035 1.055			
Die									80C-P10H			
55LT									1.000 1.020			
Die										80C-P12H		
560										1.150 1.170		
Die					80C-P04H		80C-P06H	80C-P08H	80C-P10H			
580N 588N					0.668 0.688		0.785 0.805	0.900 0.920	1.000 1.020			
Die									80C-P10H			
590									1.000 1.020			
Die							80C-P0715	80C-P08	80C-P1015			
D6							0.705 0.725	0.840 0.860	1.005 1.025			
Die							80C-P0705	80C-P08J				
H6							0.695 0.715	0.815 0.835				
Die							80C-P0725	80C-P08J				
HFS							0.715 0.735	0.815 0.835				
Die							80C-P0725	80C-P08				
HFS2							0.715 0.735	0.840 0.860				
Die							80C-P0725	80C-P08J				
HR1C							0.715 0.735	0.815 0.835				
Die							80C-P0725	80C-P08				
HR2C							0.715 0.735	0.840 0.860				
Die							80C-P0730	80C-P08				
R6							0.720 0.740	0.840 0.860				
Die								80C-P08H				
S4								0.900 0.920				
Die									80C-P10S			
S5									1.060 1.080			
Die							80C-P08J					
SLH							0.815 0.835					
Die	91 Series			80C-T03							80C-T20	
919				0.295 0.305							1.415 1.435	

(Cont.) Refer to notes on pg. G-38 at end of Karrykrimp 1 and Parkrimp 1 charts.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Die Selection & Crimp Specification Charts

## Karrykrimp and Parkrimp 1 (cont.)

Hose	Fittings	Die Selection and Crimping Diameters											
		Hose Dash Size											
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	
Die	91N Series				80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16N		
919 919B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065		
Die					80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16H		
929 929B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120		
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16HJ		
929BJ					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120		
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16J		
919J 919U					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065		
Die		92 Series			80C-T05			80C-T06N	80C-T08N	80C-T10N	80C-T12N		
PTH					0.450 0.470			0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810		
Die	93N Series							83C-T08	83C-T10	83C-T12			
939 939B								0.750 0.770	0.910 0.930	1.090 1.110			
Die	CY Series		80C-P0368										
56DH 568DH			0.361 0.375										
Die			80C-P0368	80C-P0505									
HLB		0.361 0.375	0.495 0.515										
Die	MS Series					80C-M05	80C-M06						
MSH						0.535 0.555	0.640 0.660						
Die						80C-M05							
MSXL						0.535 0.555							
Die	SF Series	80C-T03											
56DH 568DH		0.295 0.315											

### Notes:

1. The Silver Spacer Ring (Part # 82C-R01) is required for all crimping operations listed unless noted
2. Crimp values applicable for steel, brass & stainless Parflex fittings
3. Refer to [www.parker.com/crimpsource](http://www.parker.com/crimpsource) for updates, assembly instructions and other crimping options



For detailed ordering information, please consult price list or contact Parflex® Division.

# Die Selection & Crimp Specification Charts

## Minikrimp™

Hose	Fittings	Die Selection and Crimping Diameters										
		Hose Dash Size										
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20
Die	54 Series				80C-544F		80C-546F					
515H				0.480	0.490		0.620	0.630				
Die	55 Series				80C-P04		80C-P06					
1035A 1035HT					0.560 0.580		0.675 0.695					
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08				
510A				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860				
Die				80C-P03	80C-P04J	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16	
510C 518C				0.480 0.500	0.535 0.555	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365	
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08	80C-P10			
520N 528N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860	0.950 0.970			
Die				80C-P03	80C-P04		80C-P06					
526BA				0.480 0.500	0.560 0.580		0.675 0.695					
Die				80C-P03	80C-P04							
527BA				0.480 0.500	0.560 0.580							
Die				80C-P03	80C-P0550		80C-P0705	80C-P0870				
53DM 538DM				0.480 0.500	0.540 0.560		0.695 0.715	0.860 0.880				
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12		
540N				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120		
Die					80C-P04		80C-P06	80C-P08		80C-P12		
540P					0.560 0.580		0.675 0.695	0.840 0.860		1.100 1.120		
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08		80C-P12	80C-P16	
55LT				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.840 0.860		1.100 1.120	1.345 1.365	
Die				80C-P03	80C-P04	80C-P05	80C-P06	80C-P08J	80C-P10			
560				0.480 0.500	0.560 0.580	0.620 0.640	0.675 0.695	0.815 0.835	0.950 0.970			
Die				80C-P03	80C-P04		80C-P06	80C-P08				
575X				0.480 0.500	0.560 0.580		0.675 0.695	0.840 0.860				
Die				80C-P03	80C-P04		80C-P06	80C-P08J				
590				0.480 0.500	0.560 0.580		0.675 0.695	0.815 0.835				
Die					80C-P04		80C-P06	80C-P08J		80C-P12		
83FR					0.560 0.580		0.675 0.695	0.815 0.835		1.100 1.120		
Die					80C-P04J	80C-P0625	80C-P0705	80C-P0845	80C-P10H			
B9					0.535 0.555	0.615 0.635	0.695 0.715	0.835 0.855	1.000 1.020			
Die								80C-P08				
S5								0.840 0.860				
Die	57 Series		80C-P02H									
510A 510C 518C 540N 55LT			0.396 0.410									

(Cont.) Refer to notes on pg. G-40 at end of Minikrimp charts.

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



# Die Selection & Crimp Specification Charts

## Minikrimp (cont.)

Hose	Fittings	Die Selection and Crimping Diameters											
		Hose Dash Size											
		-1.5	-2	-3	-4	-5	-6	-8	-10	-12	-16	-20	
Die	58 Series								80C-P10H				
510C 518C									1.000 1.020				
Die						80C-P05R	80C-P0715	80C-P0885	80C-P1045				
53DM 538DM						0.650 0.670	0.705 0.725	0.875 0.895	1.035 1.055				
Die									80C-P10H				
55LT									1.000 1.020				
Die										80C-P12H			
560										1.150 1.170			
Die					80C-P04H		80C-P06H	80C-P08H	80C-P10H				
580N 588N					0.668 0.688		0.785 0.805	0.900 0.920	1.000 1.020				
Die									80C-P10H				
590									1.000 1.020				
Die							80C-P0715	80C-P08					
D6							0.705 0.725	0.840 0.860					
Die							80C-P0705	80C-P08J					
H6							0.695 0.715	0.815 0.835					
Die							80C-P0725	80C-P08J					
HFS							0.720 0.740	0.815 0.835					
Die		91 Series			80C-T03								80C-T20
919					0.295 0.305								1.415 1.435
Die	91N Series				80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16N		
919 919B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065		
Die					80C-T04N	80C-T05N	80C-T06N	80C-T08N	80C-T10N	80C-T12N	80C-T16H		
929 929B					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120		
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16HJ		
929BJ					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.100 1.120		
Die					80C-T04J	80C-T05J	80C-T06J	80C-T08J	80C-T10J	80C-T12J	80C-T16J		
919J 919U					0.335 0.355	0.385 0.405	0.470 0.490	0.565 0.585	0.665 0.685	0.790 0.810	1.045 1.065		
Die		92 Series			80C-T05								
PTH					0.450 0.470								
Die	93N Series				80C-P04			83C-T08					
939 939B					0.560 0.580			0.750 0.770					
Die	CY Series			80C-P0368									
56DH 568DH				0.361 0.375									
Die				80C-P0368	80C-P0505								
HLB				0.361 0.375	0.495 0.515								
Die	MS Series					80C-M05	80C-M06						
MSH						0.535 0.555	0.640 0.660						
Die						80C-M05							
MSXL					0.535 0.555								
Die	SF Series			80C-T03									
56DH 568DH				0.295 0.315									

**Notes:**

1. The Silver Spacer Ring (Part # 82C-R01-PFD) is required for all crimping operations listed unless noted
2. Crimp values applicable for steel, brass & stainless Parflex fittings
3. Refer to [www.parker.com/crimpsource](http://www.parker.com/crimpsource) for updates, assembly instructions and other crimping options



For detailed ordering information, please consult price list or contact Parflex® Division.



# Die Selection & Swage Specification Chart

## Sewer Hose

SWAGE DATA FOR SEWER CLEANING HOSE (SQ-101-SW SWAGE MACHINE ONLY)								
Hose Type	Hose I.D.	Male Pipe			Mender/Splicer		Swage O.D. +/-0.015	Swage Length
		Fitting P/N	Die P/N	Pusher P/N	Fitting P/N	Die P/N		
	inch						inch	inch
S408	1/2	-	-	-	1HU58-8-8	SQ-101-08S4S	0.910	0.750
S410	5/8	-	-	-	1HUSQ-10-10	SQ-101-10S4S5S	1.060	1.065
S508	1/2	-	-	-	1HU55-8-8	SQ-101-08S5S	0.850	0.750
S612	3/4	101SQ-12-12	SQ-101-12S6/S9	SQ-101-12P	1HUSQ-12-12	SQ-101-12S6/S9	1.172	1.109
S616	1	101SQ-16-16	SQ-101-16S6	SQ-101-16P	1HUSQ-16-16	SQ-101-16S6	1.445	1.156
S620	1-1/4	101SQ-20-20	SQ-101-20S6	SQ-101-20P	1HUSQ-20-20	SQ-101-20S6	1.850	1.625
S624	1-1/2	-	-	-	-	-	-	-
S912	3/4	101SQ-12-12	SQ-101-12S6/S9	SQ-101-12P	1HUSQ-12-12	SQ-101-12S6/S9	1.172	1.109
S916	1	101SQ-16-16	SQ-101-16S9	SQ-101-16P	1HUSQ-16-16	SQ-101-16S9	1.488	1.156

### Comments:

- Two dies required when swaging a mender/splicer fitting. A pusher is not required when swaging a mender/splicer fitting.
- One die and one pusher required when swaging a male pipe fitting.
- End fittings cannot be swaged on S4 series hose. Only mender/splicers can be swaged.
- End fittings cannot be swaged on S5 series hose. Only mender/splicers can be swaged.
- Fittings cannot be swaged on SLH series hose.
- Fittings cannot be swaged on S624 hose.

The information covered in the Swage Specification & Tool Selection Chart pertains to steel, stainless and brass hose fittings. Swage diameter roundness shall not vary by more than .010". Swage diameters are measured in the center to the crimp area. Parflex Division reserves the right to alter swage specifications.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Hose Fitting Insertion Values

## Inch

Hose Dash Size	51	54	55/57/58	58H	91N	92	93N	BU	CY	LV/LH	MS Reusable	MS Permanent
-2			5/8					1/2	1/2			
-3	13/16	5/8	29/32		7/16	9/16		13/16	13/16	13/16		
-4	15/16	3/4	1-3/16		1/2							
-5	15/16	7/8	1-3/16		9/16						11/16	11/16
-6	1-5/16	15/16	1-5/16		5/8		7/16				15/16	3/4
-8	1-19/32	15/16	1-9/16		11/16		7/16			2-1/8		
-10			1-11/16		11/16		3/4			2-1/4		
-12	1-13/16		1-23/32	2-3/16	3/4		7/8			2-3/8		
-16	1-9/16		2-9/32	2-15/16	15/16		15/16			2-13/16		
-20					1		1					
-24							1-1/8					
-32							1-3/8					









## Metric (mm)










Hose Dash Size	51	54	55/57/58	58H	91N	92	93N	BU	CY	LV/LH	MS Reusable	MS Permanent
-2			16					13	13			
-3	21	16	23		11	14		21	21	21		
-4	24	19	30		13							
-5	24	22	30		14						17	17
-6	33	24	33		16		11				24	19
-8	40	24	40		17		11			54		
-10			43		17		19			57		
-12	46		44	56	19		22			60		
-16	40		58	75	24		24			71		
-20					25		25					
-24							29					
-32							35					



# Hose Fitting Thread Guide

There are more than one hundred types of threads for fittings. Below are some of the most common thread styles offered by Parflex. The end code in a fitting part number is located directly after the first digit. ie. 10355-8-8

End Code								
Dash Size	NPTF Pipe Thread Size	SAE (JIC) 37° Flare Thread Size	SAE 45° Flare Thread Size	"O" Ring Style Straight Thread Size	SAE Inverted Flare Thread Size	PTT 30° Flare Thread Size	SAE Flareless Thread Size	Seal-Lok™ Thread
2	1/8 - 27	5/16 - 24	5/16 - 24	5/16 - 24	-	-	5/16 - 24	-
3	-	3/8 - 24	3/8 - 24	3/8 - 24	3/8 - 24	-	3/8 - 24	-
4	1/4 - 18	7/16 - 20	7/16 - 20	7/16 - 20	7/16 - 18	-	7/16 - 20	9/16 - 18
5	-	1/2 - 20	1/2 - 20	1/2 - 20	1/2 - 20	-	1/2 - 20	-
6	3/8 - 18	9/16 - 18	5/8 - 18	9/16 - 18	5/8 - 18	-	9/16 - 18	11/16 - 16
8	1/2 - 14	3/4 - 16	3/4 - 16	3/4 - 16	3/4 - 18	-	3/4 - 16	13/16 - 16
10	-	7/8 - 14	7/8 - 14	7/8 - 14	7/8 - 18	-	7/8 - 14	1 - 14
12	3/4 - 14	1 1/16 - 12	1 1/16 - 14	1 1/16 - 12	1 1/16 - 16	-	1 1/16 - 12	1 3/16 - 12
14	-	1 3/16 - 12	-	1 3/16 - 12	-	-	1 3/16 - 12	-
16	1 - 11 1/2	1 5/16 - 12	-	1 5/16 - 12	-	1 5/16 - 14	1 5/16 - 12	1 7/16 - 12
20	1 1/4 - 11 1/2	1 5/8 - 12	-	1 5/8 - 12	-	1 5/8 - 14	1 5/8 - 12	-
24	1 1/2 - 11 1/2	1 7/8 - 12	-	1 7/8 - 12	-	1 7/8 - 14	1 7/8 - 12	-
32	2 - 11 1/2	2 1/2 - 12	-	2 1/2 - 12	-	2 1/2 - 12	2 1/2 - 12	-

End Code									
Dash Size	Metric Swivel Female Thread Size	Metric Swivel Female Thread Size	Male Stud Thread Size	Male Stud Thread Size	Male BSPP Thread Size	BSP Swivel Female Thread Size	French Swivel Female Gas Series	French Swivel Female Metric Series	French Male Stud Gas Series
4	-	-	-	-	1/4"	1/4"	-	-	-
6	M12 x 1,5	-	M12 x 1,5	-	3/8"	3/8"	-	M12 x 1	-
8	M14 x 1,5	M16 x 1,5	M14 x 1,5	M16 x 1,5	1/2"	1/2"	-	M14 x 1,5	-
10	M16 x 1,5	M18 x 1,5	M16 x 1,5	M18 x 1,5	-	5/8"	-	M16 x 1,5	-
12	M18 x 1,5	M20 x 1,5	M18 x 1,5	M20 x 1,5	3/4"	3/4"	-	M18 x 1,5	-
-	-	-	-	-	-	-	M20 x 1,5	-	M20 x 1,5
14	-	M22 x 1,5	-	M22 x 1,5	-	-	-	M20 x 1,5	-
15	M22 x 1,5	-	M22 x 1,5	-	-	-	-	M22 x 1,5	-
16	-	M24 x 1,5	-	M24 x 1,5	1"	1"	-	M24 x 1,5	-
-	-	-	-	-	-	-	M24 x 1,5	-	M24 x 1,5
18	M26 x 1,5	-	M26 x 1,5	-	-	-	-	M27 x 1,5	-
20	-	M30 x 2	-	M30 x 2	-	-	-	M27 x 1,5	-
-	-	-	-	-	-	-	M30 x 1,5	-	M30 x 1,5
22	M30 x 2	-	M30 x 2	-	-	-	-	M30 x 1,5	-
25	-	M36 x 2	-	M36 x 2	-	-	-	M33 x 1,5	-
-	-	-	-	-	-	-	M36 x 1,5	-	M36 x 1,5
28	M36 x 2	-	M36 x 2	-	-	-	-	-	-
30	-	M42 x 2	-	M42 x 2	-	-	-	M39 x 1,5	-
33	-	-	-	-	-	-	M45 x 1,5	-	M45 x 1,5

For detailed ordering information, please consult price list or contact Parflex® Division.

A Hose  
 B Tubing  
 C Coiled Air Hose & Fittings  
 D Transportation  
 E Fittings  
 F Tooling, Equipment & Accessories  
 G General Technical

# Media to Fitting & Seal Compatibility

Media	Fitting Material			Seal Material			
	Brass	Steel	316 SS	BUNA-N	Ethylene Propylene	Fluorocarbon	Neoprene
Acetylene	NR	F	S	S	S	S	F
Air (oil free) @ 190° F	S	F	S	S	S	S	S
Air (oil free) @ 300° F	S	F	S	F	F	S	F
Air (oil free) @ 400° F	S	F	S	NR	NR	S	NR
Alcohol, Ethyl	S	NR	NR	NR	S	NR	S
Animal Oils (Lard Oil)	F	F	F	S	F	S	F
Aromatic Fuel - 50%	ID	ID	ID	F	NR	S	NR
Aromatic Solvents	ID	ID	F	F	ID	S	NR
Asphalt	NR	NR	S	F	NR	S	F
ASTM Oil #1	S	S	S	S	NR	S	S
ASTM Oil #2	S	S	S	S	NR	S	F
ASTM Oil #3	S	S	S	S	NR	S	NR
ASTM Oil #4	S	S	S	F	NR	S	NR
ATF Oil	S	S	S	S	NR	S	F
Automotive Brake Fluid	ID	ID	ID	NR	S	NR	F
Benzene	NR	F	NR	NR	NR	S	NR
Brine (Sodium Chloride)	NR	NR	S	S	S	S	S
Butane	NR	S	S	S	NR	S	S
Carbon Dioxide	S	F	S	S	S	S	S
Carbon Monoxide	S	S	S	S	S	S	F
Chlorine (Dry)	F	F	NR	NR	ID	F	F
Compressed Air	S	F	S	S	S	S	S
Crude Oil	NR	F	S	F	NR	S	NR
Cutting Oil	ID	S	S	S	NR	S	F
Diesel Fuel	S	S	S	S	NR	S	NR
Ethanol	S	NR	NR	NR	S	NR	S
Ethers	S	S	S	NR	F	F	NR
Freon 11	S	ID	ID	F	NR	F	NR
Freon 12	S	S	NR	F	NR	S	S
Freon 22	S	NR	S	NR	NR	NR	S
Fuel Oil	NR	S	S	S	NR	S	F
Gasoline	S	F	S	S	NR	S	NR
Gas, Liquid Propane (LPG)	S	S	S	S	NR	S	F
Gas, Natural	F	S	S	S	NR	S	S
Helium	S	S	S	S	S	S	S
Hydraulic Oil, Petroleum Base	S	S	S	S	NR	S	S
Hydraulic Oil, Water Base	ID	S	S	F	S	NR	F
Hydrogen Gas	S	S	S	S	S	S	S
Jet Fuel	S	S	S	S	NR	S	NR
Kerosene	S	S	S	S	NR	S	F
Lubricating Oil SAE 10, 20, 30, 40, 50	S	S	S	S	NR	S	F



For detailed ordering information, please consult price list or contact Parflex® Division.

# Media to Fitting & Seal Compatibility (cont.)

Media	Fitting Material			Seal Material			
	Brass	Steel	316 SS	BUNA-N	Ethylene Propylene	Fluorocarbon	Neoprene
Methanol	S	S	S	S	S	NR	S
MIL-F-8192 (JP-9)	S	S	S	NR	NR	S	NR
MIL-H-5606	S	S	S	S	NR	S	F
MIL-H-6083	S	S	S	S	NR	S	S
MIL-H-7083	S	S	S	S	S	F	F
MIL-H-8446 (MLO-8515)	F	S	S	F	NR	S	S
Mil-L-2104 & 2104B	S	S	S	S	NR	S	F
MIL-L-7808	NR	F	S	F	NR	S	NR
Mineral Oil	S	S	S	S	NR	S	F
Nitrogen	S	S	S	S	S	S	S
Petrolatum	S	S	S	S	NR	S	F
Petroleum Oil (<250° F)	S	S	S	S	NR	S	F
Propane	S	S	S	S	NR	S	F
R134A	S	S	S	NR	S	NR	NR
Sea Water	F	NR	S	S	S	S	F
Skydrol 500, Type 2	NR	S	S	NR	S	NR	NR
Skydrol 7000, Type 2	NR	S	S	NR	S	F	NR
Soap Solutions	NR	NR	S	S	S	S	F
Steam (<400° F)	F	S	S	NR	S	NR	NR
Stoddard Solvent	F	S	S	S	NR	S	F
Transmission Fluid (Type A)	S	S	S	S	NR	S	F
Trichloroethane	ID	F	S	NR	NR	S	NR
Water	S	F	S	S	S	F	F

Table U4 – Fluid Compatibility Chart

Codes:

S = Satisfactory

F = Fair

NR = Not recommended

ID = Insufficient data

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

For detailed ordering information, please consult price list or contact Parflex® Division.



# Metal Tube & Fitting Material Compatibility

As a general rule, tube and fitting materials should be the same. If different materials must be considered, the following chart can be used as a general guide. Since operating conditions differ with applications, this chart should be used only as a guide and not a firm recommendation. Before making a final

decision on material combination, it should be sufficiently tested under appropriate conditions to assure suitability for the intended application. For additional material combinations, contact the Tube Fittings Division.

Tube Material	Specification	Construction	Condition	Maximum Hardness	Temperature Range (7)	Application	Tube Material to Fitting & Material Compatibility																
							Seal-Lok™ ORFS (SAE J1453)			Triple-Lok® 37° Flare (SAE J514)			Ferulok® Flareless (SAE J514)			Intru-Lok® Flareless EO/EO-2 Flareless (ISO 8434-1)							
							S	SS	B	S	SS	B	M	S	SS	M	B	S	SS	B, M			
Carbon Steel C-1010	SAE J524 (ASTM A179) (8)	Seamless	Fully Annealed	HRB 72	-65° to 500°F -55° to 260°C	High pressure hydraulics, air, & some specialty chemicals	E	NR	(6)	G	NR	(6)	NR	E	NR	NR	NR	NR	NR	NR	NR		
	SAE J525 (ASTM A178) (8)	Welded & Drawn					E	NR	(6)	E	NR	(6)	NR	E	NR	NR	NR	NR	NR	NR	NR	NR	NR
	SAE J356	Welded & Flash Controlled					G	NR	(6)	NR	NR	(6)	NR	G	NR	NR	NR	NR	NR	NR	NR	NR	NR
Carbon Steel C-1021	SAE J2467	Welded & Flash Controlled	Fully Annealed	HRB 75	-65° to 500°F -55° to 260°C	High pressure hydraulics	E	NR	(6)	NR	NR	(6)	NR	E	NR	NR	NR	NR	NR	NR	NR		
	SAE J2435	Welded & Drawn					E	NR	(6)	E	NR	(6)	NR	E	NR	NR	NR	NR	NR	NR	NR	NR	NR
Carbon Steel High Strength Low Alloy (HSLA)	SAE 2613	Welded & Flash Controlled	Sub-critically annealed	HRB 90	-65° to 500°F -55° to 260°C	High pressure hydraulics	E	NR	(6)	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR		
	SAE J2614	Welded & Drawn					E	NR	(6)	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR
Alloy Steel 4130	ASTM A519	Seamless			-65° to 500°F -55° to 260°C	High pressure hydraulics	E	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR		
St 37.4 (Carbon Steel)	DIN 2391 Part 2 (Metric)	Seamless	Fully Annealed	HRB 72	-65° to 500°F -55° to 260°C	High pressure hydraulics, air, & some specialty chemicals	E	NR	NR	G	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	E		
Stainless Steel 304 & 316	ASTM A213 ASTM A269	Seamless	Fully Annealed	HRB 90	-425° to 1200°F -255° to 650°C (3)	High pressure, high temp, or generally corrosive media (1)	(6)	E	(6)	(6)	G	(6)	NR	(6)	E	NR	NR	NR	NR	NR	NR		
	ASTM A249 ASTM A269	Welded & Drawn					(6)	E	(6)	(6)	E	(6)	NR	(6)	E	NR	NR	NR	NR	NR	NR	NR	NR
1.4571 1.4541 Stainless Steel	DIN 17458 Tab 8 (Metric)	Seamless	Fully Annealed	HRB 90	-425° to 120°F -255° to 650°C (3)	High pressure, high temp, or generally corrosive media (1)	(6)	E	NR	(6)	G	NR	NR	NR	E	NR	NR	NR	NR	NR	E		
Copper	SAE J528 (ASTM B-75) (8)	Seamless	Soft Annealed Temper 0	60 Max. Rockwell 15T	-325° to 400°F -200° to 205°C	Low pressure, low temp, water, oil & air	E	(6)	E	G	(6)	E	NR	G	(2)	NR	NR	E	NR	NR	E		
Aluminum 6061	ASTM-B210	Seamless	T6 Temper	HRB 56	-325° to 400°F -200° to 205°C	Low pressure, low temp, water, oil, air & some specialty chemicals	NR	NR	NR	G	NR	NR	NR	E	(2)	NR	NR	(6)	NR	NR	NR		
			O & T4 Temper	HRB 30			E	(5)	NR	NR	G	NR	NR	NR	E	(2)	NR	NR	(6)	NR	NR	NR	

(Cont.)



# Metal Tube & Fitting Material Compatibility (cont.)

Tube Material	Specification	Construction	Condition	Maximum Hardness	Temperature Range (7)	Application	Tube Material to Fitting & Material Compatibility														
							Seal-Lok™ ORFS (SAE J1453)			Triple-Lok® 37° Flare (SAE J514)				Ferulok® Flareless (SAE J514)			Intru-Lok® Flareless		EO/EO-2 Flareless (ISO 8434-1)		
							S	SS	B	S	SS	B	M	S	SS	M	B	S	SS	B, M	
Monel 400	ASTM-B165	Seamless	Fully Annealed	HRB 70	-400° to 800°F -240° to 425°C	Sour gas, marine & gen chemical processing media	NR	(6)	NR	NR	(6)	NR	E	NR	(6)	E	NR	NR			
Nylon		Extruded	Flexible & Semi-Rigid		-60° to 200°F -50° to 95°C	Lube lines, chemical process controls & air	NR	NR	NR	NR	NR	NR	NR	G (2)	G (2)	G (2)	E	G (2), (9)			
Polyethylene	ASTM D-1248	Extruded	Instrument Grade		-80° to 150°F -60° to 65°C	Instrumentation lines	NR	NR	NR	NR	NR	NR	NR	G (2)	G (2)	G (2)	E	G (2), (9)			
PVC		Extruded	Instrument & Laboratory Grade		0° to 140°F -20° to 60°C	General purpose laboratory use	NR	NR	NR	NR	NR	NR	NR	NR	NR	NR	G	NR			
PTFE		Extruded & Sintered			-65° to 400°F -55° to 205°C	Very high temp, fuel, tube, chemical, pharma, food	NR	NR	NR	NR	NR	NR	NR	G (2)	G (2)	G (2)	G	G (2), (9)			

Table U7 – Tube and Fitting Material Compatibility

**Ratings Key:**

NR = Not Recommended  
 F = Fair  
 G = Good  
 E = Excellent

**Fittings Materials Code:**

S = Steel  
 SS = Stainless Steel  
 B = Brass  
 M = Monel

**Notes:**

- For highly corrosive media or service environment, contact the Tube Fittings Division.
- Requires different assembly procedure. Contact the Tube Fittings Division.
- Low temperature limit for stainless steel Ferulok® fittings is -20°F (-30°C).
- For brazing only. Grade 4130 not recommended with Parflange process.
- For use with Parflange process only. Not recommended with brazing.
- Use depends on specific application. Contact the Tube Fittings Division.
- Applies to tube material.
- Comparable specifications to SAE.
- With metric version of tubing.
- Not tested with Parflange. Contact the Tube Fittings Division.

For detailed ordering information, please consult price list or contact Parflex® Division.





# O-Ring Material Selection

Standard O-rings supplied with Parker tube fittings and adapters are 90 durometer hard nitrile (Buna-N) Parker compound #N0552. These O-rings are well suited for most industrial hydraulic and pneumatic systems. They have high extrusion resistance making them suitable for very high pressure static applications. Optional high temperature fluorocarbon, Parker compound #V0894, is also available for higher temperature specifications.

O-rings for other than normal hydraulic media or higher temperature applications can be selected from the following chart. The chart should be used only as a general guide. Before making final selection for a given application, it is recommended that appropriate tests be conducted to assure compatibility with the fluid, temperature, pressure and other environmental conditions.

For fluids not shown in the chart, please contact the Tube Fittings Division.

Polymer	Abbreviated Name	Parker Compound No.	Color	SAE J515 Type	Hardness Shore "A" <sup>7</sup>	Temperature Range	Recommended For	Not Recommended For
Nitrile-Butadiene	NBR	N0552	● B	CH <sup>2</sup>	90 <sup>6</sup>	-30° to 250°F	Petroleum base oils and fluids, mineral oils, ethylene glycol base fluids, silicone and di-ester base lubricants, air, water under 150°F, and natural gas. Hydrogen fuel cells. Meets FDA requirements for food products. CNG Applications.	Phosphate ester base hydraulic fluids, automotive brake fluids, strong acids, ozone, freons, ketones, halogenated hydrocarbons, and methanol.
		N0674		-	70	-30° to 250°F		
		N0103		-	70	-65° to 225°F		
Nitrile-Butadiene (Low compression set – N1059)		N1059		CH <sup>2</sup>	90	-30° to 275°F		
Nitrile-Butadiene		N0507		-	90	-65° to 180°F		
		N0304		-	75	-65° to 225°F		
		N0508		-	75	-35° to 250°F		
		N0756		-	75 <sup>6</sup>	-65° to 275°F		
Ethylene-Propylene		EPDM		E0540	● B	CA <sup>3</sup>		
	E0893		● P <sup>1</sup>	CA <sup>3</sup>	80			
	E0962		● B	-	90			
Neoprene	CR	C0873	● B	-	70	-45° to 250° F	Refrigerants (freons, ammonia), high aniline point petroleum oils, mild acids and silicate ester lubricants.	Phosphate ester fluids and ketones.
		C0944	● R <sup>1</sup>	-	70			
Fluorocarbon	FKM <sup>5</sup> or FPM	V0747	● B	-	75	-15° to 400° F	Petroleum base oils and fluids, some phosphate ester base fluids, silicone and silicate ester base lubricants, di-ester base lubricants, acids and halogenated hydrocarbons.	Ketones, skydrol fluids, amines (VDMH), anhydrous ammonia, low molecular weight esters and ethers, and hot hydrofluoric or chlorosulfonic acids.
		V0884	● BR <sup>1</sup>	-	75			
		V0894	● BR <sup>1</sup>	HK <sup>4</sup>	90 <sup>6</sup>			
Silicone	Si	S0604	● RU <sup>1</sup>	-	70	-65° to 450° F	Dry heat (air to 400°F) and high aniline point oils.	Most petroleum fluids, ketones, water and steam.

Table U-6 – O-Ring Selection

\*Color Code: B – Black, P – Purple, R – Red, BR – Brown, RU – Rust

#### Notes:

- These Parker "Chromassure" color assurance O-rings are available from the Parker Hannifin O-Ring Division. They help eliminate assembly errors, reduce warranty costs and liability risks, and assure safety in aftermarket business.
- Formerly SAE Type I.
- Formerly SAE Type II.
- Formerly SAE Type III.
- "FKM" is the ASTM designation for fluorocarbon. Its ISO designation is "FPM".
- Standard compounds available from stock.
- Use 90 durometer hard O-rings for applications with 1500 PSI or higher pressures.



For detailed ordering information, please consult price list or contact Parflex® Division.

# Metals Corrosion Scale

## Corrosion of Base Metals in Contact

The susceptibility of different base metals to corrosion while in contact depends upon the difference between the contact potentials or the electromotive voltages of the metals involved. The greater the potential difference is, the greater is the tendency for corrosion. The metal with the higher potential forms the anode and is corroded. The larger the separation distance in the electromotive chart between the two metals in contact, the higher the contact potential and chances for corrosion. For example, zinc and aluminum are very short distance apart in the chart; therefore potential for corrosion when these two metals are in contact is very low. On the other hand, aluminum and passivated 316 stainless steel are far apart; hence, when in contact, the potential for corrosion is very high. Aluminum, being more anodic metal, will corrode in this combination.

As a general guideline, if the metals are half the length of the chart or more apart, the combination should be avoided. Also, it is not a good idea to combine an anodic metal part with thin cross section, such as thin wall tubing, with a cathodic or less anodic metal part of a heavy cross section, such as a fitting.

**Example:** A thin wall brass tube with steel fitting is a better, although not ideal, combination than a thin wall steel tube with brass fitting.

Electromotive or Galvanic Series for Metals	
+ Anodic (least noble) corroded	Magnesium Magnesium alloys Zinc ( <b>Parker steel fittings are zinc plated</b> ) Berillium Aluminum 5052, 3004, 3003, 1100, 6053 Cadmium Aluminum 2117, 2017, 2024 Mild steel (1018), wrought iron, <b>free machining steel (12L14)</b> Low alloy high strength steel, cast iron Chrome iron (active) 430 Stainless (active) 302, 303, 321, 347, 410, 416, stainless steel (active) Ni-resist 316, 317 stainless steel (active) Carpenter 20Cb-3 stainless (active) Aluminum bronze (CA 687) Hastelloy C (active) Inconel 625 (active) Titanium (active) Lead/Tin solder Lead Tin Inconel 600 (active) Nickel (active) 60 Ni-15 Cr (active) 80 Ni-20 Cr (active) Hastelloy B (active) Naval brass (CA 464), Yellow brass (CA 268), <b>Brass (CA360)</b> Red brass (CA 230), Admiralty brass (CA 443) Copper (CA 102) Maganese bronze (CA 675), Tin bronze (CA 903, 905) 410, 416 Stainless (passive) Phosphor bronze (CA 521, 524) Silicon bronze (CA 651, 655) Nickel silver (CA 732, 735, 745, 752, 754, 757, 764, 770, 794) Cupro Ni 90-10 Cupro Ni 80-20 430 Stainless steel (passive) Cupro Ni 70-30 Nickel aluminum bronze (CA 630, 632) Monel 400, K500 Silver solder Nickel (passive) 60 Ni 15 Cr (passive) Inconel 600 (passive) 80 Ni 20 Cr (passive) Chrome iron (passive) 302, 303, 304, 321, 347 stainless steel (passive) 316, 317 stainless steel (passive) ( <b>Parker stainless steel fittings are passivated</b> ) Carpenter 20 Cb-3 stainless (passive), Incoloy 825 Silver Titanium (passive), Hastelloy C & C276 (passive), Inconel 625 (passive) Graphic Zirconium Gold Platinum
- Cathodic (most noble) protected	

Table U5 – Electromotive or Galvanic Series for Metals

For detailed ordering information, please consult price list or contact Parflex® Division.



# Materials to Parflex Part Number Guide

Ratings Code:

- G – Good to excellent. Little or no swelling, tensile or surface changes. Preferred choice.
- L – Marginal or conditional. Noticeable effects but not necessarily indicating lack of serviceability. Further testing suggested for specific application. Very long-term effects such as stiffening or potential for crazing should be evaluated.
- P – Poor or unsatisfactory. Not recommended without extensive and realistic testing.
- – Indicates that this was not tested.
- # – For fluoropolymer. Indicates good chemical resistance but potential for excessive permeation.

MATERIAL CODE FOR HOSE CORE TUBES	
H	Copolyester
N	Nylon
NC	Nylon Co-Polymer
O	Polyolefin
PFX	Proprietary Elastomer
TFE/PFA	Fluoropolymer PTFE/PFA
U	Polyurethane
MATERIAL CODE FOR HOSE COVERS	
EPDM	Copolyester (Rubber)
HF	Low Temperature Copolyester
PFX	Proprietary Elastomer
S	Silicone
U	Polyurethane
MATERIAL CODE FOR THERMOPLASTIC TUBING	
HDPE	High Density Polyethylene
N	Flexible Nylon
NR	Unplasticized Nylon (semi-rigid)
PE	Linear Low Density Polyethylene
PEFR	Flame Resistant Polyethylene
PP	Polypropylene
PV	Flexible Polyvinyl Chloride (PVC)
U	Polyurethane
MATERIAL CODE FOR FLUOROPOLYMER TUBING	
FEP	Fluorinated Ethylene Propylene
PFA	Perfluoroalkoxy
TFE	Polytetrafluoroethylene
PVDF	Polyvinylidene Fluoride

PARKER PRODUCT
D6, H6, R6, HFS, HFS2, M8, HTB, HJK, 560, 563, 590, 593, 510C, 518C, 515H, 53DM/538DM, 55LT, HLB, S4, S5, S6, S9, SLH, XDH
520N, 526BA, 527BA, 528N, 540N, 548N, 56DH/568DH, 573X, 575X, 580N, H580N, 588N, 1035HT, 5CNG, MSH, MSXL, PTH
510, 510A
540P
1035A
919/919B, 919J, 919U, 929/929B, 929BJ, 939/939B, 943B, 944B, 950B, 955B, S30/S30B, S40/S40B, STW/STWB, SCW/SCB, PCW/PCB, SBFB/SBFW, SCWW/SCBV, PCWW/PCBV, SCWW-FS/SCBV-FS, PCWW-FS/PCBV-FS
83FR, B9
PARKER PRODUCT
RCTW/RCTB (Contact Engineering for chemical resistance questions)
55LT, 53DM/538DM
510C, 518C
SWPV, 919J, 919BJ
All except 55LT, 53DM/538DM, 518C, 1035HT and PTFE hoses
PARKER PRODUCT
HDPE
N
NR
E
PEFR
PP
PV
U, HU
PARKER PRODUCT
103, 203, HS1.3FEP, HS1.6FEP,
104, 204
TFL, TFS, TFT, TFH, 101, 201, TFB, HS2TFS, HS2TFT, HS2TFL, HS2TFI, HS4TFI
110, 111

# Media to Hose Material Compatibility Guide

Media	H	N	U/HF UFR	PV	NC	O	OC	PFX	HFR	FEP	PTFE/ PFA
Acetaldehyde	G	L	L	P	-	L	P	L	G	G	G
Acetic Acid Glacial	L	L	L	G	P	G	L	L	L	L	G
Acetone	L	G	P	P	G	P	P	P	L	G	G
Acetylene	2	2	2	2	2	2	2	2	2	2	2
Air (4)	G	G	G	G	G	G	G	G	G	G	G
Ammonium Chloride	G	P	G	G	P	G	G	G	G	L	G
Ammonium Hydroxide	L	G	P	L	-	G	G	P	L	G	G
Anhydrous Ammonia	P	P	P	P	P	P	P	P	P	8	8
Aniline	P	P	P	P	P	L	P	P	P	G	G
Animal Oils (6)	G	G	G	G	G	P	P	G	G	-	G
Aromatic Hydrocarbons	L	G	L	P	G	P	-	L	L	-	G
Asphalt	G	G	G	G	G	L	L	G	G	L	G
Baygon (Insecticide)	L	G	P	-	-	-	-	P	L	-	G
Beer	G	G	G	G	-	G	G	G	G	G	G
Benzene	L	G	L	P	L	P	P	L	L	G	G
Brake Fluid (DOT #3)	-	G	P	P	-	P	P	P	-	-	G
Butane (2) (4)	G	G	L	L	P	L	P	L	G	#	#
Butter (6)	G	G	G	G	-	G	G	G	G	-	G
Calcium Chloride	G	3	G	L	3	G	G	G	G	G	G
Carbon Dioxide (4)	G	G	G	G	G	G	G	G	G	#	#
Carbon Monoxide (4)	G	3	G	G	3	L	-	G	G	#	#
Carbon Tetrachloride	L	G	P	L	G	P	P	P	L	G	G
Castor Oil	G	L	L	G	L	P	P	L	G	-	G
Chlorinated Hydrocarbon Base Fluids	L	G	L	P	-	-	-	L	L	-	G
Chlorinated Petroleum Oil	G	G	L	-	L	-	-	L	G	-	-
Chlorinated Solvents	P	3	P	L	3	L	L	P	P	-	G
Chlorine, Gaseous, Dry	P	P	P	G	P	L	P	P	P	#	#
Chlordane (Insecticide)	L	G	P	-	-	-	-	P	L	-	-
Chloroform	P	P	P	P	P	P	P	P	P	G	G
Chromic Acid	P	3	P	G	P	3	L	P	P	L	G
Citric Acid Solutions	G	G	L	G	G	G	G	L	G	G	G
Crude Petroleum Oil	G	G	G	G	G	P	P	G	G	-	G
Cyclohexane (2)	G	G	G	-	-	P	P	G	G	G	G
Cygon (Insecticide)	L	G	P	-	-	-	-	P	L	-	-
Diazin (Insecticide)	L	-	P	L	-	-					
Diesel Fuel (2)	G	G	G	L	G	P	P	G	G	-	G
Diester Oils	L	G	P	P	-	P	P	P	L	-	G
Enamels	G	G	G	L	-	L	L	G	G	-	G
Ethanol (6)	G	G	L	L	L	G	G	L	G	-	G
Ethers	L	G	P	L	G	L	P	P	L	G	G
Ethylene Glycol	L	G	L	G	G	G	G	L	G	G	G
Ethylene Oxide	G	G	L	P	-	L	L	L	G	#	#
Fatty Acids	G	G	3	G	G	L	L	3	G	G	G
Formaldehyde	L	L	P	L	L	G	L	P	L	G	G
Formic Acid	P	P	P	G	P	G	G	P	P	G	G

(Cont.)

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-51

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Media to Hose Material Compatibility Guide (cont.)

Media	H	N	U/HF UFR	PV	NC	O	OC	PFX	HFR	FEP	TFE
Freon 12 (5)	P	G	L	G	G	L	-	L	P	#	#
Freon 22 (5)	P	G	L	G	G	L	-	L	P	#	#
Fruit Juices	G	G	G	G	-	G	G	G	G	-	G
Fuel Oil (2)	G	G	L	L	G	P	P	L	G	G	G
Gas (Oil) (2)	G	G	G	G	G	P	P	G	G	-	G
Gas (Natural) (4)	2	2	2	2	2	2	2	2	2	2	2
Gasoline (2)	G	G	3	P	G	P	P	3	G	G	G
Glue	3	3	3	3	3	3	3	3	3	3	3
Glycerin	G	G	L	G	G	G	G	L	G	G	G
Glycols (to 135°F)	L	G	L	G	G	-	-	L	G	G	G
Grease (Petroleum base)	G	G	G	G	G	L	L	G	G	-	G
Heptachlor (Insecticide)	L	G	P	L	-	P	P	P	L	-	G
Hexane (2)	G	G	G	L	G	P	P	G	G	G	G
Houghto Safe-600 Series (Hydraulic fluid)	G	G	L	G	G	G	L	L	G	-	G
Houghto Safe-1000 Series (Phosphate esters)	L	G	P	G	G	P	P	P	L	-	G
Hydraulic Fluid (Petroleum base)	G	G	G	G	G	L	L	G	G	L	G
Hydraulic Fluid (Phosphate ester base)	L	G	L	L	G	P	P	P	L	-	G
Hydraulic Fluid (Water glycol base)	G	G	G	L	G	-	-	G	G	-	G
Hydraulic Oil (Petroleum base)	G	G	G	G	G	L	P	G	G	L	G
Hydrochloric Acid	P	L	P	L	P	L	P	P	P	G	G
Hydrofluoric Acid	P	P	P	L	P	L	P	P	P	G	G
Hydrogen, Gaseous (2) (4) (5)	G	G	G	G	G	G	G	G	#	#	
Hydrolube (Hydraulic fluid/water glycol base)	G	G	L	G	G	G	G	L	G	-	G
IRUS 902 (Hydraulic fluid/water-oil emulsion)	G	G	G	G	G	L	P	G	G	-	G
Isocyanates (2)	L	L	L	P	-	L	P	L	L	-	G
IsoOctane (2)	G	G	G	L	G	L	P	L	G	G	G
Isopropyl Alcohol	G	G	L	L	G	G	L	L	G	G	G
Kerosene (2)	G	G	L	L	G	L	P	P	G	G	G
Ketones	L	G	P	P	G	G	P	P	L	G	G
Lacquer Solvents	L	G	P	P	3	L	3	P	L	L	G
Lactic Acid	P	G	P	G	G	G	G	P	P	G	G
Lime (Calcium oxide)	G	G	G	G	-	G	G	G	G	G	G
Lindol (Hydraulic fluid/phosphate esters)	L	G	P	-	-	-	-	P	L	-	G
Linseed Oil	G	G	G	L	G	L	P	G	G	G	G
LP - Gas	2	2	2	2	2	2	2	2	2	2	2
Lubricating Oils (Diester base)	L	G	P	-	G	-	-	P	L	-	G
Lubricating Oils (Petroleum base)	G	G	G	G	G	L	P	G	G	G	G
Malathion (Insecticide)	L	G	P	-	-	-	-	P	L	-	G
Magnesium Hydroxide	L	G	L	G	-	G	G	L	L	G	G
Magnesium Salts	-	G	G	G	-	G	-	G	-	-	G
Mercury	G	G	G	G	G	G	G	G	G	G	G
Meropa Oil (Sulphur base)	G	G	-	-	-	-	-	-	-	-	G
Methane	2	2	2	2	2	2	2	2	2	2	2
Methanol	G	G	P	P	G	L	P	P	G	-	G
Methoxychlor (Insecticide)	L	G	P	-	-	-	-	P	L	-	G

(Cont.)



For detailed ordering information, please consult price list or contact Parflex® Division.

# Media to Hose Material Compatibility Guide (cont.)

Media	H	N	U/HF UFR	PV	NC	O	OC	PFX	HFR	FEP	TFE
Methyl Alcohol (6)	G	G	P	P	G	L	P	P	G	G	G
Methylene Chloride	P	L	P	L	P	L	P	P	P	G	G
Methyl Ethyl Ketone (MEK)	L	G	P	P	G	G	L	P	L	G	G
Methyl Ethyl Ketone Peroxide (MEKP)	-	L	P	-	-	-	-	P	-	-	G
Methyl Isobutyl Ketone (MIBK)	L	G	P	P	G	L	P	P	L	G	G
Milk (6)	G	G	G	G	-	G	G	G	G	G	G
Mineral Oil	G	G	G	G	G	L	P	G	G	G	G
Mineral Spirits	P	-	L	P	-	-	-	L	P	-	G
Motor Oils	G	G	G	G	G	-	-	G	G	G	G
Naphtha	L	G	P	P	G	P	P	P	L	G	G
Natural Gas (4)	2	2	2	2	2	2	2	2	2	2	2
Nitric Acid	P	P	P	L	P	P	P	P	P	L	G
Nitrobenzene	P	G	P	P	G	P	P	P	P	G	G
Nitrogen, Gaseous (4) (5)	G	G	G	G	G	G	G	G	G	G	G
Nitrous Oxide	-	L	-	G	-	L	-	G	-	#	#
Oil (SAE)	G	G	G	G	G	L	L	G	G	-	G
Oil of Turpentine	G	G	P	G	G	P	P	P	G	-	G
Oleic Acid	G	G	G	L	G	L	L	G	G	G	G
OS 45 Type 3 Hydraulic Fluid (Silicate esters)	L	G	L	P	-	P	P	L	L	-	-
Oxygen, Gaseous (4) (5) (6)	G	G	G	G	G	G	G	G	G	G	G
Ozone	L	P	L	G	P	L	G	P	L	G	G
Paint Solvents (Oil base)	L	G	L	P	-	P	P	L	L	-	G
Paint (Oil Base) (7)	G	G	G	P	-	L	P	G	G	-	G
Pentane (2)	G	G	L	L	-	P	P	L	G	G	G
Perchloric Acid	P	P	P	L	P	P	P	P	P	L	G
Perchloroethylene	P	P	P	L	P	P	P	P	P	-	G
Petroleum Ether	-	2	2	P	2	P	P	2	-	2	2
Petroleum Oils	G	G	G	G	G	L	P	G	G	-	G
Phenols	P	P	P	L	P	P	P	P	P	-	G
Phosphate Esters (above 135°F)	P	G	P	P	-	P	P	P	L	-	G
Phosphate Esters (to 135°F)	G	G	P	P	G	P	P	P	G	-	G
Polyol Esters	L	G	P	P	-	-	-	P	L	-	G
Potassium Hydroxide, 50%	P	P	P	L	-	L	L	P	P	G	G
Propane (4) (5)	2	2	2	2	2	2	2	2	2	2	2
Propylene Glycol	-	-	G	G	-	G	L	-	-	G	G
Pydraul F-9, 150, 160 (to 135°F)	G	G	P	P	G	P	P	P	G	-	G
Pydraul 312C, 625 (to 135°F)	P	G	P	P	G	P	P	P	G	-	G
Quintolubric 822 Fluid	-	G	G	-	-	-	-	-	-	-	G
Salt Water	3	3	3	3	3	3	3	3	3	G	G
Sevin (Insecticides in water)	G	G	G	-	-	-	-	G	G	-	G
Silicone Greases	G	G	G	G	G	-	-	G	G	-	G
Silicone Oils	G	G	G	G	G	-	-	G	G	-	G
Skydrol 500 & 7000	L	G	P	P	G	P	P	P	L	G	G
Soap Solutions	G	G	G	G	G	G	G	G	G	G	G

(Cont.)

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-53

A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

G  
General Technical

# Media to Hose Material Compatibility Guide (cont.)

Media	H	N	U/HF UFR	PV	NC	O	OC	PFX	HFR	FEP	TFE
Soda Water	G	G	G	G	G	3	3	G	G	-	G
Sodium Borate	G	G	G	G	G	G	G	G	G	G	G
Sodium Carbonate	3	3	3	3	3	3	3	3	3	3	3
Sodium Chloride Solutions	G	G	G	G	3	G	-	G	G	G	G
Sodium Hydroxide, 50%	L	P	P	L	P	L	L	P	L	G	G
Sodium Hypochlorite	L	P	P	L	-	3	3	P	L	G	G
Steam	P	P	P	P	P	P	P	P	P	G	G
Stoddard Solvent	P	G	P	L	G	P	P	P	P	G	G
Straight Synthetic Oils (Phosphate esters)	L	G	P	P	G	-	-	P	L	-	G
Sulfur	G	G	G	G	-	L	G	G	G	G	G
Sulfur Dioxide	P	L	L	L	-	P	-	L	P	G	G
Sulfur Hexafluoride Gas (4) (5)	G	G	G	G	-	G	-	G	G	-	G
Sulphuric Acid	P	P	P	3	P	P	P	P	P	-	G
Toluene	L	G	L	P	G	P	P	P	L	G	G
Toloul	L	G	L	P	G	P	P	P	L	-	G
Transmission Fluid	G	G	G	P	G	-	-	G	G	-	G
Trichloroethylene	P	L	P	L	G	P	P	P	P	G	G
Trisodium Phosphate Solutions	L	G	P	G	G	G	G	P	L	G	G
Turpentine	G	G	L	L	G	P	P	P	G	G	G
Ucon (Hydraulic fluid-water glycol base)	G	G	L	G	G	-	-	L	G	-	G
Varnish	G	G	G	P	G	G	L	G	G	-	G
Vinegar (6)	L	G	L	G	G	G	G	L	L	G	G
Water (to 135°F) (6)	G	G	G	G	G	G	G	L	G	G	G
Water (above 135°F) (6)	P	G	P	L	-	P	P	P	P	L	G
Water Glycols (to 135°F)	L	G	L	G	G	L	L	L	G	-	G
Water Glycols (above 135°F)	P	G	P	L	-	P	P	P	P	-	G
Water in oil Emulsions (to 135°F)	G	G	L	G	G	-	-	L	G	-	G
Water in oil Emulsions (above 135°F)	P	G	P	L	-	-	-	P	P	-	G
Whiskey, Wines (6)	G	G	L	G	G	G	G	G	G	G	G
Wood Oils	G	G	L	G	G	-	-	G	G	-	G
Xylene	L	G	P	P	G	P	P	P	L	G	G
Zinc Chloride	G	G	G	G	P	G	G	G	G	G	G

## Notes:

1. The Fluid Compatibility Guides are simplified rating tabulations based on immersion tests at 75°F. Higher temperatures tend to reduce ratings. Since final selection depends on pressure, fluid and ambient temperature and other factors not known to Parker Hannifin Co., no performance guarantee is expressed or implied. Ratings do not imply compliance with specialized codes such as FDA, NSF, AGA or UL and do not cover possible fluid discoloration, taste or odor effects. For conveying foodstuffs, use FDA sanctioned materials and for potable water, use NSF listed materials. For chemicals not listed, or for advice on particular applications, please consult Product Engineering, Parflex Div., Ravenna, Ohio.

2. Hose applications for these fluids must take into account legal and insurance regulations. This does not imply AGA or UL compliance.

3. Satisfactory at some concentrations and temperatures, unsatisfactory in others.

4. For high pressure gases, the cover should be pinpricked and the pressure must not be released quickly. Chain or restrain the hose to prevent personal injury in the event of damage or failure.

5. Chemical compatibility does not imply low permeation rates. Consult the Parker factory for a suggestion for your specific requirement.

6. Does not imply NSF or FDA compliance.

7. Chemical compatibility does not imply acceptability for use in airless paint spray applications. These applications require a special conductive hose.

8. Fluoropolymers are chemically compatible with Anhydrous Ammonia. However, extreme caution must be used in dealing with Anhydrous Ammonia since it can cause severe injuries such as blindness and/or chemical burns.



# Media to Plastic Tubing Material Compatibility Guide

Media	PE	HDPE	PP	N	NR	PV	U	FRPE	FEP	PFA	TFE
Acetone	P	L	G	G	G	P	P	L	G	G	G
Acetyl Bromide	L	L	L	P	P	P	-	-	-	-	-
Acetyl Chloride	L	L	L	P	P	P	-	-	G	G	G
Air	G	G	G	G	G	G	G	G	G	G	G
Alcohols	G	G	G	G	G	L	L	G	G	G	G
Aluminum Salts	G	G	G	G	G	G	G	G	-	-	-
Ammonia	G	G	G	G	G	G	G	L	-	-	-
Amyl Acetate	G	G	G	G	G	P	L	-	G	G	G
Aniline	L	G	L	P	P	P	P	-	G	G	G
Animal Oils (6)	P	L	L	G	G	G	G	-	-	-	G
Arsenic Salts	G	G	G	G	G	G	G	G	-	-	-
Aromatic Hydrocarbons	P	L	L	G	G	P	L	P	-	-	G
Barium Salts	G	G	G	G	G	G	G	G	-	-	-
Benzaldehyde	P	L	L	L	L	P	L	P	G	G	G
Benzene	P	L	L	G	G	P	L	P	G	G	G
Benzyl Alcohol	P	G	L	L	L	G	L	P	G	G	G
Bleaching Liquors	G	L	G	L	L	L	L	-	-	-	-
Boric Acid Solutions	G	G	G	G	G	G	G	G	G	G	G
Bromine	L	L	P	P	P	F	P	-	G	L	G
Butane (2)	L	G	G	G	G	L	P	-	#	#	#
Butanol	G	G	G	G	G	G	G	G	-	-	-
Butyl Acetate	G	G	L	G	G	P	L	G	G	G	G
Calcium Hypochlorite	L	L	P	P	L	L	P	L	G	G	G
Calcium Salts	G	G	G	G	G	G	G	G	-	-	-
Carbon Dioxide	G	G	G	G	G	G	G	G	#	#	#
Carbon Disulfide	L	L	L	L	L	P	L	-	#	#	#
Carbon Tetrachloride	P	P	L	L	L	L	P	P	G	G	G
Caustic Potash	G	G	G	G	G	L	G	-	G	G	G
Caustic Soda	G	G	G	G	G	L	G	-	G	L	G
Chloroacetic Acid	L	G	L	L	L	P	P	-	G	L	G
Chlorine (Dry)	L	L	L	P	P	G	P	-	#	#	#
Chlorine (Wet)	L	L	L	P	P	G	L	-	G	G	G
Chlorobenzene	P	L	L	L	L	P	L	P	G	G	G
Chloroform	P	L	P	P	P	P	P	P	G	G	G
Chromic Acid	L	L	L	P	P	G	P	-	L	G	G
Copper Salts	G	G	G	G	G	G	G	G	-	-	-
Cresol	P	L	L	P	P	L	P	P	G	G	G
Cyclohexanone	L	L	L	L	L	P	P	-	G	G	G
Ethers	L	L	P	G	G	L	P	-	G	G	G
Ethyl Acetate	G	G	G	G	G	P	L	-	G	G	G
Ethyl Alcohol	G	G	G	L	L	L	G	G	-	-	-
Ethylamine	L	G	L	L	L	P	L	-	-	-	-
Ethyl Bromide	P	L	L	L	L	P	-	P	-	-	-
Ethyl Chloride	P	L	P	L	L	P	-	P	G	G	G
Fatty Acids	L	L	L	G	G	L	L	P	G	G	G

(Cont.)

For detailed ordering information, please consult price list or contact Parflex® Division.

Parker Hannifin Corporation | Parflex® Division | Ravenna, Ohio | [parker.com/pfd](http://parker.com/pfd)



G-55

A Hose

B Tubing

C Coiled Air Hose & Fittings

D Transportation

E Fittings

F Tooling, Equipment & Accessories

G General Technical

# Media to Plastic Tubing Material Compatibility Guide (cont.)

Media	PE	HDPE	PP	N	NR	PV	U	FRPE	FEP	PFA	TFE
Ferric Salts	G	G	G	G	G	G	G	-	-	-	-
Formaldehyde	G	G	G	L	L	L	P	-	G	G	G
Formic Acid	G	G	G	P	P	G	P	G	G	G	G
Freon	L	L	L	G	G	P	L	-	#	#	#
Gasoline (2)	P	G	L	G	G	P	L	P	G	G	G
Glucose	G	G	G	G	G	G	G	G	G	G	G
Glycerin	G	G	G	G	G	G	L	G	G	G	G
Hydriodic Acid	L	G	G	P	P	G	-	-	-	-	-
Hydrochloric Acid. (Conc.)	L	G	G	L	L	L	P	-	G	L	G
Hydrochloric Acid. (Med. Conc.)	L	G	G	L	L	L	P	-	G	L	G
Hydrofluoric Acid	L	L	G	P	P	L	P	-	G	-	G
Hydrogen Peroxide (Conc.)	L	G	L	L	L	L	G	-	-	-	-
Hydrogen Peroxide (Dil.)	L	G	L	G	G	G	G	-	-	-	-
Hydrogen Sulfide	G	G	G	G	G	G	P	-	G	G	G
Iodine	L	G	G	G	G	L	L	-	G	G	G
Kerosene (2)	L	L	L	G	G	L	L	-	G	G	G
Ketones	G	G	G	G	G	P	P	-	G	G	G
Lacquer Solvents	L	L	L	G	G	P	-	-	L	G	G
Lactic Acid	G	G	G	G	G	G	G	-	G	G	G
Lead Acetate	G	G	G	G	G	G	G	-	G	G	G
Linseed Oil	L	G	G	G	G	L	G	-	G	G	G
Magnesium Salts	G	G	G	G	G	G	G	-	-	-	G
Naphtha	L	L	L	G	G	P	L	G	G	G	G
Natural Gas	L	L	L	G	G	G	G	-	2	2	2
Nickel Salts	G	G	G	G	G	G	G	-	-	-	-
Nitric Acid (Conc.)	P	L	P	P	P	L	P	G	L	L	G
Nitric Acid (Dil.)	P	G	L	L	L	G	P	P	L	L	G
Nitrobenzene	P	L	G	L	L	P	P	P	G	G	G
Nitrogen Oxides	L	L	G	L	L	G	-	-	-	-	-
Nitrous Acid	L	L	G	L	L	G	L	-	G	G	G
Oils (Animal and Mineral)	L	L	L	G	G	L	G	-	G	G	G
Oils (Vegetable)	L	L	L	G	G	L	G	-	G	G	G
Oxygen (5) (6)	G	G	G	G	G	G	G	G	G	G	G
Perchloric Acid	P	G	L	P	P	L	P	P	L	G	G
Phenols	P	G	G	P	P	L	P	P	-	-	G
Potassium Salts	G	G	G	G	G	G	G	G	-	-	-
Pyridine	L	L	L	L	L	P	P	-	G	G	G
Silver Nitrate	G	G	G	G	G	G	G	G	G	G	G
Soap Solutions	G	G	G	G	G	G	G	G	G	G	G
Sodium Salts	G	G	G	G	G	G	G	G	-	-	-
Stearic Acid	L	L	L	G	G	P	L	-	G	G	G
Sulfur Chloride	L	L	P	L	L	L	-	-	G	G	G
Sulfuric Acid (Conc.)	P	G	G	P	P	L	P	P	-	-	-
Sulfuric Acid (Dil.)	P	G	G	L	L	G	L	P	-	-	-
Sulfurous Acid	P	G	L	L	L	G	L	P	G	G	G

(Cont.)



For detailed ordering information, please consult price list or contact Parflex® Division.

# Media to Plastic Tubing Material Compatibility Guide (cont.)

Media	PE	HDPE	PP	N	NR	PV	U	FRPE	FEP	PFA	TFE
Tannic Acid	G	G	G	G	G	G	P	-	G	G	G
Tanning Extracts	G	G	G	G	G	G	P	-	-	-	-
Titanium Salts	G	G	G	G	G	G	G	G	-	-	-
Toluene	P	L	P	G	G	P	L	P	G	G	G
Trichloroacetic Acid	L	L	L	P	P	P	P	-	-	-	-
Trichloroethylene	P	L	P	L	L	P	P	P	G	G	G
Turpentine	P	P	L	G	G	L	L	-	G	G	G
Urea	G	G	G	G	G	G	G	-	G	L	G
Uric Acid	G	G	G	G	G	G	G	-	G	G	G
Water (6)	G	G	G	G	G	G	G	G	G	G	G
Xylene	P	L	P	G	G	P	P	P	G	G	G
Zinc Chloride	G	G	G	G	G	G	G	-	G	L	G

## Notes:

- The Fluid Compatibility Guides are simplified rating tabulations based on immersion tests at 75°F. Higher temperatures tend to reduce ratings. Since final selection depends on pressure, fluid and ambient temperature and other factors not known to Parker Hannifin Co., no performance guarantee is expressed or implied. Ratings do not imply compliance with specialized codes such as FDA, NSF, AGA or UL and do not cover possible fluid discoloration, taste or odor effects. For conveying foodstuffs use FDA sanctioned materials, and for potable water use NSF listed materials. For chemicals not listed, or for advice on particular applications, please consult Product Engineering, Parflex Div., Ravenna, Ohio.
- Hose applications for these fluids must take into account legal and insurance regulations. This does not imply AGA or UL compliance.
- Satisfactory at some concentrations and temperatures, unsatisfactory in others.
- For high pressure gases, the cover should be pinpricked and the pressure must not be released quickly. Chain or restrain the hose to prevent personal injury in the event of damage or failure.
- Chemical compatibility does not imply low permeation rates. Consult the Parker factory for a suggestion for your specific requirement.
- Does not imply NSF or FDA compliance.
- Chemical compatibility does not imply acceptability for use in airless paint spray applications. These applications require a special conductive hose.
- Fluoropolymers are chemically compatible with Anhydrous Ammonia. However, extreme caution must be used in dealing with Anhydrous Ammonia since it can cause severe injuries such as blindness and/or chemical burns.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Metric Conversion Chart

English to Metric			
	To Convert From	To	Multiply By
Area	Sq. in. (in <sup>2</sup> )	Sq. mm (mm <sup>2</sup> )	645.16
	Sq. in. (in <sup>2</sup> )	Sq. cm (cm <sup>2</sup> )	6.4516
	Sq. ft. (ft <sup>2</sup> )	Sq. meters (m <sup>2</sup> )	0.0929
Density	Pounds/Cubic foot (lb./ft <sup>3</sup> )	Kilograms/Cubic meter (kg/m <sup>3</sup> )	16.02
Energy	British thermal units (Btu) (1 J=Ws=0.2388 cal)	Joules (J)	1055
Force	Pounds – force (lbf) (1N=0.102 kgf)	Newtons (N)	4.448
Length	Inches (in)	Milimeters (mm)	25.4
	Feet (ft)	Meters (m)	0.3048
	Miles (mi)	Kilometers (km)	1.609
Mass (Weight)	Ounces (oz.)	Grams (g)	28.35
	Pounds – mass (lb)	Kilograms (kg)	0.4536
	Short tons (2000 lb) (tn)	Metric tons (100 kg) (t)	0.9072
Power	Horsepower (550 ft lb/s) (hp)	Kilowatts (kW)	0.7457
Pressure	Pounds/square inch (PSI)	Kilograms (f)/square cm (kg(f)/cm <sup>2</sup> )	0.7457
		Kilopascals (kPa)	0.0703
		Bars (100 kPa)	6.8948
Stress	Pounds/square inch (PSI) (1N/mm <sup>2</sup> =1MPa)	megapascals (MPa)	0.006895
Temperature	Degrees Fahrenheit (°F)	Degrees Celsius (°C)	5/9 (after subtracting 32)
Torque or Bending Moment	Pounds-force-foot (lb-ft)	Newtons-meter (Nm)	1.3567
	Pounds-force-inch (lb-in)		0.113
Velocity	Feet/second (ft/s)	Meters/second (m/s)	0.3048
Viscosity	Dynamic (centipoise)	Pascal-second (Pas)	.001
	Denematic – foot <sup>2</sup> /sec (ft <sup>2</sup> /s)	Meter <sup>2</sup> /sec (m <sup>2</sup> /s)	0.0929
Volume	Cubic inch (in <sup>3</sup> )	Cubic centimeter (cm <sup>3</sup> ) (milliliter)	16.3871
	Quarts (qt)	Liters (1000 cm <sup>3</sup> )	0.9464
	Gallons (gal)	Liters	3.7854

Metric to English			
To Convert From	To	Multiply By	
Sq. mm (mm <sup>2</sup> )	Sq. in. (in <sup>2</sup> )	0.00155	
Kilograms/Cubic meter (kg/m <sup>3</sup> )	Pounds/Cubic foot (lb./ft <sup>3</sup> )	0.0624	
Joules (J)	British Thermal Units (Btu)	0.000947	
Newtons (N)	Pounds - force (lbf)	0.2248	
Milimeters (mm)	Inches (in)	0.03937	
Meters (m)	Feet (ft)	3.281	
Kilometers (km)	Miles (mi)	0.621	
Grams (g)	Ounces (oz.)	0.035	
Kilograms (kg)	Pounds - mass (lb)	2.205	
Metric tons (100 kg) (t)	Short tons (2000 lb) (tn)	1.102	
Kilowatts (kW)	Horsepower (550 ft lb/s) (hp)	1.341	
Kilograms (f)/square cm (kg(f)/cm <sup>2</sup> )	Pounds/square inch (PSI)	14.22	
		Kilopascals (kPa)	0.145
		Bars (100 kPa)	14.503
megapascals (MPa)	Pounds/square inch (PSI) (1N/mm <sup>2</sup> =1MPa)	145.039	
Degrees Celsius (°C)	Degrees Fahrenheit (°F)	9/5 (then add 32)	
Newtons-meter (Nm)	Pounds-force-foot (lb-ft)	0.737	
	Pounds-force-inch (lb-in)	8.85	
Meters/second (m/s)	Feet/second (ft/s)	3.2808	
Pascal-second (Pas)	Dynamic (centipoise)	1000	
Meter <sup>2</sup> /sec (m <sup>2</sup> /s)	Denematic - foot <sup>2</sup> /sec (ft <sup>2</sup> /s)	10.7643	
Cubic centimeter (cm <sup>3</sup> ) (milliliter)	Cubic inch (in <sup>3</sup> )	0.061	
Liters (1000 cm <sup>3</sup> )	Quarts (qt)	1.057	
Liters	Gallons (gal)	0.2642	



# Government & Agency Specifications

Agency and Specifications	Approved Parflex Products
<b>Flame Resistance:</b>	
MSHA	83FR, D6, HFS, HFS2, HTB, M8, 560, 563, 593, 590 (except -3), 510A (except -4, -5, -6), 510C (except -4), 515H, 520N, 540N, 56DH, 573X-3, 575X, 580N, HLB, HJK
UL94V-2	PEFR
UL94HB	NN, NR, NBR (Wall Thickness Above 0.033"), 83FR
SAE J1942	HFS, HFS2, HTB
<b>Dry Food Contact:</b>	
FDA, CFR21 Part 177	E, PP, PV, 540P, 919, 919J, 919U, 929, 939, S30, S40, STW, SBFW, SCW, PCW, SCWV, PCWV, SCWV, PCWV-FS, SCWV-FS, RCTW
<b>Natural Gas Service:</b>	
For Vehicles and Dispensing Systems ANSI IAS NGV4.2 - CSA 12.52	5CNG
European Safety Standard (TUV) Kraftfahrt-Bundesamt ECE R110	5CNG-3, 5CNG-8 (From Parker Polyflex Europe Only)
<b>Potable Water, Liquid Foods:</b>	
NSF Standard 51*	540P Hose; E, PP, NT Series Tubing
NSF Standard 61*	E Series Tubing
<b>Hydraulic Service:</b>	
SAE 100R1	HFS, HFS2, 560
SAE 100R2	590, 593, XDH
SAE 100R7	540N, 548N, 510C, 518C, 55LT, 510A, 540P
SAE 100R8	520N, 528N, 580N, 588N
SAE 100R12	M8
SAE 100R14	919, 919J, 919U, 929
SAE 100R14B	919B, 929B, 929BJ
SAE 100R16	HFS2, 590, XDH
SAE 100R17	D6, H6, R6, 563, XDH
SAE 100R18	53DM, 538DM
SAE 100R19	XDH
<b>WASTEC WRP05-1996 (check revision)</b>	
Waste Equipment Technology Association	S4, S5, S6, S9
<b>Transportation Standards:</b>	
SAE J844, FMVSS106 (49CFR571.106)	1120A, 1120B, BRAKCOIL®, Dollycoil™, Duo-Coil™, SliderCoil™
<b>Electrical, Non-Conductivity:</b>	
SAE J517	518C, 548N, 528N, 588N, 568DH, 538DM
<b>DNV (with approved fittings only)</b>	
Det Norski (Norwegian) Veritas Marine Steel Ships, Mobile Offshore and Fixed Offshore Drilling Units	520N, 580N, 588N, H580N, 518C, 540N, 573X, 575X, 590, 593, 560
<b>Breathing Air Applications:</b>	
CGA (Compressed Gas Association)- G-7.1-1997 Grade E Breathing Air	526BA, 527BA
NFPA 1901	526BA, 527BA

\*Indicates that products shown have been tested and certified by NSF International to the requirements of NSF Standards 51 and 61. NSF does not express or imply an approval on any product.

For detailed ordering information, please consult price list or contact Parflex® Division.



# Parker Safety Guide

## For selecting and using Hose, Tubing, Fittings, and Related Accessories



### Parker Safety Guide for Selecting and Using Hose, Tubing, Fittings and Related Accessories Publication No. 4400-B.1 Revised: August 2007

**WARNING:** Failure or improper selection or improper use of hose, tubing, assemblies, fittings, quick action couplings or related accessories ("Products") can cause death, personal injury and property damage. Possible consequences of failure or improper selection or improper use of these Products include but are not limited to:

- Fittings thrown off at high speed.
- High velocity fluid discharge.
- Explosion or burning of the conveyed fluid.
- Electrocutation from high voltage electric power lines.
- Contact with suddenly moving or falling objects that are controlled by the conveyed fluid.
- Injections by high-pressure fluid discharge.
- Dangerously whipping hose.
- Contact with conveyed fluids that may be hot, cold, toxic, or otherwise injurious.
- Sparking or explosion caused by static electricity buildup or other sources of electricity.
- Sparking or explosion while spraying paint or flammable liquids.
- Injuries resulting from inhalation, ingestion or exposure to fluids.

Before selecting or using any of these Products, it is important that you read and follow the instructions below. Only Hose from Parker's Stratoflex Products Division is approved for in-flight aerospace applications.

### 1.0 GENERAL INSTRUCTIONS

**1.1 Scope:** This safety guide provides instructions for selecting and using (including assembling, installing, and maintaining) these Products. For convenience, all rubber and/or thermoplastic products commonly called "hose" or "tubing" are called "Hose" in this safety guide. All assemblies made with Hose are called "Hose Assemblies". All products commonly called "fittings", "couplings" or "adapters" are called "Fittings". All related accessories (including crimping and swaging machines and tooling) are called "Related Accessories". This safety guide is a supplement to and is to be used with, the specific Parker publications for the specific Hose, Fittings and Related Accessories that are being considered for use. Parker publications are available at [www.parker.com](http://www.parker.com). SAE J1273 ([www.sae.org](http://www.sae.org)) and ISO 17165-2 ([www.ansi.org](http://www.ansi.org)) also provide recommended practices for hydraulic Hose Assemblies.

**1.2 Fail-Safe:** Hose, Hose Assemblies and Fittings can and do fail without warning for many reasons. Design all systems and equipment in a fail-safe mode, so that failure of the Hose, or Hose Assembly or Fitting will not endanger persons or property.

**1.3 Distribution:** Provide a copy of this safety guide to each person responsible for selecting or using Hose and Fitting products. Do not select or use Parker Hose or Fittings without thoroughly reading and understanding this safety guide as well as the specific Parker publications for the Products.

**1.4 User Responsibility:** Due to the wide variety of operating conditions and applications for Hose and Fittings, Parker does not represent or warrant that any particular Hose or Fitting is suitable for any specific end use system. This safety guide does not analyze all technical parameters that must be considered in selecting a product. The user, through its own analysis and testing, is solely responsible for:

- Making the final selection of the Products.
- Assuring that the user's requirements are met and that the application presents no health or safety hazards.
- Providing all appropriate health and safety warnings on the equipment on which the Products are used.
- Assuring compliance with all applicable government and industry standards.

**1.5 Additional Questions:** Call the appropriate Parker technical service department if you have any questions or require any additional information. See the Parker publication for the Products being considered or used, or call 1-800-CPARKER, or go to [www.parker.com](http://www.parker.com), for telephone numbers of the appropriate technical service department.

### 2.0 HOSE AND FITTINGS SELECTION INSTRUCTIONS

**2.1 Electrical Conductivity:** Certain applications require that the Hose be nonconductive to prevent electrical current flow. Other applications require the Hose and the Fittings and the Hose/Fitting interface to be sufficiently

conductive to drain off static electricity. Extreme care must be exercised when selecting Hose and Fittings for these or any other applications in which electrical conductivity or nonconductivity is a factor.

The electrical conductivity or nonconductivity of Hose and Fittings is dependent upon many factors and may be susceptible to change. These factors include but are not limited to the various materials used to make the Hose and the Fittings, Fitting finish (some Fitting finishes are electrically conductive while others are nonconductive), manufacturing methods (including moisture control), how the Fittings contact the Hose, age and amount of deterioration or damage or other changes, moisture content of the Hose at any particular time, and other factors. The following are considerations for electrically nonconductive and conductive Hose. For other applications consult the individual catalog pages and the appropriate industry or regulatory standards for proper selection.

**2.1.1 Electrically Nonconductive Hose:** Certain applications require that the Hose be nonconductive to prevent electrical current flow or to maintain electrical isolation. For applications that require Hose to be electrically nonconductive, including but not limited to applications near high voltage electric lines, only special nonconductive Hose can be used. The manufacturer of the equipment in which the nonconductive Hose is to be used must be consulted to be certain that the Hose and Fittings that are selected are proper for the application. Do not use any Parker Hose or Fittings for any such application requiring nonconductive Hose, including but not limited to applications near high voltage electric lines, unless (i) the application is expressly approved in the Parker technical publication for the product, (ii) the Hose is marked "nonconductive", and (iii) the manufacturer of the equipment on which the Hose is to be used specifically approves the particular Parker Hose and Fittings for such use.

**2.1.2 Electrically Conductive Hose:** Parker manufactures special Hose for certain applications that require electrically conductive Hose. Parker manufactures special Hose for conveying paint in airless paint spraying applications. This Hose is labeled "Electrically Conductive Airless Paint Spray Hose" on its layline and packaging. This Hose must be properly connected to the appropriate Parker Fittings and properly grounded in order to dissipate dangerous static charge buildup, which occurs in all airless paint spraying applications. Do not use any other Hose for airless paint spraying, even if electrically conductive. Use of any other Hose or failure to properly connect the Hose can cause a fire or an explosion resulting in death, personal injury, and property damage.

Parker manufactures a special Hose for certain compressed natural gas ("CNG") applications where static electricity buildup may occur. Parker CNG Hose assemblies comply with the requirements of ANSI/IAS NGV 4.2-1999; CSA 12.52-M99, "Hoses for Natural Gas Vehicles and Dispensing Systems" ([www.ansi.org](http://www.ansi.org)). This Hose is labeled "Electrically Conductive for CNG

Use” on its layline and packaging. This Hose must be properly connected to the appropriate Parker Fittings and properly grounded in order to dissipate dangerous static charge buildup, which occurs in, for example, high velocity CNG dispensing or transfer. Do not use any other Hose for CNG applications where static charge buildup may occur, even if electrically conductive. Use of other Hoses in CNG applications or failure to properly connect or ground this Hose can cause a fire or an explosion resulting in death, personal injury, and property damage. Care must also be taken to protect against CNG permeation through the Hose wall. See section 2.6, Permeation, for more information. Parker CNG Hose is intended for dispenser and vehicle use at a maximum temperature of 180°F (82°C). Parker CNG Hose should not be used in confined spaces or unventilated areas or areas exceeding 180°F (82°C). Final assemblies must be tested for leaks. CNG Hose Assemblies should be tested on a monthly basis for conductivity per ANSI/IAS NGV 4.2-1999; CSA 12.52-M99.

Parker manufactures special Hose for aerospace in-flight applications. Aerospace in-flight applications employing Hose to transmit fuel, lubricating fluids and hydraulic fluids require a special Hose with a conductive inner tube. This Hose for in-flight applications is available only from Parker’s Stratoflex Products Division. Do not use any other Parker Hose for in-flight applications, even if electrically conductive. Use of other Hoses for in-flight applications or failure to properly connect or ground this Hose can cause a fire or an explosion resulting in death, personal injury and property damage. These Hose assemblies for in-flight applications must meet all applicable aerospace industry, aircraft engine and aircraft requirements.

**2.2 Pressure:** Hose selection must be made so that the published maximum working pressure of the Hose and Fittings are equal to or greater than the maximum system pressure. The maximum working pressure of a Hose Assembly is the lower of the respective published maximum working pressures of the Hose and the Fittings used. Surge pressures or peak transient pressures in the system must be below the published maximum working pressure for the Hose. Surge pressures and peak pressures can usually only be determined by sensitive electrical instrumentation that measures and indicates pressures at millisecond intervals. Mechanical pressure gauges indicate only average pressures and cannot be used to determine surge pressures or peak transient pressures. Published burst pressure ratings for Hose is for manufacturing test purposes only and is no indication that the Product can be used in applications at the burst pressure or otherwise above the published maximum recommended working pressure.

**2.3 Suction:** Hoses used for suction applications must be selected to insure that the Hose will withstand the vacuum and pressure of the system. Improperly selected Hose may collapse in suction application.

**2.4 Temperature:** Be certain that fluid and ambient temperatures, both steady and transient, do not exceed the limitations of the Hose. Temperatures below and above the recommended limit can degrade Hose to a point where a failure may occur and release fluid. Properly insulate and protect the Hose Assembly when routing near hot objects (e.g. manifolds). Do not use any Hose in any application where failure of the Hose could result in the conveyed fluids (or vapors or mist from the conveyed fluids) contacting any open flame, molten metal, or other potential fire ignition source that could cause burning or explosion of the conveyed fluids or vapors.

**2.5 Fluid Compatibility:** Hose Assembly selection must assure compatibility of the Hose tube, cover, reinforcement, and Fittings with the fluid media used. See the fluid compatibility chart in the Parker publication for the product being considered or used. This information is offered only as a guide. Actual service life can only be determined by the end user by testing under all extreme conditions and other analysis.

Hose that is chemically compatible with a particular fluid must be assembled using Fittings and adapters containing likewise compatible seals.

**2.6 Permeation:** Permeation (that is, seepage through the Hose) will occur from inside the Hose to outside when Hose is used with gases, liquid and gas fuels, and refrigerants (including but not limited to such materials as helium, diesel fuel, gasoline, natural gas, or LPG). This permeation may result in high concentrations of vapors which are potentially flammable, explosive, or toxic, and in loss of fluid. Dangerous explosions, fires, and other hazards can result when using the wrong Hose for such applications. The system designer must take into account the fact that this permeation will take place and must not use Hose if this permeation could be hazardous. The system designer

must take into account all legal, government, insurance, or any other special regulations which govern the use of fuels and refrigerants. Never use a Hose even though the fluid compatibility is acceptable without considering the potential hazardous effects that can result from permeation through the Hose Assembly.

Permeation of moisture from outside the Hose to inside the Hose will also occur in Hose assemblies, regardless of internal pressure. If this moisture permeation would have detrimental effects (particularly, but not limited to refrigeration and air conditioning systems), incorporation of sufficient drying capacity in the system or other appropriate system safeguards should be selected and used.

**2.7 Size:** Transmission of power by means of pressurized fluid varies with pressure and rate of flow. The size of the components must be adequate to keep pressure losses to a minimum and avoid damage due to heat generation or excessive fluid velocity.

**2.8 Routing:** Attention must be given to optimum routing to minimize inherent problems (kinking or flow restriction due to Hose collapse, twisting of the Hose, proximity to hot objects or heat sources). For additional routing recommendations see SAE J1273 and ISO 17165-2. Hose Assemblies have a finite life and if possible, should be installed in a manner that allows for ease of inspection and future replacement. Rubber Hose because of its relative short life, should not be used in residential and commercial buildings for HVAC (heating, ventilating and air conditioning) applications.

**2.9 Environment:** Care must be taken to insure that the Hose and Fittings are either compatible with or protected from the environment (that is, surrounding conditions) to which they are exposed. Environmental conditions including but not limited to ultraviolet radiation, sunlight, heat, ozone, moisture, water, salt water, chemicals and air pollutants can cause degradation and premature failure.

**2.10 Mechanical Loads:** External forces can significantly reduce Hose life or cause failure. Mechanical loads which must be considered include excessive flexing, twist, kinking, tensile or side loads, bend radius, and vibration. Use of swivel type Fittings or adapters may be required to insure no twist is put into the Hose. Unusual applications may require special testing prior to Hose selection.

**2.11 Physical Damage:** Care must be taken to protect Hose from wear, snagging, kinking, bending smaller than minimum bend radius and cutting, any of which can cause premature Hose failure. Any Hose that has been kinked or bent to a radius smaller than the minimum bend radius, and any Hose that has been cut or is cracked or is otherwise damaged should be removed and discarded.

**2.12 Proper End Fitting:** See instructions 3.2 through 3.5. These recommendations may be substantiated by testing to industry standards such as SAE J517 for hydraulic applications, or MIL-A-5070, AS1339, or AS3517 for Hoses from Parker’s Stratoflex Products Division for aerospace applications.

**2.13 Length:** When establishing a proper Hose length, motion absorption, Hose length changes due to pressure, and Hose and machine tolerances and movement must be considered.

**2.14 Specifications and Standards:** When selecting Hose and Fittings, government, industry, and Parker specifications and recommendations must be reviewed and followed as applicable.

**2.15 Hose Cleanliness:** Hose components may vary in cleanliness levels. Care must be taken to insure that the Hose Assembly selected has an adequate level of cleanliness for the application.

**2.16 Fire Resistant Fluids:** Some fire resistant fluids that are to be conveyed by Hose require use of the same type of Hose as used with petroleum base fluids. Some such fluids require a special Hose, while a few fluids will not work with any Hose at all. See instructions 2.5 and 1.5. The wrong Hose may fail after a very short service. In addition, all liquids but pure water may burn fiercely under certain conditions, and even pure water leakage may be hazardous.

**2.17 Radiant Heat:** Hose can be heated to destruction without contact by such nearby items as hot manifolds or molten metal. The same heat source may then initiate a fire. This can occur despite the presence of cool air around the Hose.

**2.18 Welding or Brazing:** When using a torch or arc welder in close proximity to hydraulic lines, the hydraulic lines should be removed or shielded



with appropriate fire resistant materials. Flame or weld spatter could burn through the Hose and possibly ignite escaping fluid resulting in a catastrophic failure. Heating of plated parts, including Hose Fittings and adapters, above 450°F (232°C) such as during welding, brazing or soldering may emit deadly gases.

**2.19 Atomic Radiation:** Atomic radiation affects all materials used in Hose assemblies. Since the long-term effects may be unknown, do not expose Hose assemblies to atomic radiation.

**2.20 Aerospace Applications:** The only Hose and Fittings that may be used for in-flight aerospace applications are those available from Parker's Stratoflex Products Division. Do not use any other Hose or Fittings for in-flight applications. Do not use any Hose or Fittings from Parker's Stratoflex Products Division with any other Hose or Fittings, unless expressly approved in writing by the engineering manager or chief engineer of Stratoflex Products Division and verified by the user's own testing and inspection to aerospace industry standards.

**2.21 Unlocking Couplings:** Ball locking Couplings or other Fittings with quick disconnect ability can unintentionally disconnect if they are dragged over obstructions, or if the sleeve or other disconnect member is bumped or moved enough to cause disconnect. Threaded Fittings should be considered where there is a potential for accidental uncoupling.

### 3.0 HOSE AND FITTINGS ASSEMBLY AND INSTALLATION INSTRUCTIONS

**3.1 Component Inspection:** Prior to assembly, a careful examination of the Hose and Fittings must be performed. All components must be checked for correct style, size, catalog number, and length. The Hose must be examined for cleanliness, obstructions, blisters, cover looseness, kinks, cracks, cuts or any other visible defects. Inspect the Fitting and sealing surfaces for burrs, nicks, corrosion or other imperfections. Do NOT use any component that displays any signs of nonconformance.

**3.2 Hose and Fitting Assembly:** Do not assemble a Parker Fitting on a Parker Hose that is not specifically listed by Parker for that Fitting, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division. Do not assemble a Parker Fitting on another manufacturer's Hose or a Parker Hose on another manufacturer's Fitting unless (i) the engineering manager or chief engineer of the appropriate Parker division approves the Assembly in writing or that combination is expressly approved in the appropriate Parker literature for the specific Parker product, and (ii) the user verifies the Assembly and the application through analysis and testing. For Parker Hose that does not specify a Parker Fitting, the user is solely responsible for the selection of the proper Fitting and Hose Assembly procedures. See instruction 1.4.

To prevent the possibility of problems such as leakage at the Fitting or system contamination, it is important to completely remove all debris from the cutting operation before installation of the Fittings. The Parker published instructions must be followed for assembling the Fittings on the Hose. These instructions are provided in the Parker Fitting catalog for the specific Parker Fitting being used, or by calling 1-800-CPARKER, or at [www.parker.com](http://www.parker.com).

**3.3 Related Accessories:** Do not crimp or swage any Parker Hose or Fitting with anything but the listed swage or crimp machine and dies in accordance with Parker published instructions. Do not crimp or swage another manufacturer's Fitting with a Parker crimp or swage die unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division.

**3.4 Parts:** Do not use any Parker Fitting part (including but not limited to socket, shell, nipple, or insert) except with the correct Parker mating parts, in accordance with Parker published instructions, unless authorized in writing by the engineering manager or chief engineer of the appropriate Parker division.

**3.5 Field Attachable/Permanent:** Do not reuse any field attachable Hose Fitting that has blown or pulled off a Hose. Do not reuse a Parker permanent Hose Fitting (crimped or swaged) or any part thereof. Complete Hose Assemblies may only be reused after proper inspection under section 4.0. Do not assemble Fittings to any previously used hydraulic Hose that was in service, for use in a fluid power application.

**3.6 Pre-Installation Inspection:** Prior to installation, a careful examination of the Hose Assembly must be performed. Inspect the Hose Assembly for any damage or defects. DO NOT use any Hose Assembly that displays any signs of nonconformance.

**3.7 Minimum Bend Radius:** Installation of a Hose at less than the minimum listed bend radius may significantly reduce the Hose life. Particular attention must be given to preclude sharp bending at the Hose to Fitting juncture. Any bending during installation at less than the minimum bend radius must be avoided. If any Hose is kinked during installation, the Hose must be discarded.

**3.8 Twist Angle and Orientation:** Hose Assembly installation must be such that relative motion of machine components does not produce twisting.

**3.9 Securement:** In many applications, it may be necessary to restrain, protect, or guide the Hose to protect it from damage by unnecessary flexing, pressure surges, and contact with other mechanical components. Care must be taken to insure such restraints do not introduce additional stress or wear points.

**3.10 Proper Connection of Ports:** Proper physical installation of the Hose Assembly requires a correctly installed port connection insuring that no twist or torque is transferred to the Hose when the Fittings are being tightened or otherwise during use.

**3.11 External Damage:** Proper installation is not complete without insuring that tensile loads, side loads, kinking, flattening, potential abrasion, thread damage or damage to sealing surfaces are corrected or eliminated. See instruction 2.10.

**3.12 System Checkout:** All air entrapment must be eliminated and the system pressurized to the maximum system pressure (at or below the Hose maximum working pressure) and checked for proper function and freedom from leaks. Personnel must stay out of potential hazardous areas while testing and using.

**3.13 Routing:** The Hose Assembly should be routed in such a manner so if a failure does occur, the escaping media will not cause personal injury or property damage. In addition, if fluid media comes in contact with hot surfaces, open flame or sparks, a fire or explosion may occur. See section 2.4.

**3.14 Ground Fault Equipment Protection Devices (GFEPDs): *WARNING!*** Fire and Shock Hazard. To minimize the danger of fire if the heating cable of a Multitube bundle is damaged or improperly installed, use a Ground Fault Equipment Protection Device. Electrical fault currents may be insufficient to trip a conventional circuit breaker.

For ground fault protection, the IEEE 515:1989 ([www.ansi.org](http://www.ansi.org)) standard for heating cables recommends the use of GFEPDs with a nominal 30 milliampere trip level for "piping systems in classified areas, those areas requiring a high degree of maintenance, or which may be exposed to physical abuse or corrosive atmospheres".

### 4.0 HOSE AND FITTING MAINTENANCE AND REPLACEMENT INSTRUCTIONS

4.1 Even with proper selection and installation, Hose life may be significantly reduced without a continuing maintenance program. The severity of the application, risk potential from a possible Hose failure, and experience with any Hose failures in the application or in similar applications should determine the frequency of the inspection and the replacement for the Products so that Products are replaced before any failure occurs. A maintenance program must be established and followed by the user and, at minimum, must include instructions 4.2 through 4.7.

**4.2 Visual Inspection Hose/Fitting:** Any of the following conditions require immediate shut down and replacement of the Hose Assembly:

- Fitting slippage on Hose;
- Damaged, cracked, cut or abraded cover (any reinforcement exposed);
- Hard, stiff, heat cracked, or charred Hose;
- Cracked, damaged, or badly corroded Fittings;
- Leaks at Fitting or in Hose;
- Kinked, crushed, flattened or twisted Hose; and
- Blistered, soft, degraded, or loose cover.

**4.3 Visual Inspection All Other:** The following items must be tightened, repaired, corrected or replaced as required:

- Leaking port conditions;
- Excess dirt buildup;
- Worn clamps, guards or shields; and
- System fluid level, fluid type, and any air entrapment.

**4.4 Functional Test:** Operate the system at maximum operating pressure and check for possible malfunctions and leaks. Personnel must avoid potential hazardous areas while testing and using the system. See section 2.2.

**4.5 Replacement Intervals:** Hose assemblies and elastomeric seals used on Hose Fittings and adapters will eventually age, harden, wear and deteriorate under thermal cycling and compression set. Hose Assemblies and elastomeric seals should be inspected and replaced at specific replacement intervals, based on previous service life, government or industry recommendations, or when failures could result in unacceptable downtime, damage, or injury risk. See section 1.2. Hose and Fittings may be subjected to internal mechanical and/or chemical wear from the conveying fluid and may fail without warning. The user must determine the product life under such circumstances by testing. Also see section 2.5.

**4.6 Hose Inspection and Failure:** Hydraulic power is accomplished by utilizing high pressure fluids to transfer energy and do work. Hoses, Fittings and Hose Assemblies all contribute to this by transmitting fluids at high pressures. Fluids under pressure can be dangerous and potentially lethal and, therefore, extreme caution must be exercised when working with fluids under pressure and handling the Hoses transporting the fluids. From time to time, Hose Assemblies will fail if they are not replaced at proper time intervals. Usually these failures are the result of some form of misapplication, abuse, wear or failure to perform proper maintenance. When Hoses fail, generally the high pressure fluids inside escape in a stream which may or may not be visible to the user. Under no circumstances should the user attempt to locate the leak by “feeling” with their hands or any other part of their body. High pressure fluids can and will penetrate the skin and cause severe tissue damage and possibly loss of limb. Even seemingly minor hydraulic fluid injection injuries must be treated immediately by a physician with knowledge of the tissue damaging properties of hydraulic fluid.

If a Hose failure occurs, immediately shut down the equipment and leave the area until pressure has been completely released from the Hose Assembly. Simply shutting down the hydraulic pump may or may not eliminate the pressure in the Hose Assembly. Many times check valves, etc., are employed in a system and can cause pressure to remain in a Hose Assembly even when pumps or equipment are not operating. Tiny holes in the Hose, commonly known as pinholes, can eject small, dangerously powerful but hard to see streams of hydraulic fluid. It may take several minutes or even hours for the pressure to be relieved so that the Hose Assembly may be examined safely. Once the pressure has been reduced to zero, the Hose Assembly may be taken off the equipment and examined. It must always be replaced if a failure has occurred. Never attempt to patch or repair a Hose Assembly that has failed. Consult the nearest Parker distributor or the appropriate Parker division for Hose Assembly replacement information.

Never touch or examine a failed Hose Assembly unless it is obvious that the Hose no longer contains fluid under pressure. The high pressure fluid is extremely dangerous and can cause serious and potentially fatal injury.

**4.7 Elastomeric seals:** Elastomeric seals will eventually age, harden, wear and deteriorate under thermal cycling and compression set. Elastomeric seals should be inspected and replaced.

**4.8 Refrigerant gases:** Special care should be taken when working with refrigeration systems. Sudden escape of refrigerant gases can cause blindness if the escaping gases contact the eye and can cause freezing or other severe injuries if it contacts any other portion of the body.

**4.9 Compressed natural gas (CNG):** Parker CNG Hose Assemblies should be tested after installation and before use, and at least on a monthly basis per ANSI/IAS NGV 4.2-1999; CSA 12.52-M99 Section 4.2 “Visual Inspection Hose/Fitting”. The recommended procedure is to pressurize the Hose and check for leaks and to visually inspect the Hose for damage. Caution: Matches, candles, open flame or other sources of ignition shall not be used for Hose inspection. Leak check solutions should be rinsed off after use.

## 5.0 HOSE STORAGE

**5.1 Age Control:** Hose and Hose Assemblies must be stored in a manner that facilitates age control and first-in and first-out usage based on manufacturing date of the Hose and Hose Assemblies. The shelf life of rubber Hose or Hose Assemblies that have passed visual inspection and a proof test is 10 years (40 quarters) from the date of manufacture. The shelf life of thermoplastic and polytetrafluoroethylene Hose or Hose Assemblies is considered to be unlimited.

**5.2 Storage:** Stored Hose and Hose Assemblies must not be subjected to damage that could reduce their expected service life and must be placed in a cool, dark and dry area with the ends capped. Stored Hose and Hose Assemblies must not be exposed to temperature extremes, ozone, oils, corrosive liquids or fumes, solvents, high humidity, rodents, insects, ultraviolet light, electromagnetic fields or radioactive materials.

# ENERPAC Warranty Policy

For those ENERPAC items sold as part of the Parker Parflex Division product offering, the following warranty applies.

ENERPAC products are warranted to be free of defects in materials and workmanship under normal use for as long as they are owned by the original purchaser, subject to the exclusions and limitations described below. This warranty does not cover

ordinary wear and tear, overloading, alterations, (including repairs or attempted repairs by parties other than ENERPAC or its authorized service representatives), improper fluid, use in a manner for which they are not intended or use which is contrary to instructions for the products.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IS IN LIEU OF ALL OTHER EXPRESS AND IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

The remedy of repair, replacement or refund is customer's exclusive remedy in the event of breach of this warranty.

SELLER SHALL NOT BE SUBJECT TO AND DISCLAIMS:

- (a) ANY OTHER OBLIGATIONS OR LIABILITIES ARISING OUT OF BREACH OF CONTRACT OR OF WARRANTY,
- (b) ANY OBLIGATIONS WHATSOEVER ARISING FROM TORT CLAIMS (INCLUDING NEGLIGENCE AND STRICT LIABILITY) OR ARISING UNDER THEORIES OR LAW WITH RESPECT TO PRODUCTS SOLD OR SERVICES RENDERED BY SELLER OR ANY UNDERTAKINGS, ACTS OR OMISSIONS RELATING THERETO, AND
- (c) ALL CONSEQUENTIAL, INCIDENTAL AND CONTINGENT DAMAGES WHATSOEVER.

ENERPAC's liability in all cases is limited to, and shall not exceed, the purchase price paid.

For the nearest authorized ENERPAC SERVICE CENTER, please call ENERPAC at 1-800-558-0530 or visit the ENERPAC web site at [www.Enerpac.com](http://www.Enerpac.com).

THIS WARRANTY IS LIMITED TO NEW PRODUCTS SOLD THROUGH ENERPAC AUTHORIZED DISTRIBUTORS, ORIGINAL EQUIPMENT MANUFACTURERS OR OTHER DESIGNATED CHANNELS OF DISTRIBUTION. NO AGENT, EMPLOYEE, OR OTHER REPRESENTATIVE OF ENERPAC HAS THE AUTHORITY TO IN ANY WAY CHANGE OR AMEND THIS WARRANTY.

Electronic products and components are warranted against defects in material and workmanship for a period of two years from the date of purchase.

The following items supplied with ENERPAC products are excluded from this warranty:

Components not manufactured by ENERPAC, including air motors, electric motors, gasoline engines, and diesel engines. Such items are warranted to the extent of the warranty provided by the manufacturers of such items.

If the customer believes a product is defective, the product must be delivered, or shipped freight prepaid, to the nearest ENERPAC Authorized Service Center. The customer should contact ENERPAC to locate and Authorized Service Center in the customer's area.

Products that do not conform to this warranty will be returned by ground transportation, freight prepaid.

# Offer of Sale

The items described in this document and other documents and descriptions provided by Parker Hannifin Corporation, its subsidiaries and its authorized distributors (“Seller”) are hereby offered for sale at prices to be established by Seller. This offer and its acceptance by any customer (“Buyer”) shall be governed by all of the following Terms and Conditions. Buyer’s order for any item described in its document, when communicated to Seller verbally, or in writing, shall constitute acceptance of this offer. All goods or work described will be referred to as “Products”.

1. **Terms and Conditions.** Seller’s willingness to offer Products, or accept an order for Products, to or from Buyer is expressly conditioned on Buyer’s assent to these Terms and Conditions and to the terms and conditions found on-line at [www.parker.com/saleterms/](http://www.parker.com/saleterms/). Seller objects to any contrary or additional term or condition of Buyer’s order or any other document issued by Buyer.

2. **Price Adjustments; Payments.** Prices stated on the reverse side or preceding pages of this document are valid for 30 days. After 30 days, Seller may change prices to reflect any increase in its costs resulting from state, federal or local legislation, price increases from its suppliers, or any change in the rate, charge, or classification of any carrier. The prices stated on the reverse or preceding pages of this document do not include any sales, use, or other taxes unless so stated specifically. Unless otherwise specified by Seller, all prices are F.O.B. Seller’s facility, and payment is due 30 days from the date of invoice. After 30 days, Buyer shall pay interest on any unpaid invoices at the rate of 1.5% per month or the maximum allowable rate under applicable law.

3. **Delivery Dates; Title and Risk; Shipment.** All delivery dates are approximate and Seller shall not be responsible for any damages resulting from any delay. Regardless of the manner of shipment, title to any products and risk of loss or damage shall pass to Buyer upon tender to the carrier at Seller’s facility (i.e., when it’s on the truck, it’s yours). Unless otherwise stated, Seller may exercise its judgment in choosing the carrier and means of delivery. No deferment of shipment at Buyers’ request beyond the respective dates indicated will be made except on terms that will indemnify, defend and hold Seller harmless against all loss and additional expense. Buyer shall be responsible for any additional shipping charges incurred by Seller due to Buyer’s changes in shipping, product specifications or in accordance with Section 13, herein.

4. **Warranty.** Seller warrants that the Products sold hereunder shall be free from defects in material or workmanship for a period of twelve months from the date of delivery to Buyer or 2,000 hours of normal use, whichever occurs first. This warranty is made only to Buyer and does not extend to anyone to whom Products are sold after purchased from Seller. The prices charged for Seller’s products are based upon the exclusive limited warranty stated above, and upon the following disclaimer: **DISCLAIMER OF WARRANTY:** THIS WARRANTY COMPRISES THE SOLE AND ENTIRE WARRANTY PERTAINING TO PRODUCTS PROVIDED HEREUNDER. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS AND IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

5. **Claims; Commencement of Actions.** Buyer shall promptly inspect all Products upon delivery. No claims for

shortages will be allowed unless reported to the Seller within 10 days of delivery. No other claims against Seller will be allowed unless asserted in writing within 60 days after delivery or, in the case of an alleged breach of warranty, within 30 days after the date within the warranty period on which the defect is or should have been discovered by Buyer. Any action based upon breach of this agreement or upon any other claim arising out of this sale (other than an action by Seller for any amount due to Seller from Buyer) must be commenced within thirteen months from the date of tender of delivery by Seller or, for a cause of action based upon an alleged breach of warranty, within thirteen months from the date within the warranty period on which the defect is or should have been discovered by Buyer.

6. **LIMITATION OF LIABILITY.** UPON NOTIFICATION, SELLER WILL, AT ITS OPTION, REPAIR OR REPLACE A DEFECTIVE PRODUCT, OR REFUND THE PURCHASE PRICE. IN NO EVENT SHALL SELLER BE LIABLE TO BUYER FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF, OR AS THE RESULT OF, THE SALE, DELIVERY, NON-DELIVERY, SERVICING, USE OR LOSS OF USE OF THE PRODUCTS OR ANY PART THEREOF, OR FOR ANY CHARGES OR EXPENSES OF ANY NATURE INCURRED WITHOUT SELLER’S WRITTEN CONSENT, EVEN IF SELLER HAS BEEN NEGLIGENT, WHETHER IN CONTRACT, TORT OR OTHER LEGAL THEORY. IN NO EVENT SHALL SELLER’S LIABILITY UNDER ANY CLAIM MADE BY BUYER EXCEED THE PURCHASE PRICE OF THE PRODUCTS.

7. **Contingencies.** Seller shall not be liable for any default or delay in performance if caused by circumstances beyond the reasonable control of Seller.

8. **User Responsibility.** The user, through its own analysis and testing, is solely responsible for making the final selection of the system and Product and assuring that all performance, endurance, maintenance, safety and warning requirements of the application are met. The user must analyze all aspects of the application and follow applicable industry standards and Product information. If Seller provides Product or system options, the user is responsible for determining that such data and specifications are suitable and sufficient for all applications and reasonably foreseeable uses of the Products or systems.

9. **Loss to Buyer’s Property.** Any designs, tools, patterns, materials, drawings, confidential information or equipment furnished by Buyer or any other items which become Buyer’s property, may be considered obsolete and may be destroyed by Seller after two consecutive years have elapsed without Buyer placing an order for the items which are manufactured using such property. Seller shall not be responsible for any loss or damage to such property while it is in Seller’s possession or control.

For detailed ordering information, please consult price list or contact Parflex® Division.



**10. Special Tooling.** A tooling charge may be imposed for any special tooling, including without limitation, dies, fixtures, molds and patterns, acquired to manufacture Products. Such special tooling shall be and remain Seller's property notwithstanding payment of any charges by Buyer. In no event will Buyer acquire any interest in apparatus belonging to Seller which is utilized in the manufacture of the Products, even if such apparatus has been specially converted or adapted for such manufacture and notwithstanding any charges paid by Buyer. Unless otherwise agreed, Seller shall have the right to alter, discard or otherwise dispose of any special tooling or other property in its sole discretion at any time.

**11. Buyer's Obligation; Rights of Seller.** To secure payment of all sums due or otherwise, Seller shall retain a security interest in the goods delivered and this agreement shall be deemed a Security Agreement under the Uniform Commercial Code. Buyer authorizes Seller as its attorney to execute and file on Buyer's behalf all documents Seller deems necessary to perfect its security interest. Seller shall have a security interest in, and lien upon, any property of Buyer in Seller's possession as security for the payment of any amounts owed to Seller by Buyer.

**12. Improper use and Indemnity.** Buyer shall indemnify, defend, and hold Seller harmless from any claim, liability, damages, lawsuits, and costs (including attorney fees), whether for personal injury, property damage, patent, trademark or copyright infringement or any other claim, brought by or incurred by Buyer, Buyer's employees, or any other person, arising out of: (a) improper selection, improper application or other misuse of Products purchased by Buyer from Seller; (b) any act or omission, negligent or otherwise, of Buyer; (c) Seller's use of patterns, plans, drawings, or specifications furnished by Buyer to manufacture Product; or (d) Buyer's failure to comply with these terms and conditions. Seller shall not indemnify Buyer under any circumstance except as otherwise provided.

**13. Cancellations and Changes.** Orders shall not be subject to cancellation or change by Buyer for any reason, except with Seller's written consent and upon terms that will indemnify, defend and hold Seller harmless against all direct, incidental and consequential loss or damage. Seller may change product features, specifications, designs and availability with notice to Buyer.

**14. Limitation on Assignment.** Buyer may not assign its rights or obligations under this agreement without the prior written consent of Seller.

**15. Entire Agreement.** This agreement contains the entire agreement between the Buyer and Seller and constitutes the final, complete and exclusive expression of the terms of the agreement. All prior or contemporaneous written or oral agreements or negotiations with respect to the subject matter are herein merged.

**16. Waiver and Severability.** Failure to enforce any provision of this agreement will not waive that provision nor will any such failure prejudice Seller's right to enforce that provision in the future. Invalidation of any provision of this agreement by legislation or other rule of law shall not invalidate any other provision herein. The remaining provisions of this agreement will remain in full force and effect.

**17. Termination.** This agreement may be terminated by Seller for any reason and at any time by giving Buyer thirty (30) days written notice of termination. In addition, Seller

may by written notice immediately terminate this agreement for the following: (a) Buyer commits a breach of any provision of this agreement (b) the appointment of a trustee, receiver or custodian for all or any part of Buyer's property (c) the filing of a petition for relief in bankruptcy of the other Party on its own behalf, or by a third party (d) an assignment for the benefit of creditors, or (e) the dissolution or liquidation of the Buyer.

**18. Governing Law.** This agreement and the sale and delivery of all Products hereunder shall be deemed to have taken place in and shall be governed and construed in accordance with the laws of the State of Ohio, as applicable to contracts executed and wholly performed therein and without regard to conflicts of laws principles. Buyer irrevocably agrees and consents to the exclusive jurisdiction and venue of the courts of Cuyahoga County, Ohio with respect to any dispute, controversy or claim arising out of or relating to this agreement. Disputes between the parties shall not be settled by arbitration unless, after a dispute has arisen, both parties expressly agree in writing to arbitrate the dispute.

**19. Indemnity for Infringement of Intellectual**

**Property Rights.** Seller shall have no liability for infringement of any patents, trademarks, copyrights, trade dress, trade secrets or similar rights except as provided in this Section. Seller will defend and indemnify Buyer against allegations of infringement of U.S. patents, U.S. trademarks, copyrights, trade dress and trade secrets ("Intellectual Property Rights"). Seller will defend at its expense and will pay the cost of any settlement or damages awarded in an action brought against Buyer based on an allegation that a Product sold pursuant to this Agreement infringes the Intellectual Property Rights of a third party. Seller's obligation to defend and indemnify Buyer is contingent on Buyer notifying Seller within ten (10) days after Buyer becomes aware of such allegations of infringement, and Seller having sole control over the defense of any allegations or actions including all negotiations for settlement or compromise. If a Product is subject to a claim that it infringes the Intellectual Property Rights of a third party, Seller may, at its sole expense and option, procure for Buyer the right to continue using the Product, replace or modify the Product so as to make it noninfringing, or offer to accept return of the Product and return the purchase price less a reasonable allowance for depreciation. Notwithstanding the foregoing, Seller shall have no liability for claims of infringement based on information provided by Buyer, or directed to Products delivered hereunder for which the designs are specified in whole or part by Buyer, or infringements resulting from the modification, combination or use in a system of any Product sold hereunder. The foregoing provisions of this Section shall constitute Seller's sole and exclusive liability and Buyer's sole and exclusive remedy for infringement of Intellectual Property Rights.

**20. Taxes.** Unless otherwise indicated, all prices and charges are exclusive of excise, sales, use, property, occupational or like taxes which may be imposed by any taxing authority upon the manufacture, sale or delivery of Products.

**21. Equal Opportunity Clause.** For the performance of government contracts and where dollar value of the Products exceed \$10,000, the equal employment opportunity clauses in Executive Order 11246, VEVRAA, and 41 C.F.R. §§ 60-1.4(a), 60-741.5(a), and 60-250.4, are hereby incorporated.

01/09

# Part Number Index

Part Number	Page	Part Number	Page	Part Number	Page
015301.....	F-14	10693N.....	E-67	13957.....	E-39
015302.....	F-10	10694.....	E-70	13958.....	E-22
015303.....	F-10	10695.....	E-70	13958H.....	E-43
015304.....	F-10	106CY.....	E-82	13991N.....	E-57
015305.....	F-10	106HY.....	E-91	13993N.....	E-68
015306.....	F-8, F-10	106LV.....	E-104	139CY.....	E-83
015307.....	F-8	106SF.....	E-85	139HY.....	E-97
015308.....	F-8, F-10	10755.....	E-18	13D55.....	E-35
015309.....	F-8	10758.....	E-18	13D58.....	E-35
015310.....	F-10	10791N.....	E-55	13DHY.....	E-100
015411.....	F-10 : F-11	107HY.....	E-92	13E55.....	E-15
015412.....	F-10 : F-11	10855.....	E-18	13E58.....	E-15
015413.....	F-10 : F-11	10858.....	E-18	14155.....	E-23
015414.....	F-10 : F-11	10891N.....	E-55	14158.....	E-23
015415.....	F-10 : F-11	108HY.....	E-92	14191N.....	E-57
025349.....	F-8, F-11	108MS.....	E-105	141HY.....	E-97
025399.....	F-11, F-14	10GHY.....	E-93	14K93N.....	E-68
045234.....	F-9	10LHY.....	E-93	15555.....	E-24
090.....	E-51	110-(PVDF).....	B-82 : B-83	15558.....	E-24
101-(PTFE).....	B-56 : B-57	111-(PVDF).....	B-84 : B-85	16191N.....	E-58
10155.....	E-13	11155.....	E-19	16755.....	E-24
10157.....	E-38	11158.....	E-19	16758.....	E-24
10158.....	E-13	11192.....	E-65	16791N.....	E-58
10158H.....	E-42	111HY.....	E-94	16792.....	E-66
10191N.....	E-53	1120-.....	D-4	167HY.....	E-98
10193N.....	E-67	11255.....	E-19	16955.....	E-25
101CY.....	E-82	11258.....	E-19	16958.....	E-25
101HY.....	E-88	11355.....	E-20	16991N.....	E-59
101SF.....	E-85	11357.....	E-38	16992.....	E-66
101SQ.....	E-107	11358.....	E-20	169HY.....	E-98
10255.....	E-14	113CY.....	E-83	17791N.....	E-59
10258.....	E-14	113HY.....	E-94	177HY.....	E-98
102CY.....	E-82	11D55.....	E-34	17991N.....	E-59
102HY.....	E-89	11D58.....	E-34	179HY.....	E-99
103-(FEP).....	B-70 : B-71	11L55.....	E-20	19255.....	E-35
10355.....	E-14	11L58.....	E-20	19258.....	E-35
10358.....	E-14	11LHY.....	E-95	19291N.....	E-64
1035A.....	A-50	12891N.....	E-55	193HY.....	E-99
1035HT.....	A-51	12892.....	E-65	1AL55.....	E-29
10391N.....	E-53	128HY.....	E-95	1AL58.....	E-29
103HY.....	E-89	129HY.....	E-96	1AL91N.....	E-60
104-(PFA).....	B-78 : B-79	1320.....	D-5	1B155.....	E-36
10455.....	E-15	13491N.....	E-56	1B158.....	E-36
10458.....	E-15	134HY.....	E-96	1B255.....	E-36
10555.....	E-16	134MS.....	E-105	1B258.....	E-36
10558.....	E-16	13755.....	E-21	1B291N.....	E-64
105HY.....	E-90	13754.....	E-10	1C655.....	E-32
10654.....	E-9	13954.....	E-10	1C658.....	E-32
10655.....	E-17	13757.....	E-39	1C955.....	E-32
10657.....	E-38	13758.....	E-21	1C958.....	E-32
10658.....	E-17	13758H.....	E-42	1D055.....	E-33
10658H.....	E-42	13791N.....	E-56	1D058.....	E-33
10691N.....	E-54	13793N.....	E-68	1D0HY.....	E-99
10691NRD.....	E-54	137HY.....	E-96	1D255.....	E-33
		13955.....	E-22	1D258.....	E-33

For detailed ordering information, please consult price list or contact Parflex® Division.



A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

Index

# Part Number Index (cont.)

Part Number	Page	Part Number	Page	Part Number	Page
1D955	E-34	1L955	E-23	510A	A-34
1D958	E-34	1L958	E-23	510C	A-35
1D9HY	E-100	1LMCY	E-84	515H	A-37
1FN91N	E-60	1MU55	E-30	518C	A-36
1FU55	E-30	1MU58	E-30	520N	A-38
1FU58	E-30	1P691N	E-60	526BA	A-39
1G155	E-31	1Q191N	E-63	528N	A-38, A-64
1G158	E-31	1TFMS	E-106	527BA	A-40
1G255	E-31	1TU55	E-28	538DM	A-41
1G258	E-31	1TU58	E-28	53DM	A-41
1GJHY	E-100	1TU91N	E-63	540N	A-42
1GKCY	E-83	1UT55	E-29	540P	A-43
1GU55	E-30	1UT58	E-29	548N	A-64
1GU58	E-30	1WU54	E-11	55LT	A-44
1HUSQ	E-107	1WW54	E-10	55AG	F-22, F-24
1J055	E-26	1WY54	E-11	55SG	F-22, F-24
1J058	E-26			55SSG	F-22
1J0HY	E-103	20090	E-51	5PSG	F-22
1J155	E-27	201-(Metric FTFE)	B-58 : B-59	56DH	A-45
1J158	E-27	20151	E-5	560	A-30
1J158H	E-44	20190	E-46	563	A-31
1J191N	E-61	201BA	E-79	568DH	A-45
1J1HY	E-101	201BU	E-80	573X	A-46
1J754	E-9	203-(Metric FEP)	B-72 : B-73	575X	A-47
1J755	E-27	20351	E-6	580661	F-18
1J757	E-39	204-(Metric PFA)	B-80 : B-81	580N	A-48
1J758	E-27	20651	E-6	588N	A-48
1J758H	E-44	20690	E-46	590	A-32
1J791N	E-61	206BA	E-79	593	A-33
1J793N	E-69	206BU	E-80	5CNG	A-53
1J7HY	E-101	20851	E-7	5CNG/CNGLT	F-21
1J954	E-9	20890	E-47		
1J955	E-28	208MS	E-106	6 CTX-S	F-10
1J957	E-40	213BU	E-80	6-2 CTX-S	F-11
1J958	E-28	22890	E-47	6-6 CTX-S	F-10 : F-11
1J958H	E-44	23490	E-47	60 HAB	E-51
1J991N	E-62	23790	E-48	61 HAB	E-51
1J993N	E-69	23951	E-7	631075-PFD	F-18
1J9CY	E-84	23990	E-48	631076	F-18
1J9HY	E-102	24398	F-18	631140	F-18
1JC54	E-8	2613	F-23	68NTA	D-12
1JC55	E-26	2625	F-23	685RA	E-11
1JC57	E-40	26190	E-49		
1JC58	E-26	26790	E-49	731512-Blue, Red	D-8
1JC58H	E-43	26990	E-50	731513-Blue, Red	D-8
1JC91N	E-62	2740	F-23	731516	D-8
1JC93N	E-69	27790	E-50	731522	D-8
1JCCY	E-84	2799	F-23	731611-Blue, Red	D-8
1JCHY	E-102	27990	E-50	731612-Blue, Red	D-8
1JS55	E-25	2TFMS	E-106	741526	D-8
1JS58	E-25			741590-Blue, Red	D-8
1JS58H	E-43	316-PFD	F-19	751597	D-8
1JBSF	E-86	332T-115V-PFD	F-18	751634	D-10
1JSHY	E-103	3PSG	F-22	751641	D-8
1JSSF	E-86			751655	D-8



For detailed ordering information, please consult price list or contact Parflex® Division.



# Part Number Index (cont.)

Part Number	Page	Part Number	Page	Part Number	Page
751656-Blk	D-8	955B	A-74	M8	A-27
751657	D-11	A0	C-8	MBS-S	E-74
751658-Blue, Red	D-11	AS-Y	F-23	MC	C-10
751659	D-11	AHUF	C-17	MCB	C-18
751660-Blue, Red	D-11	AUFS	C-15	ME	C-10
801048	D-9	B9	A-52	MG	F-23
801595	D-9	CL-S	E-73	MIL-S	E-74
801632	D-9	CNG	A-53	ML	C-11
80C-061-PFD	F-12	CNGG	F-21	MLB	C-19
80C-0DR-PFD	F-20	D6	A-22	MP-S	E-75
80C-R01-PFD	F-12, F-20	E/EB	B-8 : B-10	MSAN-S	E-78
80C-SDR	F-20	E-S	E-73	MSH	A-55
811537	D-12	FBS-S	E-73	MSXL	A-56
81C-R01-PFD	F-16	FC	C-11	N	B-16 : B-19
822011	F-10 : F-11	FIL-S	E-74	NB	B-16 : B-19
822012	F-10 : F-11	FJX-S	E-76	NBR	B-22 : B-23
822031	F-10 : F-11	FL	C-11	NN	B-16 : B-19
82C-061L-PFD	F-12	FN	C-12	NNR	B-22 : B-23
82C-OAP-PFD	F-15	FORFS-S	E-76	NR	B-22 : B-23
82C-OEP-PFD	F-15	FP-S	E-75	NTNA	B-24 : B-25
82C-OHP-PFD	F-14	FR	C-12	PAT	B-20 : B-21
82C-KKB-PFD	F-12	FS	C-9	PC300	E-72
82C-R01-PFD	F-12, F-20	FS-F	F-23	PCW/PCB	A-80
83C-081-PFD	F-13	H580N	A-48	PCWV/PCBV	A-82
83C-0DR-PFD	F-20	H6	A-23	PCWV-FS/PCBV-FS	A-84
83FR	A-49	HBR	F-21	PEFR	B-12
85C-061L-PFD	F-12	HDPE	B-14 : B-15	PF ANSI Flange	E-77
85C-OHP-PFD	F-14	HFS	A-24	PFT	D-6
85C-OEP-PFD	F-15	HFS2	A-25	PLCF-S	E-76
85C-KKB-PFD	F-12	HJK	A-29	PP	B-26 : B-27
85C-R01-PFD	F-12, F-20	HLB	A-54	PPB	B-26 : B-27
881540-PFD	F-19	HS1.3FEP	B-74 : B-75	PSG	F-22 : F-23
88C-082-PFD	F-13	HS1.6FEP	B-76 : B-77	PTC	F-19
89C-061-PFD	F-13	HS2TFI	B-63	PTC-001-RB	F-19
8PC-030-PFD	F-16	HS2TFL	B-67	PTH	A-57
8PC-00P-PFD	F-16	HS2TFL, Fractional	B-62	PV (guard)	F21, F-23
8WC-00P-PFD	F-16	HS2TFS, AWG	B-64	PV (tubing)	B-39 : B-41
919	A-65	HS2TFS, Fractional	B-62	R6	A-26
919B	A-65	HS2TFS, Fractional	B-62	RC300	E-72
919J	A-66	HS2TFT, AWG	B-66	RCTW/RCTB	A-85
919U	A-67	HS2TFT, Fractional	B-62	S30/S30B	A-75
929	A-68	HS4TFI	B-68	S4	A-58
929B	A-68	HTB	A-28	S40/S40B	A-76
929BJ	A-69	HTC	F-19	S5	A-59
939	A-70	HTFL	D-7	S6	A-60
939B	A-70	HU	B-34 : B-35	S9	A-61
943B	A-71	HUFR	B-32 : B-33	SAN-S	E-78
944B	A-72	HUM	B-36 : B-37	SB	C-20
94C-080-PFD	F-6 : F-7	M8	A-27	SBF300	E-72
94C-001-PFD	F-6	MBS-S	E-74	SBFW/SBFB	A-78
94C-002-PFD	F-7	MC	C-10	SC300	E-72
94C-MKS	F-9	MCB	C-18		
950B	A-73	ME	C-10		

For detailed ordering information, please consult price list or contact Parflex® Division.



A  
Hose

B  
Tubing

C  
Coiled Air Hose  
& Fittings

D  
Transportation

E  
Fittings

F  
Tooling, Equipment  
& Accessories

Index

# Part Number Index (cont.)

Part Number	Page	Part Number	Page	Part Number	Page
SCW/SCB.....	A-79				
SCWV/SCBV.....	A-81				
SCWV-FS/SCBV-FS.....	A-83				
SFR-S.....	E-77				
SG.....	C-13, F-22				
SIL300.....	E-72				
SLH.....	A-62				
SQ-101-sw.....	F-17				
SQ Mender.....	F-17				
ST300.....	E-72				
ST301.....	E-72				
STW/STB.....	A-77				
TFB.....	B-60 : B-61				
TFH, AWG.....	B-52				
TFL, AWG.....	B-55				
TFL, Fractional.....	B-48				
TFS, AWG.....	B-53				
TFS, Fractional.....	B-48				
TFT, AWG.....	B-54				
TFT, Fractional.....	B-48				
TH11-1-PFD.....	F-19				
TS.....	C-13				
TUBE-S.....	E-77				
U.....	B-28 : 29				
UC.....	C-12				
UM.....	B-30 : B-31				
UFS.....	C-16				
VBL.....	F-17				
VBS.....	F-17				
XDH.....	A-63				



# Key Word Index

Keyword	Page	Keyword	Page	Keyword	Page
1.3/1 Heat Shrink .....	B-74	eXtreme Duty .....	A-63	Non-Conductive Hose .....	A-36, A-38, A-41, A-45, A-48, A-49, A-51
1.67/1 Heat Shrink .....	B-76	Fast Response Hose.....	A-46, A-47	NoMar Fast-Stor Assy .....	C-14, C-17
2 : 1 Heat Shrink.....	B-62 : B-67	Fast-Stor Air Hose.....	C-8 : C-9, C-14 : C-19	NoMar Fast-Stor Coils.....	C-16
4 : 1 Heat Shrink.....	B-68	Fast-Stor .....		NoMar Fast-Stor Fittings.....	C-18 : C-19
51 Series .....	E-5	Fittings .....	C-10 : C-14, C-19	Nylon Air Brake Tubing.....	D-4
54 Series .....	E-8	FEP Heat Shrink .....	B-74 : B-77	Nylon Tubing .....	B-16 : B-25
55 Series .....	E-12	FEP Tubing.....	B-70 : B-73		
57 Series .....	E-37	Field Att. Fitting.....	E-2	PAGE Fittings .....	E-71 : E-78
58 Series .....	E-12	Fifth Wheel Slider.....	D-12	PAGE-flex SBF .....	A-78
58H Series.....	E-41	Firescreen.....	A-24, A-25	Parkrimp Dies .....	F-20
90 Series .....	E-45	Fire Sleeve.....	F-23	Parkrimp 1.....	F-12
91N/91 Series.....	E-52	Flange .....	E-60, E-68, E-77, E-78	Parkrimp 2.....	F-13
92 Series .....	E-65	Flange Retainer .....	E-77	Partek Sleeve.....	F-23
93N Series.....	E-67	Flame Resistant .....		PFA Tubing.....	B-78 : B-81
94 Series .....	E-70	Tubing .....	B-12, B-42 : B-85	PHastkrimp .....	F-13
95 Series .....	E-70	Flare-Seal Hose .....	A-83, A-84	Polyethylene Tubing .....	B-8 : B-15
Air Brake Tubing .....	D-4 : D-5	Flex Tubing .....	B-82, B-83	Polypropylene Tubing .....	B-26 : B-27
Air Hose.....	C-4 : C-21	Fluoropolymer Tubing.....	B-42 : B-85	Polyurethane Tubing .....	B-28 : B-37
A-Lok Fitting .....	E-29, E-60, E-76 : E-77			Power Cleaning Hose .....	A-50, A-51
Abrasion King .....	A-26	Gates Conversion Kit.....	F-16	Predator .....	A-58 : A-62
Adapters.....	E-11	Guards.....	F-21 : F-25	PTFE Heat Shrink.....	B-62 : B-69
Anti-Kink Casing .....	F-23			PTFE Hose .....	A-65 : A-85
Armor Guard .....	F-22, F-24	Harnesses.....	D-13	PTFE Tubing.....	B-48 : B-59
AWG Tubing .....	B-50 : B-55	Heat Shrinkable .....		Pumps (Crimpers).....	F-14 : F-15
		Tubing .....	B-62 : B-69, B-74 : B-77	Pure Air Tubing .....	B-20
BA Series.....	E-79	Heavy Wall .....		PVDF Tubing .....	B-82 : B-85
Beading .....	B-60	Hose .....	A-68, A-76, A-81, A-82		
Bend Restrictor .....	F-21	High Density Tubing .....	B-14	Quantum Tubing .....	D-5
Brakcoil .....	D-8	High Pressure Hose .A-26:A-29,A-32, A-38:A-40, .....	A-45, A-47, A-48, A-53, A-63, A-71 : A74	Rapid Assy Fitting .....	E-10 : E-11
Breathing Air Hose .....	A-39, A-40	Highjack .....	A-29	Refrigerant Hose .....	A-34
BU Series.....	E-80	Hose Cutter.....	F-18 : F-19	Replacement Parts (F.A. Fitting) .....	E-51
Bundles .....	D-13	Hose Guard.....	F-21 : F-25	Replacement Parts (Minikrimp).....	F-8
		HY Series.....	E-87	Rubber Covered Hose .....	A-85
Clear Vinyl Hose Guard.....	F-21, F-23	Hybrid Hose .....	A-22, A-24 : A-25, .....		
Clear Vinyl Tubing .....	B-39 : B-41	.....	A-27 : A-29	SCR Hose.....	D-14 : D-15
Collars .....	E-72	Hydraulic Press Kit.....	F-16	Seal-Lok Fittings.....	E-8, E-9, E-25 : E-28, E-39, ..
Crimp Fitting.....	E-2			..	E-40, E-43, E-44, E-61, E-62, E-69, E-76, E-77, ..
Crimpers.....	F-2	I-Line Fitting .....	E-74	.....	E-84, E-86, E-101 : E-103
Conversion Kits.....	F-16	Instrument Grade Tubing .....	B-8 : B-11	Sewer Hose .....	A-58 : A-62
Convuluted Hose.....	A-70, A-79 : A-84	Jackline Hose .....	A-29	SF Series .....	E-85
Cut-off Tools .....	F-18 : F-19			Sleeve .....	F-23
CY Series .....	E-81	Karrykrimp.....	F-12	SliderCoil .....	D-11
		Karrykrimp 2.....	F-12	Spaghetti Tubing .....	B-50 : B-55
Die Racks .....	F-20	Karrykut.....	F-18	Spring, External & Internal .....	F-23
Dies.....	F-20			Spring Guard .....	F-21 : F-26
Diesel Fuel Tubing.....	D-6, D-7	Lateral Cleaning.....	A-58, A-59	SQ Series.....	E-107
Duo-Coil .....	D-9	LV Series.....	E-104	Super-Flex Tubing .....	B-84 : B-85
DollyCoil .....	D-10			Superbraid.....	C-20 : C-21
Duraflex.....	A-64	Marine Hose .....	A-55 : A-57	Superkrimp.....	F-13
DuraGard .....	A-49	Microweld Tubing .....	B-32 : B-33	Swager .....	F-17
Duramax.....	A-41	Minikrimp .....	F-6, F-7		
E-Z Flex .....	A-27	Mounts .....	F-8	Table Mount.....	F-8
Electrical Insulation.....	B-43	MS Series.....	E-105		
Eliminator .....	A-28				

For detailed ordering information, please consult price list or contact Parflex® Division.

# Key Word Index (cont.)

Keyword	Page	Keyword	Page	Keyword	Page
<b>Technical Data</b>		<b>TOOLING</b>			
<b>AIR HOSE</b>		Crimp Specifications,			
Air Hose Size Selection .....	C-5	Superkrimp.....	G-30 : G-32		
Fast-Stor, Measuring Bulk Hose ....	C-6 : C-7	Parkrimp 2.....	G-30 : G-32		
Fast-Stor, How To Assemble .....	C-13	Karrykrimp 2.....	G-33 : G-35		
		Phastkrimp .....	G-33 : G-35		
		Karrykrimp.....	G-36 : G-38		
		Parkrimp 1.....	G-36 : G-38		
<b>FITTINGS</b>		Minikrimp .....	G-39 : G-40		
Standard Fitting Configurations by		Minikrimp Assembly			
Connection & End Code .....	E-4	Detail.....	F-10 : F-11		
Ferrul-Fix Installation .....	G-29	Swage Specification, (Sewer Hose) .....	G-41		
Fitting Nomenclature.....	E-3				
Media to Fitting &		<b>TUBING</b>			
Seal Compatibility .....	G-44 : G-45	Compatibility Chart for Fittings.....	B-5		
Metals Corrosion Scale .....	G-49	Fluoropolymer Quick Reference.....	B-44		
Nomar Fast-Stor Assy Instruction.....	C-19	Fluoropolymer Chemical Resistance.....	B-44		
O-Ring Material Selection Guide .....	G-48	Fluoropolymer Property Comparison ....	B-45		
		Fluoropolymer Nomenclature ....	B-46 : B-47		
<b>HOSE</b>		Media to Plastic Tubing			
Die Selection /Crimp/Swage .....	G-30 : G-41	Material Guide .....	G-55 : G-57		
Hose Assembly & Crimping .....	G-10 : G-26	Metal Tube & Fitting			
Hose Assembly Part Number.....	12	Material Guide .....	G-46 : G-47		
Hose Construction/Specifications		Pressure Ranges.....	B-7		
PSI.....	A-10 : A-13				
Hose Construction/Specifications		Thermoplastic Hose .....	A-22 : A-64		
MPa.....	A-14 : A-17	True-Bore Hose.....	A-77		
Hose Diameter Selection.....	G-4	Tube Cutter .....	F-19		
Hose Fitting Insertion Values .....	G-42				
Hose Fitting Thread Guide .....	G-43	Ultra-Lite Superbraid .....	C-20 : C-21		
Hose Permeation Data .....	G-8	Ultrapure Tubing .....	B-20 : B-21		
Hose Nomenclature		Ultraviolet Light Resistant			
Thermoplastic Hose .....	A-18	Tubing .....	B-8 : B-11		
Hose Nomenclature		Vise Blocks.....	F-17		
Parflex PTFE Hose.....	A-19	Vise Mount.....	F-8		
Hose Nomenclature		Vinyl Tubing .....	B-39 : B-41		
Parflex PAGE Hose .....	A-20 : A-21	Weatherhead Conversion Kit .....	F-16		
Hose Selection, Inst. & Mtn. ....	G-9				
Hose, Volumetric Expansion .....	G-6 : G- 7				
Media to Hose					
Material Compatibility .....	G-51 : G-54				
Stamped Form .....	11				
Swage Instructions (Sewer Hose) ...	G-24 : G-26				
Twin/Multi-Line Separation .....	G-27				
Understanding Parflex Hose .....	A-7				
<b>OTHER</b>					
Government/Agency Specifications .....	G-59				
Materials to Parflex Part Number.....	G-50				
Metric Conversion Chart .....	G-58				



# Parker's Motion & Control Product Groups

**At Parker, we're guided by a relentless drive to help our customers become more productive and achieve higher levels of profitability by engineering the best systems for their requirements. It means looking at customer applications from many angles to find new ways to create value. Whatever the motion and control technology need, Parker has the experience, breadth of product and global reach to consistently deliver. No company knows more about motion and control technology than Parker. For further info call 1 800 C-Parker (1 800 272 7537).**



## **Aerospace**

### **Key Markets**

Aftermarket services  
Commercial transports  
Engines  
General & business aviation  
Helicopters  
Launch vehicles  
Military aircraft  
Missiles  
Power generation  
Regional transports  
Unmanned aerial vehicles

### **Key Products**

Control systems & actuation products  
Engine systems & components  
Fluid conveyance systems & components  
Fluid metering, delivery & atomization devices  
Fuel systems & components  
Fuel tank inerting systems  
Hydraulic systems & components  
Thermal management  
Wheels & brakes



## **Automation**

### **Key Markets**

Alternative energy  
Conveyor & material handling  
Factory automation  
Food & beverage  
Life sciences & medical  
Machine tools  
Packaging machinery  
Paper machinery  
Plastics machinery  
Primary metals  
Safety & security  
Semiconductor & electronics  
Transportation & automotive

### **Key Products**

AC/DC drives & systems  
Air preparation  
Electric actuators, gantry robots & slides  
Human machine interfaces  
Inverters  
Manifolds  
Miniature fluidics  
Pneumatic actuators & grippers  
Pneumatic valves & controls  
Rotary actuators  
Stepper motors, servo motors, drives & controls  
Structural extrusions  
Vacuum generators, cups & sensors



## **Climate & Industrial Controls**

### **Key Markets**

Agriculture  
Air conditioning  
Construction Machinery  
Food & beverage  
Industrial machinery  
Life sciences  
Oil & gas  
Precision cooling  
Process  
Refrigeration  
Transportation

### **Key Products**

Accumulators  
Advanced actuators  
CO<sub>2</sub> controls  
Electronic controllers  
Filter driers  
Hand shut-off valves  
Heat exchangers  
Hose & fittings  
Pressure regulating valves  
Refrigerant distributors  
Safety relief valves  
Smart pumps  
Solenoid valves  
Thermostatic expansion valves



## **Filtration**

### **Key Markets**

Aerospace  
Food & beverage  
Industrial plant & equipment  
Life sciences  
Marine  
Mobile equipment  
Oil & gas  
Power generation & renewable energy  
Process  
Transportation  
Water Purification

### **Key Products**

Analytical gas generators  
Compressed air filters & dryers  
Engine air, coolant, fuel & oil filtration systems  
Fluid condition monitoring systems  
Hydraulic & lubrication filters  
Hydrogen, nitrogen & zero air generators  
Instrumentation filters  
Membrane & fiber filters  
Microfiltration  
Sterile air filtration  
Water desalination & purification filters & systems



## **Fluid Connectors**

### **Key Markets**

Aerial lift  
Agriculture  
Bulk chemical handling  
Construction machinery  
Food & beverage  
Fuel & gas delivery  
Industrial machinery  
Life sciences  
Marine  
Mining  
Mobile  
Oil & gas  
Renewable energy  
Transportation

### **Key Products**

Check valves  
Connectors for low pressure fluid conveyance  
Deep sea umbilicals  
Diagnostic equipment  
Hose couplings  
Industrial hose  
Mooring systems & power cables  
PTFE hose & tubing  
Quick couplings  
Rubber & thermoplastic hose  
Tube fittings & adapters  
Tubing & plastic fittings



## **Hydraulics**

### **Key Markets**

Aerial lift  
Agriculture  
Alternative energy  
Construction machinery  
Forestry  
Industrial machinery  
Machine tools  
Marine  
Material handling  
Mining  
Oil & gas  
Power generation  
Refuse vehicles  
Renewable energy  
Truck hydraulics  
Turf equipment

### **Key Products**

Accumulators  
Cartridge valves  
Electrohydraulic actuators  
Human machine interfaces  
Hybrid drives  
Hydraulic cylinders  
Hydraulic motors & pumps  
Hydraulic systems  
Hydraulic valves & controls  
Hydrostatic steering  
Integrated hydraulic circuits  
Power take-offs  
Power units  
Rotary actuators  
Sensors



## **Instrumentation**

### **Key Markets**

Alternative fuels  
Biopharmaceuticals  
Chemical & refining  
Food & beverage  
Marine & shipbuilding  
Medical & dental  
Microelectronics  
Nuclear Power  
Offshore oil exploration  
Oil & gas  
Pharmaceuticals  
Power generation  
Pulp & paper  
Steel  
Water/wastewater

### **Key Products**

Analytical Instruments  
Analytical sample conditioning products & systems  
Chemical injection fittings & valves  
Fluoropolymer chemical delivery fittings, valves & pumps  
High purity gas delivery fittings, valves, regulators & digital flow controllers  
Industrial mass flow meters/controllers  
Permanent no-weld tube fittings  
Precision industrial regulators & flow controllers  
Process control double block & bleeds  
Process control fittings, valves, regulators & manifold valves



## **Seal**

### **Key Markets**

Aerospace  
Chemical processing  
Consumer  
Fluid power  
General industrial  
Information technology  
Life sciences  
Microelectronics  
Military  
Oil & gas  
Power generation  
Renewable energy  
Telecommunications  
Transportation

### **Key Products**

Dynamic seals  
Elastomeric o-rings  
Electro-medical instrument design & assembly  
EMI shielding  
Extruded & precision-cut, fabricated elastomeric seals  
High temperature metal seals  
Homogeneous & inserted elastomeric shapes  
Medical device fabrication & assembly  
Metal & plastic retained composite seals  
Shielded optical windows  
Silicone tubing & extrusions  
Thermal management  
Vibration dampening



**ENGINEERING YOUR SUCCESS.**

# Parker Fluid Connectors Group

## North American Divisions & Distribution Service Centers

**Your complete source** for quality tube fittings, hose & hose fittings, brass & composite fittings, quick-disconnect couplings, valves and assembly tools, locally available from a worldwide network of authorized distributors.

### **Fittings:**

Available in inch and metric sizes covering SAE, BSP, DIN, GAZ, JIS and ISO thread configurations, manufactured from steel, stainless steel, brass, aluminum, nylon and thermoplastic.

### **Hose, Tubing and Bundles:**

Available in a wide variety of sizes and materials including rubber, wire-reinforced, thermoplastic, hybrid and custom compounds.

### **Worldwide Availability:**

Parker operates Fluid Connectors manufacturing locations and sales offices throughout North America, South America, Europe and Asia-Pacific.

**For information**, call toll free...

**1-800-C-PARKER**  
**(1-800-272-7537)**

## **North American Divisions**

### **Energy Products Division**

Stafford, TX  
phone 281 566 4500  
fax 281 530 5353

### **Fluid System Connectors Division**

Otsego, MI  
phone 269 694 9411  
fax 269 694 4614

### **Hose Products Division**

Wickliffe, OH  
phone 440 943 5700  
fax 440 943 3129

### **Industrial Hose Division**

Strongsville, OH  
phone 440 268 2120  
fax 440 268 2230

### **Parflex Division**

Ravenna, OH  
phone 330 296 2871  
fax 330 296 8433

### **Quick Coupling Division**

Minneapolis, MN  
phone 763 544 7781  
fax 763 544 3418

### **Tube Fittings Division**

Columbus, OH  
phone 614 279 7070  
fax 614 279 7685

## **Distribution Service Centers**

### **Buena Park, CA**

phone 714 522 8840  
fax 714 994 1183

### **Conyers, GA**

phone 770 929 0330  
fax 770 929 0230

### **Louisville, KY**

phone 502 937 1322  
fax 502 937 4180

### **Portland, OR**

phone 503 283 1020  
fax 503 283 2201

### **Toledo, OH**

phone 419 878 7000  
fax 419 878 7001  
fax 419 878 7420  
(FCG Kit Operations)

### **Canada**

#### **Grimsby, ONT**

phone 905 945 2274  
fax 905 945 3945  
(Contact Grimsby for other Service Center locations.)

